portable fire-extinguishing appliances, the means of access to the various compartments and decks in the craft, the ventilating system including particulars of the master fan c ontrols, the positions of dampers and identification numbers of the ventilating fans ser ving each section of the craft, the location of the international shore connection, if f itted, and the position of all means of control referred to in 7.5.3, 7.6.2, 7.7.1 and 7 .7.4.

The text of such plans* should be in the official language of the flag State.

* Refer to Graphical symbols for fire control plans adopted by the Organization by resol ution A.654(16).

W/1576n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIO NAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 63/23/Add.2 ANNEX 18 Page 76 7.9.2 7.9.3 7.9 .3.1 7.9.3.2 7.9.3.3 However, if the language is neither English nor French, a translati on into one of those languages should be included.

A duplicate set of fire control plans or a booklet containing such plans should be perma nently stored in a prominently marked weathertight enclosure outside the deckhouse for t he assistance of - A duplicate set of fire control plans or a booklet containing such pl ans should be permanently stored in a prominently marked weathertight enclosure outside the deckhouse for the assistance of shore side fire-fighting personnel.

Openings in fire-resisting divisions Except for the hatches between cargo, special categ ory, store, and baggage spaces and between such spaces and the weather decks, all openin gs should be provided with permanently attached means of closing which should be at leas t as effective for resisting fires as the divisions in which they are fitted.

It should be possible for each door to be opened and closed from each side of the bulkhe ad by one person only.

Fire doors bounding major fire hazard areas and stairway enclosures should satisfy the f ollowing requirements: .1 The doors should be self-closing and be capable of closing wit h an angle of inclination of up to 3.5 0 opposing closure, and should have an approximat ely uniform rate of closure of no more than 40 s and no less than 10 s with the craft in the upright position • .

2 Remote-controlled sliding or power-operated doors should be - and should have an appro ximately uniform rate of closure of no more than 40 s and no less than 10 s with the cra ft in the upright position • .

2 Remote-controlled sliding or power-operated doors should be equipped with an alarm tha t sounds at least 5 s but no more than 10 s before the door begins to move and continue sounding until the door is completely closed.

Doors designed to reopen upon contacting an object in their paths should reopen sufficie ntly to allow a clear passage of at least 0.75 m, but no more than 1 m • .

3 All doors should be capable of remote and automatic release from a continuously manned central control station, either simultaneously or in groups, and also individually from a position at both sides of the door.

Indication should be provided at the fire control panel in the continuously manned contr ol station wheth