satisfactorily drop-tested from at least that height.

2.2 The open reversible floating liferaft should be capable of withstanding repeated jum ps on to it from a height of at least 4.5 m.

2.3 The open reversible liferaft and its fittings should be so constructed as to enable it to be towed at a speed of 3 knots in calm water when loaded with its full complement of persons and equipment, with the sea-anchor deployed.

2.4 The open reversible liferaft when fully inflated should be capable of being boarded from the water whichever way up it inflates.

2.5 The main buoyancy chamber should be divided into: .1 not le~s than two separate comp artments, each inflated through a nonreturn inflation valve on each compartment: and Ref er to the Recommendation on the use and fitting of retro-reflective materials on life-sa ving appliances adopted by the Organization by resolution A.658(16).

W/1689n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIO NAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 63/23/Add.2 ANNEX 18 Page 217 .2 the buoyanc y chambers should be so arranged that in the event of one - W/1689n/pp/EWP RESOLUTION MS C.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 63/23/Add.2 ANNEX 18 Page 217 .2 the buoyancy chambers should be so arra nged that in the event of one of the compartments being damaged or failing to inflate, t he intact compartment should be able to support, with positive freeboard over the open r eversible liferaft's entire periphery, the number of persons which the liferaft is permi tted to accommodate, .

each having a mass of 75 kg and seated in their normal positions.

2.6 The floor of the open reversible liferaft should be waterproof.

2.7 The open reversible liferaft should be inflated with a non-toxic gas by an inflation system complying with the requirements of regulati6n III/39 of the Convention.

Inflation should be completed within the period of one minute at an ambient temperature of between 18°C and 20°C and within a period of three minutes at an ambient temperature of -18°C.

After inflation the open reversible liferaft should maintain its form when loaded with i ts full complement o f persons and equipment.

- three minutes at an ambient temperature of -18°C.

After inflation the open reversible liferaft should maintain its form when loaded with i ts full complement o f persons and equipment.

2.8 Each inflatable compartment should be capable of withstanding a pressure equal to at least three times the working pressure and should be prevented from reaching a pressure exceeding twice the working pressure either by means of relief valves or by a limited ga s supply.

Means should be provided for fitting the topping-up pump or bellows.

2.9 The surface of the buoyancy tubes should be of non-slip material.

At least 25% of these tubes should be of a highly visible colour.

2.10 The number of persons which an open reversible liferaft should be permitted to acco mmodate should be equal to the lesser of: .1 the greatest whole number obtained by divid ing by 0.0