all stations at which control functions may be exercised.

11.4.2 The alarm system should meet appropriate constructional and operational requireme nts for required alarms.~ 11.4.3 Equipment monitoring the passenger, cargo and machinery spaces for fire and flooding should, so far as is practicable, form an integrated sub-ce ntre incorporating monitoring and activation controls for all emergency situations.

This sub-centre may require feed-back instrumentation to indicate that actions initiated have been fully implemented.

11.5 Safety system Where arrangements are fitted for overriding any automatic shutdown s ystem for the main propulsion machinery in accordance ~ith 9.2.2, they should be such as to preclude inadvertent operation.

When a shutdown system is activated, an audible and visual alarm should be given at the control station and means should be provided to override the automatic shutdown except i n cases where there is a risk of complete breakdown or explosion.

* Refer to the Code on alarms and indicators adopted by the Organization by resolution A .686(17).

W/1687n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) - risk of complete breakdo wn or explosion.

* Refer to the Code on alarms and indicators adopted by the Organization by resolution A .686(17).

W/1687n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIO NAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 62/23/Add.2 ANNEX 18 Page 110 12.1 12.1.1 12 .1.

2 12.1.

3 12.1.

4 12.1.

5 12.2.

12.2.1 CHAPTER 12 - ELECTRICAL INSTALLATIONS PART A - GENERAL General Electrical insta11 ations* should be such that: .1 all electrical auxiliary services necessary for maintain ing the craft in normal operation and habitable conditions will be ensured without recou rse to the emergency source of electrical power; .2 electrical services essential for sa fety will be ensured under various emergency conditions; and .

3 the safety of passengers, crew and craft from electrical hazards will be ensured.

The FMEA should include the electrical system, taking into account the effects of electr ical failure on the systems being supplied.

In cases where faults can occur without being detected during routine checks on the inst allations, the analysis should take into account - the effects of electrical failure on the systems being supplied.

In cases where faults can occur without being detected during routine checks on the inst allations, the analysis should take into account the possibility of faults occurring sim ultaneously or consecutively.

The electrical system should be designed and installed so that the probability of the cr aft being at risk of failure of a service is extremely remote.

Where loss of particular essential service would cause serious risk to the craft, the se rvice should be fed by at least two independent circuits fed in such a way that no singl e failure in the electrical supply or distribution systems would effect both supplies.

The securing arrangements for heavy items, i.e.

accumulator batteries, should, as far as practicable, prevent excessive movemen' during the accelerations due to gro