temperature is above the minimum temperature required for starting the engine; .3 the ge
neral emergency alarm system should be tested.

Monthly inspections Inspection of the life-saving appliances, including survival craft e
quipment should be carried out monthly using the checklist required by regulation 111/52
.1 of the Convention to ensure that they are complete and in good order.

A report of the inspection should be entered in the log-book.

Servicing of inflatable liferafts, inflatable lifejackets and inflated rescue boats .1 E
very inflatable liferaft, inflatable lifejacket and MES should be serviced: .1.1 at inte
rvals not exceeding 12 months, provided where in any case this is impracticable, the Adm
inistration may extend this period by one month; .1.2 at an approved servicing station w
hich is competent to service them, maintains proper servicing facilities and uses only p
roperly trained personnel.* Refer to the Recommendation on conditions for the approval o
f servicing stations for inflatable liferafts, adopted by the Organization by resolution
A.693(17).

W/1687n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) - Refer to the Recommendat
ion on conditions for the approval of servicing stations for inflatable liferafts, adopt
ed by the Organization by resolution A.693(17).

W/1687n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIO
NAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 62123/Add.2 ANNEX 18 Page 90 8.9.8 8.9.9 8.1
0 8.10.1 All repairs and maintenance of inflated rescue boats should be carried out in a
ccordance with the manufacturer's instructions.

Emergency repairs may be carried out on board the craft; however, permanent repairs shou
ld be effected at an approved servicing station.

Periodic servicing of hydrostatic release units Hydrostatic release units should be serv
iced: .1 at intervals not exceeding 12 months, provided where in any case this is imprac
ticable, the Administration may extend this period by one 'month; .2 at a servicing stat
ion which is competent to service them, maintains proper servicing facilities and uses o
nly properly trained personnel.

Survival craft and resc ue boat~ All craft should carry: .1 survival craft with sufficie
nt capacity as will accommodate - maintains proper servicing facilities and uses only pr
operly trained personnel.

Survival craft and resc ue boat~ All craft should carry: .1 survival craft with sufficie
nt capacity as will accommodate not less than 100% of the total number of persons the cr
aft is certified to carry, subject to a minimum of two such survival craft being carried
; .2 in addition, survival craft with sufficient aggregate capacity to accommodate not l
ess than 10% of the total number of persons the craft is certified to carry; .3 in the e
vent of anyone survival craft being lost or rendered unserviceable, sufficient survival
craft to accommodate the total number of persons the craft is certified to carry; .4 at
least one rescue boat for retrieving persons from the water, but not less than one such
boat on each side when the craft is certified to carry more th