craft portable two-way VHF radiotelephone apparatus, adopted by the Organization by reso lution A.605(15).

** Refer to the Recommendation on performance standards for survival craft radar transpo nders for use in search and rescue operations, adopted by the Organization by resolution A.697(17).

WI1687n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIO NAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 62123/Add.2 ANNEX 18 Page 84 8.2.2 8.2.3 8.2 .3.1 8.2.3.2 Craft should be provided with the following on-board communications and ala rm systems: .1 an emergency means comprising either fixed or portable equipment or both for two-way communications between emergency control stations, muster and embarkation st ations and strategic positions on board; and .2 a general emergency alarm system complyi ng with the requirements of regulation III/50 of the Convention to be used for summoning passengers and crew to muster stations and to initiate the actions included in the muste r list.

The system should be supplemented by either a public address system or other suitable me ans of communication.

The systems should be - for summoning passengers and crew to muster stations and to init iate the actions included in the muster list.

The system should be supplemented by either a public address system or other suitable me ans of communication.

The systems should be operable from the operating compartment.

Signalling eguipment All craft should be provided with a portable daylight signalling la mp which is available for use in the operating compartment at all times and which is not dependent on the craft's main source of electrical power.

Craft should be provided with not less than 12 rocket parachute flares, complying with t he requirements of regulation 111/35 of the Convention, stowed in or near the operating compartment.

8.3 Personal liLe - saying appliances 8.3.1 Where passengers or crew have access to expo sed decks under normal operating conditions, at least one lifebuoy on each side of the c 'raft capable of quick release from the control compartment and from a position at or ne ar where it is stowed, should be provided with a self-igniting light and a self-activati ng smoke signal.

The positioning and securing arrangements of the self-activating smoke - a position at o r near where it is stowed, should be provided with a self-igniting light and a self-acti vating smoke signal.

The positioning and securing arrangements of the self-activating smoke signal should be such that it cannot be released or activated solely by the accelerations produced by col lisions or groundings.

8.3.2 At least one lifebuoy should be provided adjacent to each normal exit from the cra ft and on each open deck to which passengers and crew have access, subject to a minimum of two being installed.

8.3.3 Lifebuoys fitted adjacent to each normal exit from the craft should be fitted with buoyant lines of at least 30 m in length.

8.3.4 8.3.5 Not less than half the total with self-igniting lights.

self-igniting lights should accordance with 8.3.3.

number of lifebuoys should be fitted However, the lifebuoys provided wit