position-indicating radio beacon (satellite EPIRB)*** which should be: .6.1 capable of t
ransmitting a distress alert either through the polar orbiting satellite service operati
ng in the 406 MHz band or, if the craft is engaged only on voyages within INMARSAT cover
age, through the INMARSAT geostationary satellite service operating in the 1.6 GHz band*
***; .6.2 installed in an easily accessible position; .6.3 ready to be manually released
and capable of being carried by one person into a survival craft; .6.4 capable of floati
ng free if the craft sinks and of being automatically activated when afloat; and .6.5 ca
pable of being activated manually.

* Refer to resolution A.70l(17) concerning carriage of INMARSAT enhanced group call Safe
tyNET receivers under the GMDSS, adopted by the Organization.

** Refer to the Recommendation on promulgation of maritime safety information, adopted b
y the Organization by resolution A.705(17).

*** Refer to resolution A.616(15) concerning search and rescue homing capability, adopte
d by the Organization.

**** Subject to the availability of appropriate receiving and processing - *** Refer to
resolution A.616(15) concerning search and rescue homing capability, adopted by the Orga
nization.

**** Subject to the availability of appropriate receiving and processing ground faciliti
es for each ocean region covered by INMARSAT satellites.

W/1687n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIO
NAL CODE OF SAFETY FOR HIGH SPEED CRAFT 14.6.2 14.6.3 14.6.4 14.7 14.7.1 MSC 62/23/Add.2
ANNEX 18 Page 135 Until 1 February 1999, or until such other date as may be determined b
y the Maritime Safety Committee, every craft should, in addition , be fitted with a radi
o installation consisting of a radiotelephone distress frequency watch receiver capable
of operating on 2,182 kHz.

Until 1 February 1999, every craft should, unless the craft is engaged on voyages in sea
area Al only, be fitted with a device for generating the radiotelephone alarm signal on
the frequency 2,182 kHz*.

The Administration may exempt craft constructed on or after 1 February 1997 from the req
uirements prescribed by 14.6.2 and 14.6.3.

Radi o equ ipment : Sea area A1 In addition to meeting the requirements of 14.6, every c
raft engaged - 2,182 kHz*.

The Administration may exempt craft constructed on or after 1 February 1997 from the req
uirements prescribed by 14.6.2 and 14.6.3.

Radi o equ ipment : Sea area A1 In addition to meeting the requirements of 14.6, every c
raft engaged on voyages exclusively in sea area Al should be provided with a radio insta
llation capable of initiating the transmission of ship-to-shore distress alerts from the
position from which the craft is normally navigated, operating either: .1 on VHF using D
SC; this requirement may be fulfilled by the EPIRB prescribed by 14.7.3, either by insta
lling the EPIRB close to, or by remote activation from, the position from which the craf
t is normally navigated; or .

2 through the polar orbiting satellite service on 406 MHz; this requirement may be fulfi
lled by the satellite EPIRB, required by 14.6.1.6, eithe