rate of heat release from building products adopted by ISO by ISO 5660.

** Refer to the Improved recommendation on test method for qualifying marine constructio n materials as non-combustible adopted by the Organization by resolution A.472(XII).

*** Refer to the Recommendation on improved fire test procedures for "A", "B" and "F" cl ass divisions, adopted by the Organization by resolution A.754(18).

**** Refer to the Recommendation on improved fire test procedures for surface flammabili ty of bulkhead, ceiling and deck finish materials adopted by the Organization by resolut ion A.653(16).

W/1576n/pp/EWP RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIO NAL CODE OF SAFETY FOR HIGH SPEED CRAFT Machinery spaces Open vehicle spaces Spaces cont aining dangerous goods Special category spaces Store-rooms containing flammable liquids MSC 63/23/Add.2 ANNEX 18 Page 55 .2 "Areas of moderate fire hazard" referred to in table s 7.4-1 and 7.4-2 by B, include the following spaces: Auxiliary machinery spaces, as def ined in 1.4.3 Bond stores containing packaged beverages with alcohol content not exceedi ng 24% by volume Crew accommodations - and 7.4-2 by B, include the following spaces: Aux iliary machinery spaces, as defined in 1.4.3 Bond stores containing packaged beverages w ith alcohol content not exceeding 24% by volume Crew accommodations Service spaces .3 "A reas of minor fire hazard" referred to in tables 7.4-1 and 7.4-2 by C, include the follo wing spaces: Auxiliary machinery spaces, as defined in 1.4.4 Cargo spaces Fuel tank comp artments Public spaces Tanks, voids and areas of little or no fire risk .4 "Control stat ions" referred to in tables 7.4-1 and 7.4-2 by D, as defined in 1.4.13 .

.

5 "Evacuation stations and external escape routes" referred to in tables 7.4-1 and 7.4-2 by E, include the following areas: External stairs and open decks used for escape routes Muster stations, internal and external Open deck spaces and enclosed promenades forming lifeboat and liferaft embarkation and lowering stations The craft's side to the waterlin e in the lightest seagoing condition, superstructure and deckhouse sides situated below and adjacent to the liferaft's and evacuation slide's embarkation areas .6 "Open spaces" referred to in tables 7.4-1 and 7.4-2 by F, include the following areas: - condition, su perstructure and deckhouse sides situated below and adjacent to the liferaft's and evacu ation slide's embarkation areas .6 "Open spaces" referred to in tables 7.4-1 and 7.4-2 b y F, include the following areas: W/1576n/pp/EWP Open spaces locations other than evacua tion stations and external escape routes and control stations.

RESOLUTION MSC.36(63) (adopted on 20 May 1994) ADOPTION OF THE INTERNATIONAL CODE OF SAF ETY FOR HIGH SPEED CRAFT MSC 63/23/Add.2 ANNEX 18 Page 56 - N-e~ of rraj a- f 1r-e /"'e% lr'O .o.r.e~ of /Tcc::):"I dte f'ire t-czlr'O ..

.Are=~ of' min::r f ire ~z:rd..

- CO"1r:rc! ~tct!cn.

A 6 c 0 e: e:~ticn stdticns ~e~ n:ut".

, F Open Spaces WI1576n/pp/EWP Table 7.4-1 STRUCTURAL FIRE PROTECTION TIMES FOR SEPARATI NG BULKHEADS AND DECKS OF PASSENGER CRAFT / A I e I c /.

.

0 -/ e: I F IN.

I~