in the ratio of one transponder for every four liferafts.

The transponder shall be mounted inside the liferaft so its antenna is more than one met re above the sea level when the liferaft is deployed, except th at for canopied reversib le liferafts the transponder shall be so arranged as to be readily accessed and erected by survivors.

Each transponder shall be a rranged to be manually erected when the liferaft is deployed .

Containers of lifer afts fitted with transponders shall be clearly marked.

_____ * Refer to the Performance standards for survival craft radar transponders for use in search and rescue operations, adopted by the Organization by resolution A.802 (19).■ CHAPTER XII ADDITIONAL SAFETY MEASURES FOR BULK CARRIERS 9 The following new regu lations 12 and 13 are added after existing regulation 11: ■Regulation 12 Hold, ballast a nd dry space water level detectors (This regulation applies to bulk carriers regardless of their date of construction) 1 Bulk carriers shall be fitted with water level detector s: RESOLUTION MSC.134(76) (adopted on 12 December 2002) ADOPTION OF AMENDMENTS TO THE IN TERNATIONAL - 1 Bulk carriers shall be fitted with water level detectors: RESOLUTION MSC .134(76) (adopted on 12 December 2002) ADOPTION OF AMENDMENTS TO THE INTERNATIONAL CONVE NTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDEDMSC 76/23/Add.1 ANNEX 3 Page 7 I:\M SC\76\23-ADD.1.DOC .1 in each cargo hold, giving audible and visual alarms, one when the water level above the inner bottom in any hold reaches a height of 0.5 m and another at a height not less than 15% of the depth of the cargo hold but not more than 2 m.

On bulk carriers to which regulation 9.2 applies, detectors with only the latter alarm n eed be installed.

The water level detectors shall be fitted in the aft end of the cargo holds.

For cargo holds which are used for water ballast, an alarm overriding de vice may be ins talled.

The visual alarms shall clearly discriminate be tween the two different water levels det ected in each hold; .2 in any ballast tank forward of the collision bulkhead required by regulation II-1/11, giving an audible a nd visual alarm when the liquid in the tank reac hes a level not exceeding 10% of the tank capacity.

An alarm - detected in each hold; .2 in any ballast tank forward of the collision bulkhe ad required by regulation II-1/11, giving an audible a nd visual alarm when the liquid i n the tank reaches a level not exceeding 10% of the tank capacity.

An alarm overriding device may be installed to be activated when the tank is in use; and .3 in any dry or void space other than a chain cable locker, any part of which extends f orward of the foremost cargo hold, giving an audible and visual alarm at a water level o f 0.1 m above the deck.

Such alarms need not be provided in enclosed spaces the volume of which does not exceed 0.1% of the ship■s maximum displacement volume.

2 The audible and visual alarms specified in paragraph 1 shall be located on the navigat ion bridge.

3 Bulk carriers constructed before 1 July 2004 shall comply with the requir