NOTING that Article 3(3) of the AFS Conventio n prescribes that Parties to this Conventi on shall apply the requirements of this Convention as may be necessary to ensure that no more favourable treatment is given to ships of non-Parties to this Convention, NOTING AL SO resolution MEPC.105(49) by which the Committee adopted the Guidelines for inspection of anti-fouling systems on ship on 18 July 2003, NOTING FURTHER that by resolution MEPC. 105(49), the Committee resolved to keep the 2003 Guidelines under review in the light of experience gained, HAVING CONSIDERED, at its sixty-second session, the draft 2011 Guidel ines for inspection of anti-fouling systems on ships developed by the Sub-Committee on F lag State Implementation at its nineteenth session, 1.

ADOPTS the 2011 Guidelines for inspection of anti- fouling systems on ships, as set out in the annex to this resolution; - Implementation at its nineteenth session, 1.

ADOPTS the 2011 Guidelines for inspection of anti- fouling systems on ships, as set out in the annex to this resolution; 2.

INVITES Governments to apply the 2011 Guidelines when exercising port State control insp ections; 3.

RECOMMENDS that the 2011 Guidelines be adopted as amendments to resolution A.787(19) on Procedures for port State control, as amended; 4.

AGREES to keep the 2011 Guidelines under review in the light of experience gained; and 5 .

REVOKES the Guidelines adopted by resolution MEPC.105(49).

RESOLUTION MEPC.208(62) Adopted on 15 July 2011 2011 GUIDELINES FOR INSPECTION OF ANTI-F OULING SYSTEMS ON SHIPSMEPC 62/24/Add.1 Annex 27, page 2 I:\MEPC\62\24-Add-1.doc ANNEX 2 011 GUIDELINES FOR INSPECTION OF ANTI-FOULING SYSTEMS ON SHIPS 1 INTRODUCTION 1.1 The ri ght of the port State to conduct inspections of anti-fouling systems on ships is in Arti cle 11 of the AFS Convention.

The guidelines for conducting these inspections are described below.

1.2 Ships of 400 gross tonnage and above engaged in international voyages (excluding - i n Article 11 of the AFS Convention.

The guidelines for conducting these inspections are described below.

1.2 Ships of 400 gross tonnage and above engaged in international voyages (excluding fix ed or floating platforms, FSUs and FPSOs) will be required to undergo an initial survey before the ship is put into service or before the International Anti-fouling System Cert ificate (IAFS) is issued for the first time; and a survey should be carried out when the anti-fouling systems are changed or replaced.

1.3 Ships of 24 metres in length or more but less than 400 gross tonnage engaged in inte rnational voyages (excluding fixed or floating platforms, FSUs and FPSOs) will have to c arry a Declaration on Anti-fouling Systems signed by the owner or authorized agent.

Such declaration shall be accompanied by appropriate documentation (such as a p