ballast water exchange standard, set out in regulation D-1, or the ballast wat er perfor mance standard, set out in regulation D -2 of the Convention should be considered as app ropriate.

The provisions of the Guidelines for ballast water exchange in the Antarctic treaty area (resolution MEPC.163(56)) should be taken into consideration , along with other relevant guidelines developed by the Organization.

4.2 In selecting the ballast water management system, attention should be paid to limiti ng conditions specified in the appendix of the Type Approval Certificate and the tempera ture under which the system has been tested, in order to ensure its suitability and effe ctiveness in polar waters.

4.3 In order to minimize the risk of invasive aquatic species transfers via biofouling, measures should be considered to minimize the risk of more rapid degradation of anti-fou ling coatings associated with polar ice operations.

Reference is made in particular to the 2011 Guidelines for the control and management of ships ' biofouling to minimize the transfer of invasive aquatic species (resolution MEPC .207(62)).

RESOLUTION MEPC.264(68) (adopted on 15 May 2015) - 2011 Guidelines for the control and m anagement of ships ' biofouling to minimize the transfer of invasive aquatic species (re solution MEPC.207(62)).

RESOLUTION MEPC.264(68) (adopted on 15 May 2015) INTERNATIONAL CODE FOR SHIPS OPERATING IN POLAR WATERS (POLAR CODE)- 45 - Table: Example of matters related to anti-fouling sys tems taken into consideration by some ice-going ships (this table is used by some operat ors of ice-going ships) Hull Sea chest Year round operation in ice-covered polar waters ■ Abrasion resistant coating.

■ Compliant with the AFS Convention.

Thickness of anti-fouling system to be decided by shipowner.

Intermittent operation in ice-covered polar waters ■ Abrasion resistant low friction ice coating.

■ In sides, above bilge keel, max thickness of anti-fouling system 75 µm, to protect hul l between application of anti-fouling system and next anticipated voyage to ice-covered waters.

In bottom area thickness to be decided by shipowner.

Composition of anti-fouling system should also be decided by the shipowner.

■ Compliant with the AFS Convention.

Thickness of anti-fouling system to be decided by shipowner.

- area thickness to be decided by shipowner.

Composition of anti-fouling system should also be decided by the shipowner.

■ Compliant with the AFS Convention.

Thickness of anti-fouling system to be decided by shipowner.

Category B and C ships ■ Compliant with the AFS Convention.

Thickness of anti-fouling system to be decided by shipowner.

■ Compliant with the AFS Convention.

Thickness of anti-fouling system to be decided by shipowner.

RESOLUTION MEPC.264(68) (adopted on 15 May 2015) INTERNATIONAL CODE FOR SHIPS OPERATING IN POLAR WATERS (POLAR CODE)- 46 - APPENDIX I Form of Certificate for Ships operating in Polar Waters POLAR SHIP CERTIFICATE This Certificate shall be supplemented by a Record o f Equipment for the Polar Ship Certificate (Official seal) (State) Issued under the prov