the Marine Environment Protection Committee of the Organization by resolutions MSC.4(48) and MEPC.19(22) respectively, as amended.

The existing text of 3.16.

10(a) is replaced by the fol l owing : filter type respiratory protection is unacceptabl e; The following words are inserted after the third sentence of the existing text of 4.7 .21; Remote manual operation should be arranged such that remote starting of pumps suppl ying the water spray system and remote operation of any normally closed valves in the sy stem can be carried out from a suitable location outside the cargo area, adjacent to the accommodation spaces and readily accessible and operab l e in the event of fire in the a reas protected.

RESOLUTION MEPC.56(33) (adopted on 30 October 1992) ADOPTION OF AMENDMENTS TO THE CODE F OR THE CONSTRUCTION AND EQUIPMENT OF SHIPS CARRYING DANGEROUS CHEMICALS IN BULK (BCH COD E)- 4 - The existing text of 4.10 is amended as follows: New 4.10 Cargoes protected by a dd itives - ADOPTION OF AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT OF SHI PS CARRYING DANGEROUS CHEMICALS IN BULK (BCH CODE)- 4 - The existing text of 4.10 is ame nded as follows: New 4.10 Cargoes protected by add itives 4.10.1 Certai n ca r goes with a reference in colu mn 'm' in th e ta ble of chapter VI.

by the nat ure of their chemical make-u p, tend under cer t ain conditions of t emperat ure , exposure to ai r or contact with a ca tal ys t.

to undergo polymerization, decomposition, oxidation or other chemical chang es.

Mitigation of this tendency is carried ou t by introducing small amounts of chemical add itives into the liquid cargo or by controlling the cargo tank environment.

4.10.2 No change.

4 .10.3 Care should be taken to ensure th a t these cargoes are s uffi cie ntly pro tect ed to prevent de l e t erious chemical change at all times during the voyage.

Ships carrying such cargoes should be provided with a certificate of protection f rom th e manufa cture r and kept during the voyage specifying: .1 the name and amount of addi t ive present; .2 whether the additive is oxygen-dependent; .3 date additive was put in th e product and duration of - with a certificate of protection f rom the manufa cture r an d kept during the voyage specifying: .1 the name and amount of addi tive present; .2 whe ther the additive is oxygen-dependent; .3 date additive was put in the product and durat ion of effectiveness; .4 any temperature limitations qua lif ying the add i tive's effec tive lifetime; and .5 the action to be taken should the le ngth of voyage exceed the eff ective lifetime of the additive.

4.10.4 Ships using the exc lusion of air as the method of preventing oxidatio n of the c argo should comply with 2.19.3 .

4.10.5 A product co ntaini ng an oxygen-dependent additive s hould be carried without in ert ion.

4 .1 0 .

6 A, existing 4.10.5 .

4.10.7 M existing 4.10.6.

4.23 is added ., follows: 4.23 Temperature sensors Temperature sensors should be used to monitor the cargo pump temperatu