Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk , in tanks sepa rated from the outer shell by a distance of not less than 760 mm.

3 Additional guidance to chapter 5 In order to minimize the risks associated with animal cargo mortalities, consideration should be given to how animal carcasses will be managed , treated and stored on board when ships carrying such cargo are operating in polar wate rs.

Reference is made in particular to the 2012 Guidelines for the implementation of MARPOL Annex V (resolution MEPC.219(63), as amended by resolution MEPC.239(65)) and the 2012 Gu idelines for the development of garbage management plans (resolution MEPC.220(63)).

4 Additional guidance under other environmental conventions and guidelines 4.1 Until the International Convention for the Control and Management of Ships ' Ballast Water and Sed iments enters into force, the ballast water management provisions of the ballast water e xchange standard, set out in regulation D-1, or the ballast wat er performance standard, set out in regulation D -2 of the Convention should be considered as appropriate.

- ballast water exchange standard, set out in regulation D-1, or the ballast wat er perf ormance standard, set out in regulation D -2 of the Convention should be considered as a ppropriate.

The provisions of the Guidelines for ballast water exchange in the Antarctic treaty area (resolution MEPC.163(56)) should be taken into consideration , along with other relevant guidelines developed by the Organization.

4.2 In selecting the ballast water management system, attention should be paid to limiti ng conditions specified in the appendix of the Type Approval Certificate and the tempera ture under which the system has been tested, in order to ensure its suitability and effe ctiveness in polar waters.

4.3 In order to minimize the risk of invasive aquatic species transfers via biofouling, measures should be considered to minimize the risk of more rapid degradation of anti-fou ling coatings associated with polar ice operations.

Reference is made in particular to the 2011 Guidelines for the control and management of ships ' biofouling to minimize the transfer of invasive aquatic species (resolution MEPC .207(62)).

RESOLUTION MEPC.264(68) (adopted on 15 May 2015) - 2011 Guidelines for the control and m anagement of ships ' biofouling to minimize the transfer of invasive aquatic species (re solution MEPC.207(62)).

RESOLUTION MEPC.264(68) (adopted on 15 May 2015) INTERNATIONAL CODE FOR SHIPS OPERATING IN POLAR WATERS (POLAR CODE)- 45 - Table: Example of matters related to anti-fouling sys tems taken into consideration by some ice-going ships (this table is used by some operat ors of ice-going ships) Hull Sea chest Year round operation in ice-covered polar waters ■ Abrasion resistant coating.

■ Compliant with the AFS Convention.

Thickness of anti-fouling system to be decided by shipowner.

Intermittent operation in ice-covered polar waters ■ Abrasion resistant low friction ice coating.

■ In sides, above bilge keel, max thickness of anti-fouling system 75 µm, to protect hul l b