In its most simple form, the attained annual operational CII of individual ships is calc ulated as the ratio of the total mass of CO 2 (M) emitted to the total transport work (W) undertaken in a given calendar year, as follows: (1) 4.1 M ass of CO2 emissions (M) T he total mass of CO2 is the sum of CO2 emissions (in grams) from all the fuel oil consum ed on board a ship in a given calendar year, as follows: ■■ = ■■■■■■ × ■■■■■■ (2) where: ■ is the fuel oil type; ■ is the total mass (in grams) of consumed fuel oil of type in t he calendar year, as reported under IMO DCS; and ■ represents the fuel oil mass to CO 2 mass conversion factor for fuel oil type , in line with those specified in the 2018 Guid elines on the method of calculation of the attained Energy Efficiency Design Index (EED I) for new ships (resolution MEPC.308(73)), as may be further amended.

In case the type of the - calculation of the attained Energy Efficiency Design Index (E EDI) for new ships (resolution MEPC.308(73)), as may be further amended.

In case the type of the fuel oil is not covered by the guidelines, the conversion factor should be obtained from the fuel oil supplier supported by documentary evidence.

4.2 Transport work (W) In the absence of the data on actual transport work, the supply-b ased transport work (Ws) can be taken as a proxy, which is defined as the product of a s hip ■s capacity and the distance travelled in a given calendar year, as follows: Ws= C×D t (3) where: ■ C represents the ship■s capacity: - For bulk carriers, tankers, container ships, gas carriers, LNG carriers, ro- ro cargo ships, general cargo ships, refrigerated cargo carrier and combination carriers, deadweight tonnage (DWT)1 should be used as Capa city; - For cruise passenger ships, ro- ro cargo ships (vehicle carriers) and ro- ro - c arriers, deadweight tonnage (DWT)1 should be used as Capacity; - For cruise passenger sh ips, ro- ro cargo ships (vehicle carriers) and ro- ro passenger ships, gross tonnage (GT)2 should be used as Capacity; and ■ Dt represents the total distance travelled (in naut ical miles), as reported under IMO DCS.

1 Deadweight tonnage (DWT) means the difference in tonnes between the displacement of a ship in water of relative density of 1,025 kg/m3 at the summer load draught and the ligh tweight of the ship.

The summer load draught should be taken as the maximum summer draught as certified in th e stability booklet approved by the Administration or any organization recognized by it.

2 Gross tonnage (GT) should be calculated in accordance with the International Conventio n on Tonnage Measurement of Ships, 1969.

/ shipattained CII M W= j jFC j jFC j RESOLUTION MEPC.336(76) (adopted on 17 June 2021) - Measurement of Ships, 1969.

/ shipattained CII M W= j jFC j jFC j RESOLUTION MEPC.336(76) (adopted on 17 June 2021) 2021 GUIDELINES ON OPERATIONAL CARBON INTENSITY INDICATORS AND THE CALCULATION METHODS (CII GUIDELINES, G1)MEPC 76/15/Add.2 Annex 10, page 4 I:\MEPC\76\MEPC 76-15-Add.2.docx 5 Operational carbon intensity indicator (CII) of individual ships for trial purpose The f ollowing metrics are encouraged to be used for trial purposes, where applicable: .1 Ener gy Efficiency Performance Indicator (EEPI) ■■■■■■■■■ = ■■■■×■■■■ .2 cbDIST ■■■■■■ ■■■■■■ = ■■■■ ■■■■×■■■■ .3 clDIST ■■ ■■■■■■■■■■ = ■■■■■■ ■■■■■■■■■■■■■■■×■■■■ .4 EEOI, as define d in MEPC.1/Circ.684 on Guidelines for voluntary use of the ship energy efficiency opera tional indicator (EEOI).

In the formulas above: • the mass of CO2 (M