is installed; and .7 SFCSteamTurbine for steam turbine, as specified in paragraph 2.2.7.
2 of the EEDI Calculation Guidelines.

If the calculation is not available from the manufacturer, SFCSteamTurbine may be calcul
ated by the submitter.

A sample of an EEXI Technical File is provided in the appendix.

2 Electric power tables should be validated separately, taking into account the guidelin
es set out in appendix 2 of the 2014 Guidelines on survey and certification of the Energ
y Efficiency Design Index (EEDI) (resolution MEPC.254(67), as amended by resolutions MEP
C.261(68) and MEPC.309(73)); consolidated text: MEPC.1/Circ.855/Rev.2, as may be further
amended).

RESOLUTION MEPC.334(76) (adopted on 17 June 2021) 2021 GUIDELINES ON SURVEY AND CERTIFIC
ATION OF THE ATTAINED ENERGY EFFICIENCY EXISTING SHIP INDEX (EEXI)MEPC 76/15/Add.2 Annex
8, page 6 I:\MEPC\76\MEPC 76-15-Add.2.docx 4.2.3 The SFC should be corrected to the valu
e corresponding to the ISO standard reference conditions using the standard lower calori
fic value of the fuel oil, referring to ISO 15550:2002 and ISO 3046-1:2002.

For the confirmation of the SFC, a copy of the approved NOX Technical File and - conditi
ons using the standard lower calorific value of the fuel oil, referring to ISO 15550:200
2 and ISO 3046-1:2002.

For the confirmation of the SFC, a copy of the approved NOX Technical File and documente
d summary of the correction calculations should be submitted to the verifier.

4.2.4 For ships equipped with dual-fuel engine(s) using LNG and fuel oil, the CF-factor
for gas (LNG) and the specific fuel consumption (SFC) of gas fuel should be used by appl
ying the criteria specified in paragraph 4.2.3 of the 2014 Guidelines on survey and cert
ification of the E nergy Efficiency Design Index (EEDI), as amended,3 as a basis for the
guidance of the Administration.

4.2.5 Notwithstanding paragraphs 4.2.3 and 4.2.4, in cases where overridable Shaft / Eng
ine Power Limitation is installed, or in cases where engines do not have a test report i
ncluded in the NOX Technical File, SFC should be calculated in accordance with paragraph
2.2.3 of the EEXI Calculation Guidelines.

For this purpose, actual performance records of the engine may be used if satisfactory a
nd acceptable to the verifier.

- Technical File, SFC should be calculated in accordance with paragraph 2.2.3 of the EEX
I Calculation Guidelines.

For this purpose, actual performance records of the engine may be used if satisfactory a
nd acceptable to the verifier.

4.2.6 The verifier may request further information from the submitter, as specified in p
aragraph 4.2.7 of the EEDI Survey and Certification Guidelines, in addition to that cont
ained in the EEXI Technical File, as necessary, to examine the calculation process of th
e attained EEXI.

4.2.7 In cases where the sea trial report as specified in paragraph 4.2.2.9 is submitted
, the verifier should request further information from the submitter to confirm that: .1
the sea trial was conducted in accordance with the conditions specified in paragraphs 4.
3.3, 4.3.4 and 4.3.7 of the EEDI Survey and Certification Guidelin