in accordance with the cost-effectiveness (Ce) formula below: Refer to Definitions for t
he cost-effectiveness formula in regulation 13.7.5 of the revised MARPOL Annex VI (MEPC.
1/Circ.678).

28 Refer to the 2020 Guidelines for monitoring the worldwide average sulphur content of
fuel oils supplied for use on board ships (resolution MEPC.326(75)).

RESOLUTION MEPC.403(83) (adopted on 11 April 2025) AMENDMENTS TO THE 2022 GUIDELINES ON
SURVEY AND CERTIFICATION OF THE ENERGY EFFICIENCY DESIGN INDEX (EEDI) Cost of approved m
ethod• 10• Ce =---------- Power (kW) • 0.768 • 6,000 (hours/y ear) · 5 (year
s) · 6NOx (g/kWh) MEPC 83/17/Add.1 Annex 11, page 30 I:\MEPC\MEPC 83-17-Add.1.docx .2 th
e North Sea area as defined in regulation 1.14.6 of Annex V of the present Convention; .
3 the North American Emission Control Area, which means the area described by the coordi
nates provided in appendix VII; .4 the United States Caribbean Sea Emission Control Area
, which means the area described by the coordinates provided in appendix VII; .5 the Med
iterranean Sea Emission Control Area, which means the area described by the coordinates
provided in appendix VII; - area described by the coordinates provided in appendix VII;
.5 the Mediterranean Sea Emission Control Area, which means the area described by the co
ordinates provided in appendix VII; .6 the Canadian Arctic Emission Control Area, which
means the area described by the coordinates provided in appendix VII; .7 the Norwegian S
ea as defined in regulation 13.9.4 of Annex II of the present Convention; and .8 the Nor
th -East Atlantic Emission Control Area, which means the area described by the coordinat
es provided in appendix VII.

4 While a ship is operating within an emission control area, the sulphur content of fuel
oil used on board that ship shall not exceed 0.10% m/m.

5 The sulphur content of fuel oil referred to in paragraph 1 and paragraph 4 of this reg
ulation shall be documented by its supplier as required by regulation 18 of this Annex.

6 Those ships using separate fuel oils to comply with paragraph 4 of this regulation and
entering or leaving an emission control area set forth in paragraph 3 of this regulation
shall carry a written procedure showing how the fuel oil changeover is to be done, allow
ing sufficient - entering or leaving an emission control area set forth in paragraph 3 o
f this regulation shall carry a written procedure showing how the fuel oil changeover is
to be done, allowing sufficient time for the fuel oil service system to be fully flushed
of all fuel oils exceeding the applicable sulphur content specified in paragraph 4 of th
is regulation prior to entry into an emission control area.

The volume of low sulphur fuel oils in each tank as well as the date, time and position
of the ship when any fuel oil changeover operation is completed prior to the entry into
an emission control area or commenced after exit from such an area shall be recorded in
such logbook or electronic record book29 as prescribed by the Administration.

7 During the first 12 months immediately following entry into force of an amendment desi
gnating a specific emi