new ships (resolution MEPC.308(73), as amended, the "EEDI Calculation Guidelines" hereafter) as the attained EEXI if the value of the attained EEDI is equal to or less than that of the required EEXI.

2.2 Parameters For calculation of the attained EEXI by the formula in paragraph 2.1, parameters under the EEDI Calculation Guidelines apply, unless expressly provided otherwise.

In referring to the aforementioned guidelines, the terminology "EEDI" should be read as "EEXI".

2.2.1 PME(i) ; Power of main engines In cases where overridable Shaft / Engine Power Limitation is installed in accordance with the 2021 Guidelines on the shaft / engine power limit to comply with the EEXI requirements and use of a power reserve (resolution MEPC.335(76)), PME(i) is 83% of the limited installed power (MCRlim) or 75% of the original installed power (MCR), whichever is lower, for each main engine (i).

In cases where the overridable Shaft / Engine Power Limitation and shaft generator(s) are installed, in referring to paragraph 2.2.5.2 (option 1) of the EEDI Calculation Guidelines, "MCRME" should be read as "MCRlim".

engine (i).

In cases where the overridable Shaft / Engine Power Limitation and shaft generator(s) are installed, in referring to paragraph 2.2.5.2 (option 1) of the EEDI Calculation Guidelines, "MCRME" should be read as "MCRlim".

For LNG carriers having steam turbine or diesel electric propulsion, PME(i) is 83% of the limited installed power (MCRlim, MPPlim), divided by the electrical efficiency in case of diesel electric propulsion system, for each main engine (i).

For LNG carriers, the power from combustion of ( ) mrefwl c i nef f i MEFMEieffieffAEFAE nPTI i neff i iAEeffieffiPTI n j jAEFAEAEiMEiFME nME i iME n j j f V fCapacity f f f SFC C P fSFC C P f P fSFC C PSFC C P f · · · · · · ||⎠⎟|⎜⎝⎛ ∗ ∗− ||⎠⎟|⎜⎝⎛ ||⎠⎟|⎜⎝⎛ − · + ∗+ || ⎠⎟|⎜⎝⎛ ||⎠⎟|⎜⎝⎛ ∑∑ ∑∏∑∏ = · · ··= = ·=· ··= ·= 1) ( ) (1 1) () () (1) () (1) (1 RESOLUTION MEPC.333(76) (adopted on 17 June 2021) 2021 GUIDELINES ON THE METHOD OF CALCULATION OF THE ATTAINED ENERGY EFFICIENCY EXISTING SHIP INDEX (EEXI)MEPC 76/15/Add.2 Annex 7, page 4 I:\MEPC\76\MEPC 76-15-Add.2.docx the excessive natural boil-off gas in the engines or boilers to avoid releasing to the atmosphere - Annex 7, page 4 I:\MEPC\76\MEPC 76-15-Add.2.docx the excessive natural boil-off gas in the engines or boilers to avoid releasing to the atmosphere or unnecessary thermal oxidation should be deducted from PME(i) with the approval of the verifier.

2.2.2 PAE(i) ; Power of auxiliary engines 2.2.2.1 PAE(i) is calculated in accordance with paragraph 2.2.5.6 of the EEDI Calculation Guidelines.

2.2.2.2 For ships where power of auxiliary engines (PAE) value calculated by paragraphs 2.2.5.6.1 to 2.2.5.6.3 of the EEDI Calculation Guidelines is significantly diff erent from the total power used at normal seagoing, e.g.

in cases of passenger ships, the PAE value should be estimated by the consumed electric power (excluding propulsion) in conditions when the ship is engaged in a voyage at reference speed (Vref) as given in the electric po