regulation shall be provided with a manufacturer's operating manual, which is to be reta
ined with the unit and which shall specify how to operate the incinerator within the lim
its described in paragraph 2 of appendix IV of this Annex.

38 Type Approval Certificates issued taking into account the Revised guidelines for the
implementation of Annex V of MARPOL (resolution MEPC.59(33), as amended by resolution ME
PC.92(45)), or Standard specification for shipboard incinerators (resolution MEPC.76(40)
, as amended by resolution MEPC.93(45)), or the 2014 Standard specification for shipboar
d incinerators (resolution MEPC.244(66)), as amended by resolution MEPC.368(79).

39 Refer to the 2014 Standard specification for shipboard incinerators (resolution MEPC.
244(66), as amended by resolution MEPC.368(79)), or Standard specification for shipboard
incinerators (resolution MEPC.76(40), as amended by resolution MEPC.93(45)), and Type ap
proval of shipboard incinerators (MEPC.1/Circ.793).

RESOLUTION MEPC.403(83) (adopted on 11 April 2025) AMENDMENTS TO THE 2022 GUIDELINES ON
SURVEY AND CERTIFICATION OF THE ENERGY EFFICIENCY DESIGN INDEX (EEDI)MEPC 83/17/Add.1 -
RESOLUTION MEPC.403(83) (adopted on 11 April 2025) AMENDMENTS TO THE 2022 GUIDELINES ON
SURVEY AND CERTIFICATION OF THE ENERGY EFFICIENCY DESIGN INDEX (EEDI)MEPC 83/17/Add.1 An
nex 11, page 34 I:\MEPC\MEPC 83-17-Add.1.docx 8 Personnel responsible for the operation
of an incinerator installed in accordance with the requirements of paragraph 6.1 of this
regulation shall be trained to implement the guidance provided in the manufacturer's ope
rating manual as required by paragraph 7 of this regulation.

9 For incinerators installed in accordance with the requirements of paragraph 6.1 of thi
s regulation the combustion chamber gas outlet temperature shall be monitored at all tim
es the unit is in operation.

Where that incinerator is of the continuous -feed type, waste shall not be fed into the
unit when the combustion chamber gas outlet temperature is below 850°C.

Where that incinerator is of the batch-loaded type, the unit shall be designed so that t
he combustion chamber gas outlet temperature shall reach 600 °C within five minutes afte
r start -up and will thereafter stabilize at a temperature not less than 850°C.

Regulation 17 Reception facilities - chamber gas outlet temperature shall reach 600 °C w
ithin five minutes after start -up and will thereafter stabilize at a temperature not le
ss than 850°C.

Regulation 17 Reception facilities 1 Each Party undertakes to ensure the provision of fa
cilities adequate to meet the: .1 needs of ships using its repair ports for the receptio
n of ozone -depleting substances and equipment containing such substances when removed f
rom ships; .2 needs of ships using its ports, terminals or repair ports for the receptio
n of exhaust gas cleaning residues from an exhaust gas cleaning system; without causing
undue delay to ships, and .3 needs in ship -breaking facilities for the reception of ozo
ne -depleting substances and equipment containing such substances when removed from ship
s.

2 The following States may satisfy the requirements in par