Amendments related to application 1 Existing paragraphs 1.1.2 and 1.1.3 are repla ce d b y the following: "1.1.

2 Unless expressly provided otherwise, the Code applies.

to s hips the keels of which are laid or which are at a stage at whi ch: .1 construction identifiable with the ship begins; and .2 assembly of that ship has commenced comprising at least 50 teunes or l' of the estimated mass of all structural mate rial, whichever is the less; on or after 1 July 1998.

Ships constructed before 1 July 1998 are to comply with resolution MSC.5(48) adopted on 1 7 June 1963 subject to amendment s by r e solution MSC.30(61) adopted on 11 December 1 992.

1.1.3 A ship.

irrespective of the date of construction, which is converted to a gas carrier on or afte r 1 July 1998, should be treated as a gas carrier constructed on the date on which such conversion commences." Amendments related to fillipg limits 2 The existing chapter 15 is replaced by the following: "CHAPTER 15 FILLING LIMITS FOR CARGO TANKS 15.1 General 15.1. 1 No cargo tanks should have a higher filling limit (FL) than 98' at the reference tempe rature, except as permitted by 15.1.

3.

- "CHAPTER 15 FILLING LIMITS FOR CARGO TANKS 15.1 General 15.1.1 No cargo tanks should h ave a higher filling limit (FL) than 98' at the reference temperature, except as permitt ed by 15.1.

3.

15.1.2 The maximum loading limit (LL) to which a cargo tank may be loaded should be dete rmined by the following formula: LL where: LL FL PR FL PL loading limit exp r essed as a pe r centage, being the maximum allowable liguid volume rela tive to the tank volume to which the tank may be loaded; filling limit as specified i n 15.1.1 or 15.1.3; RESOLUTIO N MSC.32(63) adopted on 23 May 1994 ADOPTION OF AMENDMENTS TO THE INTERNATIONAL CODE FOR THE CONSTRUCTION AND EQUIPMENT OF SHIPS CARRYING LIQUEFIED GASES IN BULK (IGC CODE) PR P L ~ 3 ~ relative density of cargo at the reference temperature: and relative density of cargo at the loading temperature and pressure.

15.1.3 The Administration may allow a higher f illing limit (FL) than the limit of 98' s pecified in 15.1.1 at the reference temperature, taking int o account the shape of the t ank, arrangements of pressure relief valves, accuracy of level and temperature gauging a nd the difference between the - limit of 98' specified in 15.1.1 at the reference temper ature, taking int o account the shape of the tank, arrangements of pressure relief valve s, accuracy of level and temperature gauging and the difference between the loading temp erature and the temperature corresponding to the vapour pressure of the cargo at the set pressure of the pressure relief valves, provided the conditions specified in 8.2.17 are maintained.

15.1.4 For the purposes of this chapter only, "reference temperature" means: .1 the temp erature corresponding to the vapour pressure of the cargo at the set pressure of the pre ssure relief valves when DO cargo vapour pressure/temperature control as referred to in chapter 7 is provided; .2 the temperature of the cargo upon termination of loading, duri ng transport.

or at unloading, whichever is the greatest.

when a cargo vapour