ADOPTS the Guidelines for Emergency Towing Arrangements on Tankers, the text of which is set out in the Annex to the present resolution and which supersedes resolution A.535(13) ; 2.

RECOMMENDS that all Governments concerned take appropriate steps to implement the Guidel ines.

WIl648n/EWP RESOLUTION MSC.35(63) (adopted on 20 May 1994) ADOPTION OF GUIDELINES FOR EM ERGENCY TOWING ARRANGEMENTS ON TANKERS MSC 63/23/Add.l ANNEX 7 Page 2 1 PURPOSE ANNEX GU IDELINES FOR EMERGENCY TOWING ARRANGEMENTS ON TANKERS 1.1 Under regulation V/15-1 of the 1974 SOLAS Convention, as amended by resolution MSC.31(63) in 1994, new and existing tan kers of 20,000 tonnes deadweight and above shall be fitted with an emergency towing arra ngement, the design and construction of which shall be approved by the Administration, b ased on the Guidelines developed by the Organization.

- the design and construction of which shall be approved by the Administration, based on the Guidelines developed by the Organization.

1.2 The present Guidelines are intended to provide standards for the design and construc tion of emergency towing arrangements which Administrations are recommended to implement .

1.3 For existing tankers fitted with the emergency towing arrangements in accordance wit h resolution A.535(13), the existing towing arrangements forward of the ship may be reta ined, but the towing arrangements aft of the ship should be upgraded to comply with the requirements of the present Guidelines.

2 REQUIREMENTS FOR THE ARRANGEMENTS AND COMPONENTS 2.1 General The emergency towing arra ngements should be so designed as to facilitate salvage and emergency towing operations on tankers primarily to reduce the risk of pollution.

The arrangements should at all times be capable of rapid deployment in the absence of ma in power on the ship to be towed and easy - risk of pollution.

The arrangements should at all times be capable of rapid deployment in the absence of ma in power on the ship to be towed and easy connection to the towing vessel.

Figure 1 shows arrangements which may be used as reference.

2.2 Towing components The major components of the towing arrangements should consist of the following: Forward of ship'" Aft of ship Pick-up gear Towing pennant Chafing gear Fa irlead Strongpoint Roller pedestal optional optional Yes Yes Yes Yes See paragraph 3.1.4 .

W/1648n/EWP Yes Yes Depending on design Yes Yes Depending on design Strength requirement s Yes Yes Yes Yes RESOLUTION MSC.35(63) (adopted on 20 May 1994) ADOPTION OF GUIDELINES FOR EMERGENCY TOWING ARRANGEMENTS ON TANKERS M6C 63/23/Add.1 ANNEX 7 Page 3 2.3 Strenqth of the towinq components 2.3.1 Towing compo