RECALLING Article 28(b) of the Convention on the International Maritime Organization con cerning the functions of the Committee, RECALLING ALSO resolution A.328(IX), by which th e Assembly, at its ninth session, adopted the Code for the Construction and Equipment of Ships Carrying Liquefied Gases in Bulk (Gas Carrier Code) and authorized the Committee t o amend the Code as may be necessary, NOTING resolution MSC.32(63), by which the Committ ee adopted amendments to the International Code for the Construction and Equipment of Sh ips Carrying Liquefied Gases in Bulk (IGC Code), RECOGNIZING the need to bring the corre sponding amendments to the Gas Carrier Code into force on the date on which the amendmen ts to the IGC Code enter into force, - Liquefied Gases in Bulk (IGC Code), RECOGNIZING t he need to bring the corresponding amendments to the Gas Carrier Code into force on the date on which the amendments to the IGC Code enter into force, HAVING CONSIDERED at its sixty-third session amendments to the Gas Carrier Code proposed by the Sub-Committee on Bulk Chemicals, 1.

ADOPTS amendments to the Gas Carrier Code, the text of which is given in the Annex to th e present resolution; 2.

DETERMINES that the amendments should become effective on 1 July 1998 upon acceptance an d entry into force of the corresponding amendments to the IGC Code adopted by resolution MSC.32(63).

W/ 1648n / EWP RESOLUTION MSC.34(63) adopted on 23 May 1994 ADOPTION OF AMENDMENTS TO TH E CODE FOR THE CONSTRUCTION AND EQUIPMENT OF SHIPS CARRYING LIQUEFIED GASES IN BULK MSC 63/23/Add.1 ANNEX 5 Page 2 ANNEX AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPME NT OF SHIPS CARRYING LIQUEFIED GASES IN BULK 1 Existing chapter XV is replaced by the fo llowing: "CHAPTER XV FILLING LIMITS FOR CARGO TANKS 15.1 General 15.1.1 No cargo tanks s hould have a higher filling limit (FL) than 98% at - SHIPS CARRYING LIQUEFIED GASES IN B ULK 1 Existing chapter XV is replaced by the following: "CHAPTER XV FILLING LIMITS FOR C ARGO TANKS 15.1 General 15.1.1 No cargo tanks should have a higher filling limit (FL) th an 98% at the reference temperature, except as permitted by 15.1.3.

15.1.2 The maximum loading limit (LL) to which a cargo tank may be loaded should be dete rmined by the following formula: LL where: LL = FL = = = FL loading limit expressed in p ercent which means the maximum allowable liquid volume relative to the tank volume to wh ich the tank may be loaded; filling limit as specified in 15.1.1 or 15.1.3; relative den sity of cargo at the reference temperature; and relative density of cargo at the loading temperature and pressure.

15.1.3 The Administration may allow a higher filling limit (FL) than the limit of 98% sp eci