RECALLING Article 28(b) of the Convention on the International Maritime Organization con cerning the functions of the Committee, RECALLING ALSO that the Assembly, when adopting resolution A.689(17) on Testing of life-saving appliances, authorized the Committee to k eep the annexed Recommendation on testing of life -saving appliances under review and to adopt, when appropriate, amendments thereto, RECALLING FURTHER that, since the adoption of resolution A.689(17), the Committee has amended the Recommendation annexed thereto by resolutions MSC.54(66) and MSC.81(70), --- URL: https://wwwcdn.imo.org/localresources/en /KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.544(107).pdf amended the Recom mendation annexed thereto by resolutions MSC.54(66) and MSC.81(70), and by circulars MSC /Circ.596, MSC/Circ.615 and MSC/Circ.809, RECOGNIZING the need to ensure that the refere nces in the Revised recommendation on testing of life-saving appliances (resolution MSC. 81(70)) are kept up to date, 1 ADOPTS the Amendments to the Revised recommendation on te sting of life -saving appliances (resolution MSC.81(70)), set out in the annex to the pr esent resolution; 2 RECOMMENDS Governments to ensure that life -saving appliances instal led on or after 1 January 2029 conform to the amended prototype tests in sections 6 (Lif eboats) and 7 (Rescue boats and fast rescue boats), as set out in the annex to the prese nt resolution; 3 INVITES Contracting Governments to the SOLAS Convention to bring the ab ove amendments to the attention of all parties concerned.

RESOLUTION MSC.544(107) (adopted on 8 June 2023) --- URL: https://wwwcdn.imo.org/localre sources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.544(107).pdf amendme nts to the attention of all parties concerned.

RESOLUTION MSC.544(107) (adopted on 8 June 2023) AMENDMENTS TO THE REVISED RECOMMENDATIO N ON TESTING OF LIFE-SAVING APPLIANCES (RESOLUTION MSC.81(70)) MSC 107/20/Add.1 Annex 14 , page 2 I:\MSC\107\MSC 107/20/Add.1.docx ANNEX AMENDMENTS TO THE REVISED RECOMMENDATION ON TESTING OF LIFE-SAVING APPLIANCES (RESOLUTION MSC.81(70)) PART 1 – PROTOTYPE TESTS FO R LIFE-SAVING APPLIANCES 2 LIFEJACKETS 2.4 Tests of components other than buoyancy mater ials 1 The footnote to paragraph 2.4 is replaced by the following: "* Refer to the recom mendations of the International Organization for Standardization, in particular publicat ion ISO 12402 -7:2020 Personal flotation devices.

Part 7: Materials and components.

Safety requirements and test methods." 2.6 Tests for lifejacket buoyancy material Tensil e strength test 2 The footnote to paragraph 2.6.8 is replaced by the following: --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolu tions/MSC.544(107).pdf 2.6 Tests for lifejacket buoyancy material Tensile strength test 2 The footnote to paragraph 2.6.8 is replaced by the following: " * Refer to the recomme ndations of the International Organization for Standardization, in particular publicatio n ISO 12402-7:2020, Personal flotation devices.

Part 7: Materials and components.

Safety requirements and test methods." 3 IMMERSION SUITS 3.2 Thermal protective tests Ge neral 3 Paragraph 3.2.3 is replaced by the following: "3.2.3 Where human subjects are us ed, the tests should always be conducted under the supervision of a physician.

Emergency resuscitation equipment should be available during all tests.

For safety reasons, ECG should be monitored during every test.

Testing should be stopped at the wish of the test subjects, if the falling rate of the c ore temperature is more than 1.5ºC per hour after the first half hour, if the skin --- U RL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCRe solutions/MSC.544(107).pdf the core temperature is more than 1.5ºC per hour after the fi rst half hour, if the skin temperature of the hand, foot or lumbar region should fall be low 10 ºC for more than 15 minutes, or if the attending physician considers it advisable ." 6 LIFEBOATS 6.10 Lifeboat operational test Operation of engine and fuel consumption t est 4 Paragraph 6.10.1 is replaced by the following: "6.10.1 The lifeboat should be load ed with weights equal to the mass of its equipment and the number of persons for which t he lifeboat is to be approved.

The engine should be started and the lifeboat manoeuvred for a period of at least four h ours to RESOLUTION MSC.544(107) (adopted on 8 June 2023) AMENDMENTS TO THE REVISED RECOM MENDATION ON TESTING OF LIFE-SAVING APPLIANCES (RESOLUTION MSC.81(70)) MSC 107/20/Add.1 Annex 14, page 3 I:\MSC\107\MSC 107/20/Add.1.docx demonstrate satisfactory operation.

The lifeboat should be run at a speed of not less --- URL: https://wwwcdn.imo.org/localr esources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.544(107).pdf Annex

14, page 3 I:\MSC\107\MSC 107/20/Add.1.docx demonstrate satisfactory operation.

The lifeboat should be run at a speed of not less than 6 knots and, with the powered mea ns of ventilation in operation if fitted, for a period which is sufficient to ascertain the fuel consumption and to establish that t he fuel tank has the required capacity.

The maximum towing force of the lifeboat should be determined.

This information should be used to determine the largest fully loaded liferaft the lifeb oat can tow at 2 knots.

The fitting designated for towing other c raft should be secured to a stationary object by a tow rope.

The engine should be operated ahead at full speed for a period of at least two minutes, and the towing force measured and recorded.

There should be no damage to the towing fitting or its supporti ng structure.

The maximum towing force of the lifeboat should be recorded on the type approval certifi cate." --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResol utions/MSCResolutions/MSC.544(107).pdf structure.

The maximum towing force of the lifeboat should be recorded on the type approval certifi cate." 6.14 Additional tests for totally enclosed lifeboats 5 Paragraph 6.14.1 is replac ed by the following: "6.14.1 A suitable means should be provided to rotate the lifeboat about a longitudinal axis to any angle of heel and then release it.

The lifeboat, in the enclosed condition, should be incrementally rotated to angles of he el up to and including 180° and should be released.

After release, the lifeboat should always return to the upright position without the ass istance of the occupants.

The ventilation system of either powered or passive type while in operation should not c ompromise the ability of the lifeboat to self-right under any circumstance.

These tests should be conducted in the following conditions of load:" 6 The following ne w paragraph 6.14.9 is added after existing paragraph 6.14.8: "Ventilation performance te st --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutio ns/MSCResolutions/MSC.544(107).pdf 6 The following new paragraph 6.14.9 is added after e xisting paragraph 6.14.8: "Ventilation performance test 6.14.9 The ventilation rate requ ired by paragraph 4.6.6.1 of the LSA Code should be measured under moored conditions.

The test should be carried out with only the persons necessary on board to perform the t est.

All entrances and hatches should be kept closed.

Ventilation openings should stay open.

The measured ventilation rate should not be less than 5 m 3/hour per person for the tota l number of persons which the lifeboat is permitted to accommodate." 7 RESCUE BOATS AND FAST RESCUE BOATS 7.4 Rigid fast rescue boats 7 Paragraph 7.4.1 is replaced by the follo wing: "7.4.1 Rigid fast rescue boats should be subjected to the tests prescribed in 6.2 to 6.12 (except 6.3, 6.4.2, 6.5, 6.6.2, 6.7.1, 6.9.6, 6.9.7, 6.10.1), 6.14.1 to 6.14.8 (if a rigid fast rescue boat is self-righting), 7.1.2 to 7.1.4, 7.1.6, 7.1.7 (if a rigid fast rescue --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMO Resolutions/MSCResolutions/MSC.544(107).pdf rigid fast rescue boat is self-righting), 7. 1.2 to 7.1.4, 7.1.6, 7.1.7 (if a rigid fast rescue boat is not self -righting), 7.1.8, 7 .1.9 and 7.2.4.2.

In the case of open fast rescue boats, the self-righting test should only be done in the light condition, and 6.14.1.1, 6.14.3, 6.14.4, 6.14.5 and 6.14.9 are not applicable.

With regard to 6.14.2, a bo at fitted with a helmsman 's emergency release switch should be considered to be arranged to stop automatically when inverted." RESOLUTION MSC.544(10 7) (adopted on 8 June 2023) AMENDMENTS TO THE REVISED RECOMMENDATION ON TESTING OF LIFE-SAVING APPLIANCES (RESOLUTION MSC.81(70)) MSC 107/20/Add.1 Annex 14, page 4 I:\MSC\107\M SC 107/20/Add.1.docx 7.5 Inflated fast rescue boats 8 Paragraph 7.5 is replaced by the f ollowing: "Inflated fast rescue boats should be subjected to the tests prescribed in 6.4 .1, 6.6.1, 6.7.2, 6.9.1 to 6.9.5, 6.10 (except 6.10.1), 6.11, 6.12, 6.14.1 to 6.14.8 (if inflated fast --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofI MOResolutions/MSCResolutions/MSC.544(107).pdf 6.7.2, 6.9.1 to 6.9.5, 6.10 (except 6.10.1), 6.11, 6.12, 6.14.1 to 6.14.8 (if inflated fast rescue boat is self-righting), 7.1.2, 7.1.3, 7.1.6 (if inflated fast rescue boat is equipped with outboard motor), 7.1.7 (if i

nflated fast rescue boat is not self-righting), 7.1.8, 7.2.2 to 7.2.16 and 7.4.2." 7.6 R
igid/inflated fast rescue boats 9 Paragraph 7.6 is replaced by the following: "Rigid/inf
lated fast rescue boats should be subjected to the tests prescribed in 6.2 (for hull), 7
.2.14 (for inflated part), 6.4.1, 6.6.1, 6.7.2, 6.9.1 to 6.9.5, 6.10 (except 6.10.1) to
6.12, 6.14.1 to 6.14.8 (if rigid/inflated fast rescue boat it self-righting), 7.1.2 to 7
.1.4, 7.1.6 (if rigid/inflated rescue boat is equipped with outboard motor), 7.1.7 (if r
igid/inflated fast rescue boat is not self -righting), 7.1.8, 7.2.2 to 7.2.11, 7.2.15, 7
.2.16, 7.3.2 and 7.4.2." APPENDIX 1 ADULT REFERENCE TEST DEVICE (RTD) DESIGN AND CONSTRU
CTION --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolu
tions/MSCResolutions/MSC.544(107).pdf 7.2.16, 7.3.2 and 7.4.2." APPENDIX 1 ADULT REFEREN
CE TEST DEVICE (RTD) DESIGN AND CONSTRUCTION 10 Paragraph 2 is replaced by the following
: "2 MATERIALS All materials used should comply with ISO 12402-7:2020." APPENDIX 2 CHILD
REFERENCE TEST DEVICE (RTD) DESIGN AND CONSTRUCTION 11 Paragraph 2 is replaced by the fo
llowing: "2 MATERIALS All materials used should comply with ISO 12402-7:2020." APPENDIX
3 INFANT REFERENCE TEST DEVICE (RTD) DESIGN AND CONSTRUCTION 12 Paragraph 2 is replaced
by the following: "2 MATERIALS All materials used should comply with ISO 12402-7:2020."
*** RESOLUTION MSC.544(107) (adopted on 8 June 2023) AMENDMENTS TO THE REVISED RECOMMEND
ATION ON TESTING OF LIFE-SAVING APPLIANCES (RESOLUTION MSC.81(70)) RESOLUTION MSC.544(10
7) (adopted on 8 June 2023) AMENDMENTS TO THE REVISED RECOMMENDATION ON TESTING OF LIFE-
SAVING APPLIANCES (RESOLUTION MSC.81(70)) --- URL: https://wwwcdn.imo.org/localresources
/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.545(107).pdf RESOLUTION MSC
.545(107) (adopted on 8 June 2023) AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIP
MENT OF MOBILE OFFSHORE DRILLING UNITS, 1979 (1979 MODU CODE) MSC 106/19/Add.1 Annex 22,
page 1 I:\MSC\107\MSC 107/20/Add.1.docx ANNEX 22 RESOLUTION MSC.545(107) (adopted on 8 J
une 2023) AMENDMENTS TO THE CODE FOR THE CONSTRUCTION AND EQUIPMENT OF MOBILE OFFSHORE D
RILLING UNITS, 1979 (1979 MODU CODE) THE MARITIME SAFETY COMMITTEE, RECALLING Article 28
(b) of the Convention on the International Maritime Organization concerning the function
s of the Committee, NOTING that mobile offshore drilling units continue to be moved and
operated internationally, RECALLING that the Assembly, when adopting the Code for the Co
nstr