RECALLING Article 28(b) of the Convention on the International Maritime Organization con cerning the functions of the Committee, RECALLING ALSO article VIII(b) of the Internatio nal Convention for the Safety of Life at Sea, 1974 ("the Convention"), concerning the am endment procedure applicable to the annex to the Convention, other than to the provision s of chapter I, HAVING CONSIDERED, at its 108th session, amendments to the Convention pr oposed and circulated in accordance with article VIII(b)(i) of the Convention, 1 ADOPTS, in accordance with article VIII(b)(iv) of the Convention, amendments to --- URL: https:/ /wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/M SC.550(108).pdf 1 ADOPTS, in accordance with article VIII(b)(iv) of the Convention, amen dments to the Convention, the text of which is set out in the annex to the present resol ution; 2 DETERMINES, in accordance with article VIII(b)(vi)(2)(bb) of the Convention, th at the said amendments shall be deemed to have been accepted on 1 July 2025, unless, pri or to that date, more than one third of the Contracting Governments to the Convention or Contracting Governments the combined merchant fleets of which constitute not less than 5 0% of the gross tonnage of the world's merchant fleet have notified the Secretary-Genera l of their objections to the amendments; 3 INVITES Contracting Governments to the Conven tion to note that, in accordance with article VIII(b)(vii)(2) of the Convention, the ame ndments shall enter into force on 1 January 2026 upon their acceptance in accordance wit h paragraph 2 above; 4 REQUESTS the Secretary -General, for the purposes of article VIII (b)(v) of --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMORe solutions/MSCResolutions/MSC.550(108).pdf 4 REQUESTS the Secretary -General, for the pur poses of article VIII(b)(v) of the Convention, to transmit certified copies of the prese nt resolution and the text of the amendments contained in the annex to all Contracting G overnments to the Convention; 5 ALSO REQUESTS the Secretary -General to transmit copies of this resolution and its annex to Members of the Organization which are not Contractin g Governments to the Convention.

RESOLUTION MSC.550(108) (adopted on 23 May 2024) AMENDMENTS TO CHAPTERS II-2 AND V OF TH E INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974 - 2 - ANNEX AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974 CHAPTER II-2 CONSTRUCTI ON – FIRE PROTECTION, FIRE DETECTION AND FIRE EXTINCTION Part B Prevention of fire and e xplosion Regulation 4 Probability of ignition 1 At the end of paragraph 2.1.7, the word "and" is deleted and at the end of paragraph 2.1.8, "." is replaced by "; and".

--- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/ MSCResolutions/MSC.550(108).pdf Probability of ignition 1 At the end of paragraph 2.1.7, the word "and" is deleted and at the end of paragraph 2.1.8, "." is replaced by "; and".

2 The following new sub-paragraph is added after existing paragraph 2.1.8: ".9 oil fuel delivered to and used on board ships shall not jeopardize the safety of ships or adverse ly affect the performance of the machinery or be harmful to personnel." Part C Suppressi on of fire Regulation 7 Detection and alarm 5 Protection of accommodation and service sp aces and control stations 3 Paragraph 5.2 is replaced by the following: "5.2 Requirement s for passenger ships carrying more than 36 passengers A fixed fire detection and fire a larm system shall be so installed and arranged as to provide smoke detection in service spaces, control stations and accommodation spaces, including corridors, stairways and es cape routes within accommodation spaces.

Smoke detectors need not be fitted in private bathrooms and galleys.

Spaces --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResol utions/MSCResolutions/MSC.550(108).pdf spaces.

Smoke detectors need not be fitted in private bathrooms and galleys.

Spaces having little or no fire risk such as voids, public toilets, carbon dioxide rooms and similar spaces need not be fitted with a fixed fire detection and fire alarm system.

Detectors fitted in cabins, when activated, shall also be capable of emitting, or cause to be emitted, an audible alarm within the space where they are located." 4 Section 5.5 (Cargo ships) is replaced by the following: "5.5 Cargo ships (The requirements of paragr aph 5.5 shall apply to ships constructed on or after 1 January 2026.

Ships constructed before 1 January 2026 shall comply with the previously applicable requ irements of paragraph 5.5.) Accommodation and service spaces and control stations of car go ships shall be protected by a fixed fire detection and fire alarm system and/or an au tomatic sprinkler, fire detection and fire alarm system as follows depending on a protec tion method --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMO

Resolutions/MSCResolutions/MSC.550(108).pdf fire detection and fire alarm system as foll ows depending on a protection method adopted in accordance with regulation 9.2.3.1.

RESOLUTION MSC.550(108) (adopted on 23 May 2024) AMENDMENTS TO CHAPTERS II-2 AND V OF TH E INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974 - 3 - 5.5.1 Method IC A f ixed fire detection and fire alarm system shall be so installed and arranged as to provi de smoke detection in all corridors, stairways and escape routes within accommodation sp aces and in all control stations and cargo control rooms.

5.5.2 Method IIC An automatic sprinkler, fire detection and fire alarm system of an appr oved type complying with the relevant requirements of the Fire Safety Systems Code shall be so installed and arranged as to protect accommodation spaces, galleys and other servi ce space s, except spaces which afford no substantial fire risk such as void spaces, san itary spaces, etc.

In addition, a fixed fire detection and fire alarm system --- URL: https://wwwcdn.imo.or g/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.550(108).pd f spaces, sanitary spaces, etc.

In addition, a fixed fire detection and fire alarm system shall be so installed and arra nged as to provide smoke detection in all corridors, stairways and escape routes within accommodation spaces and in all control stations and cargo control rooms.

5.5.3 Method IIIC A fixed fire detection and fire alarm system shall be so installed and arranged as to detect the presence of fire in all accommodation spaces and service space s providing smoke detection in corridors, stairways and escape routes within accommodati on spaces, except spaces which afford no substantial fire risk such as void spaces, sani tary spaces, etc.

In addition, a fixed fire detection and fire alarm system shall be so installed and arra nged as to provide smoke detection in all corridors, stairways and escape routes within accommodation spaces and in all control stations and cargo control rooms." Regulation 9 Containment of fire 6 Protection of cargo space boundaries --- URL: https://wwwcdn.imo.o rg/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.550(108).p df control rooms." Regulation 9 Containment of fire 6 Protection of cargo space boundari es 5 Paragraph 6.1 is deleted and the subsequent paragraphs are renumbered accordingly.

Part G Special requirements Regulation 20 Protection of vehicle, special category and ro -ro spaces 6 The title of regulation 20 is replaced by the following: "Regulation 20 Pro tection of vehicle, special category, open and closed ro-ro spaces, and weather decks in tended for the carriage of vehicles" 1 Purpose 7 Paragraph 1.1 is replaced by the follow ing: ".1 fire protection systems shall be provided to adequately protect the ship from t he fire hazards associated with vehicle, special category and ro -ro spaces, and weather deck intended for the carriage of vehicles;" RESOLUTION MSC.550(108) (adopted on 23 May 2024) AMENDMENTS TO CHAPTERS II-2 AND V OF THE INTERNATIONAL CONVENTION FOR THE SAFETY O F LIFE AT SEA, 1974 - 4 - 2 General requirements 2.1 Application --- URL: https://wwwcdn .imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.550(108).pdf INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974 - 4 - 2 General re quirements 2.1 Application 8 The following new paragraph 2.1.3 is added after existing p aragraph 2.1.2: "2.1.3 Passenger ships constructed before 1 January 2026, including thos e constructed before 1 July 2012, shall also comply with regulations 20.4.1.6, 20.4.4 an d 20.6.2.3, as adopted by resolution MSC.550(108)." 3 Precaution against ignition of fla mmable vapours in closed vehicle spaces, closed ro-ro spaces and special category spaces 9 Paragraph 3.1.5 is replaced by the following: "3.1.5 Permanent openings In cargo ships , permanent openings in the side plating, the ends or deckhead of the space shall be so situated that a fire in the cargo space does not endanger stowage areas and embarkation stations for survival craft and accommodation spaces, service spaces and control station s in superstructures and deckhouses above the cargo spaces." 4 Detection and alarm --- U RL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCRe solutions/MSC.550(108).pdf spaces and control stations in superstructures and deckhouses above the cargo spaces." 4 Detection and alarm 10 The following new paragraph is added u nder the existing title of section 4 (Detection and alarm): "Passenger ships constructed before 1 January 2026 , including those constructed before 1 July 2012, shall comply wit h the requirements of paragraph 4.1.6 not later than the first survey on or after 1 Janu ary 2028." 4.1 Fixed fire detection and fire alarm systems 11 Section 4.1 (Fixed fire de tection and fire alarm systems) is replaced by the following: "4.1 Fixed fire detection and fire alarm systems The requirements of paragraphs 4.1.1 through 4.1.4 shall only app ly to passenger ships constructed on or after 1 January 2026.

Passenger ships constructed before 1 January 2026, including those constructed before 1

July 2012, shall comply with the requirements of paragraph 4.1.6 and the previously appl
icable requirements --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/In
dexofIMOResolutions/MSCResolutions/MSC.550(108).pdf with the requirements of paragraph 4
.1.6 and the previously applicable requirements of paragraph 4.1.

The requirements of paragraph 4.1.5 shall apply to cargo ships constructed on or after 1
January 2026.

Cargo ships constructed before 1 January 2026 shall comply with the previously applicabl
e requirements of paragraph 4.1.

4.1.1 In vehicle, special category and ro -ro spaces, there shall be provided an individ
ually identifiable fixed fire detection and fire alarm system.

The system shall comply with the requirements of the Fire Safety Systems Code.

4.1.1.1 The fixed fire detection and fire alarm system shall provide smoke and heat dete
ction throughout vehicle, special category and ro -ro spaces.

The Administration may accept linear heat detectors as the required system for heat dete
ction.

The system shall be capable of rapidly detecting the onset of fire.

The location of RESOLUTION MSC.550(108) (adopted on 23 May 2024) AMENDMENTS TO CHAPTERS
II-2 AND V OF THE --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/Inde
xofIMOResolutions/MSCResolutions/MSC.550(108).pdf RESOLUTION MSC.550(108) (adopted on 23
May 2024) AMENDMENTS TO CHAPTERS II-2 AND V OF THE INTERNATIONAL CONVENTION FOR THE SAFE
TY OF LIFE AT SEA, 1974 - 5 - detectors shall be to the satisfaction of the Administrati
on, taking into account the effects of ventilation and other relevant factors.

After being installed, the system shall be tested under normal ventilation conditions an
d shall give an overall response time to the satisfaction of the Administration.

4.1.2 If a fixed water -based deluge system is used for vehicle, special category and ro
-ro spaces, then a fire detection and fire alarm system identifiable to the same section
s of the deluge system shall be arranged.

4.1.3 The fire detection and fire alarm system shall be designed with a system interface
which provides logical and unambiguous presentation of the information, to allow a quick
and correct understanding and decision -making.

In particular, section --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre
/IndexofIMOResolutions/MSCResolutions/MSC.550(108).pdf allow a quick and correct underst
anding and decision -making.

In particular, section numbering of the alarm system shall coincide with that of other s
ystems, such as a fixed water-based fire-extinguishing system or video monitoring system
, if available.

4.1.4 There shall be provided a fixed fire detection and fire alarm system for the area
on the weather deck intended for the carriage of vehicles.

The fixed fire detection system shall be capable of rapidly detecting the onset of the f
ire anywhere on the area.

The type of detectors and their spacing and location shall be to the satisfaction of the
Administration, taking into account the effects of weather conditions, cargo obstruction
and other relevant factors.

Different settings may be used for specific operation sequences, such as during loading
or unloading and during voyage, in order to reduce the false alarms.

4.1.5 In cargo ships, vehicle spaces, special category spaces and ro -ro spaces --- URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolu
tions/MSC.550(108).pdf to reduce the false alarms.

4.1.5 In cargo ships, vehicle spaces, special category spaces and ro -ro spaces shall be
provided with a fixed fire detection and fire alarm system complying with the requiremen
ts of the Fire Safety Systems Code.

The fixed fire detection system shall be capable of rapidly detecting the onset of fire.

The type of detectors and their spacing and location shall be to the satisfaction of the
Administration, taking into account the effects of ventilation and other relevant factor
s.

After being installed, the system shall be tested under normal ventilation conditions an
d shall give an overall response time to the satisfaction of the Administration.

4.1.6 For passenger ships constructed before 1 January 2026 , including those constructe d before 1 July 2012, a fixed fire detection and fire alarm system complying with the re quirements of the Fire Safety Systems Code shall be provided in special --- URL: https:/ /wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/M SC.550(108).pdf with the requirements of the Fire Safety Systems Code shall be provided in special category spaces, open and closed ro-ro and vehicle spaces.

The fixed fire detection system shall be capable of rapidly detecting the onset of fire.

The fixed fire detection and fire alarm system shall provide smoke and heat detection th roughout vehicle, special category and ro-ro spaces.

In this context, heat detectors shall comply with the spacing and coverage area requirem ents as applicable for smoke detectors.

Heat detectors are only required where there is already a smoke detector." 4.3 Special c ategory spaces 12 Paragraph 4.3.1 is replaced by the following: "4.3.1 An efficient fire patrol system shall be maintained in special category spaces." RESOLUTION MSC.550(108) (adopted on 23 May 2024) AMENDMENTS TO CHAPTERS II-2 AND V OF THE INTERNATIONAL CONVENTIO N FOR THE SAFETY OF LIFE AT SEA, 1974 - 6 - 13 The following n ew section 4.4 is added a fter existing section 4.3 (Special category --- URL: https://wwwcdn.imo.org/localresourc es/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.550(108).pdf - 6 - 13 The following n ew section 4.4 is added after existing section 4.3 (Special category spaces) : "4.4 Video monitoring The requirements of paragraphs 4.4.1 and 4.4.2 apply to ships co nstructed on or after 1 January 2026.

Passenger ships with vehicle, special category or ro-ro spaces constructed before 1 Janu ary 2026, including those constructed before 1 July 2012, shall comply with the requirem ents of paragraphs 4.4.1 and 4.4.2 not later than the first survey on or after 1 January 2028.

4.4.1 For passenger ships, an effective video monitoring system shall be arranged in veh icle, special category and ro -ro spaces for continuous monitoring of these spaces.

The system shall be provided with immediate playback capability to allow for quick ident ification of fire location, as far as practicable.

Cameras shall be installed to cover the whole space, high enough to see over cargo and v ehicles after loading.

--- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/ MSCResolutions/MSC.550(108).pdf cover the whole space, high enough to see over cargo and vehicles after loading.

4.4.2 The videos recorded by this monitoring system shall be available for replay at a c ontinuously manned control station or at the safety centre for at least seven days for i nstallation on ro -ro passenger ships constructed on or after 1 January 2026 and 24 hour s for existing ro-ro passenger ships constructed before 1 January 2026, including those constructed before 1 July 2012 .

The correspondence between any one video camera and the section of the fixed water-based fire-extinguishing system protecting the space covered by this camera shall be clearly d isplayed close to the video monitor.

Continuous monitoring of the video image by the crew is not required." 5 Structural fire protection 14 Section 5 (Structural fire protection) is replaced by the following: "5 St ructural fire protection and arrangement of openings --- URL: https://wwwcdn.imo.org/loc alresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.550(108).pdf 14 Section 5 (Structural fire protection) is replaced by the following: "5 Structural fire protection and arrangement of openings This paragraph applies to passenger ships constru cted on or after 1 January 2026.

Passenger ships constructed before 1 January 2026 shall comply with the previously appli cable requirements of paragraph 5.

5.1 Structural fire protection 5.1.1 In passenger ships carrying more than 36 passengers , the boundary bulkheads and decks of special category and ro-ro spaces shall be insulat ed to "A-60" class standard.

However, where a category (5), (9) and (10) space, as defined in regulation 9.2.2.3, is on one side of the division, the standard may be reduced to "A-0".

Where fuel oil tanks are below a special category space, the integrity of the deck betwe en such spaces may be reduced to "A-0" standard.

5.1.2 Where a special category space or ro -ro space is sub divided with internal --- UR

L: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCRes
olutions/MSC.550(108).pdf between such spaces may be reduced to "A-0" standard.

5.1.2 Where a special category space or ro -ro space is sub divided with internal decks,
the fire rating of these decks shall be determined based on the capacity and arrangement
of the fixed water -based fire -extinguishing system.

If the fixed water-based fire -extinguishing system cannot simultaneously cover the appl
icable area above and below a given deck, this deck shall be of "A -30" standard while a
ny ramps and doors between decks shall be made of steel and of a design being as tight a
s practical.

RESOLUTION MSC.550(108) (adopted on 23 May 2024) AMENDMENTS TO CHAPTERS II-2 AND V OF TH
E INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974 - 7 - 5.2 Arrangement of
openings in ro-ro spaces and special category spaces 5.2.1 Openings in the side plating,
the ends or deckhead of the ro -ro space shall be situated and arranged so that a fire i
n the ro-ro space does not endanger: --- URL: https://wwwcdn.imo.org/localresources/en/K
nowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.550(108).pdf be situated and arr
anged so that a fire in the ro-ro space does not endanger: .1 stowage areas for survival
craft; .2 embarkation stations and assembly stations, including access to such stations;
and .3 accommodation spaces, control stations and normally occupied service spaces in su
perstructures and deckhouses above the ro-ro space.

Openings are not permitted for all decks directly below these objects and within a safet
y distance of minimum 6.0 m measured horizontally.

5.2.2 This requirement does not apply to openings fitted with closing arrangements, such
as ramps and doors.

Ramps and doors shall be of steel for all decks directly below accommodation spaces, con
trol stations and normally occupied service spaces, and minimum "A -0" for all dec ks di
rectly below survival craft, embarkation stations and assembly stations.

5.2.3 Openings are, however, accepted in ro -ro spaces below accommodation --- URL: http
s://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolution
s/MSC.550(108).pdf embarkation stations and assembly stations.

5.2.3 Openings are, however, accepted in ro -ro spaces below accommodation spaces, contr
ol stations and normally occupied service spaces, when the fire integrity of the ship 's
side, including windows and doors, is "A-60" on boundaries in a rectangular area measure
d 6.0 m horizontally forward and aft of the openings and vertically minimum two deck lev
els above the deck level with the opening.

"A-0" windows protected by a water -based system with an application rate of at least 5.
0 L/min per square metre may be accepted as equivalent to "A-60" windows.

Ventilation inlets shall be designed to minimize the risk of contamination.

5.2.4 Openings for mechanical ventilation of ro-ro and special category spaces are permi
tted below accommodation spaces, service spaces and control stations in superstructures,
if the opening is protected by a closing device, with a closing --- URL: https://wwwcdn.
imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.550(1
08).pdf superstructures, if the opening is protected by a closing device, with a closing
arrangement not likely to be cut off in case of a fire in the ro -ro spaces, capable of
being closed from a readily accessible position.

The closing device shall be made of steel or other fire-resistant material.

Such openings are not permitted below survival craft, the emergency generator and air in
takes for the engine-room(s).

5.2.5 Notwithstanding the above, air intakes serving machinery used for the ship's main
propulsion, power generation and emergency power generation shall be in a position minim
izing the risk of being contaminated by a fire in the ro -ro space or special category s
pace.

5.3 Arrangement of weather deck intended for the carriage of vehicles 5.3.1 Appropriate
arrangements shall be made so that a fully developed fire on weather decks intended for
the carriage of vehicles does not endanger: .1 stowage areas for survival craft; --- URL
: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCReso
lutions/MSC.550(108).pdf weather decks intended for the carriage of vehicles does not en
danger: .1 stowage areas for survival craft; .2 embarkation stations and assembly statio
ns including access to these; and RESOLUTION MSC.550(108) (adopted on 23 May 2024) AMEND
MENTS TO CHAPTERS II-2 AND V OF THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT S

EA, 1974 - 8 - .3 accommodation spaces, control stations and normally occupied service s paces in superstructures and deckhouses adjacent to the weather deck.

5.3.2 Appropriate arrangements shall be made providing a safety distance, measured horiz ontally, from the designated vehicle lanes of more than 6.0 m to accommodation spaces, c ontrol stations and normally occupied service spaces in superstructures and deckhouses a djacent to the weather deck.

5.3.3 The safety distance can be reduced to 3.0 m when boundaries, including windows and doors, within 6.0 m are of "A -60" integrity.

Alternatively, "A -0" --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.550(108).pdf windows and doors, within 6.0 m ar e of "A -60" integrity.

Alternatively, "A -0" boundaries protected by a water -based system with an application rate of at least 5.0 L/min per square metre may be accepted as equivalent.

5.3.4 Survival craft and embarkation stations, including access to these, shall be prote cted with a safety distance of more than 12.0 m.

Safety distances shall be measured horizontally.

5.3.5 Notwithstanding the above, air intakes serving machinery used for the ship's main propulsion, power generation and emergency power generation shall be in a position minim izing the risk of being contaminated by a fire on the weather deck intended for carriage of vehicles." 6 Fire extinction 6.1 Fixed fire-extinguishing systems 15 The explanatory paragraph under the title of existing section 6.1 (Fixed fire-extinguishing systems) is replaced by the following: "(The requirements of paragraphs 6.1.1 and 6.1.2 shall apply to ships constructed on --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentr e/IndexofIMOResolutions/MSCResolutions/MSC.550(108).pdf fire-extinguishing systems) is r eplaced by the following: "(The requirements of paragraphs 6.1.1 and 6.1.2 shall apply t o ships constructed on or after 1 July 2014.

Ships constructed before 1 July 2014 shall comply with the previously applicable require ments of paragraphs 6.1.1 and 6.1.2.

The requirements of paragraphs 6.2.1 and 6.2.2 shall apply to ro-ro passenger ships cons tructed on or after 1 January 2026.

Passenger ships with vehicle, special category or ro-ro spaces constructed before 1 Janu ary 2026, including those constructed before 1 July 2012, shall comply with the requir e ments of paragraph 6.2.3 not later than the first survey on or after 1 January 2028.)" 1 6 The following new section 6.2 is inserted after existing section 6.1 (Fixed fire-extin guishing systems) and the subsequent section (Portable fire extinguishers) and its parag raphs are renumbered accordingly: "6.2 Fixed water -based fire -extinguishing system on weather decks --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofI MOResolutions/MSCResolutions/MSC.550(108).pdf paragraphs are renumbered accordingly: "6. 2 Fixed water -based fire -extinguishing system on weather decks intended for carriage o f vehicles 6.2.1 In passenger ships, a fixed water-based fire-extinguishing system based on monitor(s) shall be installed in order to cover weather decks intended for the carria ge of vehicles.

The monitor(s) shall comply with the provisions of the Fire Safety Systems Code.

6.2.2 In passenger ships, drainage shall be provided where a fixed water -based fire-ext inguishing system is installed to cover weather decks intended for carriage of vehicles.

The system shall be sized to remove no less than 125% of the combined capacity of both t he monitor(s) and the required number of fire hose nozzles.

RESOLUTION MSC.550(108) (adopted on 23 May 2024) AMENDMENTS TO CHAPTERS II-2 AND V OF TH E INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974 - 9 - 6.2.3 For passenger ships constructed before 1 January 2026 , including those --- URL: https://wwwcdn.imo.or g/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.550(108).pd f INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974 - 9 - 6.2.3 For passenger ships constructed before 1 January 2026 , including those constructed before 1 July 2012 , a fixed water-based fire-extinguishing system based on monitor(s) shall be installed i n order to protect areas on weather decks intended for the carriage of vehicles.

Monitors shall be located in positions which ensure unobstructed protection of vehicles i n the area on the weather deck intended for carriage for vehicles, as far as practicab le.

Operation of monitors shall be ensured by safe access ways or remote control not to be i

mpaired by a fire in the area protected by that monitor.

Capacity of each monitor shall be at least 1,250 L/min.

The Administration may permit lower flow rates when the required rate is not practical g iven the size and arrang ement of the ship.

The Administration may also permit alternative arrangements for ships that have already installed a fixed water -based --- URL: https://wwwcdn.imo.org/localresources/en/Knowled geCentre/IndexofIMOResolutions/MSCResolutions/MSC.550(108).pdf alternative arrangements for ships that have already installed a fixed water -based fire-extinguishing system bas ed on monitor(s) prior to 1 January 2026." 17 Under the renumbered section 6.3 (Portable fire extinguishers), in the chapeau of the renumbered paragraph 6.3.2, the reference to paragraph "6.2.1" is replaced by "6.3.1" consequentially, as follows: "6.3 Portable fire extinguishers 6.3.2 In addition to the provision of paragraph 6.3.1, the following fire-extinguishing appliances shall be provided in vehicle, ro -ro and special category space s intended for the carriage of motor vehicles with fuel in their tanks for their own pro pulsion: " 18 The following new section 7 is added after existing section 6 (Fire extinc tion): "7 Decision-making (The requirements of paragraph 7 shall apply to passenger ship s constructed on or after 1 January 2026.) In passenger ships, vehicle, special category and ro-ro spaces, where fixed pressure --- URL: https://wwwcdn.imo.org/localresources/en /KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.550(108).pdf after 1 January 2 026.) In passenger ships, vehicle, special category and ro-ro spaces, where fixed pressu re water-spraying systems are fitted, shall be provided with suitable signage and markin g on deckhead and bulkhead and on the vertical boundaries allowing easy identification o f the sections o f the fixed fire -extinguishing system.

Suitable signage and markings shall be adapted to typical patterns of crew movement taki ng into consideration obstruction by cargo or fixed installations.

Section number signs shall be of photoluminescent material .

The section numbering indicated inside the space shall be same as section valve identifi cation and section identification at the safety centre or continuously manned control st ation." Regulation 23 Safety centre on passenger ships 6 Control and monitoring of safet y systems 19 Paragraph 6.10 is replaced by the following: ".10 fire detection and fire a larm system;" RESOLUTION MSC.550(108) (adopted on 23 May 2024) --- URL: https://wwwcdn.i mo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.550(10 8).pdf 19 Paragraph 6.10 is replaced by the following: ".10 fire detection and fire alar m system;" RESOLUTION MSC.550(108) (adopted on 23 May 2024) AMENDMENTS TO CHAPTERS II-2 AND V OF THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974 - 10 - CHAPTER V SAFETY OF NAVIGATION Regulation 31 Danger messages 20 The following new paragraphs are inserted after existing paragraph 1: "2.1 The master of every ship involved in the loss of freight container(s), shall communicate the particulars of such an incident by approp riate means without delay and to the fullest extent possible to ships in the vicinity, t o the nearest coastal State, and also to the flag State.

2.2 In the event of the ship referred to in paragraph 2.1 being abandoned, or in the eve nt of a report from such a ship being incomplete or unobtainable, the company, as define d in regulation IX/1.2, shall, to the fullest extent possible, assume the obligations pl aced upon the master by this regulation.

--- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/ MSCResolutions/MSC.550(108).pdf as defined in regulation IX/1.2, shall, to the fullest e xtent possible, assume the obligations placed upon the master by this regulation.

2.3 The flag State, once informed in accordance with paragraph 2.1, shall report to the Organization on the loss of freight container(s).

2.4 The master of every ship that observes freight container(s) drifting at sea, shall c ommunicate the particulars of such an observation by appropriate means without delay and to the fullest extent possible to ships in the vicinity and to the nearest coastal State ." 21 Existing paragraphs 2, 3 and 4 are renumbered as paragraphs 3, 4 and 5, respective ly.

Regulation 32 Information required in danger messages 22 The following new paragraph is inserted after existing paragraph 2 (Tropical cyclones (storms)): "3 Loss or observation of freight container(s) .1 Loss of freight container(s) from a ship It is recognized tha t at the time of the initial reporting, not all of the information --- URL: https://wwwc dn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.55 0(108).pdf .1 Loss of freight container(s) from a ship It is recognized that at the time of the initial reporting, not all of the information elements may be available.

Any subsequent and/or additional information shall be reported by the master at the earl
iest opportunity after the initial reporting.

The report shall include: .1 General information - Type of report: Loss of freight conta
iner(s) from a ship - Time (Universal Coordinated Time) and date - Ship's identity (IMO
number/name/call sign/MMSI) - From: Master of the ship, or contact details of their repr
esentative reporting on master's behalf RESOLUTION MSC.550(108) (adopted on 23 May 2024)
AMENDMENTS TO CHAPTERS II-2 AND V OF THE INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE
AT SEA, 1974 - 11 - - To: Nearest coastal State where the incident occurred and flag Sta
te - The message number: In chronological order if other freight container loss messages
are sent following the first one.

--- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/
MSCResolutions/MSC.550(108).pdf flag State - The message number: In chronological order
if other freight container loss messages are sent following the first one.

At the earliest, safe and practicable opportunity, a thorough inspection shall be conduc
ted.

The number or estimated number of lost freight container(s) shall be verified.

A message containing this verified number shall be marked as "final" and sent to the sam
e recipients.

.2 Position reporting Position in latitude and longitude, or true bearing and distance i
n nautical miles from a clearly identified landmark (where possible) - Position of the s
hip when freight container(s) were lost; or - If the position of the ship when the freig
ht container(s) were lost is not known, the estimated position of the ship when the frei
ght container(s) were lost; or - If an estimated position of the ship when the freight c
ontainer(s) were lost is not known or cannot be determined, the position of the ship upo
n discovery of the loss.

--- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/
MSCResolutions/MSC.550(108).pdf container(s) were lost is not known or cannot be determi
ned, the position of the ship upon discovery of the loss.

.3 Total number or estimated number of freight container(s) lost, as appropriate: .4 Typ
e of goods in freight container(s): - Dangerous goods: Yes/No - UN number (if known) .5
Description of freight container(s) lost as far as available and practicable: .1 Dimensi
on of freight container(s) (e.g.

20 foot); .2 Type(s) of freight container(s) (e.g.

reefer); and .3 Number or estimated number of empty freight container(s).

.6 The master may provide additional information, if available and practicable, for exam
ple but not limited to: - Cargo description according to the dangerous goods manifest (i
f applicable) - Description of any cargo spill RESOLUTION MSC.550(108) (adopted on 23 Ma
y 2024) AMENDMENTS TO CHAPTERS II-2 AND V OF THE INTERNATIONAL CONVENTION FOR THE SAFETY
OF LIFE AT SEA, 1974 - 12 - - Wind direction and speed - Sea current direction and speed
--- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/
MSCResolutions/MSC.550(108).pdf INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA,
1974 - 12 - - Wind direction and speed - Sea current direction and speed - Estimated dri
ft direction and speed of lost freight container(s) - Sea state and wave height .2 Obser
vation of freight container(s) drifting at sea .1 General information - Type of report:
Observation of freight container(s) drifting at sea - Time (Universal Coordinated Time)
and date - Ship's identity (IMO number/name/call sign/MMSI) - From: Master of the ship -
To: Nearest coastal State to the position of observation .2 Position reporting Time (Uni
versal Coordinated Time), date and position of the observed freight container(s) in lati
tude and longitude, or true bearing and distance in nautical miles from a clearly identi
fied landmark (where possible) .3 Total number of freight container(s) observed .4 The m
aster may provide additional information, if available and practicable, for example but
not limited to: --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/Indexo
fIMOResolutions/MSCResolutions/MSC.550(108).pdf .4 The master may provide additional inf
ormation, if available and practicable, for example but not limited to: - Dimension of f
reight container(s) (e.g.

20 foot) - Type(s) of freight container(s) (e.g.

reefer) - Description of any cargo spill - Wind direction and speed - Sea current direct
ion and speed - Estimated drift direction and speed of observed freight container(s) - S
ea state and wave height " 23 Existing paragraphs 3, 4 and 5 are re numbered as paragrap
hs 4, 5 and 6 , respectively.

RESOLUTION MSC.550(108) (adopted on 23 May 2024) AMENDMENTS TO CHAPTERS II-2 AND V OF TH E INTERNATIONAL CONVENTION FOR THE SAFETY OF LIFE AT SEA, 1974 RESOLUTION MSC.550(108) (adopted on 23 May 2024) AMENDMENTS TO CHAPTERS II-2 AND V OF THE INTERNATIONAL CONVENTIO N FOR THE SAFETY OF LIFE AT SEA, 1974 --- URL: https://wwwcdn.imo.org/localresources/en/ KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.548(107).pdf RESOLUTION MSC.548 (107) (adopted on 5 June 2023) INTERNATIONAL CODE OF SAFETY OR DIVING OPERATIONS, 2023 (2023 DIVING CODE) MSC 107/20/Add.1 Annex 35, page 1 I:\MSC\107\MSC 107/20/Add.1.docx ANN EX 35 RESOLUTION MSC.548(107) (adopted on 5 June 2023) INTERNATIONAL CODE OF SAFETY FOR DIVING OPERATIONS, 2023 (2023 DIVING CODE) THE MARITIME SAFETY COMMITTEE, RECALLING Arti cle 28(b) of the Convention on the International Maritime Organization concerning the fu nctions of the Committee, RECALLING ALSO that the Assembly, when adopting, by resolution A.831(19), the Code of Safety for Diving Systems, 1995 (1995 Diving Code), authorized th e Committee to amend the Code as necessary in the light of further developments and expe rience gained from