RECALLING Article 28(b) of the Convention on the International Maritime Organization con cerning the functions of the Committee, NOTING resolution MSC.391(95), by which it adopt ed the International Code of Safety for Ships using Gases or other Low -flashpoint Fuels (IGF Code), which has become mandatory under chapters II-1 and II-2 of the International Convention for the Safety of Life at Sea, 1974 ("the Convention"), NOTING ALSO article V III(b) and regulation II -1/2.28 of the Convention concerning the procedure for amending the IGF Code, HAVING CONSIDERED, at its 108th session, amendments to the IGF Code propos ed and --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResol utions/MSCResolutions/MSC.551(108).pdf procedure for amending the IGF Code, HAVING CONSI DERED, at its 108th session, amendments to the IGF Code proposed and circulated in accor dance with article VIII(b)(i) of the Convention: 1 ADOPTS, in accordance with article VI II(b)(iv) of the Convention, amendments to the IGF Code, the text of which is set out in the annex to the present resolution; 2 DETERMINES, in accordance with article VIII(b)(vi)(2)(bb) of the Convention, that the said amendments shall be deemed to have been accept ed on 1 July 2025, unless, prior to that date, more than one third of the Contracting Go vernments to the Convention or Contracting Governments the combined merchant fleets of w hich constitute not less than 50% of the gross tonnage of the world's merchant fleet hav e notified the Secretary -General of their objections to the amendments; 3 INVITES Contr acting Governments to the Convention to note that, in accordance with --- URL: https://w wwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC .551(108).pdf to the amendments; 3 INVITES Contracting Governments to the Convention to note that, in accordance with article VIII(b)(vii)(2) of the Convention, the amendments shall enter into force on 1 January 2026 upon their acceptance in accordance with paragr aph 2 above; 4 REQUESTS the Secretary -General, for the purposes of article VIII(b)(v) o f the Convention, to transmit certified copies of the present resolution and the text of the amendments contained in the annex to all Contracting Governments to the Convention; 5 ALSO REQUESTS the Secretary-General to transmit copies of this resolution and its anne x to Members of the Organization which are not Contracting Governments to the Convention .

RESOLUTION MSC.551(108) (adopted on 23 May 2024) AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) - 2 - ANNEX AMENDM ENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT F UELS (IGF CODE) Part A --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre /IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf - 2 - ANNEX AMENDMENTS TO THE INT ERNATIONAL CODE OF SAFETY FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) Part A 2 General 2.2 Definitions 1 The following new paragraph 2.2.43 is added after exi sting paragraph 2.2.42: "2.2.43 Ship constructed on or after 1 January 2026 means: .1 fo r which the building contract is placed on or after 1 January 2026; or .2 in the absence of a building contract, the keels of which are laid or which are at a similar stage of c onstruction on or after 1 July 2026; or .3 the delivery of which is on or after 1 Januar y 2030." 4 General requirements 4.2 Risk assessment 2 Paragraph 4.2.2 is replaced by the following: "4.2.2 For ships to which part A-1 applies, the risk assessment required by 4 .2.1 need only be conducted where explicitly required by paragraphs 5.10.5, 5.12.3, 6.4. 1.1, 6.4.15.4.7.2, 8.3.1.1, 8.4.2, 13.4.1, 13.7 and 15.8.1.10 as well as by paragraphs 4 .4 and 6.8 of the annex." Part A-1 --- URL: https://wwwcdn.imo.org/localresources/en/Kno wledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf 6.4.1.1, 6.4.15.4.7.2 , 8.3.1.1, 8.4.2, 13.4.1, 13.7 and 15.8.1.10 as well as by paragraphs 4.4 and 6.8 of the annex." Part A-1 Specific requirements for ships using natural gas as fuel 5 Ship design and arrangement 5.3 Regulation - General 3 Paragraph 5.3.3.3 is replaced by the followin g: "5.3.3.3 For independent tanks the protective distance shall be measured to the tank shell (the primary barrier of the fuel containment system).

For membrane tanks the distance shall be measured to the bulkheads surrounding the tank insulation." 4 Paragraph 5.3.4.4 is replaced by the following: "5.3.4.4 For independent tanks the protective distance shall be measured to the tank shell (the primary barrier o f the fuel containment system).

For membrane tanks the distance shall be measured to the bulkheads surrounding the tank insulation." RESOLUTION MSC.551(108) (adopted on 23 May 2024) AMENDMENTS TO THE INTERNAT IONAL CODE OF SAFETY --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/I ndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf RESOLUTION MSC.551(108) (adopted on 23 May 2024) AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USING GASES OR OTH ER LOW-FLASHPOINT FUELS (IGF CODE) - 3 - 5.12 Regulations for airlocks 5 Paragraph 5.12.

1 is replaced by the following: "5.12.1 For ships constructed on or after 1 January 2026
, a n air lock is a space enclosed by gastight bulkheads with two substantially gastight
doors spaced at least 1.5 m and not more than 2.5 m apart.

Unless subject to the requirements of the International Convention on Load Line, the sil
l height of the door leading to the hazardous area shall not be less than 300 mm.

The doors shall be self-closing without any holding back arrangements." 6 Fuel containme
nt system 6.4 Regulations for liquefied gas fuel containment 6.4.15 Tank types 6.4.15.3
Type C independent tanks 6.4.15.3.1 Design basis 6 Paragraph 6.4.15.3.1.2 is replaced by
the following: "6.4.15.3.1.2 The design vapour pressure shall not be less than: --- URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolu
tions/MSC.551(108).pdf 6.4.15.3.1 Design basis 6 Paragraph 6.4.15.3.1.2 is replaced by t
he following: "6.4.15.3.1.2 The design vapour pressure shall not be less than: ■0 = 0.2
+ ■■(■■) 1.5 (MPa) where: ■ = 0.00185 (■■ / ∆■■) 2 with: ■■ = design primary membrane st
ress; ∆■■ = allowable dynamic membrane stress (double amplitude at probability level Q =
10-8) and equal to: - 55 N/mm2 for ferritic-perlitic, martensitic and austenitic steel;
- 25 N/mm2 for aluminium alloy (5083-O); ■ = a characteristic tank dimension to be taken
as the greatest of the following: h, 0.75b or 0.45■, with: h = height of tank (dimension
in ship's vertical direction) (m); b = width of tank (dimension in ship's transverse dir
ection) (m); ■ = length of tank (dimension in ship's longitudinal direction) (m); ■■ = t
he relative density of the fuel (■■ = 1 for fresh water) at the design temperature." RE
SOLUTION MSC.551(108) (adopted on 23 May 2024) AMENDMENTS TO THE INTERNATIONAL CODE OF S
AFETY --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolu
tions/MSCResolutions/MSC.551(108).pdf design temperature." RESOLUTION MSC.551(108) (adop
ted on 23 May 2024) AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USING GASES
OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) - 4 - 6.7 Regulations for pressure relief syste
m 6.7.3 Sizing of pressure relieving system 6.7.3.1 Sizing of pressure relief valves 7 T
he chapeau of paragraph 6.7.3.1.1 is replaced by the following: "6.7.3.1.1 For ships con
structed on or after 1 January 2026, the pressure relief system for each liquefied gas f
uel tank shall be designed so that, regardless of the state of any one PRV, the capacity
of the residual PRVs meets the combined relieving capacity requirements of the system.

The combined relieving capacity shall be the greater of the following, with no more than
20% rise in liquefied gas fuel tank pressure above the MARVS.

The tank shall not be loaded until the full relieving capacity is restored:" 8 Paragraph
6.7.3.1.1.2 is replaced by the following: --- URL: https://wwwcdn.imo.org/localresources
/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf restored:" 8 P
aragraph 6.7.3.1.1.2 is replaced by the following: "6.7.3.1.1.2 vapours generated under
fire exposure computed using the following formula: ■ = ■■■0.82 (m3/s) where: ■ = minimu
m required rate of discharge of air at standard conditions of 273.15 Kelvin (K) and 0.10
13 MPa.

■ = fire exposure factor for different liquefied gas fuel tank types: ■ = 1.0 for tanks
without insulation located on deck; …" 6.9 Regulations for the maintaining of fuel stora
ge condition 6.9.1 Control of tank pressure and temperature 9 The chapeau of paragraph 6
.9.1.1 is replaced by the following: "6.9.1.1 For ships constructed on or after 1 Januar
y 2026, w ith the exception of liquefied gas fuel tanks designed to withstand the full g
auge vapour pressure of the fuel under conditions of the upper ambient design temperatur
e, liquefied gas fuel tanks' pressure and temperature shall be maintained at all times w
it hin their design --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/In
dexofIMOResolutions/MSCResolutions/MSC.551(108).pdf tanks' pressure and temperature shal
l be maintained at all times wit hin their design range by means acceptable to the Admin
istration, e.g.

by one or more of the following methods:" RESOLUTION MSC.551(108) (adopted on 23 May 202
4) AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USING GASES OR OTHER LOW-FLA
SHPOINT FUELS (IGF CODE) - 5 - 7 Material and general pipe design 7.3 Regulations for ge
neral pipe design 7.3.2 Wall thickness 10 Paragraph 7.3.2.1 is replaced by the following
: "7.3.2.1 For ships constructed on or after 1 January 2026, the minimum wall thickness
shall be calculated as follows: t = (t0 + b + c) / (1 – |■|/100) (mm) where: t0 = theore
tical thickness t0 = PD / (2.0Ke + P) (mm) with: P = design pressure (MPa) referred to i
n 7.3.3; D = outside diameter (mm); K = allowable stress (N/mm²) referred to in 7.3.4; a
nd e = efficiency factor equal to 1.0 for seamless pipes and for --- URL: https://wwwcdn
.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(
108).pdf K = allowable stress (N/mm²) referred to in 7.3.4; and e = efficiency factor eq
ual to 1.0 for seamless pipes and for longitudinally or spirally welded pipes, delivered

by approved manufacturers of welded pipes, that are considered equivalent to seamless pi
pes when non -destructive testing on welds is carried out in accordance with recognized
standards.

In other cases an efficiency factor of less than 1.0, in accordance with recognized stan
dards, may be required depending on the manufacturing process; b = allowance for bending
(mm).

The value of b shall be chosen so that the calculated stress in the bend, due to interna
l pressure only, does not exceed the allowable stress.

Where such justification is not given, b shall be: b = D■t0 / 2.5r (mm) with: r = mean r
adius of the bend (mm); c = corrosion allowance (mm).

If corrosion or erosion is expected the wall thickness of the piping shall be increased
over that required by other --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeC
entre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf thickness of the piping shal
l be increased over that required by other design regulations.

This allowance shall be consistent with the expected life of the piping; and ■ = negativ
e manufacturing tolerance for thickness (%), i.e.

where ■ is the manufacturing tolerance of -5%, |■| is equal to 5 and shall be entered in
to the formula as 1- (5/100)." RESOLUTION MSC.551(108) (adopted on 23 May 2024) AMENDMEN
TS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUE
LS (IGF CODE) - 6 - 8 Bunkering 8.4 Regulations for manifold 11 Paragraph 8.4.1 is repla
ced by the following: "8.4.1 The bunkering manifold shall be designed to withstand the e
xternal loads during bunkering.

The connections at the bunkering station shall be arranged in order to achieve a dry-dis
connect operation in one of the followings ways: .1 a dry-disconnect / connect coupling
in accordance with a standard at least equivalent to those acceptable to the Organizatio
n; or --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolu
tions/MSCResolutions/MSC.551(108).pdf .1 a dry-disconnect / connect coupling in accordan
ce with a standard at least equivalent to those acceptable to the Organization; or .2 a
manual connect coupler or hydraulic connect coupler, used to connect the bunker system t
o the receiving vessel bunkering manifold presentation flange; or .3 a bolted flange to
flange assembly.

12 The following new paragraphs are added after existing paragraph 8.4.1: ■8.4.2 When in
tended to use either of the connections specified in paragraphs 8.4.1.2 and 8.4.1.3, the
se shall be combined with operating procedures that ensure a dry-disconnect is achieved.

The arrangement shall be subject to special consideration informed by a bunkering arrang
ement risk assessment conducted at the design stage and considering dynamic loads at the
bunkering manifold connection to a recognized standard acceptable to the Administration,
the safe operation of the ship and other hazards that may be r elevant to the ship durin
g bunkering operation.

--- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/
MSCResolutions/MSC.551(108).pdf ship and other hazards that may be r elevant to the ship
during bunkering operation.

The fuel handling manual required by 18.2.3 shall include documentation that the bunkeri
ng arrangement risk assessment was conducted, and that special consideration was granted
under this requirement.■ ■8.4.3 An emergency release coupler (ERC) / Emergency Release S
ystem (ERS) or equivalent means shall be provided, unless installed on the bunkering sup
ply side of the bunkering line, and the said means shall be in accordance with a standar
d equivalent to those acceptable to the Organization; it shal l enable a quick physical
disconnection ■dry break-away■ of the bunker system in an emergency event." 9 Fuel suppl
y to consumers 9.3 Regulations on redundancy of fuel supply 13 Paragraph 9.3.1 is replac
ed by the following: "9.3.1 For ships constructed on or after 1 January 2026, for single
fuel installations the fuel supply system shall be arranged with redundancy and segregat
ion, so that a --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/Indexof
IMOResolutions/MSCResolutions/MSC.551(108).pdf the fuel supply system shall be arranged
with redundancy and segregation, so that a leakage in one system, or failure of one of t
he fuel supply essential auxiliaries, does not lead to an unacceptable loss of power.

In the event of a leakage or failure, and in accordance with SOLAS regulation II -1/26.3
, the Administration, having regard to overall safety considerations, may accept a parti
al reduction in propulsion capabili ty from normal operation." RESOLUTION MSC.551(108) (
adopted on 23 May 2024) AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USING G

ASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) - 7 - 9.4 Regulations on safety functions of gas supply system 14 Paragraph 9.4.7 is replaced by the following: "9.4.7 For ships constructed on or after 1 January 2026, in cases where the master gas fuel valve is automatically shut down when the safety system as required in 15.2.2 is activated, the complete gas supply pipe between this master gas fuel valve and the --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf is activated, the complete gas supply pipe between this master gas fuel valve and the double block and bleed valves and between the double block and bleed valves and the consumer shall be automatically vented." 15 Paragraph 9.4.8 is replaced by the following: "9.4.8 For ships constructed on or after 1 January 2026, there shall be one manually operated shutdown valve in the gas supply line to each gas consumer upstream of the double block and bleed valves to assure safe isolation during maintenance on the gas consumer." 9.6 Regulations for fuel supply to consumers in gas-safe machinery spaces 16 Paragraph 9.6.1.1 is replaced by the following: "9.6.1 Gas fuel piping in gas-safe machinery spaces shall be completely enclosed by a double pipe or duct fulfilling one of the following conditions: .1 the gas fuel piping shall be a double wall piping system with the gas fuel contained in the inner pipe.

The space between the concentric --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf .1 the gas fuel piping shall be a double wall piping system with the gas fuel contained in the inner pipe.

The space between the concentric pipes shall be pressurized with inert gas at a pressure greater than the gas fuel pressure.

Suitable alarms shall be provided to indicate a loss of inert gas pressure between the pipes; or" 9.8 Regulations for the design of ventilated duct, outer pipe against inner pipe gas leakage 17 Paragraph 9.8.1 is replaced by the following: "9.8.1 For ships constructed on or after 1 January 2026, the design pressure of the outer pipe or duct of fuel systems shall not be less than the maximum working pressure of the inner pipe.

Alternatively, the design pressure of the outer pipe or duct may be calculated in accordance with 9.8.2." 18 The chapeau of paragraph 9.8.2 is replaced by the following: "9.8.2 For ships constructed on or after 1 January 2026, alternatively to 9.8.1, the --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf "9.8.2 For ships constructed on or after 1 January 2026, alternatively to 9.8.1, the design pressure of the outer pipe or duct shall be taken as the higher of the following:" 19 Paragraph 9.8.4 is replaced by the following: "9.8.4 For ships constructed on or after 1 January 2026, the duct shall be pressure- tested to show that it can withstand the expected maximum pressure at fuel pipe rupture." 11 Fire safety 11.3 Regulations for fire protection 20 Paragraph 11.3.1 is replaced by the following: "11.3.1 For ships constructed on or after 1 January 2026, fuel preparation rooms shall, for the purpose of the application of SOLAS regulation II-2/9, be regarded as a machinery space of category A." RESOLUTION MSC.551(108) (adopted on 23 May 2024) AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) - 8 - 11.6 Regulations for dry chemical powder fire-extinguishing system 21 Paragraph 11.6.2 is replaced by the following: --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf - 8 - 11.6 Regulations for dry chemical powder fire-extinguishing system 21 Paragraph 11.6.2 is replaced by the following: "11.6.2 In addition to any other portable fire extinguishers that may be required elsewhere in IMO instruments, one portable dry powder extinguisher of at least 5 kg capacity shall be located near the bunkering station and in the fuel preparation room.

For ships constructed before 1 January 2026, the portable dry powder extinguisher shall be provided in the fuel preparation room not later than the first survey on or after 1 January 2026." 12 Explosion prevention 12.5 Hazardous area zones 22 Paragraph 12.5.1 is replaced by the following: "12.5.1 Hazardous area zone 0 For ships constructed on or after 1 January 2026, this zone includes, but is not limited to, the interiors of fuel tanks, any pipework for pressure relief or other venting systems for fuel tanks, pipes and equipment containing fuel, and interbarrier spaces as defined --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf for fuel tanks, pipes and equipment containing fuel, and interbarrier spaces as defined by paragraph 2.2.15.2." 12.5.2 Hazardous area zone 1 23 Paragraph 12.5.2.1 is replaced by the following: ".1 for ships constructed on or after 1 January 2026, tank connection spaces and fuel storage hold spaces;" 15 Control, monitoring and safety systems 15.4 Regulations for bunkering and liquefied gas fuel tank monitoring 15.4.1 Level indicators for liquefied gas fuel tanks 24 Paragraph 15.4.1.3 is replaced by the following: ".3 For

ships constructed on or after 1 January 2026, liquefied gas fuel tank liquid level gauge
s may be of the following types: .1 indirect devices which determine the amount of fuel
by means such as weighing or in-line flow metering; .2 closed devices which do not penet
rate the liquefied gas fuel tank, such as devices using radioisotopes or ultrasonic devi
ces; or .3 closed devices which penetrate the liquefied gas fuel tank but which --- URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolu
tions/MSC.551(108).pdf such as devices using radioisotopes or ultrasonic devices; or .3
closed devices which penetrate the liquefied gas fuel tank but which form part of a clos
ed system and keep the gas fuel from being released.

Such devices shall be considered as tank connections.

If the closed gauging device is not mounted directly onto th e tank, it shall be provide
d with a shut off valve located as close as possible to the tank." RESOLUTION MSC.551(10
8) (adopted on 23 May 2024) AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USI
NG GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) - 9 - Part B-1 16 Manufacture, workman
ship and testing 16.3 Welding of metallic materials and non -destructive testing for the
fuel containment system 16.3.5 Production weld tests 25 Paragraph 16.3.5.1 is replaced b
y the following: "16.3.5.1 For all fuel tanks and process pressure vessels except membra
ne tanks, production weld tests shall generally be performed for approximately --- URL:
https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolu
tions/MSC.551(108).pdf tanks, production weld tests shall generally be performed for app
roximately each 50 m of butt -weld joints and shall be representative of each welding po
sition.

For secondary barriers, the same type production tests as required for primary barriers
shall be performed, except that the number of tests may be reduced subject to agreement
with the Administration.

Tests, other than those specified in 16.3.5.2 to 16.3.5.5, may be required for fuel tank
s or secondary barriers." Part C-1 18 Operation 18.4 Regulations for bunkering operation
s 18.4.1 Responsibilities 26 Paragraph 18.4.1.1.1 is replaced by the following: "18.4.1.
1 Before any bunkering operation commences, the master of the receiving ship or their re
presentative and the representative of the bunkering source (Persons In Charge, PIC) sha
ll: .1 agree in writing the transfer procedure, including cooling down and if necessary,
gassing up; the maximum transfer rate at all stages ; --- URL: https://wwwcdn.imo.org/lo
calresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.551(108).pdf .1
agree in writing the transfer procedure, including cooling down and if necessary, gassin
g up; the maximum transfer rate at all stages ; minimum and maximum limiting transfer pr
essure and temperature; bunkering line PRVs settings; and volume to be transferred;" RES
OLUTION MSC.551(108) (adopted on 23 May 2024) AMENDMENTS TO THE INTERNATIONAL CODE OF SA
FETY FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) RESOLUTION MSC.551(1
08) (adopted on 23 May 2024) AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS US
ING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) --- URL: https://wwwcdn.imo.org/local
resources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.552(108).pdf RESOL
UTION MSC.553(108) (adopted on 23 May 2024) AMENDMENTS TO THE INTERNATIONAL CODE ON THE
ENHANCED PROGRAMME OF INSPECTIONS DURING SURVEYS OF BULK CARRIERS AND OIL TANKERS, 2011
(2011 ESP CODE) RESOLUTION MSC.553(108) (adopted on 23 May 2024) AMENDMENTS TO THE INTER
NATIONAL CODE ON THE ENHANCED PROGRAMME OF INSPECTIONS DURING SURVEYS OF BULK CARRIERS A
ND OIL TANKERS, 2011 (2011 ESP CODE) THE MARITIME SAFETY COMMITTEE, RECALLING Article 28
(b) of the Convention on the International Maritime Organization concerning the function
s of the Committee, NOTING resolution A.1049(27), by which the Assembly adopted the Inte
rnational Code on the Enhanced Programme of Inspections during Surveys of Bulk Carriers
and Oil Tankers, 2011 ("the 2011 ES