RECALLING Article 28(b) of the Convention on the International Maritime Organization con cerning the functions of the Committee, NOTING resolution MSC.391(95), by which it adopt ed the International Code of Safety for Ships using Gases or other Low -flashpoint Fuels (IGF Code), which has become mandatory under chapter II -1 of the International Conventi on for the Safety of Life at Sea, 1974 ("the Convention"), and subsequent amendments ado pted to the IGF Code, NOTING ALSO article VIII(b) and regulation II -1/2.28 of the Conve ntion concerning the procedure for amending the IGF Code, --- URL: https://wwwcdn.imo.or g/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.567(109).pd f NOTING ALSO article VIII(b) and regulation II -1/2.28 of the Convention concerning the procedure for amending the IGF Code, HAVING CONSIDERED, at its 109th session, amendments to the IGF Code proposed and circulated in accordance with article VIII(b)(i) of the Con vention: 1 ADOPTS, in accordance with article VIII(b)(iv) of the Convention, amendments to the IGF Code, the text of which is set out in the annex to the present resolution; 2 DETERMINES, in accordance with article VIII(b)(vi)(2)(bb) of the Convention, that the sa id amendments shall be deemed to have been accepted on 1 July 2027, unless, prior to tha t date, more than one third of the Contracting Governments to the Convention or Contract ing Governments the combined merchant fleets of which constitute not less than 50% of th e gross tonnage of the world's merchant fleet have notified the Secretary -General of th eir objections to the amendments; --- URL: https://wwwcdn.imo.org/localresources/en/Know ledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.567(109).pdf tonnage of the world's merchant fleet have notified the Secretary -General of their objections to the amendment s; 3 INVITES Contracting Governments to the Convention to note that, in accordance with article VIII(b)(vii)(2) of the Convention, the amendments shall enter into force on 1 Ja nuary 2028 upon their acceptance in accordance with paragraph 2 above; 4 REQUESTS the Se cretary -General, for the purposes of article VIII(b)(v) of the Convention, to transmit certified copies of the present resolution and the text of the amendments contained in t he annex to all Contracting Governments to the Convention; 5 ALSO REQUESTS the Secretary -General to transmit copies of this resolution and its annex to Members of the Organizat ion which are not Contracting Governments to the Convention.

RESOLUTION MSC.567(109) (adopted on 6 December 2024) AMENDMENTS TO THE INTERNATIONAL COD E OF SAFETY FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) -2- ANNEX --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCR esolutions/MSC.567(109).pdf AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USI NG GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) -2- ANNEX AMENDMENTS TO THE INTERNATIO NAL CODE OF SAFETY FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) PART A 2 General 2.2 Definitions 1 The following new paragraph 2.2.44 is added after paragraph 2.2.43: "2.2.44 Ship constructed on or after 1 January 2028 means: .1 for which the buil ding contract is placed on or after 1 January 2028; or .2 in the absence of a building c ontract, the keels of which are laid or which are at a similar stage of construction on or after 1 July 2028; or .3 the delivery of which is on or after 1 January 2032." PART A -1 Specific requirements for ships using natural gas as fuel 5 Ship design and arrangeme nt 5.3 Regulations – General 2 The following new paragraph 5.3.3.5.1 is inserted after p aragraph 5.3.3.5 and before paragraph 5.3.3.6: --- URL: https://wwwcdn.imo.org/localreso urces/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.567(109).pdf 5.3 Regul ations – General 2 The following new paragraph 5.3.3.5.1 is inserted after paragraph 5.3 .3.5 and before paragraph 5.3.3.6: "5.3.3.5.1 For ships with suction wells installed in fuel tanks, the bottom of the suction well may protrude into the vertical extent of the minimum distance specified in 5.3.3.5, provided that such wells are as small as practica ble and the protrusion below the inner bottom plating does not exceed 25% of the depth o f the double bottom or 350 mm, whichever is less." 3 In sub-paragraph 5.3.4.2, the defin ition of "H" is replaced by the following: "H is the distance from baseline, in metres, to the lowermost boundary of the fuel tank excluding the suction well, if installed; and " 7 Material and general pipe design 7.3 Regulations for general pipe design 4 The follo wing new paragraph 7.3.1.4 is inserted after paragraph 7.3.1.3 and the subsequent paragr aphs 7.3.1.4 and 7.3.1.5 are renumbered as 7.3.1.5 and 7.3.1.6 accordingly: --- URL: htt ps://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutio ns/MSC.567(109).pdf subsequent paragraphs 7.3.1.4 and 7.3.1.5 are renumbered as 7.3.1.5 and 7.3.1.6 accordingly: RESOLUTION MSC.567(109) (adopted on 6 December 2024) AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) -3- "7.3.1.4 For ships constructed on or after 1 January 2028, pressure relie f valves discharging liquid or gas from the piping system shall discharge into the fuel tanks whenever the tank MARVS pressure is lower than the setting of the pressure relief

valves in accordance with the arrangements in 9.4.2, and shall be designed to ensure tha t the required discharge capacity is met.

Alternatively, they may discharge to the vent mast, if means are provided to detect and dispose of any liquid that may flow into the vent system." 9 Fuel supply to consumers 9. 4 Regulations on safety functions of gas supply system 5 The following new paragraph 9.4 .2 is inserted after paragraph 9.4.1 and the --- URL: https://wwwcdn.imo.org/localresour ces/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.567(109).pdf 9.4 Regulat ions on safety functions of gas supply system 5 The following new paragraph 9.4.2 is ins erted after paragraph 9.4.1 and the subsequent paragraphs 9.4.2 to 9.4.10 are renumbered as 9.4.3 to 9.4.11 accordingly: "9.4.2 For ships constructed on or after 1 January 2028, fuel tank inlets from pressure relief valve discharge lines, protecting the piping syste m according to 7.3.1.4, shall be provided with non-return valves in lieu of valves that are automatically operated when the safety system required in 15.2.2 is activated.

Safe means for tank isolation during maintenance shall be available according to 18.3 wi thout affecting the proper operation of pressure relief valves." 11 Fire safety 11.3 Reg ulations for fire protection 6 Paragraph 11.3.2 is replaced by the following: "11.3.2.1 Any boundary of accommodation spaces, service spaces, control stations, escape routes an d machinery spaces, facing fuel tanks on open deck, shall be --- URL: https://wwwcdn.imo .org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.567(109) .pdf escape routes and machinery spaces, facing fuel tanks on open deck, shall be shield ed by A -60 class divisions.

The A -60 class divisions shall extend up to the underside of the deck of the navigation bridge.

For ships constructed on or after 1 January 2028, any such boundary facing the fuel tank on the open deck which is separated by a minimum distance, as determined to the satisfac tion of the Administration through a heat anal ysis to provide protection equivalent to an A -60 class division, shall be considered acceptable, and intermediate structures pro viding heat protection to the above spaces may also be considered acceptable.

Notwithstanding the above-mentioned requirements: .1 for oil tankers and chemical tanker s constructed on or after 1 January 2028, A -60 insulation, required by SOLAS regulation II - 2/9.2.4.2.5, shall be considered to meet the above -mentioned requirements provided that the fuel tank is located in the cargo area --- URL: https://wwwcdn.imo.org/localres ources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.567(109).pdf 2/9.2.4. 2.5, shall be considered to meet the above -mentioned requirements provided that the fue l tank is located in the cargo area forward of accommodation spaces, service spaces, con trol stations, escape routes and machinery spaces.

Consideration for the protection of accommodation block sides may be necessary; and .2 f or ships constructed on or after 1 January 2028, where no source of gas release from the fuel containment system is considered possible, e.g.

a type C tank in which tank connections are in a tank connection space, A-60 class shiel ding is not required.

11.3.2.2 Fuel tanks shall be segregated from cargo in accordance with the requirements o f the International Maritime Dangerous Goods (IMDG) Code where fuel tanks are regarded a s bulk packaging.

For the purposes of stowage and segregation requirements of the IMDG Code, a fuel tank o n the open deck shall be considered as a class 2.1 package." RESOLUTION MSC.567(109) (ad opted on 6 December 2024) --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCen tre/IndexofIMOResolutions/MSCResolutions/MSC.567(109).pdf a class 2.1 package." RESOLUTI ON MSC.567(109) (adopted on 6 December 2024) AMENDMENTS TO THE INTERNATIONAL CODE OF SAF ETY FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) -4- 7 Paragraph 11.3. 3.1 is replaced by the following: "11.3.3.1 Notwithstanding the last sentence in paragra ph 11.3.3, for ships constructed on or after 1 January 202 8, the fuel storage hold spac e may be considered as a cofferdam provided that: .1 the type C tank is not located dire ctly above machinery spaces of category A or other rooms with high fire risk; and .2 the minimum distance to the A-60 boundary from the outer surface of the insulation system of a type C tank or the boundary of the tank connection space, if any, is not less than 900 mm.

For the vacuum insulated type C tank, outer surface of the insulation system means outer surface of the outer shell." 12 Explosion prevention 12.5 Hazardous area zones 12.5.2 Ha zardous area zone 1 --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/In dexofIMOResolutions/MSCResolutions/MSC.567(109).pdf outer surface of the outer shell." 1

2 Explosion prevention 12.5 Hazardous area zones 12.5.2 Hazardous area zone 1 8 Sub-para graph 12.5.2.3 is replaced by the following: ".3 For ships constructed on or after 1 Jan uary 2028, areas on open deck, or semi-enclosed spaces on deck, within 3 m of any fuel t ank outlet, gas or vapour outlet, bunker manifold valve, other fuel valve, fuel pipe fla nge, ventilation outlets from zone 1 spaces and fuel tank openings for pressure release provided to permit the flow of small volumes of gas or vapour mixtures caused by thermal variation; 9 The following new sub -paragraph 12.5.2.4 is inserted after sub -paragraph 12.5.2.3 and the subsequent sub -paragraphs 12.5.2.4 to 12.5.2.9 are renumbered as 12.5. 2.5 to 12.5.2.10 accordingly: ".4 for ships constructed on or after 1 January 2028, area s on open deck, or semi -enclosed spaces on open deck above and in the vicinity of a fue l tank vent mast outlet within a vertical cylinder of --- URL: https://wwwcdn.imo.org/lo calresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.567(109).pdf de ck, or semi -enclosed spaces on open deck above and in the vicinity of a fuel tank vent mast outlet within a vertical cylinder of unlimited height and 6 m radius centred upon t he centre of t he outlet, and within a hemisphere of 6 m radius below the outlet.

Where it is not possible to maintain the above distances due to the size and layout of t he ship, a reduced zone can be accepted based on a dispersion analysis, using 50% LEL cr iteria.

Th e zone dimensions shall never be less than those given in 12.5.2.3, and shall include a surrounding zone 2 hazardous area meeting the dimensions given in 12.5.3.1." 12.5.3 Ha zardous area zone 2 10 The following new paragraph 12.5.3.3 is added after paragraph 12. 5.3.2: "12.5.3.3 In lieu of 12.5.3.1, for ships constructed on or after 1 January 2028, this zone includes spaces 4 m beyond the cylinder and 4 m beyond the hemisphere defined in 12.5.2.4".

RESOLUTION MSC.567(109) (adopted on 6 December 2024) --- URL: https://wwwcdn.imo.org/loc alresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.567(109).pdf def ined in 12.5.2.4".

RESOLUTION MSC.567(109) (adopted on 6 December 2024) AMENDMENTS TO THE INTERNATIONAL COD E OF SAFETY FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) -5- 13 Ventil ation 13.3 Regulations – General 11 Paragraph 13.3.5 is replaced by the following: "13.3 .5 For ships constructed on or after 1 January 2028, air inlets for hazardous enclosed s paces shall be taken from areas that, except for the inlets, would be non-hazardous.

Air inlets for non-hazardous enclosed spaces shall be taken from non-hazardous areas at least 1.5 m away from the boundaries of any hazardous area." 12 The following new paragr aph 13.3.8 is inserted after paragraph 13.3.7 and the subsequent paragraphs 13.3.8 to 13 .3.10 are renumbered as 13.3.9 to 13.3.11 accordingly: "13.3.8 For ships constructed on or after 1 January 2028: .1 where the ventilation ducts serving non -hazardous spaces pa ss through a hazardous space, the ducts shall be gastight and have --- URL: https://wwwc dn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.56 7(109).pdf .1 where the ventilation ducts serving non -hazardous spaces pass through a h azardous space, the ducts shall be gastight and have overpressure relative to that hazar dous space; and .2 where the ventilation ducts serving hazardous spaces pass through les s hazardous or non -hazardous spaces, the ducts shall be gastight and have underpressure relative to the less hazardous or non-hazardous spaces.

Ventilation pipes serving hazardous spaces that pass through less hazardous or non -haza rdous spaces are acceptable without the need for underpressure, provided that they are f ully welded and designed in accordance with chapter 7." _____ RESOLUTION MSC.567(1 09) (adopted on 6 December 2024) AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIP S USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) RESOLUTION MSC.567(109) (adopted on 6 December 2024) AMENDMENTS TO THE INTERNATIONAL CODE OF SAFETY FOR SHIPS USING GASES OR OTHER LOW-FLASHPOINT FUELS (IGF CODE) --- URL: https://wwwcdn.imo.org/localresources/ en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.563(108).pdf RESOLUTION MSC. 563(108) (adopted on 23 May 2024) AMENDMENTS TO THE REVISED RECOMMENDATION ON TESTING OF LIFE-SAVING APPLIANCES (RESOLUTION MSC.81(70)) MSC 108/20/Add.1 Annex 15, page 1 I:\MSC\ 108\MSC 108-20-Add.1.docx ANNEX 15 RESOLUTION MSC.563(108) (adopted on 23 May 2024) AMEN DMENTS TO THE REVISED RECOMMENDATION ON TESTING OF LIFE-SAVING APPLIANCES (RESOLUTION MS C.81(70)) THE MARITIME SAFETY COMMITTEE, RECALLING Article 28(b) of the Convention on th e International Maritime Organization concerning the functions of the Committee, RECALLI NG ALSO that the Assembly, when adopting resolution A.689(17) on Testing of life-saving appliances, authorized the Committee to keep the annexed Recommendation on testing of li fe -saving applianc