of Ships Carrying Dangerous Chemical s in Bulk adopted by the Maritime Safety Committee by resolution MSC.4(48), hereinafter referred to as “the International Bulk Chemical Co de”, as may be amended by the Organization; or .2 chapter VI of the Code for the Constru ction and Equipment of Ships Carrying Dangerous Chemicals in Bulk adopted by the Assembl y of the Organization by resolution A.212(VII), hereinafter referred to as “the Bulk Che mical Code”, as has been or may be amended by the Organization, whichever is applicable.

20 Gas carrier is a cargo ship constructed or ad apted and used for the carriage in bulk of any liquefied gas or other products listed in either: .1 chapter 19 of the Internatio nal Code for the Construction and Equipment of Ships Carrying Liquefied Gases in Bulk ad opted by the Maritime Safety Committee by resolution MSC.5(48), he reinafter referred to as “the International Gas Carrier Code”, as may be amended by the Organization; or - Com mittee by resolution MSC.5(48), he reinafter referred to as “the International Gas Carri er Code”, as may be amended by the Organization; or .2 chapter XIX of the Code for the C onstruction and Equipment of Ships Carrying Liquefied Gases in Bulk adopted by the Organ ization by resolution A.328(IX), herein after referred to as “the Gas Carrier Code”, as has been or may be amended by the Organization, whichever is applicable.

RESOLUTION MSC.216(82) (adopted on 8 December 2006) AMENDMENTS TO THE INTERNATIONAL CONV ENTION FOR THE SAFETY OF LIFE AT SEA, 1974, AS AMENDED- 18 - PART B SUBDIVISION AND STAB ILITY Regulation 4 General 1 The damage stability requirements in pa rts B-1 through B-4 shall apply to cargo ships of 80 m in length (L) and upwards and to all passenge r ship s regardless of length but shall exclude those cargo ships which are shown to co mply wi th subdivision and - ships of 80 m in length (L) and upwards and to all passenge r ship s regardless of length but shall exclude those cargo ships which are shown to co mply wi th subdivision and damage stability regulations in other instruments developed by the Or ganization.

2 The Administration may, for a particular ship or group of ships, accept alternative me thodologies if it is satisfied that at least the same degree of safety as represented by these regulations is achieved.

Any Admi nistration which allows such alternative methodologies shall communicate to the Organization particulars thereof.

3 Ships shall be as efficiently subdivided as is possible having regard to the nature of the service for which they are intended.

The degree of subdivision shall vary with the subdivision length (Ls) of the ship and w ith the service, in such manner that the highest degree of subdivision corresponds with th e ships of greatest subdivision length (Ls), - subdivision length (Ls) of the ship and with the service, in such manner that the highest degree of subdivision corresponds with th e ships of greatest subdivision length (Ls), primarily engaged in the carriage of passengers.

4 Where it is proposed to fit decks, inner skins or longitudinal bulkheads of sufficient tightness to seriously restrict the flow of water, the Administration shall be satisfied that proper consideration is given to beneficial or adve rse effects of such structures in the calculations.

PART B-1 STABILITY Regulation 5 Intact stability information 1 Every passenger ship rega rdless of si ze and every cargo ship having a length (L) of 24 m and upwards, shall be inclined upon its completion and the elements of its stability determined.

2 The Administration may allow the inclining test of an individ