RECALLING Article 28(b) of the Convention on the International Maritime Organization con cerning the functions of the Committee, RECALLING ALSO resolution MSC.98(73), by which i t adopted the International Code for Fire Safety Systems ("the FSS Code"), which has bec ome mandatory under chapter II -2 of the International Convention for the Safety of Life at Sea, 1974 ("the Convention"), RECALLING FURTHER article VIII(b) and regulation II -2/ 3.22 of the Convention concerning the procedure for amending the FSS Code, HAVING CONSID ERED, at its 108th session, amendments to the FSS Code, proposed and circulated in accor dance with article VIII(b)(i) of the Convention, --- URL: https://wwwcdn.imo.org/localre sources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.555(108).pdf circula ted in accordance with article VIII(b)(i) of the Convention, 1 ADOPTS, in accordance wit h article VIII(b)(iv) of the Convention, amendments to the FSS Code, the text of which i s set out in the annex to the present resolution; 2 DETERMINES, in accordance with artic le VIII(b)(vi)(2)(bb) of the Convention, that the amendments shall be deemed to have bee n accepted on 1 July 2025 unless, prior to that date, more than one third of the Contrac ting Governments to the Convention, or Cont racting Governments the combined merchant fl eets of which constitute not less than 50% of the gross tonnage of the world's merchant fleet have notified the Secretary -General of their objections to the amendments; 3 INVI TES Contracting Governments to note that, in accordance with article VIII(b)(vii)(2) of the Convention, the amendments shall enter into force on 1 January 2026 upon their accep tance in accordance with paragraph 2 above; --- URL: https://wwwcdn.imo.org/localresourc es/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.555(108).pdf upon their a cceptance in accordance with paragraph 2 above; 4 REQUESTS the Secretary -General, in co nformity with article VIII(b)(v) of the Convention, to transmit certified copies of the present resolution and the text of the amendments contained in the annex to all Contract ing Governments to the Convention; 5 ALSO REQUESTS the Secretary-General to transmit cop ies of this resolution and its annex to Members of the Organization which are not Contra cting Governments to the Convention.

RESOLUTION MSC.555(108) (adopted on 23 May 2024) AMENDMENTS TO THE INTERNATIONAL CODE FO R FIRE SAFETY SYSTEMS (FSS CODE) - 2 - ANNEX AMENDMENTS TO THE INTERNATIONAL CODE FOR FI RE SAFETY SYSTEMS (FSS CODE) CHAPTER 7 Fixed pressure water-spraying and water mist fire -extinguishing systems 2 Engineering specifications 1 The following new section 2.5 is a dded after existing section 2.4 (Fixed water-based fire-fighting systems for ro-ro space s, vehicle spaces and special category spaces): --- URL: https://wwwcdn.imo.org/localres ources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.555(108).pdf fire-fig hting systems for ro-ro spaces, vehicle spaces and special category spaces): "2.5 Fixed water-based fire-extinguishing system on ro-ro passenger ships' weather decks intended f or the carriage of vehicles This paragraph details the specification of fixed water-base d fire-extinguishing system on ro-ro passenger ships having weather decks intended for t he carriage of vehicles as required by chapter II -2 of the Convention.

The requirements of this paragraph shall apply to ro-ro passenger ships constructed on o r after 1 January 2026.

2.5.1 The protected area shall be the entire length and width of the weather deck intend ed for the carriage of vehicles.

The fixed monitor(s) shall be capable of delivering water to: .1 the area of weather dec ks intended for carriage of vehicles; and .2 the area, including superstructure boundari es located up to 8.0 m, measured horizontally, from the area intended for vehicle storag e, or the next vertical boundaries, whichever is less.

--- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/ MSCResolutions/MSC.555(108).pdf measured horizontally, from the area intended for vehicl e storage, or the next vertical boundaries, whichever is less.

2.5.2 The combined capacity of all fixed monitors shall be minimum 2.0 L/min per square metre of the protected area, but in no case shall the output of any monitor be less than 1,250 L/min.

Even distribution of water shall be ensured.

2.5.3 The distance from the monitor to the farthest extremity of the protected area forw ard of that monitor shall not be more than 75% of the monitor throw in still air conditi ons.

2.5.4 Each monitor shall be located outside the area which it protects, in a safe positi on, with access not likely to be cut off in case of fire.

Monitors shall be installed in positions which allow for unobstructed water coverage wit
h vehicles stowed to maximum capacity of the weather deck.

However, areas that cannot be covered by water monitors shall be protected by water nozz
les.

--- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/
MSCResolutions/MSC.555(108).pdf cannot be covered by water monitors shall be protected b
y water nozzles.

Nozzles shall be designed and installed taking into account weather conditions and provi
de 5.0 L/min per square metre for the area they cover and have release controls in a pos
ition being accessible in case of a fire.

2.5.5 The system shall be available for immediate use and capable of continuously supply
ing water.

The water supply shall be capable of simultaneously supplying water at the required rate
for the entire width of the weather deck intended for carriage of vehicles and a length
of 40 m, or the entire length of the weather deck if this is less than 40 m.

In no case shall the supply capacity be less than that required for the largest monitor.

RESOLUTION MSC.555(108) (adopted on 23 May 2024) AMENDMENTS TO THE INTERNATIONAL CODE FO
R FIRE SAFETY SYSTEMS (FSS CODE) - 3 - 2.5.6 The system may be supplied by the fire main
, the pump(s) serving other fixed --- URL: https://wwwcdn.imo.org/localresources/en/Know
ledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.555(108).pdf - 3 - 2.5.6 The system
may be supplied by the fire main, the pump(s) serving other fixed water-based fire-fight
ing systems or a dedicated pump providing a continuous supply of seawater.

Where the ship's fire pumps are used to feed the monitor(s): .1 it shall be possible to
segregate the ship's fire main from the monitor(s) by means of a valve in order to opera
te both systems separately or simultaneously; and .2 the capacity of the pumps shall be
sufficient to serve both systems simultaneously, including two jets of water at the requ
ired pressure from the fire main system.

In case the weather deck shall also carry dangerous goods, capacity for four jets of wat
er at the required pressure shall be provided.

Where another fixed water-based fire-fighting system is used to feed the monitor(s): .3
it shall be possible to segregate the other fixed water -based fire-fighting system from
the monitor(s) by means of a valve in order --- URL: https://wwwcdn.imo.org/localresourc
es/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.555(108).pdf .3 it shall
be possible to segregate the other fixed water -based fire-fighting system from the moni
tor(s) by means of a valve in order to operate both systems separately or simultaneously
; and .4 the capacity of the pump(s) shall, in case of open ro -ro spaces, be sufficient
to serve both systems simultaneously, minimum two sections of the fixed water-based fire
-fighting system being close to the openings facing weather deck and one monitor serving
the weather deck.

For closed ro-ro spaces and special category spaces, simultaneous operation is not requi
red." CHAPTER 9 Fixed fire detection and fire alarm systems 1 Application 2 Paragraph 1.
1 is replaced by the following: "1.1 This chapter details the specification of fixed fir
e detection and fire alarm systems as required by chapter II -2 of the Convention.

Unless expressly provided otherwise, the requirements of this chapter shall apply to shi
ps constructed on or after --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCe
ntre/IndexofIMOResolutions/MSCResolutions/MSC.555(108).pdf otherwise, the requirements o
f this chapter shall apply to ships constructed on or after 1 July 2 012.

The requirements of 2.3.1.5 and 2.4.2.2 of this chapter shall apply to ships constructed
on or after 1 January 2026." 2 Engineering specifications 2.3 Component requirements 3 P
aragraphs 2.3.1.3 and 2.3.1.4 are replaced by the following: "2.3.1.3 Heat detectors and
linear heat detectors shall be certified to operate before the temperature exceeds 78ºC
but not until the temperature exceeds 54ºC, when the temperature is raised to those limi
ts at a rate less than 1ºC per min, when tested according to relevant parts of standards
EN 54:2001 and IEC 60092-504.

Alternative testing standards may be used as determined by the Administration.

At higher rates of temperature rise, the heat detector and linear heat detector shall op
erate within temperature limits to the satisfaction of the Administration having regard
to the avoidance of detector insensitivity or oversensitivity.

--- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/

MSCResolutions/MSC.555(108).pdf temperature limits to the satisfaction of the Administra tion having regard to the avoidance of detector insensitivity or oversensitivity.

RESOLUTION MSC.555(108) (adopted on 23 May 2024) AMENDMENTS TO THE INTERNATIONAL CODE FO R FIRE SAFETY SYSTEMS (FSS CODE) - 4 - 2.3.1.4 The operation temperature of heat detecto rs and linear heat detectors in drying rooms and similar spaces of a normal high ambient temperature may be up to 130ºC, and up to 140ºC in saunas." 4 The following new paragrap h 2.3.1.5 is inserted after the existing paragraph 2.3.1.4 and subsequent paragraphs are renumbered accordingly: "2.3.1.5 Linear heat detectors shall be tested according to stan dards EN 54-22:2015 and IEC 60092-504.

Alternative testing standards may be used as determined by the Administration." 2.4 Inst allation requirements 2.4.2 Positioning of detectors 5 Paragraph 2.4.2.2 and the associa ted table 9.1 (Spacing of detectors) therein are replaced by the following: --- URL: htt ps://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutio ns/MSC.555(108).pdf 2.4.2 Positioning of detectors 5 Paragraph 2.4.2.2 and the associate d table 9.1 (Spacing of detectors) therein are replaced by the following: "2.4.2.2 The m aximum spacing of detectors shall be in accordance with the table below: Table 9.1 – Spa cing of detectors Type of detector Maximum floor area per detector (m2) Maximum distance apart between centres (m) Maximum distance away from bulkheads (m) Heat 37 9 4.5 Smoke 7 4 11 5.5 Combined smoke and heat 74 9 4.5 2.4.2.2.1 The Administration may require or pe rmit other spacing based upon test data which demonstrate the characteristics of the det ectors.

Detectors located below movable ro-ro decks shall be in accordance with the above.

2.4.2.2.2 The distance between two sensor cables of the linear heat detection system sha ll not be more than 9.0 m, while the distance between such cables and bulkheads shall no t be more than 4.5 m." 2.5 System control requirements 2.5.1 Visual and audible fire sig nals --- URL: https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolut ions/MSCResolutions/MSC.555(108).pdf bulkheads shall not be more than 4.5 m." 2.5 System control requirements 2.5.1 Visual and audible fire signals 6 The following new paragraph s 2.5.1.2, 2.5.1.3 and 2.5.1.4 are inserted after paragraph 2.5.1.1 and the subsequent p aragraphs are renumbered accordingly: "2.5.1.2 On ro -ro passenger ships constructed on or after 1 January 2026, alarm notifications shall follow a consistent alarm presentatio n scheme (wording, vocabulary, colour and position).

Alarms shall be immediately recognizable on the navigation bridge and shall not be compr omised by noise or poor placing.

2.5.1.3 On ro -ro passenger ships constructed on or after 1 January 2026, the interface shall provide alarm addressability, allow the crew to identify the alarm history, the mo st recent alarm and the means to suppress alarms while ensuring the alarms with ongoing trigger conditions are still clearly visible.

RESOLUTION MSC.555(108) (adopted on 23 May 2024) --- URL: https://wwwcdn.imo.org/localre sources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC.555(108).pdf alarms with ongoing trigger conditions are still clearly visible.

RESOLUTION MSC.555(108) (adopted on 23 May 2024) AMENDMENTS TO THE INTERNATIONAL CODE FO R FIRE SAFETY SYSTEMS (FSS CODE) - 5 - 2.5.1.4 On ro-ro passenger ships constructed on o r after 1 January 2026, the smoke detector function in special category and ro -ro space s may be disconnected during loading and unloading of vehicles.

The time of disconnection shall be adapted to the time of loading/unloading and be autom atically reset after this predetermined t ime.

The central unit shall indicate whether the detector sections are disconnected or not.

Disconnection of the heat detection function or manual call points shall not be permitte d." RESOLUTION MSC.555(108) (adopted on 23 May 2024) AMENDMENTS TO THE INTERNATIONAL COD E FOR FIRE SAFETY SYSTEMS (FSS CODE) RESOLUTION MSC.555(108) (adopted on 23 May 2024) AM ENDMENTS TO THE INTERNATIONAL CODE FOR FIRE SAFETY SYSTEMS (FSS CODE) --- URL: https://w wwcdn.imo.org/localresources/en/KnowledgeCentre/IndexofIMOResolutions/MSCResolutions/MSC .555(108).pdf RESOLUTION MSC.555(108) (adopted on 23 May 2024) AMENDMENTS TO THE INTERNA TIONAL CODE FOR FIRE SAFETY SYSTEMS (FSS CODE) RESOLUTION MSC.555(108) (adopted on 23 Ma y 2024) AMENDMENTS TO THE INTERNATIONAL CODE FOR FIRE SAFETY SYSTEMS (FSS CODE) THE MARI TIME SAFETY COMMITTEE, RECALLING Article 28(b) of the Convention on the International Ma ritime Organization concerning the functions of the Committee, RECALLING ALSO resolution MSC.98(73), by which it adopted the International Code for Fire Safety Systems ("the FSS Code"), which has become mandatory under chapter II -2 of the International Convention f or the Safety of Life at Sea, 1974 ("the Convention"), RECALLING FURTHER article VIII(b)

and regulation II -2/3.22 of the Convention concernin