

Ex. No: 11

```
CREATE KEYSPACE library WITH REPLICATION = { 'class': 'SimpleStrategy',  
'replication_factor': 3 };
```

Output:

Keyspace created.

```
USE library;
```

Output:

Context switched to library.

```
CREATE TABLE authors (  
  AuthorID int PRIMARY KEY,  
  FirstName text,  
  LastName text  
);
```

Output:

Table created.

```
INSERT INTO authors (AuthorID, FirstName, LastName) VALUES (1, 'George',  
'Orwell');  
INSERT INTO authors (AuthorID, FirstName, LastName) VALUES (2, 'Aldous',  
'Huxley');  
INSERT INTO authors (AuthorID, FirstName, LastName) VALUES (3, 'J.K.',  
'Rowling');
```

Output:

3 rows inserted.

```
SELECT * FROM authors;
```

Output:

authorid	firstname	lastname
1	George	Orwell
2	Aldous	Huxley
3	J.K.	Rowling

```
UPDATE authors SET LastName = 'Smith' WHERE AuthorID = 1;  
SELECT * FROM authors WHERE AuthorID = 1;
```

Output:

authorid	firstname	lastname
1	George	Smith

DELETE FROM authors WHERE AuthorID = 1;

SELECT * FROM authors WHERE AuthorID = 1;

Output:

(Empty result set)