

Ex. No: 13

BEGIN

```
DBMS_XMLSCHEMA.registerSchema(  
    schemaurl => 'my_schema.xsd',  
    schemadoc => '<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema"  
elementFormDefault="qualified">  
<xs:element name="shiporder"><xs:complexType><xs:sequence>  
<xs:element name="orderperson" type="xs:string"/>  
<xs:element name="shipto"><xs:complexType><xs:sequence>  
<xs:element name="name" type="xs:string"/>  
<xs:element name="address" type="xs:string"/>  
<xs:element name="city" type="xs:string"/>  
<xs:element name="country" type="xs:string"/>  
</xs:sequence></xs:complexType></xs:element>  
<xs:element name="item"  
maxOccurs="unbounded"><xs:complexType><xs:sequence>  
<xs:element name="title" type="xs:string"/>  
<xs:element name="note" type="xs:string" minOccurs="0"/>  
<xs:element name="quantity" type="xs:positiveInteger"/>  
<xs:element name="price" type="xs:decimal"/>  
</xs:sequence></xs:complexType></xs:element>  
</xs:sequence><xs:attribute name="orderid" type="xs:string"  
use="required"/></xs:complexType></xs:element>  
</xs:schema>',  
    local    => TRUE,  
    gentypes => FALSE,  
    gentables => FALSE);  
END;  
/
```

Output:

PL/SQL procedure successfully completed.

```
CREATE TABLE t1 (id NUMBER, xml_doc XMLTYPE);
```

Output:

Table created.

```
INSERT INTO t1 VALUES (1, XMLTYPE(q'[<?xml version="1.0" encoding="UTF-  
8"?>  
<shiporder orderid="889923">  
<orderperson>John Smith</orderperson>
```

```

<shipto><name>Ola Nordmann</name><address>Langgt 23</address><city>4000
Stavanger</city><country>Norway</country></shipto>
<item><title>Empire Burlesque</title><note>Special
Edition</note><quantity>1</quantity><price>10.90</price></item>
<item><title>Hide your
heart</title><quantity>1</quantity><price>9.90</price></item>
</shiporder>]]);
INSERT INTO t1 VALUES (2, XMLTYPE(q['<?xml version="1.0" encoding="UTF-
8"?>
<shiporder orderid="889923">
<orderperson>John Smith</orderperson>
<shipto><name1>Ola Nordmann</name1><address>Langgt 23</address><city>4000
Stavanger</city><country>Norway</country></shipto>
<item><title>Empire Burlesque</title><note>Special
Edition</note><quantity>1</quantity><price>10.90</price></item>
<item><title>Hide your
heart</title><quantity>1</quantity><price>9.90</price></item>
</shiporder>]]));

```

Output:

2 rows created.

COMMIT;

Output:

Commit complete.

```
SELECT t.id, t.xml_doc.isSchemaValid('my_schema.xsd') AS is_valid FROM t1 t;
```

Output:

ID	IS_VALID
1	1
2	0