

Ex. No: 8

System-defined exception:

```
SET SERVEROUTPUT ON;
DECLARE
    c_id customers.id%type := 5;
    c_name customers.name%type;
    c_addr customers.address%type;
BEGIN
    SELECT name, address INTO c_name, c_addr FROM customers WHERE id = c_id;
    dbms_output.put_line('name: ' || c_name);
    dbms_output.put_line('address: ' || c_addr);
EXCEPTION
    WHEN no_data_found THEN
        dbms_output.put_line('no such customer!');
    WHEN others THEN
        dbms_output.put_line('error!');
END;
/
```

Output:

```
name: Hardik
address: Bhopal
PL/SQL procedure successfully completed.
```

User-defined exception:

```
DECLARE
    c_id customers.id%type := &cc_id;
    c_name customers.name%type;
    c_addr customers.address%type;
    ex_invalid_id EXCEPTION;
BEGIN
    IF c_id <= 0 THEN
        RAISE ex_invalid_id;
    ELSE
        SELECT name, address INTO c_name, c_addr FROM customers WHERE id =
c_id;
        DBMS_OUTPUT.PUT_LINE('Name: ' || c_name);
        DBMS_OUTPUT.PUT_LINE('Address: ' || c_addr);
    END IF;
END;
```

```
END IF;  
EXCEPTION  
  WHEN ex_invalid_id THEN  
    dbms_output.put_line('ID must be greater than zero!');  
  WHEN no_data_found THEN  
    dbms_output.put_line('No such customer!');  
  WHEN others THEN  
    dbms_output.put_line('Error!');  
END;  
/
```

Output:

*Enter value for cc_id: -6
ID must be greater than zero!
PL/SQL procedure successfully completed.*