Main.java

Share Run

```java
import java.util.Scanner;
class Main {
    public static void main(String[] args) {
        Scanner as=new Scanner(System.in);
        int i,n,m;
        n=as.nextInt();
        m=as.nextInt();
        for( i=1;i<=m;i++)
    {
         System.out.println(n*i);
    }

    }

}

```

Output

```
7
4
7
14
21
28

=== Code Execution Successful ===
```

```java
import java.util.Scanner;
class Main {
    public static void main(String[] args) {
        Scanner as=new Scanner(System.in);
        int n;
        n=as.nextInt();
        if(n%4==0){
            System.out.println("Divisible");

        }
        else{
            System.out.println("Not Divisible");
        }

    }
}
```

```
4
Divisible

=== Code Execution Successful ===
```

```java
import java.util.Scanner;
class Main {
    public static void main(String[] args) {
        Scanner as=new Scanner(System.in);
        int mark;
        mark=as.nextInt();
        if(mark>=40){
            System.out.println("pass");
        }
        else{
            System.out.println("fail");
        }
    }
}
```

```
45
pass

=== Code Execution Successful ===
```

```java
import java.util.Scanner;
class Main {
    public static void main(String[] args) {
        Scanner as=new Scanner(System.in);
        int temp,f;
        temp=as.nextInt();
        f=((temp*(9/5))+32);
        System.out.println(f);
    }
}
```

```
12
44

=== Code Execution Successful ===
```

```java
import java.util.Scanner;
class Main {
    public static void main(String[] args) {
        Scanner as=new Scanner(System.in);
        int l,b;
        l=as.nextInt();
        b=as.nextInt();
        System.out.println("Perimeter="+(2*(l+b)));
    }
}
```

```
5
2
Perimeter=14

=== Code Execution Successful ===
```

```java
import java.util.Scanner;
class Main {
    public static void main(String[] args) {
        Scanner as=new Scanner(System.in);
        int n;
        n=as.nextInt();
        System.out.println("n=10");
    }
}
```

```
5
n=10

=== Code Execution Successful ===
```

```java
import java.util.Scanner;
class Main {
    public static void main(String[] args) {
        Scanner as=new Scanner(System.in);
        int a,b,c,d;
        a=as.nextInt();
        b=as.nextInt();
        c=as.nextInt();
        d=as.nextInt();
        if(a>b && a>c &&a>d)
        {
            System.out.println("A is greater");
        }
        else if (c>a && c>b && c>d)
        {
            System.out.println("C is greater");
        }
        else if(b>a && b>c && b>d)
        {
            System.out.println("b is greater ");
        }
            else{
                System.out.println("d is greater");
            }
    }
}
```

```
5
6
7
9
d is greater

=== Code Execution Successful ===
```

```java
import java.util.Scanner;
class Main {
    public static void main(String[] args) {
        Scanner as=new Scanner(System.in);
        int n;
        n=as.nextInt();
        if(n>100)
        {
            System.out.println("the number is greater than 100");
        }
        else{
            System.out.println("the numbr is not greater than 100");
        }
    }
}
```

```
99
the numbr is not greater than 100

=== Code Execution Successful ===
```

```java
import java.util.Scanner;
class Main {
    public static void main(String[] args) {
        Scanner as=new Scanner(System.in);
        int a,b,c,d,e;
        a=as.nextInt();
        b=as.nextInt();
        c=as.nextInt();
        d=as.nextInt();
        e=((a+b+c+d)/4);
        System.out.println("average="+e);
    }
}
```

```
1
2
3
4
average=2

=== Code Execution Successful ===
```

```java
import java.io.*;
import java.util.*;

public class Solution {

    public static void main(String[] args) {
        Scanner as=new Scanner(System.in);
        int n=as.nextInt();
        int fact=1;
        for(int i=1;i<=n;i++)
        {
            fact=fact*i;
        }
        System.out.println(fact);
    }
}
```

```
8
40320

=== Code Execution Successful ===
```

```java
import java.io.*;
import java.util.*;

public class Solution {

    public static void main(String[] args) {
        Scanner as=new Scanner(System.in);
        int a;
        a=as.nextInt();
        System.out.println("next number="+(a+1));
    }
}
```

```
2
next number=3

=== Code Execution Successful ===
```

```java
import java.io.*;
import java.util.*;

public class Solution {

    public static void main(String[] args) {
        Scanner as=new Scanner(System.in);
        int count=0;
        int n=as.nextInt();
        if(n==0)
        {
            count=1;
        }
        else{
            while(n>0){
                n=n/10;
                count++;
            }
        }
        System.out.println(count);
    }
}
```

```
4599
4

=== Code Execution Successful ===
```

```java
import java.io.*;
import java.util.*;

public class Solution {

    public static void main(String[] args) {
        Scanner as=new Scanner(System.in);
       int sum=0;
        for (int i=1;i<=50;i++)
        {
            if(i%2!=0)
            {
        sum=sum+i;
            }
        }
        System.out.println(sum);
    }
}
```

```
625

=== Code Execution Successful ===
```

```java
import java.io.*;
import java.util.*;

public class Solution {

    public static void main(String[] args) {
        Scanner as=new Scanner(System.in);
       int sum=0;
        for (int i=1;i<=50;i++)
        {
            if(i%2!=0)
            {
        sum=sum+i;
            }
        }
        System.out.println(sum);
    }
}
```

```
625

=== Code Execution Successful ===
```

```java
import java.io.*;
import java.util.*;

public class Solution {

    public static void main(String[] args) {
        Scanner as=new Scanner(System.in);
       int a,b;
      int sum=0;
      a=as.nextInt();
      while(a>0)
      {
          b=a%10;
          sum=sum+b;
          a=a/10;
      }
      System.out.println(sum);
    }
}
```

```
123
6

=== Code Execution Successful ===
```

```java
import java.io.*;
import java.util.*;
public class Solution {
    public static void main(String[] args) {
        Scanner as=new Scanner(System.in);
       int n=as.nextInt();
       int count=0;
       for(int i=1;i<=n;i++){
           if(i%2==0){
               count++;
           }
       }
      System.out.println(count);
    }


}
```

```
8
4

=== Code Execution Successful ===
```

```java
import java.io.*;
import java.util.*;
public class Solution {
    public static void main(String[] args) {
        Scanner as=new Scanner(System.in);
       int n=as.nextInt();
       int count=0;
       for(int i=1;i<=n;i++){
           if(i%2==0){
               count++;
           }
       }
      System.out.println(count);
    }


}

```

```
8
4

=== Code Execution Successful ===
```

```java
import java.io.*;
import java.util.*;
public class Solution {
    public static void main(String[] args) {
        Scanner as=new Scanner(System.in);
       int n=as.nextInt();
       int s;
       int count=0;
       while(n>0){
           s=n%10;
           if(s>=5){
               count++;
           }
           n=n/10;
       }System.out.println(count);
    }
}
```

```
6
1

=== Code Execution Successful ===
```

```java
import java.io.*;
import java.util.*;
public class Solution {
    public static void main(String[] args) {
        Scanner as=new Scanner(System.in);
      int n=as.nextInt();
      int s;
      int count=0;
      while(n>0){
          s=n%10;
          if(s==0){
              count++;
          }
          n=n/10;
      }System.out.println(count);
    }
}
```

```
202090
3

=== Code Execution Successful ===
```

```java
import java.io.*;
import java.util.*;
public class Solution {
    public static void main(String[] args) {
        Scanner as=new Scanner(System.in)
       int n=as.nextInt();
       for(int i=1;i<=n;i++){
           if(i%2==0){
           System.out.println(i);
           }
       }
    }
}
```

```
10
2
4
6
8
10

=== Code Execution Successful ===
```