## EXPERIMENT:01 Write the Python Program to solve 8-Puzzle Problem.

## **PROGRAM:**

```
from collections import deque
```

```
GOAL = [[1,2,3],[4,5,6],[7,8,0]]
DIRS = [(-1,0),(1,0),(0,-1),(0,1)]
def find blank(s): return [(i,j) for i in range(3) for j in range(3) if s[i][j]==0][0]
def clone(s): return [r[:] for r in s]
def bfs(start):
  q, visited = deque([(start, [])]), set()
  while q:
     state, path = q.popleft()
     if state == GOAL: return path + [state]
     b = tuple(sum(state, []))
     if b in visited: continue
     visited.add(b)
     i,j = find blank(state)
     for di,dj in DIRS:
       ni,nj = i+di,j+dj
       if 0<=ni<3 and 0<=nj<3:
          new = clone(state)
          new[i][j], new[ni][nj] = new[ni][nj], new[i][j]
          q.append((new, path+[state]))
start state = [[1,2,3],[4,0,6],[7,5,8]]
for step in bfs(start_state):
  for row in step: print(row)
  print()
```

## **OUTPUT:**

```
[1, 2, 3]
[4, 0, 6]
[7, 5, 8]

[1, 2, 3]
[4, 5, 6]
[7, 0, 8]

[1, 2, 3]
[4, 5, 6]
[7, 8, 0]

...Program finished with exit code 0
Press ENTER to exit console.
```