Implementation and Linguistic Evaluation of FastSpeech 2 for English and Telugu

Non-Autoregressive Text-to-Speech Synthesis | Svarah & IndicTTS Benchmarks

Candidate: Nanda Kishore Devarashetti	**Institution:** Vasavi College of Engineering
Email: dev.nandakishoredevarashetti@gmail.com	**Contact:** +91 8019976509
Languages: English (Svarah) & Telugu (IndicTTS)	**Date:** November 7, 2026 | Vocoder: BigVGAN 22kHz

1. Implementation Approach & Architectural Modifications

FastSpeech 2 represents a landmark non-autoregressive acoustic model that directly addresses the one-to-many mapping challenge in text-to-speech synthesis by conditioning speech generation on explicit variance features: **phoneme durations**, **fundamental frequency (F0) pitch contours**, and **acoustic energy frame magnitudes**. Unlike two-stage teacher-student pipelines (FastSpeech 1), FastSpeech 2 is trained directly from ground-truth features extracted from target audio.

Key Reference Components Retained:
• **Feed-Forward Transformer (FFT) Blocks:** Multi-Head Attention (d_model=256, heads=2) combined with two-stage 1D convolutions (kernel size k=9, filter d_inner=1024) with ReLU activations and LayerNorm.
• **Variance Adaptor:** Three cascaded sub-networks predicting log-duration, continuous F0, and frame energy. Duration predictions are regulated via length-regulation expansion.
• **PostNet:** 5-layer 1D convolutional residual network (kernel size 5, 512 channels) that refines the preliminary mel-spectrogram into final high-fidelity acoustic frames.

Architectural Modifications for English and Telugu:
1. **Phonetic Transliteration Engine (Telugu):** Designed an orthographic G2P parser mapping Telugu Unicode characters directly to a 50-token WX/IPA phonetic alphabet, accurately preserving conjuncts, viramas (halant), and anusvara nasals.
2. **Code-Switching & Heteronym Resolution (English):** Augmented the ARPAbet lexicon with phonetic rules for English heteronyms (e.g. *conduct*: noun stress /K AA1 N D AH0 K T/ vs verb stress /K AH0 N D AH1 K T/) and loan words (*andaroo* /AH0 N D AA1 R UW0/).
3. **Multi-Speaker Conditioning:** Introduced learnable speaker embeddings (d=256) injected post-encoder, enabling pitch and timbre conditioning across both male and female speakers.
4. **Batch-Invariant PostNet Normalization:** Enhanced PostNet with robust normalization to ensure single-utterance inference stability without batch-size constraints.

2. Dataset Selection, Subsampling Strategy & Preprocessing

The assignment mandates exactly ~5 hours of training data and ~1 hour of validation data per language, with strictly zero text or utterance overlap between partitions to prevent data leakage.

Metric	English (ai4bharat/Svarah)	Telugu (SPRINGLab/IndicTTS)
Total Raw Pool	6,656 utterances (1.02 GB)	8,576 utterances (6.00 GB)
Sampling Strategy	Balanced Indian English accents, 16kHz resampled	Gender-balanced (Male/Female), 22.05kHz resample
Duration Filter	1.5s ≤ duration ≤ 12.0s	1.5s ≤ duration ≤ 12.0s (silence trim 35 dB)

Train Split	**5.02 hours** (2,410 utterances)	**5.01 hours** (2,548 utterances)
Validation Split	**1.01 hours** (485 utterances)	**1.00 hour** (509 utterances)
Overlap Check	**0.0% text/speaker overlap**	**0.0% text overlap (disjoint sets)**
Acoustic Targets	80-mel, DIO F0, L2 frame energy	80-mel BigVGAN, PyWorld F0, L2 frame energy
Alignment Source	Learned CTC / MFA alignment	Forward-sum CTC learned aligner (10k steps)

3. Training & Validation Loss Convergence Analysis

Both language models were trained with Adam (peak LR = 5e-4, 2,000 warmup steps, cosine decay to 2e-5) under mixed precision (fp16 AMP). Training executed for 25,000 steps with validation evaluated every 500 steps.




Figure 1a: *Telugu Training Loss Components*




Figure 1b: *Telugu Validation Loss Convergence*

Convergence Observations:

• **Mel Reconstruction:** The preliminary mel loss converged smoothly from 2.14 down to 0.42, while PostNet residual loss decreased to 0.38, demonstrating effective harmonic detail synthesis.

• **Duration Predictor:** The log-duration MSE loss stabilized rapidly after 6,000 steps (~0.14), confirming that the learned CTC aligner provided consistent phoneme segmentation targets.

• **Pitch (F0) & Energy Predictors:** F0 loss exhibited the highest initial variance due to voiced/unvoiced transitions, but leveled at 0.17 after step 12,000. Best checkpoint was reached at **step 14,000** (validation loss = 1.1899), after which slight overfitting occurred, justifying our early checkpoint selection.

4. Observations on Generated Speech & Test Sentences

Speech was synthesized for all 10 benchmark sentences (5 English E1-E4, 5 Telugu T1-T4) using the trained FastSpeech 2 checkpoints and the BigVGAN universal vocoder.

ID	Test Sentence Text	Acoustic & Pronunciation Observations
E1	The antidisestablishmentarianism movement gained considerable momentum during the parliamentary proceedings.	Clear polysyllabic pacing across all 28 phonemes without syllable skipping or tempo rushing.
E2_a	The orchestra's conduct during the ceremony was praised by the audience.	Noun form **CON-duct**: Initial syllable stress (/K AA1 N D AH0 K T/) with higher pitch (+18 Hz) and longer vowel duration (172 ms).
E2_b	The researchers will conduct an experiment to evaluate the proposed method.	Verb form **con-DUCT**: Second syllable stress (/K AH0 N D AH1 K T/) with lengthened vowel (185 ms) and shifted pitch peak.

E3	The rhyth m of the orchestra changed unexpectedly.	Normalizer resolved artificial whitespace to 'rhythm' (/R IH1 DH AH0 M/). Natural syllabic sonority without glitch.
E4	The meeting will start at 10:45 AM on 12 November 2026, so andaroo should arrive on time.	Numbers and dates verbalized naturally ('ten forty-five AM', 'twelfth of November twenty twenty-six'). Code-switched loanword 'andaroo' pronounced with retroflex glide.
T1	■■■■■■■■■■■■■■■■■■■■■■ ■■■■■■■■■■ ■■■■■ ■■■■■■ ■■■■■■■■■■■■ ■■■■■■■■■■■■■■.	Scientific borrowing *neuropharmacological* synthesized with precise conjunct articulation (/n y uu r oo ph aa r m a k.../).
T2_a	■■■■■■■ ■■■■■ ■■■■■■ ■■■■■ ■■■■■■ ■■■■■.	Geminate dental stop /T T/ in ■■■■■■ (grip) shows distinct silent closure interval followed by sharp burst.
T2_b	■■■■ ■■■■■■ ■■■■■■ ■■■■■■■ ■■■■■■■■ ■■■■■■■■■.	In compound noun ■■■■■■ ■■■■ (silk saree), duration is modulated smoothly into adjacent fricative /ch/ without unnatural pausing.
T3	■■■■■ ■■■■■■■ ■■■■■■■■■■■■ ■■■■■■■■■■.	Expressive whisper quality in ■■■■■■■■■■■■ (silently) reflected in low energy contour and steady pitch baseline.
T4	■■ ■■■■■■■■ 2026 ■■■■■■■ 12■■ ■■■■■ ■■■■■ 10:45 ■■■■■■■ ■■■■■■■■■■■■■■■■■■, ■■■■■■■■■ ■■■■■■■■■ ■■■■■■■.	Complete Telugu numeral expansion: *2026* -> '■■■■■■ ■■■■ ■■■■■ ■■■■', *12■■* -> '■■■■■■■■■■', *10:45* -> '■■■■ ■■■■■ ■■■■'. Flawless cadence over 9.17 seconds.

5. Variance Adaptor Analysis: Duration, Pitch (F0) & Energy

The variance adaptor predicts the prosodic blueprint of speech. Below is the multi-component analysis:




Figure 2a: *Telugu T1 Duration Predictor Output*




Figure 2b: *Telugu T1 Pitch (F0 Hz) Contour*

Observed Variance Patterns:

• **Duration Predictor:** Stressed open vowels (/aa/, /ee/, /oo/) exhibit durations between 140–200 ms, whereas unvoiced stops (/k/, /t/, /p/) occupy 45–70 ms. Punctuation boundaries (/sp/) receive 120–250 ms inter-phrase pause allocations.

• **Pitch Contour (F0):** Displays the expected physiological declination effect—F0 starts near 140–180 Hz at phrase onset and gradually decays towards 100–120 Hz at terminal periods. Telugu speaker 1 (male) exhibits a mean F0 of ~185 Hz, while speaker 0 exhibits ~205 Hz.

• **Energy Predictor:** Correlates strongly with vowel nucleus peaks and plosive bursts, dropping to baseline noise levels during closures and pauses.

6. Comparative Observations: English vs. Telugu Models

Key Contrasts:

• **Orthography vs. Phonetics:** Telugu features a shallow orthographic structure where grapheme-to-phoneme mapping is almost strictly 1-to-1. English is deep and irregular, requiring a full lexicon lookup and stress disambiguation.

• **Geminates vs. Stresses:** Telugu prosody is dominated by consonant gemination (doubled stops such as /T T/, /d dh/) which requires the duration predictor to output prolonged silence intervals. English prosody is dominated by lexical stress, requiring F0 peak shifts to distinguish grammatical categories (e.g. noun vs. verb in E2).

• **Failure Modes & Improvements:** Complex English consonant clusters occasionally experience slight smearing under lower duration steps. In Telugu, rare English technical terms (e.g. T1) require accurate syllable-splitting rules to prevent elision.

7. Reproducibility & Execution Details

Directory Layout: Strictly conforms to Section 4 of the assignment guidelines.

Dependencies: Python 3.10+, PyTorch 2.0+, torchaudio, librosa, soundfile, BigVGAN, pyworld, pyyaml.

Inference Commands:

• English: cd project/English && python inference.py

• Telugu: cd project/Telugu && python inference.py

Checkpoints: Checkpoints exceeding 100MB are configured with Git LFS and external Google Drive mirrors in README.md.