

S3

Enable

▼ Advanced settings

Object Lock
Store objects using a write-once-read-many (WORM) model to help you prevent objects from being deleted or overwritten for a fixed amount of time or indefinitely. Object Lock works only in versioned buckets. [Learn more](#)

☒ Disable
☐ Enable
Permanently allows objects in this bucket to be locked. Additional Object Lock configuration is required in bucket details after bucket creation to protect objects in this bucket from being deleted or overwritten.

Object Lock works only in versioned buckets. Enabling Object Lock automatically enables Versioning.

After creating the bucket, you can upload files and folders to the bucket, and configure additional bucket settings.

Cancel Create bucket

and application failures. [Learn more](#)

Bucket Versioning
☒ Disable
☐ Enable

Tags - optional (1)
You can use bucket tags to track storage costs and organize buckets. [Learn more](#)

Key	Value - optional	
Aspire	TN	Remove

Add tag

Default encryption [Info](#)
Server-side encryption is automatically applied to new objects stored in this bucket.

AWS Region
Asia Pacific (Mumbai) ap-south-1

Bucket name [Info](#)
rmgdotnetapp
Bucket name must be unique within the global namespace and follow the bucket naming rules. [See rules for bucket naming](#)

Copy settings from existing bucket - optional
Only the bucket settings in the following configuration are copied.
Choose bucket
Format: s3://bucket/prefix

Object Ownership [Info](#)
Control ownership of objects written to this bucket from other AWS accounts and the use of access control lists (ACLs). Object ownership determines who can specify access to objects.

☒ **ACLs disabled (recommended)**
All objects in this bucket are owned by this account. Access to this bucket and its objects is specified using only policies.

☐ **ACLs enabled**
Objects in this bucket can be owned by other AWS accounts. Access to this bucket and its objects can be specified using ACLs.

Object Ownership



