

# GE23131-Programming Using C-2024

Quiz navigation



Show one page at a time

Finish review

Status	Finished
Started	Monday, 13 January 2025, 8:52 PM
Completed	Monday, 13 January 2025, 9:06 PM
Duration	13 mins 52 secs

Question 1

Correct

Marked out of 1.00

Flag question

You are a bank account hacker. Initially you have 1 rupee in your account, and you want exactly **N** rupees in your account. You wrote two hacks, first hack can multiply the amount of money you own by 10, while the second can multiply it by 20. These hacks can be used any number of time. Can you achieve the desired amount **N** using these hacks.

Constraints:

$1 \leq T \leq 100$   
 $1 \leq N \leq 10^{12}$

Input

- The test case contains a single integer N.

Output

For each test case, print a single line containing the string "1" if you can make exactly N rupees or "0" otherwise.

SAMPLE INPUT

1

SAMPLE OUTPUT

1

### SAMPLE INPUT

2

### SAMPLE OUTPUT

0

**Answer:** (penalty regime: 0 %)

Reset answer

```
1  /*
2  * Complete the 'myFunc' function below.
3  *
4  * The function is expected to return an INTEGER.
5  * The function accepts INTEGER n as parameter.
6  */
7
8  int myFunc(long long N){
9      //Base case: if we reach 1, we can achieve it
10     if(N == 1)
11     {
12         return 1;
13     }
14     // If N is less than 1,we cannot achieve it
15     if(N < 1){
16         return 0;
17     }
18     //Check if we can achieve N by dividing by 10 or 20
19     if (N % 10 == 0 && myFunc(N / 10)){
20         return 1;
21     }
22     if (N % 20 == 0 && myFunc(N / 20)){
23         return 1;
24     }
25     // If neither condition is satisfied,return 0
26     return 0;
27 }
28
```

	Test	Expected	Got	
✓	printf("%d", myFunc(1))	1	1	✓
✓	printf("%d", myFunc(2))	0	0	✓

✓	<code>printf("%d", myFunc(10))</code>	1	1	✓
✓	<code>printf("%d", myFunc(25))</code>	0	0	✓
✓	<code>printf("%d", myFunc(200))</code>	1	1	✓

Passed all tests! ✓

Question **2**

Correct

Marked out of  
1.00

🚩 [Flag question](#)

Find the number of ways that a given integer,  $X$ , can be expressed as the sum of the  $N^{th}$  powers of unique, natural numbers.

For example, if  $X = 13$  and  $N = 2$ , we have to find all combinations of unique squares adding up to  $13$ . The only solution is  $2^2 + 3^2$ .

### Function Description

Complete the powerSum function in the editor below. It should return an integer that represents the number of possible combinations.

powerSum has the following parameter(s):

X: the integer to sum to

N: the integer power to raise numbers to

Input Format

The first line contains an integer  $X$ .

The second line contains an integer  $N$ .

### Constraints

$$1 \leq X \leq 1000$$

$$2 \leq N \leq 10$$

### Output Format

Output a single integer, the number of possible combinations calculated.

### Sample Input 0

10

2

#### Sample Output 0

1

#### Explanation 0

If  $X = 10$  and  $N = 2$ , we need to find the number of ways that **10** can be represented as the sum of squares of unique numbers.

$$10 = 1^2 + 3^2$$

This is the only way in which **10** can be expressed as the sum of unique squares.

#### Sample Input 1

100

2

#### Sample Output 1

3

#### Explanation 1

$$100 = (10^2) = (6^2 + 8^2) = (1^2 + 3^2 + 4^2 + 5^2 + 7^2)$$

#### Sample Input 2

100

3

## Sample Output 2

1

### Explanation 2

**100** can be expressed as the sum of the cubes of **1, 2, 3, 4**.

**(1 + 8 + 27 + 64 = 100)**. There is no other way to express **100** as the sum of cubes.

**Answer:** (penalty regime: 0 %)

Reset answer

```
1  /*
2  * Complete the 'powerSum' function below.
3  *
4  * The function is expected to return an INTEGER.
5  * The function accepts following parameters:
6  * 1. INTEGER x
7  * 2. INTEGER n
8  */
9  #include<stdio.h>
10 #include<math.h>
11
12 int powerSum(int X, int current, int N)
13 {
14     if(X == 0) {
15         return 1;
16     }
17
18     if(X < 0 || pow(current, N) > X){
19         return 0;
20     }
21
22     int include = powerSum(X - pow(current,N),current + 1,N);
23
24     int exclude = powerSum(X, current + 1,N);
25
26     return include + exclude;
27 }
28
```

	Test	Expected	Got	
✓	printf("%d", powerSum(10, 1, 2))	1	1	✓

Passed all tests! ✓

Finish review