

Anchor Node Placement for Localization in Wireless Sensor Networks

by

Benjamin Tatham

A Dissertation submitted to
the Faculty of Graduate Studies and Research
in partial fulfilment of
the requirements for the degree of
Master of Applied Science

Ottawa-Carleton Institute for
Electrical and Computer Engineering

Department of Systems and Computer Engineering

Carleton University

Ottawa, Ontario, Canada

April 2009

Copyright ©

2009 - Benjamin Tatham

The undersigned recommend to
the Faculty of Graduate Studies and Research
acceptance of the Dissertation

Anchor Node Placement for Localization in Wireless Sensor Networks

Submitted by **Benjamin Tatham**
in partial fulfilment of the requirements for the degree of
Master of Applied Science

Thomas Kunz, Supervisor

V. Aitken, Department Chair

Carleton University

2009

Abstract

An abstract should be short and to the point.

This is the dedication...

Acknowledgments

I would like to acknowldege

Table of Contents

Abstract	iii
Acknowledgments	v
Table of Contents	vi
List of Figures	vii
1 Introduction	1
1.1 Anchor Placement: Equal distribution along 45 Degree Axis	1
2 The Beginning of the Details	4
2.1 Section Heading	4
2.1.1 Sub-Section Heading	4
Appendix A Derivation of Some Nasty Equation	5
List of References	5

List of Figures

1.1	The random network used, showing the 6 position sets of anchors. . .	2
1.2	Maximum, median, and minimum errors for various network conditions	2
1.3	The random network used, showing the 6 position sets of anchors. . .	3
1.4	Maximum, median, and minimum errors for various network conditions	3

Chapter 1

Introduction

1.1 Anchor Placement: Equal distribution along 45 Degree Axis

For the first round of testing, chosen more as an exercise in the simulation analysis package in MATLAB®, 4 anchor nodes are placed at the closest node to the 45-degree axes, with increasing distance from the center. 1.1 shows the positions for each iteration.

The 2nd graph in 1.2 shows that the best localization performance is achieved when the 4 anchors are roughly midway between the center of the network and the corners.

The same test is repeated for a grid network layout instead of a random network layout.






Figure 1.1: The random network used, showing the 6 position sets of anchors.



(a) Error decreasing as network connectivity increases



(b) Error is lowest as the anchors are near the midpoint between center and corners

Figure 1.2: Maximum, median, and minimum errors for various network conditions






Figure 1.3: The random network used, showing the 6 position sets of anchors.



(a) Error decreasing as network connectivity increases



(b) Error is lowest as the anchors are near the midpoint between center and corners

Figure 1.4: Maximum, median, and minimum errors for various network conditions

Chapter 2

The Beginning of the Details

2.1 Section Heading

Sample section text.

New paragraph.

2.1.1 Sub-Section Heading

Sample text.

new paragraph.

Sub-Sub-Section Heading

Sample text.

Sorry no details available [?, ?].

Appendix A

Derivation of Some Nasty Equation

Here is the derivation.