RAJALAKSHMI ENGINEERING COLLEGE

Kishore Kumar M 250701359-2025-CSE

K2

Started on	Wednesday, 16 September 2026, 9:14 AM
State	Finished
Completed on	Wednesday, 16 September 2026, 9:28 AM
Time taken	13 mins 57 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```
#include <stdio.h>
#include <stdlib.h>
int compareAsc(const void *a, const void *b) {
    return (*(int*)a - *(int*)b);
}
int compareDesc(const void *a, const void *b) {
    return (*(int*)b - *(int*)a);
}

int main() {
    int n;
    if (scanf("%d", &n) != 1 || n <= 0) {
        printf("Invalid size.\n");
        return 1;
    }
    int arr1[n];
    int arr2[n];
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr1[i]);
    }
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr2[i]);
    }
    qsort(arr1, n, sizeof(int), compareAsc);
    qsort(arr2, n, sizeof(int), compareDesc);
    long long minProductSum = 0;
    for (int i = 0; i < n; i++) {
        minProductSum += (long long)arr1[i] * arr2[i];
    }
    printf( "%lld\n", minProductSum);
    return 0;
}

```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔

	Input	Expected	Got	
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course