RAJALAKSHMI ENGINEERING COLLEGE

Kishore Kumar S (dob 20.03.2007) 251001123-2025-IT

K2

Started on	Wednesday, 7 October 2026, 9:00 AM
State	Finished
Completed on	Wednesday, 7 October 2026, 9:01 AM
Time taken	54 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

Answer: (penalty regime: 0 %)

```
#include <stdio.h>
#include <stdlib.h>
void solve() {
    int n1, n2;
    if (scanf("%d", &n1) != 1) return;
    int *arr1 = (int *)malloc(n1 * sizeof(int));
    for (int i = 0; i < n1; i++) {
        scanf("%d", &arr1[i]);
    }
    if (scanf("%d", &n2) != 1) {
        free(arr1);
        return;
    }
    int *arr2 = (int *)malloc(n2 * sizeof(int));
    for (int i = 0; i < n2; i++) {
        scanf("%d", &arr2[i]);
    }
    int i = 0, j = 0;
    int has_elements = 0;
    int last_added = 0;

    while (i < n1 && j < n2) {
        if (arr1[i] == arr2[j]) {
```

```
            // Check if it's the first match or a unique new element
            if (has_elements == 0 || arr1[i] != last_added) {
                if (has_elements > 0) {
                    printf(" ");
                }
                printf("%d", arr1[i]);
                last_added = arr1[i];
                has_elements = 1;
            }
            i++;
            j++;
        } else if (arr1[i] < arr2[j]) {
            i++;
        } else {
            j++;
        }
    }
    printf("\n");
    free(arr1);
    free(arr2);
}
int main() {
    int t;
    if (scanf("%d", &t) == 1) {
        while (t--) {
            solve();
        }
    }
    return 0;
```

	Input	Expected	Got	
✔	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	✔
✔	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course