RAJALAKSHMI ENGINEERING COLLEGE

Kishore Kumar S (dob 20.03.2007) 251001123-2025-IT

K2

Started on	Wednesday, 7 October 2026, 8:50 AM
State	Finished
Completed on	Wednesday, 7 October 2026, 8:51 AM
Time taken	55 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>
int ascending(const void *a, const void *b) {
    int x = *(const int *)a;
    int y = *(const int *)b;
    if (x < y)
        return -1;
    if (x > y)
        return 1;
    return 0;
}
int descending(const void *a, const void *b) {
    int x = *(const int *)a;
    int y = *(const int *)b;
    if (x < y)
        return 1;
    if (x > y)
        return -1;
    return 0;
}
int main() {
    int n;
    scanf("%d", &n);
    long long A[n], B[n];
    for (int i = 0; i < n; i++) {
        scanf("%lld", &A[i]);
    }
    for (int i = 0; i < n; i++) {
        scanf("%lld", &B[i]);
    }
    qsort(A, n, sizeof(long long), ascending);
    qsort(B, n, sizeof(long long), descending);
    long long sum = 0;
    for (int i = 0; i < n; i++) {
        sum += A[i] * B[i];
    }
    printf("%lld\n", sum);
    return 0;
}
```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course