| | |
|---|---|
| **Status** | Finished |
| **Started** | Saturday, 10 October 2026, 10:32 PM |
| **Completed** | Saturday, 10 October 2026, 11:15 PM |
| **Duration** | 42 mins 36 secs |
| **Grade** | **10.00** out of 10.00 (**100**%) |

Question **1**

Correct

Mark 1.00 out of 1.00

Coders here is a simple task for you, Given string str. Your task is to check whether it is a binary string or not by using python set.

Examples:

Input: str = "01010101010"

Output: Yes

Input: str = "REC101"

Output: No

**For example:**

| Input | Result |
|---|---|
| 01010101010 | Yes |
| 010101 10101 | No |

**Answer:** (penalty regime: 0 %)

```
s = input()

if set(s) <= {'0', '1'}:
    print("Yes")
else:
    print("No")
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✓ | 01010101010 | Yes | Yes | ✓ |
| ✓ | REC123 | No | No | ✓ |
| ✓ | 010101 10101 | No | No | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **2**

Correct

Mark 1.00 out of 1.00

# Check if a set is a subset of another set.

Example:

Sample Input1:

mango apple

mango orange

mango

output1:

yes

set3 is subset of set1 and set2

```
input2:
mango orange
banana orange
grapes
output2:
```

no

**For example:**

| Test | Input | Result |
|---|---|---|
| 1 | mango apple<br>mango orange<br>mango | yes<br>set3 is subset of set1 and set2 |
| 2 | mango orange<br>banana orange<br>grapes | No |

**Answer:** (penalty regime: 0 %)

```
set1 = set(input().split())
set2 = set(input().split())
set3 = set(input().split())

if set3.issubset(set1) and set3.issubset(set2):
    print("yes")
    print("set3 is subset of set1 and set2")
else:
    print("No")
```

| | Test | Input | Expected | Got | |
|---|---|---|---|---|---|
| ✓ | 1 | mango apple<br>mango orange<br>mango | yes<br>set3 is subset of set1 and set2 | yes<br>set3 is subset of set1 and set2 | ✓ |
| ✓ | 2 | mango orange<br>banana orange<br>grapes | No | No | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **3**

Correct

Mark 1.00 out of 1.00

Program to print all the distinct elements in an array. Distinct elements are nothing but the unique (non-duplicate) elements present in the given array.

Input Format:

First line take an Integer input from stdin which is array length n.

Second line take n Integers which is inputs of array.

Output Format:

Print the Distinct Elements in Array in single line which is space Separated

Example Input:

5

1 2 2 3 4

Output:

1 2 3 4

Example Input:

6

1 1 2 2 3 3

Output:

1 2 3

**For example:**

| Input | Result |
|---|---|
| 5<br>1<br>2<br>2<br>3<br>4 | 1 2 3 4 |

**Answer:** (penalty regime: 0 %)

```
n = int(input())
a = []

while len(a) < n:
    a.extend(map(int, input().split()))

b = []

for i in a:
    if i not in b:
        b.append(i)

print(*b)
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✓ | 5<br>1<br>2<br>2<br>3<br>4 | 1 2 3 4 | 1 2 3 4 | ✓ |
| ✓ | 6<br>1<br>1<br>2<br>2<br>3<br>3 | 1 2 3 | 1 2 3 | ✓ |
| ✓ | 5<br>11<br>22<br>11<br>22<br>11 | 11 22 | 11 22 | ✓ |
| ✓ | 10<br>1<br>2<br>3<br>4<br>5<br>1<br>2<br>3<br>4<br>5 | 1 2 3 4 5 | 1 2 3 4 5 | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **4**

Correct

Mark 1.00 out of 1.00

The **DNA sequence** is composed of a series of nucleotides abbreviated as `'A'`, `'C'`, `'G'`, and `'T'`.

- For example, `"ACGAATTCCG"` is a **DNA sequence**.

When studying **DNA**, it is useful to identify repeated sequences within the DNA.

Given a string `s` that represents a **DNA sequence**, return all the `10`**-letter-long** sequences (substrings) that occur more than once in a DNA molecule. You may return the answer in **any order**.

**Example 1:**

```
Input: s = "AAAAACCCCCAAAAACCCCCCAAAAAGGGTTT"
Output: ["AAAAACCCCC","CCCCCAAAAA"]
```

**Example 2:**

```
Input: s = "AAAAAAAAAAAAA"
Output: ["AAAAAAAAAA"]
```

**For example:**

| Input | Result |
|---|---|
| AAAAACCCCCAAAAACCCCCCAAAAAGGGTTT | AAAAACCCCC<br>CCCCCAAAAA |

**Answer:** (penalty regime: 0 %)

```
s = input()

seen = set()
repeated = []

for i in range(len(s) - 9):
    sub = s[i:i+10]

    if sub in seen and sub not in repeated:
        repeated.append(sub)
    seen.add(sub)

for i in repeated:
    print(i)
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✓ | AAAAACCCCCAAAAACCCCCCAAAAAGGGTTT | AAAAACCCCC<br>CCCCCAAAAA | AAAAACCCCC<br>CCCCCAAAAA | ✓ |

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✓ | AAAAAAAAAAAA | AAAAAAAAAA | AAAAAAAAAA | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **5**


Correct

Mark 1.00 out of 1.00

Given an array of strings `words`, return *the words that can be typed using letters of the alphabet on only one row of American keyboard like the image below.*

In the **American keyboard**:

- the first row consists of the characters `"qwertyuiop"`,
- the second row consists of the characters `"asdfghjkl"`, and
- the third row consists of the characters `"zxcvbnm"`.




**Example 1:**

```
Input: words = ["Hello","Alaska","Dad","Peace"]
Output: ["Alaska","Dad"]
```

**Example 2:**

```
Input: words = ["omk"]
Output: []
```

**Example 3:**

```
Input: words = ["adsdf","sfd"]
Output: ["adsdf","sfd"]
```

**For example:**

| Input | Result |
|---|---|
| 4<br>Hello<br>Alaska<br>Dad<br>Peace | Alaska<br>Dad |
| 2<br>adsfd<br>afd | adsfd<br>afd |

**Answer:** (penalty regime: 0 %)

```
n = int(input())
words = []

for i in range(n):
    words.append(input())
```

```
6
7  row1 = "qwertyuiop"
8  row2 = "asdfghjkl"
9  row3 = "zxcvbnm"
10
11 found = False
12
13 for word in words:
14     w = word.lower()
15     if all(ch in row1 for ch in w) or all(ch in row2 for ch in w) or all(ch in row3 for ch in w):
16         print(word)
17         found = True
18
19 if not found:
20     print("No words")
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✓ | 4<br>Hello<br>Alaska<br>Dad<br>Peace | Alaska<br>Dad | Alaska<br>Dad | ✓ |
| ✓ | 1<br>omk | No words | No words | ✓ |
| ✓ | 2<br>adsfd<br>afd | adsfd<br>afd | adsfd<br>afd | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **6**

Correct

Mark 1.00 out of 1.00

Write a program to eliminate the common elements in the given 2 arrays and print only the non-repeating elements and the total number of such non-repeating elements.

Input Format:

The first line contains space-separated values, denoting the size of the two arrays in integer format respectively.

The next two lines contain the space-separated integer arrays to be compared.

Sample Input:

5 4

1 2 8 6 5

2 6 8 10

Sample Output:

1 5 10

3

Sample Input:

5 5

1 2 3 4 5

1 2 3 4 5

Sample Output:

NO SUCH ELEMENTS

**For example:**

| Input | Result |
|---|---|
| 5 4<br>1 2 8 6 5<br>2 6 8 10 | 1 5 10<br>3 |
| 5 5<br>1 2 3 4 5<br>1 2 3 4 5 | NO SUCH ELEMENTS |

**Answer:** (penalty regime: 0 %)

```
n, m = map(int, input().split())
a = list(map(int, input().split()))
b = list(map(int, input().split()))

result = sorted(set(a) ^ set(b))

if result:
    print(*result)
    print(len(result))
else:
    print("NO SUCH ELEMENTS")
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✓ | 5 4<br>1 2 8 6 5<br>2 6 8 10 | 1 5 10<br>3 | 1 5 10<br>3 | ✓ |
| ✓ | 3 3<br>10 10 10<br>10 11 12 | 11 12<br>2 | 11 12<br>2 | ✓ |
| ✓ | 5 5<br>1 2 3 4 5<br>1 2 3 4 5 | NO SUCH ELEMENTS | NO SUCH ELEMENTS | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **7**

Correct

Mark 1.00 out of 1.00

Given a tuple and a positive integer k, the task is to find the count of distinct pairs in the tuple whose sum is equal to **K**.

**Examples:**

**Input:** t = (5, 6, 5, 7, 7, 8 ), K = 13
**Output:** 2
**Explanation:**
Pairs with sum K( = 13) are {(5, 8), (6, 7), (6, 7)}.
Therefore, distinct pairs with sum K( = 13) are { (5, 8), (6, 7) }.
Therefore, the required output is 2.

**For example:**

| Input | Result |
|---|---|
| 1,2,1,2,5<br>3 | 1 |
| 1,2<br>0 | 0 |

**Answer:** (penalty regime: 0 %)

```
t = tuple(map(int, input().split(',')))
k = int(input())

pairs = set()

for i in t:
    j = k - i
    if j in t and i != j:
        pairs.add(tuple(sorted((i, j))))
    elif i == j and t.count(i) >= 2:
        pairs.add((i, i))

print(len(pairs))
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✓ | 5,6,5,7,7,8<br>13 | 2 | 2 | ✓ |
| ✓ | 1,2,1,2,5<br>3 | 1 | 1 | ✓ |
| ✓ | 1,2<br>0 | 0 | 0 | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **8**

Correct

Mark 1.00 out of 1.00

There is a malfunctioning keyboard where some letter keys do not work. All other keys on the keyboard work properly.

Given a string text of words separated by a single space (no leading or trailing spaces) and a string brokenLetters of all distinct letter keys that are broken, return the number of words in text you can fully type using this keyboard.

Example 1:

Input: text = "hello world", brokenLetters = "ad"

Output:

1

Explanation: We cannot type "world" because the 'd' key is broken.

**For example:**

| Input | Result |
|---|---|
| hello world<br>ad | 1 |
| Faculty Upskilling in Python Programming<br>ak | 2 |

**Answer:** (penalty regime: 0 %)

```
import sys

data = sys.stdin.read().split()
broken = data[-1].lower()
words = data[:-1]

count = 0
for word in words:
    if all(c.lower() not in broken for c in word):
        count += 1

print(count)
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✓ | hello world<br>ad | 1 | 1 | ✓ |
| ✓ | Welcome to REC<br>e | 1 | 1 | ✓ |
| ✓ | Faculty Upskilling in Python Programming<br>ak | 2 | 2 | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **9**

Correct

Mark 1.00 out of 1.00

You are given an integer tuple `nums` containing distinct numbers. Your task is to perform a sequence of operations on this tuple until it becomes empty. The operations are defined as follows:

1. If the first element of the tuple has the smallest value in the entire tuple, remove it.
2. Otherwise, move the first element to the end of the tuple.

You need to return an integer denoting the number of operations required to make the tuple empty.

## Constraints

- The input tuple `nums` contains distinct integers.
- The operations must be performed using tuples and sets to maintain immutability and efficiency.
- Your function should accept the tuple `nums` as input and return the total number of operations as an integer.

Example:

Input: nums = (3, 4, -1)
Output: 5

Explanation:
Operation 1: [3, 4, -1] -> First element is not the smallest, move to the end -> [4, -1, 3]
Operation 2: [4, -1, 3] -> First element is not the smallest, move to the end -> [-1, 3, 4]
Operation 3: [-1, 3, 4] -> First element is the smallest, remove it -> [3, 4]
Operation 4: [3, 4] -> First element is the smallest, remove it -> [4]
Operation 5: [4] -> First element is the smallest, remove it -> []
Total operations: 5

**For example:**

| Test | Result |
|---|---|
| `print(count_operations((3, 4, -1)))` | 5 |

**Answer:** (penalty regime: 0 %)

Reset answer

```
def count_operations(nums):
    nums = tuple(nums)
    s = set(nums)
    count = 0

    while nums:
        count += 1

        if nums[0] == min(s):
            s.remove(nums[0])
            nums = nums[1:]
        else:
            nums = nums[1:] + (nums[0],)

    return count
```

| | Test | Expected | Got | |
|---|---|---|---|---|
| ✓ | `print(count_operations((3, 4, -1)))` | 5 | 5 | ✓ |
| ✓ | `print(count_operations((1, 2, 3, 4, 5)))` | 5 | 5 | ✓ |
| ✓ | `print(count_operations((5, 4, 3, 2, 1)))` | 15 | 15 | ✓ |
| ✓ | `print(count_operations((42, )))` | 1 | 1 | ✓ |
| ✓ | `print(count_operations((-2, 3, -5, 4, 1)))` | 11 | 11 | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **10**

Correct

Mark 1.00 out of 1.00

Given an array of integers `nums` containing `n + 1` integers where each integer is in the range `[1, n]` inclusive.There is only **one repeated number** in `nums`, return *this repeated number*. Solve the problem using set.

**Example 1:**

```
Input: nums = [1,3,4,2,2]
```

```
Output: 2
```

**Example 2:**

```
Input: nums = [3,1,3,4,2]
```

```
Output: 3
```

**For example:**

| Input | Result |
|---|---|
| 1 3 4 4 2 | 4 |

**Answer:** (penalty regime: 0 %)

```
nums = list(map(int, input().split()))
seen = set()

for i in nums:
    if i in seen:
        print(i)
        break
    seen.add(i)
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✓ | 1 3 4 4 2 | 4 | 4 | ✓ |
| ✓ | 1 2 2 3 4 5 6 7 | 2 | 2 | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.