

Evidence-Verified Adversarial Review for Code-Review Claims

ANONYMOUS AUTHOR(S)

When a code-review agent cites the wrong lines, asking a second language model whether the finding sounds reasonable can reproduce the same mistake. We test a stricter alternative. Evidence-Verified Adversarial Review (EVAR) requires the reviewer to submit a structured receipt—a file, line range, expected observation, falsification condition, and optionally a bounded command—and makes deterministic verification a precondition for actionability. We compare ordinary adversarial review (AR), textual evidence (AR-Text), and EVAR-Hard with matched prompts, cases, and call budgets. Our final holdout contains 120 decisions over temporal pairs derived from ten public pull-request comments. On this holdout, GPT-4.1-mini gives the same FCR/SCR operating point for AR-Text and EVAR-Hard (.200/.700), while GPT-4.1 favors AR-Text (.200/.700 versus .300/.600). Results from three newer OpenAI models are similarly mixed. A five-provider extension records 300 further attempts under a shared 2,400-token cap: Claude and Gemini complete every cell, while DeepSeek, Kimi, and Qwen expose 33 schema-generation failures. Across the full artifact, 1,167 of 1,200 attempts produce scored decisions. The hard gate changes which findings survive but does not consistently improve decision quality. What it does provide is a reproducible acceptance boundary: an actionable EVAR finding has a machine-checked receipt, and failed evidence remains visible in the record.

CCS Concepts: • **Software and its engineering** → **Software testing and debugging**; • **Computing methodologies** → *Natural language processing*.

Additional Key Words and Phrases: code review, language-model agents, evidence verification, benchmark, reliability

ACM Reference Format:

Anonymous Author(s). 2026. Evidence-Verified Adversarial Review for Code-Review Claims. In *ACM International Conference on the Foundations of Software Engineering (FSE 2027)*. ACM, New York, NY, USA, 18 pages.

1 Introduction

Reviewer-critic systems use a second model call to challenge or refine a first model’s answer. Iterative self-feedback and multi-agent debate can improve generation and reasoning [1, 2], but textual agreement is not independent evidence. In code review, two agents can converge on the same plausible interpretation of code while both overlook the observation that would falsify it.

Consider a documentation finding from Black pull request 5272 in our holdout. A human reviewer asked that an internal explanation involving `hug_power_op` and cloned leaves be replaced with a concise user-facing changelog entry. The same claim is true at the reviewed commit and false after the merge edit. A textual critic can accept the finding in either snapshot because the wording remains plausible. An evidence receipt must instead identify the exact changelog lines present in that snapshot. The example captures our unit of analysis: not whether a model can discover every issue in a pull request, but whether one candidate finding deserves to cross an actionability boundary.

EVAR changes the acceptance rule. A reviewer submits a structured evidence receipt; a deterministic verifier checks a source location or executes a bounded witness; and only a verified receipt can become actionable. We ask whether that external gate reduces false consensus without suppressing supported findings.

We organize the study around three research questions:

FSE 2027, Trondheim, Norway
2026.

RQ1 (decision quality). Does deterministic evidence verification reduce unsupported actionable findings without an unacceptable loss of supported findings?

RQ2 (model sensitivity). Does the safety–retention operating point persist across model capability and cost tiers?

RQ3 (auditability). Which protocol failures become mechanically observable when actionability requires a verified receipt?

The distinction between decision quality and auditability matters throughout the paper. A receipt can be mechanically valid yet irrelevant to the claim, and a protocol can be easier to audit without producing a better FCR/SCR pair.

Our contributions are:

- (1) **Protocol:** a structured evidence receipt and deterministic gate that make acceptance conditions externally inspectable;
- (2) **Benchmark:** a temporally paired holdout built from public human review comments at reviewed and merged commits;
- (3) **Evidence:** matched AR, AR-Text, and EVAR-Hard experiments that expose a model-sensitive safety–retention tradeoff; and
- (4) **Artifact:** frozen inputs, transcripts, result manifests, and judge-free audits for 1,200 attempted decisions, including 33 provider failures retained explicitly.

2 Related Work

2.1 Reflection, critique, and debate

Self-Refine uses model-generated feedback to iteratively improve a model’s output [1]. Reflexion incorporates linguistic feedback into an episodic memory rather than updating model weights [3]. Multi-agent debate has similarly improved reasoning and factuality through textual deliberation [2]. These methods motivate the AR baselines but do not, by themselves, make agreement independent evidence. The same model family can reproduce a shared misconception across reviewer and critic roles.

Prior work also questions whether intrinsic self-correction is reliable without external feedback. CRITIC couples model critique to tool interactions and reports gains across question answering, program synthesis, and toxicity reduction [4]. EVAR adopts the external-feedback premise but narrows both the task and the acceptance rule: the system judges a pre-specified code-review claim, and a deterministic receipt check is a necessary gate rather than optional context for another revision.

2.2 Tool-using software-engineering agents

SWE-agent shows that the interface between a model and a computer materially affects software-engineering performance [5]. Executable feedback can reveal failures that are invisible in a textual conversation, but unrestricted agent execution also introduces a large design surface. EVAR uses a deliberately narrow interface: structural source checks or a shell-free verification process launched from the benchmark fixture under a timeout. This makes the acceptance boundary easier to audit, at the cost of incomplete coverage for repository-scale semantic claims. The current code includes a hardened container option for future runs; the experiments reported here used trusted fixtures and the local backend.

2.3 Code review as a sociotechnical practice

Modern code review is not reducible to defect detection. Interviews at Microsoft identify knowledge transfer, alternative solutions, and team awareness alongside finding defects [10]; Google’s review

process likewise emphasizes a lightweight, tool-mediated practice embedded in development rather than a standalone classifier [11]. This broader view constrains our claims. FCR and SCR measure the fate of a supplied technical claim, not whether a generated comment is timely, understandable, or useful to a team. Industrial studies of deployed automated review systems further show why adoption and workflow outcomes require separate measurement [12, 13]. We therefore treat developer utility as future work rather than inferring it from benchmark accuracy.

2.4 Automated code review and benchmarks

CodeReviewer pre-trains on code changes and review activities, evaluating quality estimation, comment generation, and refinement [6]. That line of work asks whether a system can generate or improve reviews. Our task begins later in the pipeline: a candidate claim already exists, and the system must decide whether the repository snapshot supports actionability.

Hybrid review systems combine learned generation with rule-based analyzers to recover some precision without surrendering broad issue coverage [14]. EVAR shares the motivation but assigns the deterministic component a different role: it validates the submitted observation and controls actionability; it neither generates a parallel comment nor establishes semantic relevance by itself.

Software-engineering benchmarks increasingly ground tasks in public development history. SWE-bench uses real GitHub issues and pull requests and demonstrates the need for repository context and executable environments [7]. SWE-PRBench evaluates code-review models against pull-request feedback and reports limited detection of human-flagged issues [8]. Our task is narrower: a candidate claim is given, and the system must decide whether it remains actionable under the supplied repository snapshot.

SWR-Bench makes a complementary choice: it evaluates 1,000 complete pull requests with full-project context and structured ground truth, then asks whether generated reviews cover the reported issues [9]. EVAR is smaller and deliberately different. It does not score open-ended issue discovery; it fixes one candidate claim and asks whether that claim can cross an auditable evidence boundary. That trades breadth for a clean test of false consensus and lets us report why a finding was accepted, rejected, or mechanically unverifiable. A future larger benchmark should combine EVAR's receipt-level audit with the PR-scale context and manual verification used by SWR-Bench.

ContextCRBench reaches a different scale, with context-enriched entries for quality assessment, localization, and comment generation [15]. Its emphasis on issue context and fine-grained localization reinforces an important external-validity limit here: EVAR's focused excerpts isolate the verification question, but they cannot substitute for evaluating complete pull requests with developer intent.

3 Protocols

All protocols receive the same candidate claim, task description, repository context, model configuration, and two-call interaction budget: one reviewer call followed by one critic call. The reviewer always returns exactly one schema-constrained receipt. The protocols differ in what happens to that receipt before criticism.

An EVAR receipt contains the claim, evidence type and role, file and line range, optional verification command, expected observation, and falsification condition. Structural evidence is accepted only by exact source matching after conservative cleanup of display-only line numbers and Markdown fences. Behavioral witnesses must exit successfully and print a designated pass marker only when the claim is supported. The verifier does not use semantic fuzzy matching or model judgment.

In every run, the reviewer sees the candidate claim and repository snapshot but not the benchmark label. AR passes the submitted claim and receipt fields to a critic but labels verification as unused. AR-Text converts the receipt into a textual-evidence object (file, range, quoted or paraphrased

Table 1. Compared protocols.

Protocol	Evidence handling	Actionability gate
AR	Reviewer proposes a finding; critic evaluates textually.	Critic returns ACCEPT.
AR-Text	Reviewer adds textual evidence when challenged.	Critic returns ACCEPT.
EVAR-Hard	Reviewer submits a receipt; verifier checks structural or behavioral evidence.	Verifier returns VERIFIED and critic returns ACCEPT.




Fig. 1. Matched protocol flow. All variants use the same reviewer and critic call count; only EVAR-Hard makes deterministic verification a necessary gate.

support, and falsification condition) without executing it. EVAR-Hard verifies the receipt before the critic call. The critic still receives failed verification, but its acceptance cannot override the hard gate. This makes three failure modes visible separately: misunderstanding the claim, citing evidence that does not verify, and presenting a verified observation that is irrelevant to the claim.

3.1 Actionability semantics

Let c be a candidate claim, $d \in \{\text{ACCEPT}, \text{REJECT}\}$ the critic decision, and $v \in \{\text{VERIFIED}, \text{FAILED}\}$ the verifier outcome. The final gates are

$$A_{\text{AR}}(c) = 1[d = \text{ACCEPT}], \quad A_{\text{EVAR}}(c) = 1[d = \text{ACCEPT} \wedge v = \text{VERIFIED}].$$

AR-Text shares the AR gate but supplies textual evidence to the critic. The distinction is therefore not whether evidence appears in the dialogue; it is whether an external deterministic observation is mandatory for actionability.

3.2 Receipt verification

Receipts declare an evidence *role*: support or contradiction. A structural receipt names a repository-relative file, line interval, and expected source observation. A behavioral receipt additionally declares a command, expected exit code, required output marker, and falsification condition. The verifier rejects irrecoverable paths, malformed ranges, mismatched source, malformed commands, timeouts, unexpected exit status, or absent witness markers. For structural receipts only, a frozen conservative recovery can resolve an unambiguous fixture file or search that file when display-derived line numbers are stale; these recovery rules are fixed and deterministic. A failed receipt cannot be rescued by critic agreement.

The frozen evaluator includes two deterministic, non-model repair rules developed before Human PR 20: an AST result may flip a receipt's evidence role when the verifier explicitly observed the opposite role, and an inline-Python syntax failure may fall back from behavioral to structural verification. Both the original failure and repair event appear in the transcript. No free-form semantic repair is performed.

Verification is intentionally syntactic and operational rather than semantic. This avoids substituting a hidden judge model for the critic, but it creates two separate correctness questions: whether the receipt is mechanically valid and whether the verified observation actually bears on the claim. The experiments record both the verifier outcome and final critic decision so these surfaces remain distinguishable.

3.3 Threat model and scope

The failure of interest is *false consensus*: reviewer and critic agree that an unsupported claim should be actionable. We do not assume malicious agents. The threat is correlated model error under plausible code-review language, incomplete context, or an attractive but irrelevant citation. The benchmark runner removes ground-truth labels and explanations from model-visible tasks. The verifier reads only the submitted receipt and fixture repository; it never reads the benchmark label.

4 Benchmarks and Freeze Procedure

The project contains synthetic diagnostics, source snapshots, commit-grounded cases, a 50-case frozen external benchmark, a separate v2 development split, and the final human-comment holdout. Frozen results are never overwritten by later development runs.

Table 2. Evaluation artifacts and their role in the study.

Artifact	Cases	Labels	Role
Manual 50	50	balanced	Synthetic diagnostic and smoke-test benchmark.
External PR 20	20	balanced	Commit-grounded development diagnosis; later receipt repair is post-hoc.
External PR 50	50	balanced	First frozen external evaluation, five repositories and 25 commits.
Development PR 20	20	balanced	Receipt-format and prompt development after the first frozen study.
Human PR 20	20	balanced	Untouched temporal holdout from ten human review comments.

External PR 50 contains 50 balanced claims grounded in 25 commits from Click, pluggy, attrs, more-itertools, and Requests. Its 600 model decisions exposed a false-consensus versus retention tradeoff and motivated receipt-generation work. No code or prompt change was evaluated against that benchmark again.

Human PR 20 was created after v2 development. Ten comments by non-bot GitHub reviewers were selected from Black, pytest, Rich, Pydantic, and Poetry, none of which appeared in External PR 50. Each comment yields a temporal pair: the reviewed commit supports the claim and the merged commit no longer does. Cases preserve the exact public comment URL, author, path, line, pull request, and commit. Each contains a focused changed-target excerpt and a companion changed-file excerpt when available, with less than 30 KB total context. This yields ten supported and ten unsupported cases.

4.1 Temporal-pair construction

The temporal design controls claim wording within each pair. At the reviewed commit, the human comment states a condition that is present in the code and the case is labeled supported. At the merge commit, the relevant code has changed such that the same claim is no longer supported. Pairing reduces wording and topic variation between labels, but it also means the two rows derived from one comment are statistically related. Bootstrap resampling therefore clusters on the source case identifier.

Selection required a public non-bot comment, an identifiable reviewed commit, a reconstructable merge state, a file-local claim, and a clear temporal contrast. These constraints improve provenance and auditability while excluding diffuse architectural comments, style preferences, and claims that require unavailable runtime systems. The benchmark is consequently a controlled slice of review reasoning, not a representative sample of all pull-request feedback.

4.2 Study chronology and leakage control

The chronology is part of the methodology. External PR 50 was frozen and evaluated first. Its receipt failures were inspected only after completion. Receipt-generation changes were then developed on Development PR 20, after which Human PR 20 was generated and frozen before its first model call. The original Human PR results were known before the GPT-5.6 model extension, so that extension is explicitly exploratory. No extension result is relabeled as a new untouched test.

The evaluator commit, prompts, configs, cases, and source excerpts were hashed before the first model call. Two model configurations each ran AR, AR-Text, and EVAR-Hard once. Ground-truth fields are removed from the model-visible task object. Every attempted case produces a result row and transcript. A separate audit checks prompt hashes, transcript integrity, actionability gates, token counts, latency, and failures without calling a judge model.

Table 3. Study phases and evidential status. Only Human PR 20 is an untouched post-development holdout.

Phase	Cases	Decisions	Role in inference
External PR 50	50	600	Frozen first evaluation; later inspected to diagnose receipt failures.
Development PR 20	20	diagnostic	Prompt and verifier development only; no generalization claim.
Human PR 20	20	120	Untouched final holdout and primary evidence for RQ1.
GPT-5.6 extension	20 reused	180	Pre-specified exploratory model-sensitivity analysis.
Cross-provider extension	20 reused	300 attempted	Five models and three matched protocols; 267 decisions valid.

After the original Human PR 20 study was released, we specified an exploratory model extension before making its benchmark calls. The unchanged cases, prompts, verifier semantics, scoring, and budgets were evaluated once per protocol with GPT-5.6 Luna, Terra, and Sol. All configurations used explicit reasoning effort none; seed 41 is a provenance label rather than a deterministic inference control. A transport-only backend change omitted the unsupported temperature field for these models. The evaluator and three configurations were frozen before evaluation.

4.3 Exploratory cross-provider design

We evaluated five exact OpenRouter model slugs: Claude Sonnet 5, Gemini 3.1 Pro Preview, DeepSeek V4 Pro, Kimi K3, and Qwen3.8 Max. The canonical extension reused Human PR 20, seed label 67, low reasoning effort, a shared 2,400-token output cap, and the frozen prompts, verifier, and scoring code. Gateway routing was restricted to endpoints accepting the requested JSON Schema. Every model attempted all 60 decisions. We do not selectively retry failed cases or treat a transport failure as a negative prediction. Instead, only 20/20-valid cells receive FCR/SCR estimates, and incomplete cells contribute operational reliability evidence.

5 Metrics and Analysis

For completed cases, false consensus rate and supported-claim retention are

$$\text{FCR} = \frac{\text{unsupported actionable}}{\text{unsupported completed}}, \quad \text{SCR} = \frac{\text{supported actionable}}{\text{supported completed}}.$$

Lower FCR and higher SCR are desirable. Failures remain explicit and are excluded from both denominators. We report 10,000-sample bootstrap intervals, resampling by case identifier. Paired protocol deltas match model, replicate label, and case before resampling. These are descriptive intervals: the holdout is small and not a random sample from a defined population.

5.1 Why two primary metrics

Reporting only unsupported acceptance would reward a protocol that rejects every claim. Reporting only supported retention would reward one that accepts everything. The pair (FCR, SCR) exposes this tradeoff without collapsing it into a utility function whose error costs are unknown. A protocol dominates another only when it has no higher FCR and no lower SCR, with at least one strict improvement. We use “non-dominance” when one metric improves while the other worsens or when outcomes tie.

5.2 Paired uncertainty

For two protocols p and q , we compute case-matched differences $\Delta\text{FCR} = \text{FCR}_p - \text{FCR}_q$ and $\Delta\text{SCR} = \text{SCR}_p - \text{SCR}_q$. Resampling preserves label balance through the eligible metric denominator and preserves temporal dependence through case clusters. Intervals describe sensitivity to the observed cases; they do not justify frequentist population claims because the benchmark is purposively constructed.

5.3 Operational measurements and audit

Every result row stores run status, model configuration, prompt hashes, verifier outcome, critic decision, final actionability, token counts, latency, and transcript path. The judge-free audit checks that each attempted case has one result and transcript, prompt hashes match the freeze, recorded token totals match model calls, durations are nonnegative, and final actionability obeys the protocol gate. API cost is reconstructed from recorded input/output tokens and the price frozen for each exact model. Failures remain explicit rows and are not silently converted into rejections.

6 Results

6.1 Untouched Human PR 20 holdout

Table 4 reports the final holdout. All 120 attempts completed. Both EVAR configurations produced 18 verified and two failed receipts. The complete audit found no integrity or accounting inconsistency.

Table 4. Human PR 20 results. Each metric has ten eligible cases per row.

Model	Protocol	FCR (95% CI)	SCR (95% CI)	Verified	Cost (USD)
GPT-4.1	AR	.400 (.100-.700)	.700 (.400-1.000)	–	.136
GPT-4.1	AR-Text	.200 (.000-.500)	.700 (.400-1.000)	–	.143
GPT-4.1	EVAR-Hard	.300 (.000-.600)	.600 (.300-.900)	18	.145
GPT-4.1-mini	AR	.400 (.100-.700)	.900 (.700-1.000)	–	.027
GPT-4.1-mini	AR-Text	.200 (.000-.500)	.700 (.400-1.000)	–	.029
GPT-4.1-mini	EVAR-Hard	.200 (.000-.500)	.700 (.400-1.000)	18	.030

With GPT-4.1-mini, AR-Text and EVAR-Hard have identical decisions: relative to AR, both change FCR by -0.200 (95% CI -0.500 to 0.000) and SCR by -0.200 (-0.500 to 0.000). With GPT-4.1, AR-Text changes FCR by -0.200 with no SCR change, whereas EVAR-Hard changes both metrics by -0.100. Thus, this holdout provides no evidence that EVAR-Hard dominates AR-Text.

6.2 Case-level decision transitions

Aggregate rates conceal whether the hard gate merely filters AR-Text decisions or changes the critic’s reasoning. Table 5 compares AR-Text with EVAR-Hard on the same cases. GPT-4.1-mini changes two supported decisions in opposite directions, leaving both aggregate metrics unchanged. GPT-4.1 changes four decisions: two supported claims are lost, one supported claim is recovered, and one unsupported claim becomes actionable. The last transition is especially important. EVAR-Hard is not a monotone post-filter because the critic sees a different evidence representation; verified but irrelevant evidence can persuade it to accept a claim that the textual protocol rejected.

Table 5. AR-Text → EVAR-Hard decision transitions on Human PR 20. “Keep” denotes unchanged actionability.

Model	Supported (10)			Unsupported (10)		
	Keep	Accept→Reject	Reject→Accept	Keep	Accept→Reject	Reject→Accept
GPT-4.1	7	2	1	9	0	1
GPT-4.1-mini	8	1	1	10	0	0

The case-level view rules out a simple interpretation of the gate as a conservative filter. On the untouched holdout it neither outperforms textual evidence nor merely removes claims that AR-Text would have accepted. The outcome depends on whether the receipt verifies and on what the critic makes of the verified observation.

6.3 Exploratory GPT-5.6 model extension

All 180 extension attempts completed, and the judge-free audit reported no inconsistency. Table 6 shows one run per model and protocol. Verified counts apply to the 20 EVAR-Hard receipts; other protocols do not submit receipts. Standard token prices at the August 30, 2026 freeze came from the official OpenAI model comparison.¹

Table 6. Exploratory extension on the unchanged Human PR 20 cases.

Model	Protocol	FCR (95% CI)	SCR (95% CI)	Verified	Cost (USD)
Luna	AR	.100 (.000-.300)	.700 (.400-1.000)	–	.015
Luna	AR-Text	.100 (.000-.300)	.700 (.400-1.000)	–	.015
Luna	EVAR-Hard	.000 (.000-.000)	.600 (.300-.900)	17	.016
Terra	AR	.100 (.000-.300)	.800 (.500-1.000)	–	.149
Terra	AR-Text	.100 (.000-.300)	.600 (.300-.900)	–	.155
Terra	EVAR-Hard	.100 (.000-.300)	.800 (.500-1.000)	18	.158
Sol	AR	.100 (.000-.300)	.800 (.500-1.000)	–	.292
Sol	AR-Text	.100 (.000-.300)	.700 (.400-1.000)	–	.302
Sol	EVAR-Hard	.100 (.000-.300)	.700 (.400-1.000)	19	.308

Luna EVAR-Hard exchanges a 0.100 FCR reduction for a 0.100 SCR reduction relative to AR. Terra EVAR-Hard exactly matches AR and retains two more supported claims than AR-Text. Sol EVAR-Hard exactly matches AR-Text and retains one fewer supported claim than AR. Descriptively

¹<https://developers.openai.com/api/docs/models/compare>

pooling repeated measurements on the same 20 cases gives AR 0.100/0.767, AR-Text 0.100/0.667, and EVAR-Hard 0.067/0.700 for FCR/SCR; this is not an independent-sample estimate. Total estimated token cost was \$1.411.

Nor do the three newer models form a simple capability ladder. Receipt verification rises from 85% for Luna to 95% for Sol, but neither final metric improves monotonically. Better receipt construction is useful, yet it is plainly not sufficient.

6.4 Cross-model Pareto synthesis

Table 7 compares EVAR-Hard with each matched baseline instead of averaging across models. A negative Δ FCR is favorable; a positive Δ SCR is favorable. Of the ten comparisons, EVAR-Hard dominates once, is dominated twice, ties three times, and exchanges safety for retention four times. The only dominance result is Terra against AR-Text. It disappears when Terra is compared with AR and is not repeated by Luna or Sol. Pooling these outcomes would produce a cleaner number but a less faithful account of the experiment.

Table 7. Matched Pareto comparison on Human PR 20. Deltas are EVAR-Hard minus baseline.

Model	Baseline	Δ FCR	Δ SCR	Relation
GPT-4.1	AR	-.100	-.100	Tradeoff
GPT-4.1	AR-Text	+.100	-.100	Dominated
GPT-4.1-mini	AR	-.200	-.200	Tradeoff
GPT-4.1-mini	AR-Text	.000	.000	Tie
Luna	AR	-.100	-.100	Tradeoff
Luna	AR-Text	-.100	-.100	Tradeoff
Terra	AR	.000	.000	Tie
Terra	AR-Text	.000	+.200	Dominates
Sol	AR	.000	-.100	Dominated
Sol	AR-Text	.000	.000	Tie

Taken together, the five OpenAI configurations show that verification is not a model-independent wrapper with a stable effect. The reviewer, receipt representation, deterministic checks, and critic jointly determine the operating point.

6.5 Exploratory cross-provider results

Table 8 reports a fresh matched run in which every model attempted all three 20-case cells. Claude and Gemini produced 60 valid decisions each. Kimi produced 55, Qwen 49, and DeepSeek 43. The 33 failures were overwhelmingly empty reviewer responses after the endpoint consumed the output allowance in reasoning; the runner records them as ModelOutputError. We retain these gaps because they describe whether the experiment is operationally viable, not because they can be filled by imputation.

Eight cells are complete. Claude yields zero false consensus under all protocols, with supported-claim retention of .600, .600, and .500 for AR, AR-Text, and EVAR-Hard. Gemini moves from .100/.800 under AR to .000/.800 under both evidence protocols. Kimi’s complete AR-Text and EVAR-Hard cells score .000/.700 and .000/.800, respectively, but its incomplete AR cell prevents the intended three-way comparison. Claude’s 18/20 verified receipts and Gemini’s 20/20 again show that a high receipt-verification rate does not imply a retention gain.

The cross-provider run therefore adds two lessons. Gemini provides one favorable paired point: both evidence protocols remove one AR false consensus without losing a supported claim. Claude

Table 8. Canonical cross-provider accounting. “Complete cells” counts 20-case protocol blocks.

Model	Attempted	Valid	Failed	Complete cells
Claude Sonnet 5	60	60	0	3/3
Gemini 3.1 Pro	60	60	0	3/3
DeepSeek V4 Pro	60	43	17	0/3
Kimi K3	60	55	5	2/3
Qwen3.8 Max	60	49	11	0/3

Table 9. Descriptive operating points for complete cross-provider cells. No intervals are shown because these are exploratory single calls on reused cases.

Model	Protocol	FCR	SCR	Verified
Claude	AR	.000	.600	–
Claude	AR-Text	.000	.600	–
Claude	EVAR-Hard	.000	.500	18/20
Gemini	AR	.100	.800	–
Gemini	AR-Text	.000	.800	–
Gemini	EVAR-Hard	.000	.800	20/20
Kimi	AR-Text	.000	.700	–
Kimi	EVAR-Hard	.000	.800	19/20

provides the counterexample: EVAR-Hard loses one supported claim while all protocols already have zero FCR. More basically, model reasoning quality cannot be compared until the serving path reliably returns the receipt schema. DeepSeek and Qwen did not meet that prerequisite, even after the shared cap was doubled from the earlier pilot setting. The canonical run cost an estimated \$3.350 from recorded tokens; exploratory retries and diagnostics raised total gateway usage to \$9.241.

6.6 Earlier frozen External PR 50 experiment

The earlier study pooled two repetitions for each model and protocol. GPT-4.1 EVAR-Hard reduced FCR from 0.120 under both baselines to 0.060 while reducing SCR from 1.000 to 0.860. GPT-4.1-mini reduced FCR from 0.160 under AR and 0.120 under AR-Text to 0.041, but reduced SCR from 0.980 to 0.420. One mini EVAR output failed JSON parsing and remained an explicit failed row. The directionally favorable FCR result therefore came with substantial missed supported claims.

Table 10. Earlier External PR 50 operating points (two repetitions pooled).

Model	Protocol	Attempts	Failed	FCR	SCR
GPT-4.1	AR	100	0	.120	1.000
GPT-4.1	AR-Text	100	0	.120	1.000
GPT-4.1	EVAR-Hard	100	0	.060	.860
GPT-4.1-mini	AR	100	0	.160	.980
GPT-4.1-mini	AR-Text	100	0	.120	.980
GPT-4.1-mini	EVAR-Hard	100	1	.041	.420

6.7 Receipt validity and decision quality

The studies show that receipt validity and final quality are not interchangeable. In the first frozen external experiment, GPT-4.1 produced 76 verified receipts per 100 attempts while GPT-4.1-mini produced 47 among 99 completed attempts; their supported retention differed accordingly. After v2 development, both original Human PR models verified 18 of 20 receipts, yet EVAR-Hard did not improve on AR-Text. In the GPT-5.6 extension, receipt validity rose from 17/20 for Luna to 19/20 for Sol without monotonic improvement in either primary metric.

Table 11. Failure surfaces exposed by the receipt pipeline.

Surface	Observable signal	Effect on actionability
Serialization	Invalid or truncated structured output	Explicit failed call or bounded parse retry
Path/range	Missing file or invalid line interval	Receipt fails verification
Structural match	Submitted source does not match fixture	Receipt fails verification
Behavioral witness	Timeout, exit mismatch, or absent pass marker	Receipt fails verification
Evidence relevance	Valid observation does not establish the claim	Critic may reject; otherwise residual false consensus
Critic judgment	Verified evidence is interpreted incorrectly	False acceptance or supported-claim loss remains possible

6.8 Development diagnostics versus held-out evidence

Synthetic and small commit-grounded pilots were useful for finding implementation faults, including display-line cleanup, evidence-role inversion, path recovery, import-complete fixtures, evaluation-order checks, and brittle one-line witnesses. A post-hoc receipt-repair pass reached perfect scores on the inspected External PR 20 cases. That result is not counted as independent evaluation: those cases directly informed the repair. Its scientific role is diagnostic evidence that the harness can encode discovered checks, not evidence that those checks generalize.

7 Discussion

The empirical story is less tidy than the protocol. External PR 50 initially suggested a familiar bargain: the hard gate admitted fewer unsupported claims, but it also discarded supported ones. We then improved receipt generation on a separate development split. On Human PR 20, 90% of receipts verified for both models, so the obvious mechanical bottleneck had largely receded. The expected gain over textual evidence did not appear. GPT-4.1-mini tied AR-Text, and GPT-4.1 was slightly worse on both measures.

Looking at individual transitions explains why. EVAR-Hard is not AR-Text followed by a filter. The critic receives a different representation of the evidence, and that can alter its judgment in either direction. In one GPT-4.1 case, an unsupported claim rejected by AR-Text became actionable under EVAR-Hard. The receipt was valid enough to pass the verifier, but validity did not make the observation relevant. Conversely, a failed receipt can suppress a sound claim before the critic has any opportunity to recover it. Mechanical validity, relevance, critic judgment, and final actionability are separate stages, and errors can enter at each one.

The newer models do not simplify the picture. Luna exchanges a lower FCR for lower retention, Terra matches AR while outperforming AR-Text on retention, and Sol matches AR-Text. Receipt verification improves from 85% to 95% across those models without a corresponding ordering of final decisions. The natural conclusion is not that verification wins or loses, but that its effect

depends on who writes the receipt, what the verifier can check, and how the critic interprets the result.

The sample is too small to rank protocols in a broader population: one changed decision moves a holdout rate by 0.100. It is large enough to reject the claim that a hard evidence gate is automatically better than textual evidence. The benefit that survives every run is narrower and procedural. EVAR makes the acceptance path inspectable, retains failed evidence instead of burying it in dialogue, and prevents critic agreement from overriding a failed check.

7.1 Answers to the research questions

RQ1: decision quality. Deterministic verification changes which claims become actionable, but it does not improve the two primary metrics consistently. The first frozen study trades lower unsupported acceptance for lost supported claims. On the untouched human holdout, EVAR-Hard ties or trails AR-Text.

RQ2: model sensitivity. Receipt construction varies sharply with the model, especially in the earlier external study. Even so, the later extension shows that a higher verification rate does not order the final outcomes. The protocol behaves as an interaction among the reviewer, critic, receipt language, and verifier, not as a fixed post-processing step.

RQ3: auditability. Here the result is clearer. Invalid JSON, missing paths, source mismatches, failing witnesses, timeouts, and gate inconsistencies become named records rather than unobserved reasoning errors. That record makes it possible to reconstruct why a finding crossed—or failed to cross—the actionability boundary.

7.2 Design implications

An evidence schema is part of the model interface, not neutral plumbing. Path vocabulary, source formatting, nullable fields, and repair policy all affect whether the model can express an observation that the verifier understands. The low verification rate of GPT-4.1-mini on External PR 50 and the much higher rate after development make this dependence visible.

Verifier coverage also needs the same train/test discipline as a learned component. It is tempting to add a structural check whenever a final case fails. Doing so may improve the tool, but the resulting score is diagnostic, not held-out evidence. Our post-hoc perfect result on External PR 20 is reported in exactly that role.

Finally, a failed receipt is an abstention, even when the implementation records it as a rejected finding. A production system needs to decide where those abstentions go. Silently dropping them may be acceptable in a high-noise assistant, but not in a safety-sensitive review process. A more useful deployment might keep deterministic verification as a privileged signal while routing unverified claims to a clearly separated human-review queue.

Replacing the deterministic gate with another semantic judge would improve coverage, but it would also recreate the correlated-error problem that motivated EVAR. Such a judge may still be useful, provided its output is reported as judgment rather than verification.

7.3 What the study does not establish

This experiment evaluates supplied claims, not open-ended review. It says nothing directly about how many defects an agent discovers, whether developers value its comments, or whether review becomes faster. We also leave the relative cost of a false alarm and a missed finding unspecified; that is why FCR and SCR remain separate. The cross-provider extension broadens model coverage, but it reuses the same cases and contributes repeated and operational evidence, not new independent examples. Incomplete provider cells cannot be used to rank protocols because the missing outputs are neither random nor negative decisions.

8 Threats to Validity

Construct validity. FCR is the rate at which supplied unsupported claims become actionable. It should not be read as the false-positive rate of an agent searching freely for defects. Likewise, SCR captures retention of comments grounded in a public review-and-fix sequence, not whether each comment is well written or useful to a developer. A verified receipt proves only that the submitted observation passed a check; it does not prove semantic entailment. Keeping these measurements separate avoids treating source matching as review correctness.

Internal validity. Human PR 20 treats the reviewed commit and the later merge edit as temporal evidence for the label. This is auditable, but a merge may address only part of a comment, and we necessarily inspected every pair while constructing the benchmark. We froze the evaluator before the holdout calls, removed labels from model-visible prompts, clustered temporal pairs in the bootstrap, and retained failed calls. Independent expert adjudication would still be stronger than this construction procedure.

External validity. The final holdout is ten source comments from five Python repositories, paired into ten cases per label. Requiring a clean temporal contrast favors localized, explicit claims. Diffuse architectural concerns, other programming languages, and review comments that depend on an unavailable runtime are largely absent. Focused excerpts also offer much less context than a full pull request—less to search, but also less to misunderstand.

Reliability and conclusion validity. Most holdout cells contain one stochastic call per case, and the configured seeds are provenance labels rather than guaranteed inference controls. With ten eligible cases, a single decision moves a metric by .100. The cluster bootstrap shows sensitivity to the observed pairs; it does not create a sampled population. Gateway routing, throttling, and structured-output failures add further variability to the provider extension, so incomplete cells are excluded from performance comparisons.

Data ethics. The source repositories and review comments are public, and URLs and usernames are retained for provenance. No private communication or inferred developer attributes are included. Public availability is not the same as research consent, however: the comments were written to maintain software. We therefore restrict the analysis to technical claims and report model behavior in aggregate rather than profiling reviewers.

Extension validity. Both model extensions reuse Human PR 20 after the original outcomes were known. They are repeated measurements, not additional benchmark examples. Reasoning settings are not necessarily comparable across vendors, and exact model aliases, routing, behavior, and prices can change after the freeze. The gateway may also choose among eligible serving providers. These facts are why the provider analysis separates complete-cell quality estimates from 300-attempt reliability accounting.

Implementation scope and safety. The verifier is Python-specific and recognizes a limited set of structural and behavioral observations. The reported experiments used trusted fixtures and shell-free local execution under a timeout. The current evaluator additionally offers a hardened Docker backend with a read-only repository mount, no network, no Linux capabilities, a non-root user, a no-new-privileges policy, and CPU, memory, process, and temporary-filesystem limits. Its command construction is covered by tests, but Docker Desktop was unavailable for an end-to-end smoke run in this environment; we therefore do not retroactively describe the reported results as containerized.

9 Reproducibility and Availability

The existing artifact contains evaluator code, prompts, configs, benchmark snapshots, all 720 original canonical decisions and transcripts, input and output manifests, audit reports, analysis scripts, and the independent-review packet. The 180-decision GPT-5.6 extension and 300-attempt cross-provider extension are prepared for the revised artifact; their configs, run indices, reports, transcripts, and failed rows preserve the extension evidence. The Human PR 200 acquisition pool and annotation software are work in progress, and the paper makes no result claim from those unlabeled candidates. Identifying repository and project-site URLs are omitted during double-blind review. An anonymized snapshot will be supplied through the venue’s artifact mechanism; archival DOI and public links will be restored in the non-anonymous version.

The artifact has four layers. Input manifests hash cases, repository snapshots, prompts, model configs, evaluator code, verifier code, and scoring code. Run indices identify canonical JSONL outputs. Judge-free audit reports check completeness and invariants. Output manifests hash every canonical result and transcript. The cross-provider manifest additionally records the gateway endpoint, exact model slugs, reasoning setting, token cap, and schema-routing requirement.

The core deterministic reproduction path is:

```
python -m unittest discover -s tests
python -m evar.preflight --config CONFIG --cases CASES
python -m evar.run --protocol PROTOCOL --cases CASES \
    --config CONFIG --output-dir RESULTS
python scripts/report_human_pr_20_cross_provider.py
python scripts/audit_human_pr_20_cross_provider.py
```

Model-backed reproduction requires the corresponding API credential and will not be byte-identical because provider inference is not guaranteed deterministic. The preserved transcripts and metadata support outcome-level rather than bit-level replication.

10 Conclusion

EVAR began with a simple premise: agreement between two language models should not be enough to make a code-review claim actionable. Requiring a checked receipt does enforce a clearer boundary, and it turns several hidden failures into inspectable records. The experiments also show the limit of that idea. A receipt can verify and still be irrelevant, while a sound claim can be lost because its receipt fails. On the final human-comment holdout, the hard gate offers no decision-quality advantage over textual evidence; across later models, its effect varies.

That leaves a narrower but useful result. Deterministic evidence improves the provenance of an accepted finding, not necessarily the finding itself. The five-provider extension sharpens rather than overturns that conclusion: Gemini gives a favorable point, Claude gives a retention counterexample, and 33 provider failures show that schema reliability is itself part of the system. Establishing a performance benefit still requires more independent review comments, expert adjudication, repeated calls, and full pull-request context. The artifact now includes the acquisition and adjudication machinery for that larger test without presenting unreviewed candidates as ground truth.

A Frozen Protocol Pseudocode

```
input: candidate claim c, repository snapshot R
receipt = reviewer(c, R)          # one schema-constrained call

if protocol == AR:
```

```

687     observation = NOT_USED
688     decision = critic(c, receipt, observation)
689 elif protocol == AR_TEXT:
690     text_evidence = project_text_fields(receipt)
691     decision = critic(c, receipt, text_evidence)
692 else:
693     # EVAR-Hard
694     observation = deterministic_verify(receipt, R)
695     receipt, observation = deterministic_repair_if_applicable(
696         receipt, observation, R)
697     decision = critic(c, receipt, observation)
698 actionable = (decision == ACCEPT)
699 if protocol == EVAR_HARD:
700     actionable = actionable and observation == VERIFIED \
701         and receipt.role == SUPPORTS_CLAIM

```

702
703 emit result row and complete transcript

704 The pseudocode elides bounded schema retry and error recording but preserves the configured
705 acceptance semantics. Every protocol uses one reviewer and one critic call. AR-Text changes the
706 evidence projection and critic prompt; EVAR-Hard changes the verifier input, critic prompt, and
707 final gate.

708 709 **B Case and Output Schemas**

710 Each benchmark case is a JSON object with four field groups: identity and label; claim and family;
711 repository snapshot and context paths; and source-comment provenance. The runner exposes only
712 the task description, candidate claim, claim family, valid repository paths, and file contents to
713 the model. Labels, snapshot kind, pairing, source-comment metadata, and construction evidence
714 remain evaluator-only. Prompt-template SHA-256 hashes are recorded with every result; Appendix
715 data files preserve the exact field names.

716 All three reviewer prompts use the same strict top-level schema: an object containing exactly
717 one receipt. The receipt requires a claim identifier and text, evidence type and role, file, nullable
718 line bounds, nullable verification command, nullable expected exit code, nullable expected-output
719 substring, and a falsification condition. The schema rejects additional properties. A response that
720 cannot be parsed after the configured retry becomes `ModelOutputError`; the evaluator does not
721 synthesize a replacement.

722 723 **C Interaction Schedule**

724 The configured protocols are matched at two model calls per case. The reviewer emits one receipt.
725 AR calls the critic with a sentinel stating that external verification is unused. AR-Text constructs a
726 textual-evidence view from the receipt and calls its evidence-aware critic prompt. EVAR-Hard per-
727 forms deterministic verification (and, when triggered, one deterministic repair and re-verification)
728 before calling the critic. There is no model revision turn in the reported configured runs.

729 The runner records a call-level trace with request role, model slug, prompt hash, request start/end
730 timestamps, token counts, response text, parser outcome, and retry number. A transcript is written
731 even when the first call fails. This is useful in practice: invalid JSON, a valid JSON object with an
732 empty receipt list, and a valid receipt that points at the wrong commit are different observations
733 and should not collapse into one generic failure.

734
735

D Receipt Validation Rules

Structural validation normalizes display artifacts such as Markdown fences, leading line numbers, and surrounding whitespace. It reads the requested file from the frozen snapshot and normally compares the normalized observation with the selected interval. Two conservative recovery paths are part of the frozen verifier: an unambiguous suffix, function-name, or sole-Python-file match can recover a stale structural path; and an interval extending beyond end-of-file can search the recovered file for the submitted observation. Behavioral receipts receive neither recovery. Behavioral validation parses the command into an argument vector, applies a timeout, and checks exit status plus a required EVAR_WITNESS_PASS marker. The local backend uses `shell=False`. The optional container backend invokes Docker without a shell and adds `-network none`, a read-only bind mount, capability dropping, `no-new-privileges`, a non-root UID, PID/CPU/memory limits, and a bounded temporary filesystem. The verifier returns typed failure reasons for missing paths, wrong observations, exit mismatches, and timeouts. Generic successful structural recovery is deterministic but is not separately tagged, an auditability limitation for a future version.

The evidence role is checked independently of textual similarity. The evaluator performs only two frozen deterministic repairs: it aligns the role with an explicit opposite-role AST observation, or falls back from a syntactically invalid inline-Python behavioral witness to structural checking. Each repair is logged and re-verified. It does not rewrite claims, choose new files or ranges, or ask a model for semantic repair.

E Statistical and Cost Details

FCR and SCR are computed after filtering to completed rows of the relevant ground-truth class. We report the numerator and denominator alongside each rate. Bootstrap intervals resample source case identifiers, not individual protocol rows, so the two temporal members of a human comment remain together. Paired deltas first join protocols on model, replicate, and case identifier and then resample those joined case clusters. A zero-width interval can occur for a metric that is identical in every resampled cluster; it is not evidence of large population certainty.

Token cost is computed from recorded input and output tokens and the price table frozen with each model configuration. Retries are included in cost and latency. Failed requests therefore consume budget and remain part of operational reporting even though they do not enter FCR/SCR denominators. The cross-provider table is restricted to validity accounting because gateway routing, model availability, and duplicate pilot attempts make a pooled quality estimate inappropriate.

F Representative Failure Cases

The most common EVAR failure on the frozen external benchmark was not a verifier bug but a receipt that cited a nearby true line which did not establish the claim. Other examples included a command that passed but never printed the required marker, a line range copied from a display excerpt rather than the repository file, and a contradiction receipt submitted with the support role. On the cross-provider run, DeepSeek frequently returned an empty or non-JSON reviewer response after consuming its output budget; those rows are 'ModelError', not negative review decisions. These examples explain why the paper reports receipt validity, critic decisions, and actionability as separate fields.

G What a Larger Replication Should Add

The current design deliberately controls context and claim wording. A stronger replication should sample review comments before seeing their outcome, include complete pull-request snapshots, obtain two independent expert labels with adjudication, and preregister the sampling frame. It should

also repeat each model-protocol cell, report calibration and abstention, and evaluate multilingual repositories. The present artifact supplies the receipt and audit machinery needed for that study; it should not be mistaken for evidence that 20 temporal cases represent the wider code-review population.

H Human PR 200 Expansion Protocol

We have acquired, but not labeled, the candidate pool for the larger replication. The combined pool contains 682 public review-comment candidates from 63 repositories. Acquisition requires a human-authored inline review comment, a merged pull request, an exact reviewed commit and merge commit, a changed anchored target, hashes of both complete files, and stable source URLs. It retains at most one candidate per pull request and excludes repositories used by Human PR 20. These filters establish provenance; they do not establish eligibility or a benchmark label.

The first annotation tranche contains 276 candidates, selected before annotation with up to 50 comments per available language and no more than six per repository. Two experts receive independently randomized, label-free records containing the comment, review snapshot, merge snapshot, and provenance. Each marks eligibility, writes a short normalized claim, chooses one of the five frozen claim families, and separately judges support at review and absence at merge. An excluded item requires a reason. The two exports must contain identical candidate sets, distinct stable reviewer identifiers, and complete decisions.

Exact agreements are resolved automatically. Any difference in eligibility, normalized claim, family, temporal judgment, or exclusion reason enters a third, blinded adjudication queue. The adjudicator must have an identifier distinct from both reviewers. The merger stores reviewer identifiers, resolution mode, adjudicator identifier when used, and SHA-256 hashes of every input export. The case renderer rejects a row unless that provenance is complete. This closes a weakness in the earlier draft, whose renderer could accept one filled annotation object even though the written protocol called for two reviewers.

After adjudication, deterministic selection first establishes at least 20 represented repositories and then balances language and claim family while enforcing the six-comment repository cap. It fails closed unless 100 eligible source comments remain. Those comments yield 200 temporal cases, one supported review snapshot and one unsupported merge snapshot per claim. The frozen manifest records the source and output hashes, seed, candidate identifiers, repository count, and stratum counts. Until experts complete this process, the 682 records remain an acquisition artifact and no Human PR 200 performance result is reported.

I Cross-Provider Frozen Configuration

Table 12. Exact models frozen for the exploratory cross-provider extension.

Family	Exact model slug	Shared settings	Cells
Claude	anthropic/claude-sonnet-5	low reasoning, 2,400-token cap	3
Gemini	google/gemini-3.1-pro-preview	low reasoning, 2,400-token cap	3
Kimi	moonshotai/kimi-k3	low reasoning, 2,400-token cap	3
DeepSeek	deepseek/deepseek-v4-pro-0813	low reasoning, 2,400-token cap	3
Qwen	qwen/qwen3.8-max	low reasoning, 2,400-token cap	3

Temperature is omitted for all five models. Structured output uses strict JSON Schema, and gateway provider routing requires endpoints that accept the requested parameters. Seed 67 is stored only as provenance unless the routed endpoint explicitly honors it.

J Audit Invariants

For each canonical run, the audit requires: (1) exactly one row for each attempted case; (2) a corresponding transcript; (3) model and protocol agreement between row and transcript; (4) frozen prompt hashes; (5) nonnegative latency; (6) call-level token totals equal to row totals; (7) failed runs contain a failure type and reason; and (8) EVAR actionability implies both a verified receipt and critic acceptance. These checks do not judge semantic correctness; benchmark labels determine the reported metrics.

References

- [1] A. Madaan et al. Self-Refine: Iterative Refinement with Self-Feedback. *arXiv:2303.17651*, 2023.
- [2] Y. Du, S. Li, A. Torralba, J. B. Tenenbaum, and I. Mordatch. Improving Factuality and Reasoning in Language Models through Multiagent Debate. *arXiv:2305.14325*, 2023.
- [3] N. Shinn, F. Cassano, E. Berman, A. Gopinath, K. Narasimhan, and S. Yao. Reflexion: Language Agents with Verbal Reinforcement Learning. *arXiv:2303.11366*, 2023.
- [4] Z. Gou et al. CRITIC: Large Language Models Can Self-Correct with Tool-Interactive Critiquing. *arXiv:2305.11738*, 2023.
- [5] J. Yang et al. SWE-agent: Agent-Computer Interfaces Enable Automated Software Engineering. *arXiv:2405.15793*, 2024.
- [6] Z. Li et al. Automating Code Review Activities by Large-Scale Pre-training. *arXiv:2203.09095*, 2022.
- [7] C. E. Jimenez et al. SWE-bench: Can Language Models Resolve Real-World GitHub Issues? *arXiv:2310.06770*, 2023.
- [8] D. Kumar. SWE-PRBench: Benchmarking AI Code Review Quality Against Pull Request Feedback. *arXiv:2603.26130*, 2026.
- [9] Z. Zeng et al. Benchmarking and Studying the LLM-based Code Review. *arXiv:2509.01494*, 2025.
- [10] A. Bacchelli and C. Bird. Expectations, Outcomes, and Challenges of Modern Code Review. In *Proceedings of ICSE*, pp. 712–721, 2013. doi:10.1109/ICSE.2013.6606617.
- [11] C. Sadowski, E. Söderberg, L. Church, M. Sipko, and A. Bacchelli. Modern Code Review: A Case Study at Google. In *Proceedings of ICSE-SEIP*, pp. 181–190, 2018.
- [12] U. Cihan et al. Automated Code Review in Practice. In *Proceedings of ICSE-SEIP*, 2025. doi:10.1109/ICSE-SEIP66354.2025.00043.
- [13] K. Tantithamthavorn et al. RovoDev Code Reviewer: A Large-Scale Online Evaluation of LLM-based Code Review Automation at Atlassian. In *Proceedings of ICSE-SEIP*, 2026. doi:10.1145/3786583.3786851.
- [14] I. Jaoua, O. Ben Sghaier, and H. A. Sahraoui. Combining Large Language Models with Static Analyzers for Code Review Generation. In *Proceedings of MSR*, pp. 174–186, 2025.
- [15] R. Hu et al. Benchmarking LLMs for Fine-Grained Code Review with Enriched Context in Practice. In *Proceedings of FSE Industry Papers*, 2026. *arXiv:2511.07017*.