REVERSE PAIRS

*In this problem, similar to counting inversions we are supposed to count number of pairs where left element is greater than double of right element,

Brute force solution is to obviously check for all pairs by using 2 loops. Time Complexity is $O(N^2)$

Optimal solution is to use a solution similar to our counting pairs solution with slight modification. When an element on the left fails to form a pair with an element on the right, we increment left but we let right stay as we know right will definitely form pairs

Pseudocode:

merge Sort (am, low, high) el

if (low > = high) return

mid = (low + high) | 2

merge Sort (am, low, mid)

merge Sort (am, mid + 1, high)

merge (am, low, mid, high)

merge (am, low, mid, high) el

left = low

wight = mid + 1

```
int ans[]
   while (left <= mid && right < high) &
      if (aur [left] > 2 * aur [right]) '
         count + = mid - left + 1
         right ++
        elše
        Left ++
   left = low
   right = mid + 1
   while (left <= mid && right < high)
if (arr [left] > = arr [right]) {
         ans append (aur [right])
         right ++ , count + = (mid-left+1)
      r else
         ans append (aur [left])
         Left ++
   while (left <= mid)
      are append (am [left])
      Left++
  while (might < high) (
are append (arm [might])
 return aris
count = 0
reverse Pairs (arr, N)
  merge Sort (aur, 0, N-1)
```

