Ember power card: after an outage, the kiln lead inspects the load before authorizing a new firing event.

Ember cooling card: a thermocouple fault blocks unloading until an independent calibrated probe confirms the temperature.

Ember sample card: glaze test tiles are stored with their glaze batch ID for 18 months.

Ember restart card: restarting does not erase the original power-loss timestamp or the interrupted curve.

Ember witness card: witness cones are placed on the upper and lower shelves to compare heatwork.

Ember terminology: TC means thermocouple; a TC reading is temperature evidence, not a food-safety certification.

Ember board card: a glaze run requires inspection of the affected kiln board before it is reused.

Ember repair card: only the maintenance technician disconnects and opens the controller enclosure.

Ember audit card: every revised firing plan records the kiln lead identity and the reason for change.

Ember storage card: unfired wet pieces stay on the drying rack, not inside a warm kiln awaiting an unscheduled cycle.

Ember schedule card: the standard glaze cycle starts its front ramp at 100 degrees Celsius.

Ember cooling log: natural cooling observations are recorded every 30 minutes until unloading is permitted.

Ember packaging card: a visible through-crack must be disclosed; packaging cannot turn a cracked piece into an intact delivery.

Ember inventory card: every kiln board has an asset label distinct from a firing batch identifier.

Ember hygiene card: dry sanding dust is collected at the workstation, not blown into the shared room.

Ember transport card: cooled pieces are counted against the loading map before packaging.

Ember contact card: maintenance is requested through the workshop register; no controller override password is published.

Ember scope card: firing temperatures alone do not establish compliance for food-contact use.