# .\SQLEXPRESS

## Greencard

| | |
|---|---|
| **Server** | .\SQLEXPRESS |
| **Author** | sosewe |
| **Created** | Monday, February 20, 2017 2:06:55 PM |
| **File Path** | C:\Users\sosewe\Desktop\GreencardDatabaseDocumentation-2017-02-20T14-06-55.pdf |

# Table of Contents

Table of Contents ..... 2
- .\SQLEXPRESS ..... 4
  - User databases ..... 6
    - Greencard Database ..... 7
      - Tables ..... 10
        - [dbo].[AdherenceOutcome] ..... 13
        - [dbo].[AdverseEvent] ..... 15
        - [dbo].[ARTInitiationBaseline] ..... 17
        - [dbo].[ARTUseHistory] ..... 20
        - [dbo].[ARVTreatmentTracker] ..... 22
        - [dbo].[ComplaintsHistory] ..... 24
        - [dbo].[County] ..... 26
        - [dbo].[Disclosure] ..... 28
        - [dbo].[HIVEnrollmentBaseline] ..... 30
        - [dbo].[HIVTesting] ..... 32
        - [dbo].[LookupItem] ..... 34
        - [dbo].[LookupMaster] ..... 36
        - [dbo].[LookupMasterItem] ..... 38
        - [dbo].[ModuleMaster] ..... 39
        - [dbo].[Patient] ..... 41
        - [dbo].[PatientAllergy] ..... 43
        - [dbo].[PatientAppointment] ..... 45
        - [dbo].[PatientCareending] ..... 47
        - [dbo].[PatientChronicIllness] ..... 49
        - [dbo].[PatientClinicalDiagnosis] ..... 51
        - [dbo].[PatientClinicalNotes] ..... 53
        - [dbo].[PatientDiagnosis] ..... 55
        - [dbo].[PatientEncounter] ..... 57
        - [dbo].[PatientEnrollment] ..... 59
        - [dbo].[PatientFamilyPlanning] ..... 61
        - [dbo].[PatientFamilyPlanningMethod] ..... 63
        - [dbo].[PatientIdentifier] ..... 64
        - [dbo].[PatientLabTracker] ..... 66
        - [dbo].[PatientMaritalStatus] ..... 68
        - [dbo].[PatientMasterVisit] ..... 70
        - [dbo].[PatientOVCStatus] ..... 72
        - [dbo].[PatientPHDP] ..... 74

[dbo].[PatientPopulation] ..... 76
[dbo].[PatientProphylaxis] ..... 78
[dbo].[PatientReferral] ..... 80
[dbo].[PatientScreening] ..... 82
[dbo].[PatientTransferIn] ..... 84
[dbo].[PatientTreatmentSupporter] ..... 86
[dbo].[PatientVitals] ..... 88
[dbo].[Person] ..... 90
[dbo].[PersonContact] ..... 92
[dbo].[PersonLocation] ..... 94
[dbo].[PersonRelationship] ..... 96
[dbo].[PhysicalExamination] ..... 97
[dbo].[Pregnancy] ..... 99
[dbo].[PregnancyIndicator] ..... 101
[dbo].[ServiceEntryPoint] ..... 103
[dbo].[TBTreatmentTracker] ..... 105
[dbo].[TreatmentEventTracker] ..... 107
[dbo].[User] ..... 109
[dbo].[Vaccination] ..... 111
Views ..... 113
[dbo].[LookupItemView] ..... 114
Database Roles ..... 116
db_accessadmin ..... 116
db_backupoperator ..... 116
db_datareader ..... 117
db_datawriter ..... 117
db_ddladmin ..... 117
db_denydatareader ..... 118
db_denydatawriter ..... 118
db_owner ..... 118
db_securityadmin ..... 118
public ..... 119

# .\SQLEXPRESS

## Databases (1)

- Greencard

## Server Properties

| Property | Value |
|---|---|
| Product | Microsoft SQL Server |
| Version | 12.0.2569.0 |
| Language | English (United States) |
| Platform | NT x64 |
| Edition | Enterprise Edition (64-bit) |
| Processors | 4 |
| OS Version | 6.3 (14393) |
| Physical Memory | 7888 |
| Is Clustered | False |
| Root Directory | C:\Program Files\Microsoft SQL Server\MSSQL12.SQLEXPRESS\MSSQL |
| Collation | SQL_Latin1_General_CP1_CI_AS |

## Server Settings

| Property | Value |
|---|---|
| Default data file path | C:\Program Files\Microsoft SQL Server\MSSQL12.SQLEXPRESS\MSSQL\DATA\ |
| Default backup file path | C:\Program Files\Microsoft SQL Server\MSSQL12.SQLEXPRESS\MSSQL\Backup |
| Default log file path | C:\Program Files\Microsoft SQL Server\MSSQL12.SQLEXPRESS\MSSQL\DATA\ |
| Recovery Interval (minutes) | 0 |
| Default index fill factor | 0 |
| Default backup media retention | 0 |
| Compress Backup | False |

## Advanced Server Settings

| Property | Value |
|---|---|
| Locks | 0 |
| Nested triggers enabled | True |
| Allow triggers to fire others | True |

| | |
|---|---|
| Default language | English |
| Network packet size | 4096 |
| Default fulltext language LCID | 1033 |
| Two-digit year cutoff | 2049 |
| Remote login timeout | 10 |
| Cursor threshold | -1 |
| Max text replication size | 65536 |
| Parallelism cost threshold | 5 |
| Scan for startup procs | False |
| Transform noise words | False |
| Blocked process threshold | 0 |
| Filestream access level | False |
| Optimize for ad hoc workloads | False |

# User databases

## Databases (1)

- Greencard

# Greencard Database

## Database Properties

| Property | Value |
|---|---|
| SQL Server Version | SQL Server 2014 |
| Compatibility Level | SQL Server 2014 |
| Last backup time | 02/08/2017 |
| Last log backup time | - |
| Creation date | Dec 21 2016 |
| Users | 4 |
| Database Encryption Enabled | False |
| Database Encryption Algorithm | None |
| Database size | 7.50 MB |
| Unallocated space | 2.77 MB |

## Database Options

| Property | Value |
|---|---|
| Compatibility Level | 120 |
| Database collation | SQL_Latin1_General_CP1_CI_AS |
| Restrict access | MULTI_USER |
| Is read-only | False |
| Auto close | False |
| Auto shrink | False |
| Database status | ONLINE |
| In standby | False |
| Cleanly shutdown | False |
| Supplemental logging enabled | False |
| Snapshot isolation state | OFF |
| Read committed snapshot on | False |
| Recovery model | SIMPLE |
| Page verify option | CHECKSUM |
| Auto create statistics | True |
| Auto update statistics | True |
| Auto update statistics asynchronously | False |
| ANSI NULL default | False |
| ANSI NULL enabled | False |
| ANSI padding enabled | False |

| | |
|---|---|
| ANSI warnings enabled | False |
| Arithmetic abort enabled | False |
| Concatenating NULL yields NULL | False |
| Numeric roundabort enabled | False |
| Quoted Identifier On | False |
| Recursive triggers enabled | False |
| Close cursors on commit | False |
| Local cursors by default | False |
| Fulltext enabled | True |
| Trustworthy | False |
| Database chaining | False |
| Forced parameterization | False |
| Master key encrypted by server | False |
| Published | False |
| Subscribed | False |
| Merge published | False |
| Is distribution database | False |
| Sync with backup | False |
| Service broker GUID | 5805df63-48d9-49e0-8b59-7115fb140e33 |
| Service broker enabled | False |
| Log reuse wait | NOTHING |
| Date correlation | False |
| CDC enabled | False |
| Encrypted | False |
| Honor broker priority | False |
| Default language | English |
| Default fulltext language LCID | 1033 |
| Nested triggers enabled | True |
| Transform noise words | False |
| Two-digit year cutoff | 2049 |
| Containment | NONE |
| Target recovery time | 0 |
| Database owner | sa |

## Files

| Name | Type | Size | Maxsize | Autogrowth | File Name |
|---|---|---|---|---|---|
| Greencard | Data | 6.00 MB | unlimited | 1.00 MB | C:\Program Files\Microsoft SQL Server\MSSQL12.SQLEXPRESS\MSSQL\DATA\Greencard.mdf |
| Greencard_log | Log | 1.50 MB | 2048.00 GB | 10.00 percent | C:\Program Files\Microsoft SQL Server\MSSQL12.SQLEXPRESS\MSSQ |

| | | | | | |
|---|---|---|---|---|---|
| | | | | | L\DATA\Greencard_log.ldf |

# Tables

## Objects

| Name |
|---|
| dbo.AdherenceOutcome<br>*Track patient adherance on both CTX/Dapsone or ARV* |
| dbo.AdverseEvent<br>*Track adverse events courses,medication causing the adverse events,severity and actiontaken.Recorded per visit* |
| dbo.ARTInitiationBaseline<br>*Baseline summary of Initiation parameters,collected once during enrollment* |
| dbo.ARTUseHistory<br>*Records Prior ART use experience.Especially for TI patients* |
| dbo.ARVTreatmentTracker |
| dbo.ComplaintsHistory |
| dbo.County |
| dbo.Disclosure |
| dbo.HIVEnrollmentBaseline |
| dbo.HIVTesting |
| dbo.LookupItem |
| dbo.LookupMaster |
| dbo.LookupMasterItem |
| dbo.ModuleMaster |
| dbo.Patient<br>*Master patient details.Captures generic patient information to be used across all service areas* |
| dbo.PatientAllergy<br>*Tracks patient allergies per visit* |
| dbo.PatientAppointment<br>*Tracks patient appointments and ststus of the appointments* |
| dbo.PatientCareending<br>*Tracks care ending for patients either deaths/TO* |
| dbo.PatientChronicIllness<br>*Tracks Chronic Illnesses cormodities and the current treatment of the illnesses per visit* |
| dbo.PatientClinicalDiagnosis |
| dbo.PatientClinicalNotes |
| dbo.PatientDiagnosis |

| |
|---|
| *Clinician conclusions on the treatment plan,done per visit* |
| dbo.PatientEncounter<br>*Tracks and manages all patient encounters per visit per service* |
| dbo.PatientEnrollment<br>*Tracks patient enrollment into the different service areas* |
| dbo.PatientFamilyPlanning |
| dbo.PatientFamilyPlanningMethod |
| dbo.PatientIdentifier<br>*Tracks and manages patient service identifier information* |
| dbo.PatientLabTracker |
| dbo.PatientMaritalStatus |
| dbo.PatientMasterVisit |
| dbo.PatientOVCStatus |
| dbo.PatientPHDP |
| dbo.PatientPopulation |
| dbo.PatientProphylaxis |
| dbo.PatientReferral |
| dbo.PatientScreening |
| dbo.PatientTransferIn |
| dbo.PatientTreatmentSupporter |
| dbo.PatientVitals |
| dbo.Person |
| dbo.PersonContact<br>*Tracks and manages patient contact information,can be updated to reflect the current contact details with history of the previous contacts* |
| dbo.PersonLocation |
| dbo.PersonRelationship |
| dbo.PhysicalExamination |
| dbo.Pregnancy |
| dbo.PregnancyIndicator |
| dbo.ServiceEntryPoint |

| |
|---|
| dbo.TBTreatmentTracker |
| dbo.TreatmentEventTracker |
| dbo.User |
| dbo.Vaccination |

# [dbo].[AdherenceOutcome]

## MS_Description

Track patient adherance on both CTX/Dapsone or ARV

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| FK | PatientId | int | 4 | False | | |
| FK | PatientMasterVisitId | int | 4 | False | | |
| | AdherenceType | int | 4 | False | | |
| | Score | int | 4 | False | | |
| | ScoreDescription | varchar(150) | 150 | True | | |
| | DeleteFlag<br>*Defaults to zero(0) and one (1) when deleted* | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | |
| | AuditData | xml | max | False | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_AdherenceOutcome | Id | True |

## Foreign Keys

| Name | Columns |
|---|---|
| FK_AdherenceOutcome_Patient | PatientId->[dbo].[Patient].[Id] |
| FK_PatientAdheranceAssessment_PatientMasterVisit | PatientMasterVisitId->[dbo].[PatientMasterVisit].[Id] |

## SQL Script

```
CREATE TABLE [dbo].[AdherenceOutcome]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[PatientMasterVisitId] [int] NOT NULL,
[AdherenceType] [int] NOT NULL,
[Score] [int] NOT NULL,
[ScoreDescription] [varchar] (150) COLLATE SQL_Latin1_General_CP1_CI_AS NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_PatientAdheranceAssessment_Void] DEFAULT
((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL,
[AuditData] [xml] NOT NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[AdherenceOutcome] ADD CONSTRAINT [PK_AdherenceOutcome] PRIMARY KEY
CLUSTERED  ([Id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[AdherenceOutcome] ADD CONSTRAINT [FK_AdherenceOutcome_Patient]
FOREIGN KEY ([PatientId]) REFERENCES [dbo].[Patient] ([Id])
GO
ALTER TABLE [dbo].[AdherenceOutcome] ADD CONSTRAINT [FK_PatientAdheranceAssessment_-
PatientMasterVisit] FOREIGN KEY ([PatientMasterVisitId]) REFERENCES [dbo].[Patient-
MasterVisit] ([Id])
GO
EXEC sp_addextendedproperty N'MS_Description', N'Track patient adherance on both
CTX/Dapsone or ARV ', 'SCHEMA', N'dbo', 'TABLE', N'AdherenceOutcome', NULL, NULL
GO
EXEC sp_addextendedproperty N'MS_Description', N'Defaults to zero(0) and one (1) when
deleted', 'SCHEMA', N'dbo', 'TABLE', N'AdherenceOutcome', 'COLUMN', N'DeleteFlag'
GO
```

## Uses

[dbo].[Patient]
[dbo].[PatientMasterVisit]

# [dbo].[AdverseEvent]

## MS_Description

Track adverse events courses,medication causing the adverse events,severity and actiontaken.Recorded per visit

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| FK | PatientId | int | 4 | False | | |
| FK | PatientMasterVisitId | int | 4 | False | | |
| | EventName | varchar(250) | 250 | False | | |
| | EventCause | varchar(250) | 250 | True | | |
| | Severity | varchar(250) | 250 | True | | |
| | Action | varchar(250) | 250 | True | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |
| | AuditData | xml | max | True | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_AdverseEvent | Id | True |

## Foreign Keys

| Name | Update | Delete | Columns |
|---|---|---|---|
| FK_AdverseEvent_Patient | | | PatientId->[dbo].[Patient].[Id] |
| FK_AdverseEvent_PatientMasterVisit | Cascade | Cascade | PatientMasterVisitId->[dbo].[PatientMaster- |

| | | | |
|---|---|---|---|
| | | | Visit].[Id] |

## SQL Script

```
CREATE TABLE [dbo].[AdverseEvent]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[PatientMasterVisitId] [int] NOT NULL,
[EventName] [varchar] (250) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[EventCause] [varchar] (250) COLLATE SQL_Latin1_General_CP1_CI_AS NULL,
[Severity] [varchar] (250) COLLATE SQL_Latin1_General_CP1_CI_AS NULL,
[Action] [varchar] (250) COLLATE SQL_Latin1_General_CP1_CI_AS NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_AdverseEvent_DeleteFlag] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_AdverseEvent_CreateDate] DEFAULT
(getdate()),
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[AdverseEvent] ADD CONSTRAINT [PK_AdverseEvent] PRIMARY KEY CLUSTERED
([Id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[AdverseEvent] ADD CONSTRAINT [FK_AdverseEvent_Patient] FOREIGN KEY
([PatientId]) REFERENCES [dbo].[Patient] ([Id])
GO
ALTER TABLE [dbo].[AdverseEvent] ADD CONSTRAINT [FK_AdverseEvent_PatientMasterVisit]
FOREIGN KEY ([PatientMasterVisitId]) REFERENCES [dbo].[PatientMasterVisit] ([Id]) ON
DELETE CASCADE ON UPDATE CASCADE
GO
EXEC sp_addextendedproperty N'MS_Description', N'Track adverse events
courses,medication causing the adverse events,severity and actiontaken.Recorded per
visit', 'SCHEMA', N'dbo', 'TABLE', N'AdverseEvent', NULL, NULL
GO
```

## Uses

[dbo].[Patient]
[dbo].[PatientMasterVisit]

# [dbo].[ARTInitiationBaseline]

## MS_Description

Baseline summary of Initiation parameters,collected once during enrollment

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Persisted | Computed | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|---|---|
| FK C | Id | int | | | 4 | False | 1 - 1 | |
| FK | PatientId | int | | | 4 | False | | |
| FK | PatientMasterVisitId | int | | | 4 | False | | |
| | HBVInfected | bit | | | 1 | False | | |
| | Pregnant | bit | | | 1 | False | | |
| | TBinfected | bit | | | 1 | False | | |
| | WHOStage | int | | | 4 | False | | |
| | BreastFeeding | bit | | | 1 | False | | |
| | CD4Count | int | | | 4 | True | | |
| | ViralLoad | int | | | 4 | True | | |
| | ViralLoadDate | date | | | 3 | True | | |
| | MUAC | decimal(8,2) | | | 5 | True | | |
| | Weight | decimal(8,2) | | | 5 | False | | |
| | Height | decimal(8,2) | | | 5 | False | | |
| | BMI | decimal(38,20) | True | True | 17 | True | | |
| | ARTCohort | varchar(50) | | | 50 | True | | |
| | FirstLineStartDate | date | | | 3 | True | | |
| | StartRegimen | int | | | 4 | True | | |
| | DeleteFlag | bit | | | 1 | True | | ((0)) |
| | CreateDate | datetime | | | 8 | False | | (getdate()) |
| | CreateBy | int | | | 4 | False | | |

## Computed columns

| Name | Column definition |
|---|---|
| BMI | ([Weight]/(([Height]/(100))*([Height]/(100)))) |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientARTInitiationBaseline | Id | True |

## Foreign Keys

| Name | Update | Delete | Columns |
|---|---|---|---|
| FK_ARTInitiationBaseline_Patient | | | PatientId->[dbo].[Patient].[Id] |
| FK_ARTInitiationBaseline_PatientMasterVisit | Cascade | Cascade | PatientMasterVisitId->[dbo].[PatientMasterVisit].[Id] |

## SQL Script

```
CREATE TABLE [dbo].[ARTInitiationBaseline]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[PatientMasterVisitId] [int] NOT NULL,
[HBVInfected] [bit] NOT NULL,
[Pregnant] [bit] NOT NULL,
[TBinfected] [bit] NOT NULL,
[WHOStage] [int] NOT NULL,
[BreastFeeding] [bit] NOT NULL,
[CD4Count] [int] NULL,
[ViralLoad] [int] NULL,
[ViralLoadDate] [date] NULL,
[MUAC] [decimal] (8, 2) NULL,
[Weight] [decimal] (8, 2) NOT NULL,
[Height] [decimal] (8, 2) NOT NULL,
[BMI] AS ([Weight]/(([Height]/(100))*([Height]/(100)))) PERSISTED,
[ARTCohort] [varchar] (50) COLLATE SQL_Latin1_General_CP1_CI_AS NULL,
[FirstLineStartDate] [date] NULL,
[StartRegimen] [int] NULL,
[DeleteFlag] [bit] NULL CONSTRAINT [DF_PatientARTInitiationBaseline_void] DEFAULT
((0)),
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_ARTInitiationBaseline_CreateDate]
DEFAULT (getdate()),
[CreateBy] [int] NOT NULL
) ON [PRIMARY]
GO
ALTER TABLE [dbo].[ARTInitiationBaseline] ADD CONSTRAINT [PK_PatientARTInitiation-
Baseline] PRIMARY KEY CLUSTERED  ([Id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[ARTInitiationBaseline] ADD CONSTRAINT [FK_ARTInitiationBaseline_-
Patient] FOREIGN KEY ([PatientId]) REFERENCES [dbo].[Patient] ([Id])
GO
ALTER TABLE [dbo].[ARTInitiationBaseline] ADD CONSTRAINT [FK_ARTInitiationBaseline_-
PatientMasterVisit] FOREIGN KEY ([PatientMasterVisitId]) REFERENCES [dbo].[Patient-
MasterVisit] ([Id]) ON DELETE CASCADE ON UPDATE CASCADE
GO
EXEC sp_addextendedproperty N'MS_Description', N'Baseline summary of Initiation
parameters,collected once during enrollment', 'SCHEMA', N'dbo', 'TABLE',
N'ARTInitiationBaseline', NULL, NULL
GO
```

## Uses

[dbo].[Patient]
[dbo].[PatientMasterVisit]

# [dbo].[ARTUseHistory]

## MS_Description

Records Prior ART use experience.Especially for TI patients

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| FK | PatientId | int | 4 | False | | |
| FK | PatientMasterVisitId | int | 4 | False | | |
| | TreatmentType | varchar(50) | 50 | False | | |
| | Purpose | varchar(150) | 150 | False | | |
| | Regimen | varchar(150) | 150 | False | | |
| | DateLastUsed | date | 3 | False | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_ARTUseHistory | Id | True |

## Foreign Keys

| Name | Columns |
|---|---|
| FK_ARTUseHistory_Patient | PatientId->[dbo].[Patient].[Id] |
| FK_ARTUseHistory_PatientMasterVisit | PatientMasterVisitId->[dbo].[PatientMasterVisit].[Id] |

## SQL Script

```
CREATE TABLE [dbo].[ARTUseHistory]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[PatientMasterVisitId] [int] NOT NULL,
[TreatmentType] [varchar] (50) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[Purpose] [varchar] (150) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[Regimen] [varchar] (150) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[DateLastUsed] [date] NOT NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_ARTUseHistory_Void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_ARTUseHistory_CreateDate] DEFAULT
(getdate())
) ON [PRIMARY]
GO
ALTER TABLE [dbo].[ARTUseHistory] ADD CONSTRAINT [PK_ARTUseHistory] PRIMARY KEY
CLUSTERED  ([Id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[ARTUseHistory] ADD CONSTRAINT [FK_ARTUseHistory_Patient] FOREIGN KEY
([PatientId]) REFERENCES [dbo].[Patient] ([Id])
GO
ALTER TABLE [dbo].[ARTUseHistory] ADD CONSTRAINT [FK_ARTUseHistory_PatientMasterVisit]
FOREIGN KEY ([PatientMasterVisitId]) REFERENCES [dbo].[PatientMasterVisit] ([Id])
GO
EXEC sp_addextendedproperty N'MS_Description', N'Records Prior ART use
experience.Especially for TI patients', 'SCHEMA', N'dbo', 'TABLE', N'ARTUseHistory',
NULL, NULL
GO
```

## Uses

[dbo].[Patient]
[dbo].[PatientMasterVisit]

# [dbo].[ARVTreatmentTracker]

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| | ServiceAreaId | int | 4 | False | | |
| | PatientMasterVisitId | int | 4 | False | | |
| | RegimenStartDate | int | 4 | False | | |
| | RegimenId | int | 4 | False | | |
| | Regimen | varchar(50) | 50 | False | | |
| | RegimenLineId | int | 4 | False | | ((0)) |
| | RegimenLine | varchar(50) | 50 | False | | |
| | DrugId | int | 4 | False | | ((0)) |
| | RegimenStatusDate | datetime | 8 | False | | |
| | TreatmentStatusId | int | 4 | False | | |
| | ParentId | int | 4 | False | | ((0)) |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |
| | AuditData | xml | max | True | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_ARVTreatmentTracker | Id | True |

## SQL Script

```
CREATE TABLE [dbo].[ARVTreatmentTracker]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[ServiceAreaId] [int] NOT NULL,
[PatientMasterVisitId] [int] NOT NULL,
[RegimenStartDate] [int] NOT NULL,
[RegimenId] [int] NOT NULL,
[Regimen] [varchar] (50) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[RegimenLineId] [int] NOT NULL CONSTRAINT [DF_ARVTreatmentTracker_RegimenLineId]
DEFAULT ((0)),
[RegimenLine] [varchar] (50) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[DrugId] [int] NOT NULL CONSTRAINT [DF_ARVTreatmentTracker_DrugId] DEFAULT ((0)),
[RegimenStatusDate] [datetime] NOT NULL,
[TreatmentStatusId] [int] NOT NULL,
[ParentId] [int] NOT NULL CONSTRAINT [DF_ARVTreatmentTracker_ParentId] DEFAULT ((0)),
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_ARVTreatmentTracker_DeleteFlag] DEFAULT
((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_ARVTreatmentTracker_CreateDate] DEFAULT
(getdate()),
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[ARVTreatmentTracker] ADD CONSTRAINT [PK_ARVTreatmentTracker] PRIMARY
KEY CLUSTERED  ([Id]) ON [PRIMARY]
GO
```

# [dbo].[ComplaintsHistory]

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| FK | PatientMasterVisitId | int | 4 | False | | |
| | PresentingComplaint | varchar(1000) | 1000 | False | | |
| | ComplaintHistory | varchar(1000) | 1000 | True | | |
| | DeleteFlag | bit | 1 | False | | |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |
| | AuditData | xml | max | True | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_ComplaintsHistory | Id | True |

## Foreign Keys

| Name | Update | Delete | Columns |
|---|---|---|---|
| FK_ComplaintsHistory_PatientMasterVisit | Cascade | Cascade | PatientMasterVisitId->[dbo].[PatientMasterVisit].[Id] |

## SQL Script

```
CREATE TABLE [dbo].[ComplaintsHistory]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[PatientMasterVisitId] [int] NOT NULL,
[PresentingComplaint] [varchar] (1000) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[ComplaintHistory] [varchar] (1000) COLLATE SQL_Latin1_General_CP1_CI_AS NULL,
[DeleteFlag] [bit] NOT NULL,
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_ComplaintsHistory_CreateDate] DEFAULT
(getdate()),
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[ComplaintsHistory] ADD CONSTRAINT [PK_ComplaintsHistory] PRIMARY KEY
CLUSTERED  ([Id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[ComplaintsHistory] ADD CONSTRAINT [FK_ComplaintsHistory_Patient-
MasterVisit] FOREIGN KEY ([PatientMasterVisitId]) REFERENCES [dbo].[PatientMasterVisit]
([Id]) ON DELETE CASCADE ON UPDATE CASCADE
GO
```

## Uses

[dbo].[PatientMasterVisit]

# [dbo].[County]

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 1424 |
| Created | 4:46:20 PM Monday, January 9, 2017 |
| Last Modified | 4:46:20 PM Monday, January 9, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity |
|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 |
|  | CountyId | int | 4 | True |  |
|  | CountyName | nvarchar(255) | 510 | True |  |
|  | SubcountyId | int | 4 | True |  |
|  | Subcountyname | nvarchar(255) | 510 | True |  |
|  | WardId | int | 4 | True |  |
|  | WardName | nvarchar(255) | 510 | True |  |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_County | Id | True |

## SQL Script

```
CREATE TABLE [dbo].[County]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[CountyId] [int] NULL,
[CountyName] [nvarchar] (255) COLLATE SQL_Latin1_General_CP1_CI_AS NULL,
[SubcountyId] [int] NULL,
[Subcountyname] [nvarchar] (255) COLLATE SQL_Latin1_General_CP1_CI_AS NULL,
[WardId] [int] NULL,
[WardName] [nvarchar] (255) COLLATE SQL_Latin1_General_CP1_CI_AS NULL
) ON [PRIMARY]
GO
ALTER TABLE [dbo].[County] ADD CONSTRAINT [PK_County] PRIMARY KEY CLUSTERED  ([Id]) ON
[PRIMARY]
GO
```

# [dbo].[Disclosure]

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| FK | PatientMasterVisitId | int | 4 | False | | |
| | Category | varchar(15) | 15 | False | | |
| | DisclosureStage | varchar(10) | 10 | False | | |
| | DisclosureDate | date | 3 | True | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_Disclosure_1 | Id | True |

## Foreign Keys

| Name | Update | Delete | Columns |
|---|---|---|---|
| FK_Disclosure_PatientMasterVisit | Cascade | Cascade | PatientMasterVisitId->[dbo].[PatientMasterVisit].[Id] |

## SQL Script

```
CREATE TABLE [dbo].[Disclosure]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[PatientMasterVisitId] [int] NOT NULL,
[Category] [varchar] (15) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[DisclosureStage] [varchar] (10) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[DisclosureDate] [date] NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_Disclosure_Void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_Disclosure_CreateDate] DEFAULT
(getdate())
) ON [PRIMARY]
GO
ALTER TABLE [dbo].[Disclosure] ADD CONSTRAINT [PK_Disclosure_1] PRIMARY KEY CLUSTERED
([Id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[Disclosure] ADD CONSTRAINT [FK_Disclosure_PatientMasterVisit]
FOREIGN KEY ([PatientMasterVisitId]) REFERENCES [dbo].[PatientMasterVisit] ([Id]) ON
DELETE CASCADE ON UPDATE CASCADE
GO
```

## Uses

[dbo].[PatientMasterVisit]

# [dbo].[HIVEnrollmentBaseline]

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| | PatientMasterVisitId | int | 4 | False | | |
| | HIVDiagnosisDate | date | 3 | False | | |
| | EnrollmentDate | date | 3 | False | | |
| | EnrollmentWHOStage | int | 4 | False | | |
| | ARTInitiationDate | date | 3 | False | | |
| | ARTHistoryUse | bit | 1 | False | | |
| | HIVRetest | bit | 1 | False | | |
| | HIVRetestTypeId | int | 4 | True | | |
| | ReasonForNoRetest | varchar(250) | 250 | True | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_HIVEnrollmentBaseline | Id | True |

## SQL Script

```
CREATE TABLE [dbo].[HIVEnrollmentBaseline]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[PatientMasterVisitId] [int] NOT NULL,
[HIVDiagnosisDate] [date] NOT NULL,
[EnrollmentDate] [date] NOT NULL,
[EnrollmentWHOStage] [int] NOT NULL,
[ARTInitiationDate] [date] NOT NULL,
[ARTHistoryUse] [bit] NOT NULL,
[HIVRetest] [bit] NOT NULL,
[HIVRetestTypeId] [int] NULL,
[ReasonForNoRetest] [varchar] (250) COLLATE SQL_Latin1_General_CP1_CI_AS NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_DiagnosisARVHistory_Void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_DiagnosisARVHistory_CreateDate] DEFAULT
(getdate())
) ON [PRIMARY]
GO
ALTER TABLE [dbo].[HIVEnrollmentBaseline] ADD CONSTRAINT [PK_HIVEnrollmentBaseline]
PRIMARY KEY CLUSTERED  ([Id]) ON [PRIMARY]
GO
EXEC sp_addextendedproperty N'MS_Description', N'', 'SCHEMA', N'dbo', 'TABLE',
N'HIVEnrollmentBaseline', NULL, NULL
GO
```

Project > .\SQLEXPRESS > User databases > Greencard > Tables > dbo.HIVTesting

# [dbo].[HIVTesting]

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Default |
|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | |
| | PersonId | int | 4 | False | |
| | BaselineResult | int | 4 | False | |
| | BaselineDate | datetime | 8 | True | |
| | TestingDate | date | 3 | False | |
| | TestingResult | int | 4 | False | |
| | ReferredToCare | bit | 1 | False | |
| | CCCNumber | varchar(20) | 20 | True | |
| | EnrollementId | int | 4 | True | |
| | DeleteFlag | bit | 1 | False | ((0)) |
| | CreateBy | int | 4 | False | |
| | CreateDate | datetime | 8 | False | (getdate()) |
| | AuditData | xml | max | True | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_HIVTesting | Id | True |

## SQL Script

```
CREATE TABLE [dbo].[HIVTesting]
(
[Id] [int] NOT NULL,
[PersonId] [int] NOT NULL,
[BaselineResult] [int] NOT NULL,
[BaselineDate] [datetime] NULL,
[TestingDate] [date] NOT NULL,
[TestingResult] [int] NOT NULL,
[ReferredToCare] [bit] NOT NULL,
[CCCNumber] [varchar] (20) COLLATE SQL_Latin1_General_CP1_CI_AS NULL,
[EnrollementId] [int] NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_HIVTesting_DeleteFlag] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_HIVTesting_CreateDate] DEFAULT
(getdate()),
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[HIVTesting] ADD CONSTRAINT [PK_HIVTesting] PRIMARY KEY CLUSTERED
([Id]) ON [PRIMARY]
GO
```

# [dbo].[LookupItem]

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | Name | varchar(50) | 50 | False | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_LookupItem | Id | True |
| | IX_LookupItem | Name | True |

## SQL Script

```
CREATE TABLE [dbo].[LookupItem]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[Name] [varchar] (50) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_LookupItem_DeleteFlag] DEFAULT ((0))
) ON [PRIMARY]
GO
ALTER TABLE [dbo].[LookupItem] ADD CONSTRAINT [PK_LookupItem] PRIMARY KEY CLUSTERED
([Id]) ON [PRIMARY]
GO
CREATE UNIQUE NONCLUSTERED INDEX [IX_LookupItem] ON [dbo].[LookupItem] ([Name]) ON
[PRIMARY]
GO
```

## Used By

[dbo].[LookupItemView]

# [dbo].[LookupMaster]

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | Name | varchar(50) | 50 | False | | |
| | DisplayName | varchar(150) | 150 | False | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_LookupMaster | Id | True |
| | IX_LookupMaster | Name | True |

## SQL Script

```
CREATE TABLE [dbo].[LookupMaster]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[Name] [varchar] (50) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[DisplayName] [varchar] (150) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_LookupMaster_DeleteFlag] DEFAULT ((0))
) ON [PRIMARY]
GO
ALTER TABLE [dbo].[LookupMaster] ADD CONSTRAINT [PK_LookupMaster] PRIMARY KEY CLUSTERED
([Id]) ON [PRIMARY]
GO
CREATE UNIQUE NONCLUSTERED INDEX [IX_LookupMaster] ON [dbo].[LookupMaster] ([Name]) ON
[PRIMARY]
GO
```

## Used By

[dbo].[LookupItemView]

# [dbo].[LookupMasterItem]

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Default |
|---|---|---|---|---|---|
| PK C | LookupMasterId | int | 4 | False | |
| PK C | LookupItemId | int | 4 | False | |
| | DisplayName | varchar(50) | 50 | True | |
| | OrdRank | decimal(5,2) | 5 | True | ((0.00)) |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_LookupMasterItem | LookupMasterId, LookupItemId | True |

## SQL Script

```
CREATE TABLE [dbo].[LookupMasterItem]
(
[LookupMasterId] [int] NOT NULL,
[LookupItemId] [int] NOT NULL,
[DisplayName] [varchar] (50) COLLATE SQL_Latin1_General_CP1_CI_AS NULL,
[OrdRank] [decimal] (5, 2) NULL CONSTRAINT [DF_LookupMasterItem_OrdRank] DEFAULT
((0.00))
) ON [PRIMARY]
GO
ALTER TABLE [dbo].[LookupMasterItem] ADD CONSTRAINT [PK_LookupMasterItem] PRIMARY KEY
CLUSTERED  ([LookupMasterId], [LookupItemId]) ON [PRIMARY]
GO
```

## Used By

[dbo].[LookupItemView]

# [dbo].[ModuleMaster]

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | Name | varchar(50) | 50 | False | | |
| | ReferenceId | varchar(15) | 15 | False | | |
| | DisplayName | varchar(150) | 150 | False | | |
| | Version | varchar(50) | 50 | False | | |
| | ReleaseDate | date | 3 | False | | |
| | ReleaseVersion | varchar(8) | 8 | False | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |
| | AuditData | xml | max | True | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_ModuleMaster | Id | True |

## SQL Script

```
CREATE TABLE [dbo].[ModuleMaster]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[Name] [varchar] (50) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[ReferenceId] [varchar] (15) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[DisplayName] [varchar] (150) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[Version] [varchar] (50) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[ReleaseDate] [date] NOT NULL,
[ReleaseVersion] [varchar] (8) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_ModuleMaster_DeleteFlag] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_ModuleMaster_CreateDate] DEFAULT
(getdate()),
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[ModuleMaster] ADD CONSTRAINT [PK_ModuleMaster] PRIMARY KEY CLUSTERED
([Id]) ON [PRIMARY]
GO
```

# [dbo].[Patient]

## MS_Description

Master patient details.Captures generic patient information to be used across all service areas

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 5:53:36 PM Wednesday, December 21, 2016 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| 🖧 | Ptn_PK | int | 4 | False | | |
| FK | PersonId | int | 4 | False | | |
| | FaciltyId | int | 4 | False | | |
| 🖧 | PatientIndex | varchar(50) | 50 | False | | |
| | Active | bit | 1 | False | | ((0)) |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreatedBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | |
| | AuditData | xml | max | True | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_Patient | Id | True |
| | IX_Patient | PatientIndex | True |
| | IX_Patient_PtnPK | Ptn_PK | |

## Foreign Keys

| Name | Columns |
|---|---|

| | |
|---|---|
| FK_Patient_Person | PersonId->[dbo].[Person].[Id] |

## SQL Script

```
CREATE TABLE [dbo].[Patient]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[Ptn_PK] [int] NOT NULL,
[PersonId] [int] NOT NULL,
[FaciltyId] [int] NOT NULL,
[PatientIndex] [varchar] (50) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[Active] [bit] NOT NULL CONSTRAINT [DF_Patient_Status] DEFAULT ((0)),
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_person_void] DEFAULT ((0)),
[CreatedBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL,
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[Patient] ADD CONSTRAINT [PK_Patient] PRIMARY KEY CLUSTERED  ([Id])
ON [PRIMARY]
GO
CREATE UNIQUE NONCLUSTERED INDEX [IX_Patient] ON [dbo].[Patient] ([PatientIndex]) ON
[PRIMARY]
GO
CREATE NONCLUSTERED INDEX [IX_Patient_PtnPK] ON [dbo].[Patient] ([Ptn_PK]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[Patient] ADD CONSTRAINT [FK_Patient_Person] FOREIGN KEY ([PersonId])
REFERENCES [dbo].[Person] ([Id])
GO
EXEC sp_addextendedproperty N'MS_Description', N'Master patient details.Captures
generic patient information to be used across all service areas', 'SCHEMA', N'dbo',
'TABLE', N'Patient', NULL, NULL
GO
```

## Uses

[dbo].[Person]

## Used By

[dbo].[AdherenceOutcome]
[dbo].[AdverseEvent]
[dbo].[ARTInitiationBaseline]
[dbo].[ARTUseHistory]
[dbo].[PatientOVCStatus]
[dbo].[PatientTreatmentSupporter]

# [dbo].[PatientAllergy]

## MS_Description

Tracks patient allergies per visit

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Default |
|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | |
| | PatientId | int | 4 | False | |
| FK | PatientMasterVisitId | int | 4 | True | |
| | Allergen | varchar(250) | 250 | False | |
| | AllergyResponse | varchar(250) | 250 | False | |
| | DeleteFlag | bit | 1 | False | ((0)) |
| | CreateBy | int | 4 | False | |
| | CreateDate | datetime | 8 | False | (getdate()) |
| | AuditData | xml | max | True | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientAllergy | Id | True |

## Foreign Keys

| Name | Update | Delete | Columns |
|---|---|---|---|
| FK_PatientAllergies_PatientMasterVisit | Cascade | Cascade | PatientMasterVisitId->[dbo].[PatientMasterVisit].[Id] |

## SQL Script

```sql
CREATE TABLE [dbo].[PatientAllergy]
(
[Id] [int] NOT NULL,
[PatientId] [int] NOT NULL,
[PatientMasterVisitId] [int] NULL,
[Allergen] [varchar] (250) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[AllergyResponse] [varchar] (250) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_PatientAllergies_void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_PatientAllergy_CreateDate] DEFAULT (getdate()),
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientAllergy] ADD CONSTRAINT [PK_PatientAllergy] PRIMARY KEY CLUSTERED  ([Id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientAllergy] ADD CONSTRAINT [FK_PatientAllergies_PatientMasterVisit] FOREIGN KEY ([PatientMasterVisitId]) REFERENCES [dbo].[PatientMasterVisit] ([Id]) ON DELETE CASCADE ON UPDATE CASCADE
GO
EXEC sp_addextendedproperty N'MS_Description', N'Tracks patient allergies per visit', 'SCHEMA', N'dbo', 'TABLE', N'PatientAllergy', NULL, NULL
GO
```

## Uses

[dbo].[PatientMasterVisit]

# [dbo].[PatientAppointment]

## MS_Description

Tracks patient appointments and ststus of the appointments

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| FK | PatientMasterVisitId | int | 4 | False | | |
| | ServiceAreaId | int | 4 | False | | |
| | PatientId | int | 4 | False | | |
| | AppointmentDate | datetime | 8 | False | | |
| | ReasonId | int | 4 | False | | |
| | Description | varchar(250) | 250 | True | | |
| | StatusId | int | 4 | False | | ((0)) |
| | StatusDate | date | 3 | True | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |
| | AudityData | xml | max | True | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientAppointment | Id | True |

## Foreign Keys

| Name | Update | Delete | Columns |
|---|---|---|---|

| | | | |
|---|---|---|---|
| FK_PatientAppointment_PatientMasterVisit | Cascade | Cascade | PatientMasterVisitId->[dbo].[PatientMasterVisit].[Id] |

## SQL Script

```
CREATE TABLE [dbo].[PatientAppointment]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientMasterVisitId] [int] NOT NULL,
[ServiceAreaId] [int] NOT NULL,
[PatientId] [int] NOT NULL,
[AppointmentDate] [datetime] NOT NULL,
[ReasonId] [int] NOT NULL,
[Description] [varchar] (250) COLLATE SQL_Latin1_General_CP1_CI_AS NULL,
[StatusId] [int] NOT NULL CONSTRAINT [DF_PatientAppointment_Status] DEFAULT ((0)),
[StatusDate] [date] NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_PatientAppointment_Void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_PatientAppointment_CreateDate] DEFAULT
(getdate()),
[AudityData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientAppointment] ADD CONSTRAINT [PK_PatientAppointment] PRIMARY
KEY CLUSTERED  ([Id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientAppointment] ADD CONSTRAINT [FK_PatientAppointment_Patient-
MasterVisit] FOREIGN KEY ([PatientMasterVisitId]) REFERENCES [dbo].[PatientMasterVisit]
([Id]) ON DELETE CASCADE ON UPDATE CASCADE
GO
EXEC sp_addextendedproperty N'MS_Description', N'Tracks patient appointments and ststus
of the appointments', 'SCHEMA', N'dbo', 'TABLE', N'PatientAppointment', NULL, NULL
GO
```

## Uses

[dbo].[PatientMasterVisit]

# [dbo].[PatientCareending]

## MS_Description

Tracks care ending for patients either deaths/TO

## Properties

| Property | Value |
|---|---|
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| FK | PatientMasterVisitId | int | 4 | False | | |
| | PatientEnrollmentId | int | 4 | False | | |
| | ExitReason | int | 4 | False | | |
| | ExitDate | date | 3 | False | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | |
| | AuditData | xml | max | True | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientCareending_1 | Id | True |

## Foreign Keys

| Name | Update | Delete | Columns |
|---|---|---|---|
| FK_PatientCareending_PatientMasterVisit | Cascade | Cascade | PatientMasterVisitId->[dbo].[PatientMasterVisit].[Id] |

## SQL Script

```
CREATE TABLE [dbo].[PatientCareending]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[PatientMasterVisitId] [int] NOT NULL,
[PatientEnrollmentId] [int] NOT NULL,
[ExitReason] [int] NOT NULL,
[ExitDate] [date] NOT NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_PatientCareending_void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL,
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientCareending] ADD CONSTRAINT [PK_PatientCareending_1] PRIMARY
KEY CLUSTERED  ([Id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientCareending] ADD CONSTRAINT [FK_PatientCareending_Patient-
MasterVisit] FOREIGN KEY ([PatientMasterVisitId]) REFERENCES [dbo].[PatientMasterVisit]
([Id]) ON DELETE CASCADE ON UPDATE CASCADE
GO
EXEC sp_addextendedproperty N'MS_Description', N'Tracks care ending for patients either
deaths/TO', 'SCHEMA', N'dbo', 'TABLE', N'PatientCareending', NULL, NULL
GO
```

## Uses

[dbo].[PatientMasterVisit]

# [dbo].[PatientChronicIllness]

## MS_Description

Tracks Chronic Illnesses cormodities and the current treatment of the illnesses per visit

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| FK | PatientMasterVisitId | int | 4 | False | | |
| | ChronicIllness | int | 4 | False | | |
| | Treatment | varchar(150) | 150 | False | | |
| | Dose | int | 4 | True | | |
| | Duration | int | 4 | True | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |
| | AuditData | xml | max | True | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientChronicIllness | Id | True |

## Foreign Keys

| Name | Update | Delete | Columns |
|---|---|---|---|
| FK_PatientChronicIllness_PatientMasterVisit | Cascade | Cascade | PatientMasterVisitId->[dbo].[PatientMasterVisit].[Id] |

## SQL Script

```sql
CREATE TABLE [dbo].[PatientChronicIllness]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[PatientMasterVisitId] [int] NOT NULL,
[ChronicIllness] [int] NOT NULL,
[Treatment] [varchar] (150) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[Dose] [int] NULL,
[Duration] [int] NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_ChronicIllness_void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_PatientChronicIllness_CreateDate]
DEFAULT (getdate()),
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientChronicIllness] ADD CONSTRAINT [PK_PatientChronicIllness]
PRIMARY KEY CLUSTERED  ([Id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientChronicIllness] ADD CONSTRAINT [FK_PatientChronicIllness_-
PatientMasterVisit] FOREIGN KEY ([PatientMasterVisitId]) REFERENCES [dbo].[Patient-
MasterVisit] ([Id]) ON DELETE CASCADE ON UPDATE CASCADE
GO
EXEC sp_addextendedproperty N'MS_Description', N'Tracks Chronic Illnesses cormodities
and the current treatment of the illnesses per visit', 'SCHEMA', N'dbo', 'TABLE',
N'PatientChronicIllness', NULL, NULL
GO
```

## Uses

[dbo].[PatientMasterVisit]

# [dbo].[PatientClinicalDiagnosis]

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| FK | PatientId | int | 4 | False | | |
| | PatientMasterVisitId | int | 4 | False | | |
| | Diagnosis | varchar(250) | 250 | False | | |
| | Treatment | varchar(250) | 250 | False | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |
| | AuditData | xml | max | True | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientClinicalDiagnosis | Id | True |

## Foreign Keys

| Name | Update | Delete | Columns |
|---|---|---|---|
| FK_PatientTreatementDiagnosis_PatientMasterVisit | Cascade | Cascade | PatientId->[dbo].[PatientMasterVisit].[Id] |

## SQL Script

```sql
CREATE TABLE [dbo].[PatientClinicalDiagnosis]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[PatientMasterVisitId] [int] NOT NULL,
[Diagnosis] [varchar] (250) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[Treatment] [varchar] (250) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_PatientTreatementDiagnosis_Void] DEFAULT
((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_PatientTreatementDiagnosis_CreateDate]
DEFAULT (getdate()),
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientClinicalDiagnosis] ADD CONSTRAINT [PK_PatientClinical-
Diagnosis] PRIMARY KEY CLUSTERED  ([Id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientClinicalDiagnosis] ADD CONSTRAINT [FK_PatientTreatement-
Diagnosis_PatientMasterVisit] FOREIGN KEY ([PatientId]) REFERENCES [dbo].[PatientMaster-
Visit] ([Id]) ON DELETE CASCADE ON UPDATE CASCADE
GO
```

## Uses

[dbo].[PatientMasterVisit]

Project > .\SQLEXPRESS > User databases > Greencard > Tables > dbo.PatientClinicalNotes

# [dbo].[PatientClinicalNotes]

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| | FacilityId | int | 4 | False | | |
| | PatientMasterVisitId | int | 4 | False | | |
| | ServiceAreaId | int | 4 | False | | |
| | ClinicalNotes | varchar(8000) | 8000 | False | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |
| | ModifyFlag | bit | 1 | False | | ((0)) |
| | VersionStamp | timestamp | 8 | False | | |
| | AuditData | xml | max | True | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientClinicalNotes | Id | True |
| | IX_PatientClinicalNotes | PatientId, PatientMasterVisitId, FacilityId | |

## SQL Script

```
CREATE TABLE [dbo].[PatientClinicalNotes]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[FacilityId] [int] NOT NULL,
[PatientMasterVisitId] [int] NOT NULL,
[ServiceAreaId] [int] NOT NULL,
[ClinicalNotes] [varchar] (8000) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_dtl_PatientClinicalNotes_DeleteFlag] DEFAULT
((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_PatientClinicalNotes_CreateDate]
DEFAULT (getdate()),
[ModifyFlag] [bit] NOT NULL CONSTRAINT [DF_dtl_PatientClinicalNotes_ModifiedFlag]
DEFAULT ((0)),
[VersionStamp] [timestamp] NOT NULL,
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientClinicalNotes] ADD CONSTRAINT [PK_PatientClinicalNotes]
PRIMARY KEY CLUSTERED  ([Id]) ON [PRIMARY]
GO
CREATE NONCLUSTERED INDEX [IX_PatientClinicalNotes] ON [dbo].[PatientClinicalNotes]
([PatientId], [PatientMasterVisitId], [FacilityId]) ON [PRIMARY]
GO
```

# [dbo].[PatientDiagnosis]

## MS_Description

Clinician conclusions on the treatment plan,done per visit

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| FK | PatientMasterVisitId | int | 4 | False | | |
| | Diagnosis | int | 4 | False | | |
| | ManagementPlan | varchar(400) | 400 | True | | |
| | DeleteFlag | bit | 1 | False | | |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |
| | AuditData | xml | max | True | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientDiagnosis | Id | True |

## Foreign Keys

| Name | Update | Delete | Columns |
|---|---|---|---|
| FK_PatientDiagnosis_PatientMasterVisit | Cascade | Cascade | PatientMasterVisitId->[dbo].[PatientMasterVisit].[Id] |

## SQL Script

```
CREATE TABLE [dbo].[PatientDiagnosis]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[PatientMasterVisitId] [int] NOT NULL,
[Diagnosis] [int] NOT NULL,
[ManagementPlan] [varchar] (400) COLLATE SQL_Latin1_General_CP1_CI_AS NULL,
[DeleteFlag] [bit] NOT NULL,
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_PatientDiagnosis_CreateDate] DEFAULT
(getdate()),
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientDiagnosis] ADD CONSTRAINT [PK_PatientDiagnosis] PRIMARY KEY
CLUSTERED  ([Id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientDiagnosis] ADD CONSTRAINT [FK_PatientDiagnosis_PatientMaster-
Visit] FOREIGN KEY ([PatientMasterVisitId]) REFERENCES [dbo].[PatientMasterVisit]
([Id]) ON DELETE CASCADE ON UPDATE CASCADE
GO
EXEC sp_addextendedproperty N'MS_Description', N'Clinician conclusions on the treatment
plan,done per visit', 'SCHEMA', N'dbo', 'TABLE', N'PatientDiagnosis', NULL, NULL
GO
```

## Uses

[dbo].[PatientMasterVisit]

# [dbo].[PatientEncounter]

## MS_Description

Tracks and manages all patient encounters per visit per service

## Properties

| Property | Value |
|---|---|
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| | EncounterTypeId | int | 4 | False | | |
| FK | PatientMasterVisitId | int | 4 | False | | |
| | EncounterStartTime | datetime | 8 | False | | |
| | EncounterEndTime | datetime | 8 | False | | |
| | ServiceAreaId | int | 4 | False | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |
| | AuditData | xml | max | True | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientEncounter | Id | True |

## Foreign Keys

| Name | Update | Delete | Columns |
|---|---|---|---|
| FK_PatientEncounter_PatientMasterVisit | Cascade | Cascade | PatientMasterVisitId->[dbo].[PatientMasterVisit].[Id] |

## SQL Script

```
CREATE TABLE [dbo].[PatientEncounter]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[EncounterTypeId] [int] NOT NULL,
[PatientMasterVisitId] [int] NOT NULL,
[EncounterStartTime] [datetime] NOT NULL,
[EncounterEndTime] [datetime] NOT NULL,
[ServiceAreaId] [int] NOT NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_patient_encounter_void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_PatientEncounter_CreateDate] DEFAULT
(getdate()),
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientEncounter] ADD CONSTRAINT [PK_PatientEncounter] PRIMARY KEY
CLUSTERED  ([Id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientEncounter] ADD CONSTRAINT [FK_PatientEncounter_PatientMaster-
Visit] FOREIGN KEY ([PatientMasterVisitId]) REFERENCES [dbo].[PatientMasterVisit]
([Id]) ON DELETE CASCADE ON UPDATE CASCADE
GO
EXEC sp_addextendedproperty N'MS_Description', N'Tracks and manages all patient
encounters per visit per service', 'SCHEMA', N'dbo', 'TABLE', N'PatientEncounter',
NULL, NULL
GO
```

## Uses

[dbo].[PatientMasterVisit]

# [dbo].[PatientEnrollment]

## MS_Description

Tracks patient enrollment into the different service areas

## Properties

| Property | Value |
|---|---|
| Row Count (~) | 0 |
| Created | 11:17:10 AM Wednesday, January 4, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| | ServiceAreaId | int | 4 | False | | |
| | EnrollmentDate | date | 3 | False | | |
| | EnrollmentStatusId | int | 4 | False | | |
| | TransferIn | bit | 1 | False | | ((0)) |
| | CareEnded | bit | 1 | False | | ((0)) |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |
| | AuditData | xml | max | True | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientEnrollment | Id | True |

## SQL Script

```
CREATE TABLE [dbo].[PatientEnrollment]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[ServiceAreaId] [int] NOT NULL,
[EnrollmentDate] [date] NOT NULL,
[EnrollmentStatusId] [int] NOT NULL,
[TransferIn] [bit] NOT NULL CONSTRAINT [DF_PatientEnrollment_TransferIn] DEFAULT ((0)),
[CareEnded] [bit] NOT NULL CONSTRAINT [DF_PatientEnrollment_Active] DEFAULT ((0)),
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_patient_enrollment_void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_PatientEnrollment_CreateDate] DEFAULT
(getdate()),
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientEnrollment] ADD CONSTRAINT [PK_PatientEnrollment] PRIMARY KEY
CLUSTERED  ([Id]) ON [PRIMARY]
GO
EXEC sp_addextendedproperty N'MS_Description', N'Tracks patient enrollment into the
different service areas', 'SCHEMA', N'dbo', 'TABLE', N'PatientEnrollment', NULL, NULL
GO
```

# [dbo].[PatientFamilyPlanning]

## Properties

| Property | Value |
|---|---|
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| | PatientMasterVisitId | int | 4 | False | | |
| | FPStatusId | int | 4 | False | | |
| | ReasonNotOnFPId | int | 4 | True | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |
| | AuditData | xml | max | False | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientFamilyPlanning | Id | True |

## SQL Script

```
CREATE TABLE [dbo].[PatientFamilyPlanning]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[PatientMasterVisitId] [int] NOT NULL,
[FPStatusId] [int] NOT NULL,
[ReasonNotOnFPId] [int] NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_PatientFamilyPlanning_DeleteFlag] DEFAULT
((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_PatientFamilyPlanning_CreateDate]
DEFAULT (getdate()),
[AuditData] [xml] NOT NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientFamilyPlanning] ADD CONSTRAINT [PK_PatientFamilyPlanning]
PRIMARY KEY CLUSTERED  ([Id]) ON [PRIMARY]
GO
```

# [dbo].[PatientFamilyPlanningMethod]

## Properties

| Property | Value |
|---|---|
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| | PatientFPId | int | 4 | False | | |
| | FPMethodId | int | 4 | False | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientFamilyPlanningMethod | Id | True |

## SQL Script

```
CREATE TABLE [dbo].[PatientFamilyPlanningMethod]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[PatientFPId] [int] NOT NULL,
[FPMethodId] [int] NOT NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_PatientFamilyPlanningMethod_DeleteFlag]
DEFAULT ((0))
) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientFamilyPlanningMethod] ADD CONSTRAINT [PK_PatientFamily-
PlanningMethod] PRIMARY KEY CLUSTERED  ([Id]) ON [PRIMARY]
GO
```

# [dbo].[PatientIdentifier]

## MS_Description

Tracks and manages patient service identifier information

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| | PatientEnrollmentId | int | 4 | False | | |
| | IdentifierType | int | 4 | False | | |
| | IdentifierValue | varchar(50) | 50 | False | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientIdentifier | Id | True |

## SQL Script

```sql
CREATE TABLE [dbo].[PatientIdentifier]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[PatientEnrollmentId] [int] NOT NULL,
[IdentifierType] [int] NOT NULL,
[IdentifierValue] [varchar] (50) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_patient_identifier_void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_PatientIdentifier_CreateDate] DEFAULT
(getdate())
) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientIdentifier] ADD CONSTRAINT [PK_PatientIdentifier] PRIMARY KEY
CLUSTERED  ([Id]) ON [PRIMARY]
GO
EXEC sp_addextendedproperty N'MS_Description', N'Tracks and manages patient service
identifier information', 'SCHEMA', N'dbo', 'TABLE', N'PatientIdentifier', NULL, NULL
GO
```

# [dbo].[PatientLabTracker]

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Default |
|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | |
| | patientId | int | 4 | False | |
| FK | masterVisitId | int | 4 | False | |
| | LabName | varchar(50) | 50 | False | |
| | SampleDate | date | 3 | False | |
| | Reasons | varchar(50) | 50 | False | |
| | Results | varchar(50) | 50 | False | |
| | Void | bit | 1 | False | ((0)) |
| | VoidBy | int | 4 | True | |
| | VoidDate | datetime | 8 | True | |
| | CreateBy | int | 4 | False | |
| | CreateDate | datetime | 8 | False | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientLabTracker | Id | True |

## Foreign Keys

| Name | Update | Delete | Columns |
|---|---|---|---|
| FK_PatientLabTracker_PatientMasterVisit | Cascade | Cascade | masterVisitId->[dbo].[PatientMasterVisit].[Id] |

## SQL Script

```
CREATE TABLE [dbo].[PatientLabTracker]
(
[Id] [int] NOT NULL,
[patientId] [int] NOT NULL,
[masterVisitId] [int] NOT NULL,
[LabName] [varchar] (50) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[SampleDate] [date] NOT NULL,
[Reasons] [varchar] (50) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[Results] [varchar] (50) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[Void] [bit] NOT NULL CONSTRAINT [DF_PatientLabTracker_Void] DEFAULT ((0)),
[VoidBy] [int] NULL,
[VoidDate] [datetime] NULL,
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL
) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientLabTracker] ADD CONSTRAINT [PK_PatientLabTracker] PRIMARY KEY
CLUSTERED  ([Id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientLabTracker] ADD CONSTRAINT [FK_PatientLabTracker_Patient-
MasterVisit] FOREIGN KEY ([masterVisitId]) REFERENCES [dbo].[PatientMasterVisit] ([Id])
ON DELETE CASCADE ON UPDATE CASCADE
GO
```

## Uses

[dbo].[PatientMasterVisit]

# [dbo].[PatientMaritalStatus]

## Properties

| Property | Value |
|---|---|
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| | MaritalStatusId | int | 4 | False | | |
| | Active | bit | 1 | False | | ((1)) |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CeateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |
| | AuditData | xml | max | True | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientMaritalStatus | Id | True |

## SQL Script

```
CREATE TABLE [dbo].[PatientMaritalStatus]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[MaritalStatusId] [int] NOT NULL,
[Active] [bit] NOT NULL CONSTRAINT [DF_PatientMaritalStatus_Active] DEFAULT ((1)),
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_patient_maritalstatus_void] DEFAULT ((0)),
[CeateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_patient_maritalstatus_create_date]
DEFAULT (getdate()),
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
```

```sql
ALTER TABLE [dbo].[PatientMaritalStatus] ADD CONSTRAINT [PK_PatientMaritalStatus]
PRIMARY KEY CLUSTERED  ([Id]) ON [PRIMARY]
GO
```

# [dbo].[PatientMasterVisit]

## Properties

| Property | Value |
|---|---|
| Row Count (~) | 0 |
| Created | 5:53:36 PM Wednesday, December 21, 2016 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| | FaciltyId | int | 4 | False | | |
| | VisitDate | datetime | 8 | False | | |
| | Schedule | bit | 1 | False | | |
| | VisitBy | int | 4 | False | | |
| | StartTime | datetime | 8 | False | | |
| | EndTime | datetime | 8 | True | | |
| | ServiceAreaId | int | 4 | False | | ((0)) |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientMasterVisit | Id | True |

## SQL Script

```
CREATE TABLE [dbo].[PatientMasterVisit]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[FaciltyId] [int] NOT NULL,
[VisitDate] [datetime] NOT NULL,
[Schedule] [bit] NOT NULL,
[VisitBy] [int] NOT NULL,
[StartTime] [datetime] NOT NULL,
[EndTime] [datetime] NULL,
[ServiceAreaId] [int] NOT NULL CONSTRAINT [DF_PatientMasterVisit_status] DEFAULT ((0)),
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_PatientMasterVisit_void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL
) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientMasterVisit] ADD CONSTRAINT [PK_PatientMasterVisit] PRIMARY
KEY CLUSTERED  ([Id]) ON [PRIMARY]
GO
```

## Used By

[dbo].[AdherenceOutcome]
[dbo].[AdverseEvent]
[dbo].[ARTInitiationBaseline]
[dbo].[ARTUseHistory]
[dbo].[ComplaintsHistory]
[dbo].[Disclosure]
[dbo].[PatientAllergy]
[dbo].[PatientAppointment]
[dbo].[PatientCareending]
[dbo].[PatientChronicIllness]
[dbo].[PatientClinicalDiagnosis]
[dbo].[PatientDiagnosis]
[dbo].[PatientEncounter]
[dbo].[PatientLabTracker]
[dbo].[PatientPHDP]
[dbo].[PatientReferral]
[dbo].[PatientVitals]
[dbo].[PhysicalExamination]
[dbo].[TreatmentEventTracker]
[dbo].[Vaccination]

# [dbo].[PatientOVCStatus]

## Properties

| Property | Value |
|---|---|
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Default |
|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | |
| FK | PatientId | int | 4 | False | |
| FK | GuardianId | int | 4 | False | |
| | Orphan | bit | 1 | False | |
| | InSchool | bit | 1 | False | |
| | Active | bit | 1 | False | |
| | DeleteFlag | bit | 1 | False | ((0)) |
| | CreateBy | int | 4 | False | |
| | CreateDate | datetime | 8 | False | |
| | AuditData | xml | max | True | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientOVCStatus | Id | True |

## Foreign Keys

| Name | Columns |
|---|---|
| FK_PatientOVCStatus_Patient | PatientId->[dbo].[Patient].[Id] |
| FK_PatientOVCStatus_Person | GuardianId->[dbo].[Person].[Id] |

## SQL Script

```
CREATE TABLE [dbo].[PatientOVCStatus]
(
[Id] [int] NOT NULL,
[PatientId] [int] NOT NULL,
[GuardianId] [int] NOT NULL,
[Orphan] [bit] NOT NULL,
[InSchool] [bit] NOT NULL,
[Active] [bit] NOT NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_patient_ovcstatus_void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL,
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientOVCStatus] ADD CONSTRAINT [PK_PatientOVCStatus] PRIMARY KEY
CLUSTERED  ([Id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientOVCStatus] ADD CONSTRAINT [FK_PatientOVCStatus_Patient]
FOREIGN KEY ([PatientId]) REFERENCES [dbo].[Patient] ([Id])
GO
ALTER TABLE [dbo].[PatientOVCStatus] ADD CONSTRAINT [FK_PatientOVCStatus_Person]
FOREIGN KEY ([GuardianId]) REFERENCES [dbo].[Person] ([Id])
GO
```

## Uses

[dbo].[Patient]
[dbo].[Person]

# [dbo].[PatientPHDP]

## Properties

| Property | Value |
|---|---|
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| FK | PatientMasterVisitId | int | 4 | False | | |
| | Phdp | int | 4 | False | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |
| | AuditData | xml | max | True | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientPHDP | Id | True |

## Foreign Keys

| Name | Update | Delete | Columns |
|---|---|---|---|
| FK_PatientPHDP_PatientMasterVisit | Cascade | Cascade | PatientMasterVisitId->[dbo].[PatientMasterVisit].[Id] |

## SQL Script

```
CREATE TABLE [dbo].[PatientPHDP]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[PatientMasterVisitId] [int] NOT NULL,
[Phdp] [int] NOT NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_PatientPHDP_Void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_PatientPHDP_CreateDate] DEFAULT
(getdate()),
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientPHDP] ADD CONSTRAINT [PK_PatientPHDP] PRIMARY KEY CLUSTERED
([Id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientPHDP] ADD CONSTRAINT [FK_PatientPHDP_PatientMasterVisit]
FOREIGN KEY ([PatientMasterVisitId]) REFERENCES [dbo].[PatientMasterVisit] ([Id]) ON
DELETE CASCADE ON UPDATE CASCADE
GO
```

## Uses

[dbo].[PatientMasterVisit]

# [dbo].[PatientPopulation]

## Properties

| Property | Value |
|---|---|
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| | PopulationId | int | 4 | False | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |
| | AuditData | xml | max | True | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientPopulation | Id | True |

## SQL Script

```
CREATE TABLE [dbo].[PatientPopulation]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[PopulationId] [int] NOT NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_patient_population_void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_patient_population_create_date] DEFAULT
(getdate()),
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientPopulation] ADD CONSTRAINT [PK_PatientPopulation] PRIMARY KEY
CLUSTERED  ([Id]) ON [PRIMARY]
```

```
GO
```

# [dbo].[PatientProphylaxis]

## Properties

| Property | Value |
|---|---|
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | ProphylaxisTypeId | int | 4 | False | | |
| | PatientId | int | 4 | False | | |
| | PatientMasterVisitId | int | 4 | False | | |
| | StartDate | date | 3 | False | | |
| | Complete | bit | 1 | False | | |
| | CompletionDate | date | 3 | True | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientProphylaxis | Id | True |

## SQL Script

```
CREATE TABLE [dbo].[PatientProphylaxis]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[ProphylaxisTypeId] [int] NOT NULL,
[PatientId] [int] NOT NULL,
[PatientMasterVisitId] [int] NOT NULL,
[StartDate] [date] NOT NULL,
[Complete] [bit] NOT NULL,
[CompletionDate] [date] NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_INHProphylaxis_Void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_INHProphylaxis_CreateDate] DEFAULT
(getdate())
) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientProphylaxis] ADD CONSTRAINT [PK_PatientProphylaxis] PRIMARY
KEY CLUSTERED  ([Id]) ON [PRIMARY]
GO
```

# [dbo].[PatientReferral]

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| FK | PatientMasterVisitId | int | 4 | False | | |
| | ReferredFrom | int | 4 | False | | |
| | ReferredTo | varchar(250) | 250 | True | | |
| | ReferralReason | varchar(250) | 250 | False | | |
| | ReferralDate | datetime | 8 | False | | |
| | ReferredBy | varchar(50) | 50 | False | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |
| | AuditData | xml | max | True | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientReferral | Id | True |

## Foreign Keys

| Name | Columns |
|---|---|
| FK_PatientReferral_PatientMasterVisit | PatientMasterVisitId->[dbo].[PatientMasterVisit].[Id] |

Project > .\SQLEXPRESS > User databases > Greencard > Tables > dbo.PatientReferral

## SQL Script

```
CREATE TABLE [dbo].[PatientReferral]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[PatientMasterVisitId] [int] NOT NULL,
[ReferredFrom] [int] NOT NULL,
[ReferredTo] [varchar] (250) COLLATE SQL_Latin1_General_CP1_CI_AS NULL,
[ReferralReason] [varchar] (250) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[ReferralDate] [datetime] NOT NULL,
[ReferredBy] [varchar] (50) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_PatientReferral_DeleteFlag] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_PatientReferral_CreateDate] DEFAULT (getdate()),
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientReferral] ADD CONSTRAINT [PK_PatientReferral] PRIMARY KEY CLUSTERED  ([Id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientReferral] ADD CONSTRAINT [FK_PatientReferral_PatientMasterVisit] FOREIGN KEY ([PatientMasterVisitId]) REFERENCES [dbo].[PatientMasterVisit] ([Id])
GO
```

## Uses

[dbo].[PatientMasterVisit]

# [dbo].[PatientScreening]

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| | PatientMasterVisitId | int | 4 | False | | |
| | ScreeningTypeId | int | 4 | False | | |
| | ScreeningDone | bit | 1 | False | | |
| | ScreeningDate | date | 3 | True | | |
| | ScreeningCategoryId | int | 4 | True | | |
| | ScreeningValueId | int | 4 | True | | |
| | Comment | varchar(250) | 250 | True | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |
| | AuditData | xml | max | True | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientScreening | Id | True |

## SQL Script

```
CREATE TABLE [dbo].[PatientScreening]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[PatientMasterVisitId] [int] NOT NULL,
[ScreeningTypeId] [int] NOT NULL,
[ScreeningDone] [bit] NOT NULL,
[ScreeningDate] [date] NULL,
[ScreeningCategoryId] [int] NULL,
[ScreeningValueId] [int] NULL,
[Comment] [varchar] (250) COLLATE SQL_Latin1_General_CP1_CI_AS NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_PatientScreening_Void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_PatientScreening_CreateDate] DEFAULT
(getdate()),
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientScreening] ADD CONSTRAINT [PK_PatientScreening] PRIMARY KEY
CLUSTERED  ([Id]) ON [PRIMARY]
GO
```

# [dbo].[PatientTransferIn]

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| | ServiceAreaId | int | 4 | False | | |
| | TransferInDate | date | 3 | False | | |
| | TreatmentStartDate | date | 3 | False | | |
| | CurrentTreatment | varchar(50) | 50 | False | | |
| | FacilityFrom | varchar(150) | 150 | False | | |
| | MFLCode | int | 4 | False | | |
| | CountyFrom | varchar(150) | 150 | False | | |
| | TransferInNotes | varchar(250) | 250 | False | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientTransferIn | Id | True |

## SQL Script

```
CREATE TABLE [dbo].[PatientTransferIn]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[ServiceAreaId] [int] NOT NULL,
[TransferInDate] [date] NOT NULL,
[TreatmentStartDate] [date] NOT NULL,
[CurrentTreatment] [varchar] (50) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[FacilityFrom] [varchar] (150) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[MFLCode] [int] NOT NULL,
[CountyFrom] [varchar] (150) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[TransferInNotes] [varchar] (250) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_transfer_in_void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_PatientTransferIn_CreateDate] DEFAULT
(getdate())
) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientTransferIn] ADD CONSTRAINT [PK_PatientTransferIn] PRIMARY KEY
CLUSTERED  ([Id]) ON [PRIMARY]
GO
```

# [dbo].[PatientTreatmentSupporter]

## Properties

| Property | Value |
|---|---|
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Default |
|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | |
| FK | PatientId | int | 4 | False | |
| FK | SupporterId | int | 4 | False | |
| | DeleteFlag | int | 4 | False | ((0)) |
| | CreateBy | int | 4 | False | |
| | CreateDate | datetime | 8 | False | |
| | AuditData | xml | max | True | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientTreatmentSupporter | Id | True |

## Foreign Keys

| Name | Columns |
|---|---|
| FK_PatientTreatmentSupporter_Patient | PatientId->[dbo].[Patient].[Id] |
| FK_PatientTreatmentSupporter_Person | SupporterId->[dbo].[Person].[Id] |

## SQL Script

```
CREATE TABLE [dbo].[PatientTreatmentSupporter]
(
[Id] [int] NOT NULL,
[PatientId] [int] NOT NULL,
[SupporterId] [int] NOT NULL,
[DeleteFlag] [int] NOT NULL CONSTRAINT [DF_PatientTreatmentSupporter_Void] DEFAULT
((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL,
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientTreatmentSupporter] ADD CONSTRAINT [PK_PatientTreatment-
Supporter] PRIMARY KEY CLUSTERED  ([Id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientTreatmentSupporter] ADD CONSTRAINT [FK_PatientTreatment-
Supporter_Patient] FOREIGN KEY ([PatientId]) REFERENCES [dbo].[Patient] ([Id])
GO
ALTER TABLE [dbo].[PatientTreatmentSupporter] ADD CONSTRAINT [FK_PatientTreatment-
Supporter_Person] FOREIGN KEY ([SupporterId]) REFERENCES [dbo].[Person] ([Id])
GO
```

## Uses

[dbo].[Patient]
[dbo].[Person]

# [dbo].[PatientVitals]

## Properties

| Property | Value |
|---|---|
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| FK | PatientMasterVisitId | int | 4 | False | | |
| | Temperature | decimal(5,2) | 5 | True | | |
| | RespistoryRate | decimal(5,2) | 5 | True | | |
| | HeartRate | decimal(5,2) | 5 | True | | |
| | BPDiastolic | int | 4 | True | | |
| | BPSystolic | int | 4 | True | | |
| | Height | decimal(8,2) | 5 | True | | |
| | Weight | decimal(8,2) | 5 | True | | |
| | Muac | decimal(8,2) | 5 | True | | |
| | SP02 | decimal(5,2) | 5 | True | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PatientVitals_1 | Id | True |

## Foreign Keys

| Name | Update | Delete | Columns |
|---|---|---|---|
| FK_PatientVitals_PatientMasterVisit | Cascade | Cascade | PatientMasterVisitId->[dbo].[PatientMasterVisit].[Id] |

## SQL Script

```
CREATE TABLE [dbo].[PatientVitals]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[PatientMasterVisitId] [int] NOT NULL,
[Temperature] [decimal] (5, 2) NULL,
[RespistoryRate] [decimal] (5, 2) NULL,
[HeartRate] [decimal] (5, 2) NULL,
[BPDiastolic] [int] NULL,
[BPSystolic] [int] NULL,
[Height] [decimal] (8, 2) NULL,
[Weight] [decimal] (8, 2) NULL,
[Muac] [decimal] (8, 2) NULL,
[SP02] [decimal] (5, 2) NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_PatientVitals_Void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_PatientVitals_CreateDate] DEFAULT
(getdate())
) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientVitals] ADD CONSTRAINT [PK_PatientVitals_1] PRIMARY KEY
CLUSTERED  ([Id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PatientVitals] ADD CONSTRAINT [FK_PatientVitals_PatientMasterVisit]
FOREIGN KEY ([PatientMasterVisitId]) REFERENCES [dbo].[PatientMasterVisit] ([Id]) ON
DELETE CASCADE ON UPDATE CASCADE
GO
```

## Uses

[dbo].[PatientMasterVisit]

# [dbo].[Person]

## Properties

| Property | Value |
|---|---|
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | FirstName | varbinary(max) | max | False | | |
| | MidName | varbinary(max) | max | True | | |
| | LastName | varbinary(max) | max | False | | |
| | Sex | int | 4 | False | | |
| | Active | bit | 1 | False | | ((1)) |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_Person | Id | True |

## SQL Script

```sql
CREATE TABLE [dbo].[Person]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[FirstName] [varbinary] (max) NOT NULL,
[MidName] [varbinary] (max) NULL,
[LastName] [varbinary] (max) NOT NULL,
[Sex] [int] NOT NULL,
[Active] [bit] NOT NULL CONSTRAINT [DF_Person_Active] DEFAULT ((1)),
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_Person_DeleteFlag] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[Person] ADD CONSTRAINT [PK_Person] PRIMARY KEY CLUSTERED  ([Id]) ON
[PRIMARY]
GO
```

## Used By

[dbo].[Patient]
[dbo].[PatientOVCStatus]
[dbo].[PatientTreatmentSupporter]
[dbo].[PersonContact]
[dbo].[PersonLocation]
[dbo].[Vaccination]

# [dbo].[PersonContact]

## MS_Description

Tracks and manages patient contact information,can be updated to reflect the current contact details with history of the previous contacts

## Properties

| **Property** | **Value** |
|---|---|
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| **Key** | **Name** | **Data Type** | **Max Length (Bytes)** | **Allow Nulls** | **Default** |
|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | |
| FK | PersonId | int | 4 | False | |
| | PhysicalAddress | varbinary(800) | 800 | False | |
| | MobileNumber | varbinary(800) | 800 | False | |
| | Active | bit | 1 | False | ((1)) |
| | DeleteFlag | bit | 1 | False | ((0)) |
| | CreateBy | int | 4 | False | |
| | CreateDate | datetime | 8 | False | (getdate()) |
| | AuditData | xml | max | True | |

## Indexes

| **Key** | **Name** | **Key Columns** | **Unique** |
|---|---|---|---|
| PK C | PK_patient_contact | Id | True |

## Foreign Keys

| **Name** | **Columns** |
|---|---|
| FK_PersonContact_Person | PersonId->[dbo].[Person].[Id] |

## SQL Script

```
CREATE TABLE [dbo].[PersonContact]
```

```
(
[Id] [int] NOT NULL,
[PersonId] [int] NOT NULL,
[PhysicalAddress] [varbinary] (800) NOT NULL,
[MobileNumber] [varbinary] (800) NOT NULL,
[Active] [bit] NOT NULL CONSTRAINT [DF_PatientContact_IsActive] DEFAULT ((1)),
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_patient_contact_void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_PersonContact_CreateDate] DEFAULT
(getdate()),
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[PersonContact] ADD CONSTRAINT [PK_patient_contact] PRIMARY KEY
CLUSTERED  ([Id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PersonContact] ADD CONSTRAINT [FK_PersonContact_Person] FOREIGN KEY
([PersonId]) REFERENCES [dbo].[Person] ([Id])
GO
EXEC sp_addextendedproperty N'MS_Description', N'Tracks and manages patient contact
information,can be updated to reflect the current contact details with history of the
previous contacts', 'SCHEMA', N'dbo', 'TABLE', N'PersonContact', NULL, NULL
GO
```

## Uses

[dbo].[Person]

# [dbo].[PersonLocation]

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| FK | PersonId | int | 4 | False | | |
| | County | int | 4 | False | | |
| | SubCounty | int | 4 | True | | |
| | Ward | int | 4 | True | | |
| | Village | varchar(250) | 250 | False | | (NULL) |
| | Estate | varchar(250) | 250 | False | | (NULL) |
| | LandMark | varchar(250) | 250 | False | | (NULL) |
| | NearestHealthCentre | varchar(250) | 250 | False | | (NULL) |
| | Active | bit | 1 | False | | ((1)) |
| | SketchMap | varbinary(1000) | 1000 | False | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | ((0)) |
| | CreateDate | datetime | 8 | False | | |
| | AuditData | xml | max | True | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PersonLocation | Id | True |

## Foreign Keys

| Name | Columns |
|---|---|
| FK_PersonLocation_Person | PersonId->[dbo].[Person].[Id] |

## SQL Script

```
CREATE TABLE [dbo].[PersonLocation]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PersonId] [int] NOT NULL,
[County] [int] NOT NULL,
[SubCounty] [int] NULL,
[Ward] [int] NULL,
[Village] [varchar] (250) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL CONSTRAINT [DF_-
PatientLocation_Village] DEFAULT (NULL),
[Estate] [varchar] (250) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL CONSTRAINT [DF_-
PatientLocation_Estate] DEFAULT (NULL),
[LandMark] [varchar] (250) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL CONSTRAINT
[DF_PatientLocation_LandMark] DEFAULT (NULL),
[NearestHealthCentre] [varchar] (250) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL
CONSTRAINT [DF_PatientLocation_NearestHealthCentre] DEFAULT (NULL),
[Active] [bit] NOT NULL CONSTRAINT [DF_person_location_is_active] DEFAULT ((1)),
[SketchMap] [varbinary] (1000) NOT NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_person_location_void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL CONSTRAINT [DF_person_location_create_by] DEFAULT ((0)),
[CreateDate] [datetime] NOT NULL,
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[PersonLocation] ADD CONSTRAINT [PK_PersonLocation] PRIMARY KEY
CLUSTERED  ([Id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PersonLocation] ADD CONSTRAINT [FK_PersonLocation_Person] FOREIGN
KEY ([PersonId]) REFERENCES [dbo].[Person] ([Id])
GO
```

## Uses

[dbo].[Person]

# [dbo].[PersonRelationship]

## Properties

| Property | Value |
|---|---|
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls |
|---|---|---|---|---|
| PK C | PersonId | int | 4 | False |
| PK C | RelatedTo | int | 4 | False |
| PK C | RelationshipTypeId | int | 4 | False |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PersonRelationship | PersonId, RelatedTo, RelationshipTypeId | True |

## SQL Script

```
CREATE TABLE [dbo].[PersonRelationship]
(
[PersonId] [int] NOT NULL,
[RelatedTo] [int] NOT NULL,
[RelationshipTypeId] [int] NOT NULL
) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PersonRelationship] ADD CONSTRAINT [PK_PersonRelationship] PRIMARY
KEY CLUSTERED  ([PersonId], [RelatedTo], [RelationshipTypeId]) ON [PRIMARY]
GO
```

# [dbo].[PhysicalExamination]

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| FK | PatientMasterVisitId | int | 4 | False | | |
| | ExaminationTypeId | int | 4 | False | | |
| | ExamId | int | 4 | False | | |
| | Finding | varchar(400) | 400 | False | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PhysicalExamination_1 | Id | True |

## Foreign Keys

| Name | Update | Delete | Columns |
|---|---|---|---|
| FK_PhysicalExamination_PatientMasterVisit | Cascade | Cascade | PatientMasterVisitId->[dbo].[PatientMasterVisit].[Id] |

## SQL Script

```
CREATE TABLE [dbo].[PhysicalExamination]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[PatientMasterVisitId] [int] NOT NULL,
[ExaminationTypeId] [int] NOT NULL,
[ExamId] [int] NOT NULL,
[Finding] [varchar] (400) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_PhysicalExamination_Void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_PhysicalExamination_CreateDate] DEFAULT
(getdate())
) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PhysicalExamination] ADD CONSTRAINT [PK_PhysicalExamination_1]
PRIMARY KEY CLUSTERED  ([Id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[PhysicalExamination] ADD CONSTRAINT [FK_PhysicalExamination_Patient-
MasterVisit] FOREIGN KEY ([PatientMasterVisitId]) REFERENCES [dbo].[PatientMasterVisit]
([Id]) ON DELETE CASCADE ON UPDATE CASCADE
GO
```

## Uses

[dbo].[PatientMasterVisit]

# [dbo].[Pregnancy]

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | True | | |
| | PatientMasterVisitId | int | 4 | True | | |
| | LMP | date | 3 | False | | |
| | EDD | date | 3 | False | | |
| | Gravidae | varchar(50) | 50 | True | | |
| | Parity | varchar(50) | 50 | True | | |
| | Outcome | int | 4 | True | | |
| | DateOfOutcome | date | 3 | True | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |
| | AuditData | xml | max | True | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_Pregnancy | Id | True |

## SQL Script

```
CREATE TABLE [dbo].[Pregnancy]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NULL,
[PatientMasterVisitId] [int] NULL,
[LMP] [date] NOT NULL,
[EDD] [date] NOT NULL,
[Gravidae] [varchar] (50) COLLATE SQL_Latin1_General_CP1_CI_AS NULL,
[Parity] [varchar] (50) COLLATE SQL_Latin1_General_CP1_CI_AS NULL,
[Outcome] [int] NULL,
[DateOfOutcome] [date] NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_Pregnancy_Void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_Pregnancy_CreateDate] DEFAULT
(getdate()),
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[Pregnancy] ADD CONSTRAINT [PK_Pregnancy] PRIMARY KEY CLUSTERED
([Id]) ON [PRIMARY]
GO
```

# [dbo].[PregnancyIndicator]

## Properties

| Property | Value |
|---|---|
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| | PatientMasterVisitId | int | 4 | False | | |
| | LMP | date | 3 | False | | |
| | EDD | date | 3 | True | | |
| | PregnacyStatusId | int | 4 | True | | |
| | ANCProfile | bit | 1 | False | | ((0)) |
| | ANCProfileDate | date | 3 | True | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |
| | AuditData | xml | max | True | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_PregnancyIndicator | Id | True |

## SQL Script

```
CREATE TABLE [dbo].[PregnancyIndicator]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[PatientMasterVisitId] [int] NOT NULL,
[LMP] [date] NOT NULL,
[EDD] [date] NULL,
[PregnacyStatusId] [int] NULL,
[ANCProfile] [bit] NOT NULL CONSTRAINT [DF_PregnancyIndicator_ANCProfile] DEFAULT
((0)),
[ANCProfileDate] [date] NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_PregnancyIndicator_DeleteFlag] DEFAULT
((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_PregnancyIndicator_CreateDate] DEFAULT
(getdate()),
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[PregnancyIndicator] ADD CONSTRAINT [PK_PregnancyIndicator] PRIMARY
KEY CLUSTERED  ([Id]) ON [PRIMARY]
GO
```

# [dbo].[ServiceEntryPoint]

## Properties

| Property | Value |
|---|---|
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| | ServiceAreaId | int | 4 | False | | |
| | EntryPointId | int | 4 | False | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_ServiceEntryPoint | Id | True |

## SQL Script

```sql
CREATE TABLE [dbo].[ServiceEntryPoint]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[ServiceAreaId] [int] NOT NULL,
[EntryPointId] [int] NOT NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_ServiceEntryPoint_void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_ServiceEntryPoint_CreateDate] DEFAULT
(getdate())
) ON [PRIMARY]
GO
ALTER TABLE [dbo].[ServiceEntryPoint] ADD CONSTRAINT [PK_ServiceEntryPoint] PRIMARY KEY
CLUSTERED  ([Id]) ON [PRIMARY]
```

```
GO
```

# [dbo].[TBTreatmentTracker]

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| | PatientId | int | 4 | False | | |
| | YearMonth | varchar(8) | 8 | False | | |
| | ScreeningId | int | 4 | False | | |
| | TBRegNumber | varchar(50) | 50 | False | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |
| | AuditData | xml | max | True | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_TBTreatmentTracker | Id | True |

## SQL Script

```
CREATE TABLE [dbo].[TBTreatmentTracker]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[YearMonth] [varchar] (8) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[ScreeningId] [int] NOT NULL,
[TBRegNumber] [varchar] (50) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_TBTreatmentTracker_DeleteFlag] DEFAULT
((0)),
[CreateBy] [int] NOT NULL,
```

```sql
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_TBTreatmentTracker_CreateDate] DEFAULT
(getdate()),
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[TBTreatmentTracker] ADD CONSTRAINT [PK_TBTreatmentTracker] PRIMARY
KEY CLUSTERED  ([Id]) ON [PRIMARY]
GO
```

# [dbo].[TreatmentEventTracker]

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Default |
|---|---|---|---|---|---|
| PK C | id | int | 4 | False | |
| | patientId | int | 4 | False | |
| FK | MasterVisitId | int | 4 | False | |
| | eventDate | date | 3 | False | |
| | eventType | int | 4 | False | |
| | category | varchar(50) | 50 | False | |
| | previous | varchar(50) | 50 | False | |
| | current | varchar(50) | 50 | False | |
| | reason | varchar(150) | 150 | False | |
| | Notes | varchar(250) | 250 | False | |
| | void | int | 4 | True | ((0)) |
| | voidBy | int | 4 | True | |
| | voidDate | date | 3 | True | |
| | createBy | int | 4 | False | |
| | createDate | date | 3 | False | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_TreatmentEventTracker | id | True |

## Foreign Keys

| Name | Update | Delete | Columns |
|---|---|---|---|
| FK_TreatmentEventTracker_PatientMasterVisit | Cascade | Cascade | MasterVisitId->[dbo].[PatientMasterVisit].[Id] |

## SQL Script

```
CREATE TABLE [dbo].[TreatmentEventTracker]
(
[id] [int] NOT NULL,
[patientId] [int] NOT NULL,
[MasterVisitId] [int] NOT NULL,
[eventDate] [date] NOT NULL,
[eventType] [int] NOT NULL,
[category] [varchar] (50) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[previous] [varchar] (50) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[current] [varchar] (50) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[reason] [varchar] (150) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[Notes] [varchar] (250) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[void] [int] NULL CONSTRAINT [DF_TreatmentEventTracker_void] DEFAULT ((0)),
[voidBy] [int] NULL,
[voidDate] [date] NULL,
[createBy] [int] NOT NULL,
[createDate] [date] NOT NULL
) ON [PRIMARY]
GO
ALTER TABLE [dbo].[TreatmentEventTracker] ADD CONSTRAINT [PK_TreatmentEventTracker]
PRIMARY KEY CLUSTERED  ([id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[TreatmentEventTracker] ADD CONSTRAINT [FK_TreatmentEventTracker_-
PatientMasterVisit] FOREIGN KEY ([MasterVisitId]) REFERENCES [dbo].[PatientMasterVisit]
([Id]) ON DELETE CASCADE ON UPDATE CASCADE
GO
```

## Uses

[dbo].[PatientMasterVisit]

# [dbo].[User]

## Properties

| Property | Value |
|---|---|
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Default |
|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | |
| | UserName | varbinary(400) | 400 | False | |
| | Password | varbinary(400) | 400 | False | |
| | EmployeeId | int | 4 | False | |
| | Active | bit | 1 | False | ((0)) |
| | DeleteFlag | bit | 1 | False | ((0)) |
| | Locked | bit | 1 | False | ((0)) |
| | CreateBy | int | 4 | False | |
| | CreateDate | datetime | 8 | False | |
| | AuditLog | xml | max | True | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_User | Id | True |
| | IX_User_UserName | UserName | True |

## SQL Script

```
CREATE TABLE [dbo].[User]
(
[Id] [int] NOT NULL,
[UserName] [varbinary] (400) NOT NULL,
[Password] [varbinary] (400) NOT NULL,
[EmployeeId] [int] NOT NULL,
[Active] [bit] NOT NULL CONSTRAINT [DF_User_Active] DEFAULT ((0)),
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_User_DeleteFlag] DEFAULT ((0)),
[Locked] [bit] NOT NULL CONSTRAINT [DF_User_Locked] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL,
[AuditLog] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[User] ADD CONSTRAINT [PK_User] PRIMARY KEY CLUSTERED  ([Id]) ON
[PRIMARY]
GO
CREATE UNIQUE NONCLUSTERED INDEX [IX_User_UserName] ON [dbo].[User] ([UserName]) ON
[PRIMARY]
GO
```

# [dbo].[Vaccination]

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| Row Count (~) | 0 |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:50 AM Monday, February 20, 2017 |

## Columns

| Key | Name | Data Type | Max Length (Bytes) | Allow Nulls | Identity | Default |
|---|---|---|---|---|---|---|
| PK C | Id | int | 4 | False | 1 - 1 | |
| FK | PatientId | int | 4 | False | | |
| FK | PatientMasterVisitId | int | 4 | False | | |
| | Vaccine | int | 4 | False | | |
| | VaccineStage | varchar(50) | 50 | False | | |
| | DeleteFlag | bit | 1 | False | | ((0)) |
| | CreateBy | int | 4 | False | | |
| | CreateDate | datetime | 8 | False | | (getdate()) |
| | AuditData | xml | max | True | | |

## Indexes

| Key | Name | Key Columns | Unique |
|---|---|---|---|
| PK C | PK_Vaccination | Id | True |

## Foreign Keys

| Name | Columns |
|---|---|
| FK_Vaccination_PatientMasterVisit | PatientMasterVisitId->[dbo].[PatientMasterVisit].[Id] |
| FK_Vaccination_Person | PatientId->[dbo].[Person].[Id] |

## SQL Script

```
CREATE TABLE [dbo].[Vaccination]
(
[Id] [int] NOT NULL IDENTITY(1, 1),
[PatientId] [int] NOT NULL,
[PatientMasterVisitId] [int] NOT NULL,
[Vaccine] [int] NOT NULL,
[VaccineStage] [varchar] (50) COLLATE SQL_Latin1_General_CP1_CI_AS NOT NULL,
[DeleteFlag] [bit] NOT NULL CONSTRAINT [DF_AdultChildVaccination_Void] DEFAULT ((0)),
[CreateBy] [int] NOT NULL,
[CreateDate] [datetime] NOT NULL CONSTRAINT [DF_AdultChildVaccination_CreateDate]
DEFAULT (getdate()),
[AuditData] [xml] NULL
) ON [PRIMARY] TEXTIMAGE_ON [PRIMARY]
GO
ALTER TABLE [dbo].[Vaccination] ADD CONSTRAINT [PK_Vaccination] PRIMARY KEY CLUSTERED
([Id]) ON [PRIMARY]
GO
ALTER TABLE [dbo].[Vaccination] ADD CONSTRAINT [FK_Vaccination_PatientMasterVisit]
FOREIGN KEY ([PatientMasterVisitId]) REFERENCES [dbo].[PatientMasterVisit] ([Id])
GO
ALTER TABLE [dbo].[Vaccination] ADD CONSTRAINT [FK_Vaccination_Person] FOREIGN KEY
([PatientId]) REFERENCES [dbo].[Person] ([Id])
GO
```

## Uses

[dbo].[PatientMasterVisit]
[dbo].[Person]

# Views

## Objects

| Name |
|---|
| dbo.LookupItemView |

# [dbo].[LookupItemView]

## Properties

| Property | Value |
|---|---|
| Collation | SQL_Latin1_General_CP1_CI_AS |
| ANSI Nulls On | True |
| Quoted Identifier On | True |
| Created | 8:18:49 AM Monday, February 20, 2017 |
| Last Modified | 8:18:49 AM Monday, February 20, 2017 |

## Columns

| Name | Data Type | Max Length (Bytes) |
|---|---|---|
| MasterId | int | 4 |
| ItemId | int | 4 |
| MasterName | varchar(50) | 50 |
| ItemName | varchar(50) | 50 |
| DisplayName | varchar(50) | 50 |
| ItemDisplayName | varchar(50) | 50 |
| OrdRank | decimal(5,2) | 5 |

## SQL Script

```
CREATE view [dbo].[LookupItemView]
as
Select    M.Id            As MasterId
    ,    I.Id            As ItemId
    ,    M.Name            As MasterName
    ,    I.Name            As ItemName
    ,    L.DisplayName
    ,    L.DisplayName    As ItemDisplayName
    ,    L.OrdRank
From LookupMaster As M
Inner Join LookupMasterItem As L On M.Id = L.LookupMasterId
Inner Join LookupItem As I On L.LookupItemId = I.Id
GO
```

## Uses

[dbo].[LookupItem]
[dbo].[LookupMaster]
[dbo].[LookupMasterItem]

# *Database Roles*

## Objects

| Name |
|---|
| db_accessadmin |
| db_backupoperator |
| db_datareader |
| db_datawriter |
| db_ddladmin |
| db_denydatareader |
| db_denydatawriter |
| db_owner |
| db_securityadmin |
| public |

# db_accessadmin

## Properties

| Property | Value |
|---|---|
| Owner | dbo |

# db_backupoperator

## Properties

| Property | Value |
|---|---|
| Owner | dbo |

# db_datareader

## Properties

| Property | Value |
|---|---|
| Owner | dbo |

# db_datawriter

## Properties

| Property | Value |
|---|---|
| Owner | dbo |

# db_ddladmin

## Properties

| Property | Value |
|---|---|
| Owner | dbo |

# 👥 db_denydatareader

## Properties

| Property | Value |
|---|---|
| Owner | dbo |

# 👥 db_denydatawriter

## Properties

| Property | Value |
|---|---|
| Owner | dbo |

# 👥 db_owner

## Properties

| Property | Value |
|---|---|
| Owner | dbo |

# 👥 db_securityadmin

## Properties

| Property | Value |
|---|---|
| Owner | dbo |

# public

## Properties

| Property | Value |
|---|---|
| Owner | dbo |