

贴圆盘上表面，锁(-92.5, ±20)圆盘孔(2×M3通孔，从上往下，无沉孔) / 外伸段下面挂模块：2×M3+Φ4.2×4沉孔 + 3让位坑(底面深2) / 厚5

Technical drawing of a square mold plate with the following specifications:

- Overall Dimensions:** 41 mm (width) x 50 mm (height).
- Top Edge Features:**
 - Left side: 8 mm dimension line.
 - Right side: 40 mm (圆孔孔距) mm dimension line.
- Internal Features:**
 - Top Left:** Two circular holes with a center-to-center distance of 14 (模块孔距) mm. The holes are labeled $2 \times \Phi 3.2 + \Phi 4.2 \times 4$ 沉孔 (锁模块).
 - Top Right:** A single circular hole.
 - Bottom Left:** A dashed rectangular area labeled B, containing a dashed circle. It is labeled 3 × 让位坑 深2 (虚线, 底面).
 - Bottom Right:** A dashed rectangular area.
 - Bottom Center:** A circular hole labeled $2 \times \Phi 3.4$ (锁圆盘, 无沉孔).

侧视 (3:1) (沿 -Y 看, 厚5)

Technical drawing of a U-shaped component. The drawing includes the following dimensions and labels:

- Top left vertical dimension: 5 mm
- Top center horizontal dimension: 坑宽 mm (Hole width mm)
- Bottom left vertical dimension: 坑2 mm (Hole 2 mm)
- Bottom right vertical dimension: 5 mm
- Right side vertical dimension: 深2 mm (Depth 2 mm)
- Internal label: (底面进, 让焊脚) (Bottom face in, allow weld toe)

RED 圆盘孔=通孔无沉孔; BLUE 模块孔= $\Phi 4.2 \times 4$ 顶面沉孔; 底面 3 让位坑深2

投影 1st-angle / PLA / 单位 mm

2026-06-15 / POV3D / models / photo_sensor