

SugarTeX

SugarTeX is a more readable LaTeX language extension and a transcompiler to LaTeX.

See [PDF version of this documentation](#) - it nicely renders all Unicode characters and LaTeX example at the end. See original markdown version [here](#).

Contents

- [Command line interfaces](#)
- [Tweaking SugarTeX](#)
- [SugarTeX replacements and operators](#)
 - [Math delimiters](#)
 - [Brackets](#)
 - [Simple pre-replacements](#)
 - [Superscripts and Subscripts](#)
 - [Regular expressions pre-replacements](#)
 - [Nullary operators](#)
 - [Prefix unary operators](#)
 - [Styles](#)
 - [Styles with special brackets](#)
 - [Greedy prefix unary operators](#)
 - [Standard prefix unary operators](#)
 - [Postfix unary operators](#)
 - [Center binary operators](#)
 - [Matrices](#)

- General fractions without bars
- Greedy center binary operators
- Standard center binary operators
- Regular expressions loop replacements
- Regular expressions post-replacements
- Simple post-replacements
- Escapable characters
- Examples

Command line interfaces

1. `sugartex`:

- `sugartex` reads from stdin and writes to stdout,
- `sugartex T0` - run Pandoc filter that iterates over math blocks,
- `sugartex --kiwi` - same as above but with kiwi flavor,

2. `pre-sugartex`:

- `pre-sugartex` reads from stdin and writes to stdout,
- `pre-sugartex` - replace ``` with `$` only,
- `pre-sugartex --all` - replace everything with regexp,
- `pre-sugartex --kiwi` - same as above but with kiwi flavor.

[Panflute](#) scripts are also installed so you can use it in default Panflute [automation interface in metadata](#) or in it's CLI wrapper from [pandoctools](#):

- `panfl sugartex_panfl --to markdown`,
- `panfl sugartex_kiwi -t markdown`.

Examples. Windows:

```
chcp 65001 > NUL
set PYTHONIOENCODING=utf-8
```

```
type doc.md | ^
pre-sugartex | ^
pandoc -f markdown --filter sugartex -o doc.md.md
```

Unix:

```
export PYTHONIOENCODING=utf-8

cat doc.md | \
pre-sugartex | \
pandoc -f markdown --filter sugartex -o doc.md.md
```

Or splitting Pandoc reader-writer:

```
chcp 65001 > NUL
set PYTHONIOENCODING=utf-8

type doc.md | ^
pre-sugartex | ^
pandoc -f markdown -t json | ^
sugartex --kiwi | ^
pandoc -f json -o doc.md.md
```

Tweaking SugarTeX

SugarTeX is written in python and has a tweakable architecture. As you can see in [this filter](#) tweaks can be made in between:

```
sugartex = SugarTeX(delay=True)
...
sugartex.ready()
```

Attributes of instance of `SugarTeX` class can be changed. See them in defining of `SugarTeX` class and in it's `__init__` method [here](#). List of attributes:

- `.brackets`
- `.brackets_types`
- `.simple_pre`
- `.superscripts`
- `.subscripts`
- `.regex_pre`
- `.null_ops` (class `NullOps`)
- `.pref_un_ops` (class `PrefUnOps`), including:
 - `.styles` (class `Styles`)
 - `.other_styles` (class `OtherStyles`)
 - `.pref_un_greedy` (class `PrefUnGreedy`)
- `.postf_un_ops` (class `PostfUnOps`)
- `.bin_centr_ops` (class `BinCentrOps`), including:
 - `.matrices` (class `Matrices`)
 - `.bin_centr_greedy` (class `BinCentrGreedy`)
- `.loop_regexps`
- `.regex_post`
- `.simple_post`
- `.escapes`

SugarTeX replacements and operators

Many replacements use `amsmath` macros.

Math delimiters

In default use-case SugarTeX first preprocesses text replacing ``` with `$` (modifier letter low grave accent U+02CE). Can be escaped: `\``.

SugarTeX Completions for Atom:

- ``` \leftarrow `\``.

Brackets

Independently replace brackets:

- `.(` \rightarrow `\left({` and `.)` \rightarrow `}\right)` (modifier letter low ring U+02F3),
- `..(` \rightarrow `\bigl(` and `)..` \rightarrow `\bigr)`,
- `..(` \rightarrow `\Bigl(` and `)..` \rightarrow `\Bigr)`,
- `..(` \rightarrow `\biggl(` and `)..` \rightarrow `\biggr)`,
- `..(` \rightarrow `\Biggl(` and `)..` \rightarrow `\Biggr)` (modifier letter low vertical line U+02CC).

Instead of `(` and `)` can be other brackets:

- `[` \rightarrow `[` and `]` \rightarrow `]`,
- `(` \rightarrow `(` and `)` \rightarrow `)`,
- `{` \rightarrow `\{` and `}` \rightarrow `\}`,
- `|` \rightarrow `\vert` (box drawings light vertical U+2502, for math in markdown tables),
- `|` \rightarrow `\vert`,
- `||` \rightarrow `\Vert` (double vertical line U+2016),
- `◀` \rightarrow `.` and `▶` \rightarrow `.` (modifier letter low left/right arrowhead U+02F1/U+02F2),
- `⟨` \rightarrow `\langle` and `⟩` \rightarrow `\rangle` (mathematical left/right angle bracket U+27E8/27E9),
- `⌊` \rightarrow `\lfloor` and `⌋` \rightarrow `\rfloor` (left/right floor U+230A/U+230B),
- `⌈` \rightarrow `\lceil` and `⌉` \rightarrow `\rceil` (left/right ceiling U+2308/U+2309).

SugarTeX Completions for Atom:

Use these shortcuts for fast Unicode typing in Atom:

- $\&$ \leftarrow `\&`,
- \circ \leftarrow `_o\small`,
- \prime \leftarrow `_'\small`.
- $|$ \leftarrow `\|`,
- $\|$ \leftarrow `\||`,
- \lessdot \leftarrow `_<`,
- \gtrdot \leftarrow `_>`,
- \lessgtr \leftarrow `_<>`,
- \langle \leftarrow `\<\big`,
- \rangle \leftarrow `\>\big`,
- $\langle \rangle$ \leftarrow `\<>\big`,
- \lfloor \leftarrow `\lfloor`,
- \rfloor \leftarrow `\rfloor`,
- \lceil \leftarrow `\lceil`,
- \rceil \leftarrow `\rceil`.

Simple pre-replacements

- $\sqrt[3]{}$ \rightarrow $3\sqrt{}$ (cube root U+221B),
- $\sqrt[4]{}$ \rightarrow $4\sqrt{}$ (fourth root U+221C),
- \rightarrow $\,$ (thin space U+2009).

SugarTeX Completions for Atom:

- $\,$ \leftarrow `\,` (thin space),
- $\]$ \leftarrow `\], [` (thin space),
- $\sqrt{}$ \leftarrow `\^1/2`,
- $\sqrt[3]{}$ \leftarrow `\^1/3`,
- $\sqrt[4]{}$ \leftarrow `\^1/4`.

Superscripts and Subscripts

Groups of superscript Unicode characters like `¹²³` are replaced with `^{\123}`. Unless they are escaped with `\` or followed by `√`:

- `\¹²³√` → `¹²³√` (square root U+221A),
- `\¹²³` → `¹^{\23}`,
- `¹²³ a b c` → `^{\123abc}`.

Same is for groups of subscript Unicode characters:

- `\₁₂₃` → `₁_{23}`.
- `₁₂₃ k l m` → `_{123klm}`.

List of supported characters can be found in the beginning of the SugarTeX [source code](#).

UPDATE

Now `<>` and `{}^` from [Styles with special brackets](#) end up inside `_{}/^{}^`, like: `A<_ae>` → `A_{<ae>}`. Does not work if there are non-subscript/superscript characters inside `<>/{}^`, like: `A<^ae>` → `A<^{\a}e>`.

SugarTeX Completions for Atom:

- `₁` ← `_1`,
- `ₐ` ← `_a`,
- `¹` ← `\^1`,
- `ᵃ` ← `\^a`.

Regular expressions pre-replacements

Nothing. But can be tweaked.

Nullary operators

Big operators replacements:

- $\Sigma \rightarrow \text{\code{\sum}}$ (n-ary summation U+2211),
- $\Sigma: \rightarrow \text{\code{\sum\nolimits}}$,
- $\Sigma: \rightarrow \text{\code{\sum\limits}}$ (braille pattern dots-48 U+2888).

Supported symbols for limits:

- $:,: \rightarrow \text{\code{\limits}}$ (braille pattern dots-48/dots-17 U+2888/U+2841),
- $:,:,: \rightarrow \text{\code{\nolimits}}$ (braille pattern dots-23/dots-56 U+2806/U+2830).

Supported big operators:

- $\Sigma \rightarrow \text{\code{\sum}},$
- $\prod \rightarrow \text{\code{\prod}},$
- $\int \rightarrow \text{\code{\int}},$
- $\iint \rightarrow \text{\code{\iint}},$
- $\iiint \rightarrow \text{\code{\iiint}},$
- $\iiint \rightarrow \text{\code{\iiiint}},$
- $\oint \rightarrow \text{\code{\oint}}.$

Who knows what I was thinking about by adding them here instead of
Regular expressions replacements...

SugarTeX Completions for Atom:

- $\cdot \leftarrow \text{\code{\:\big}},$
- $\cdot \leftarrow \text{\code{\:\small}},$
- $\Sigma \leftarrow \text{\code{\sum}},$
- $\prod \leftarrow \text{\code{\prod}},$
- $\int \leftarrow \text{\code{\int}},$
- $\iint \leftarrow \text{\code{\iint}},$
- $\iiint \leftarrow \text{\code{\iiint}},$
- $\iiint \leftarrow \text{\code{\iiiint}},$

- $\oint \leftarrow \backslash \text{oint}.$

Prefix unary operators

Styles

Text inside standard brackets $((, [, \{)$ with special prefix is replaced with style operator. For example:

$[\text{rtext}]$ or $[\wedge\{r\}\text{text}] \rightarrow \mathrm{\text{text}}.$

First SugarTeX finds opening part like $[\wedge\{r\}$ then searches for the first non-escaped closing part $]$ that is not inside $\{ \}$ or $\langle \rangle$ – SugarTeX counts opening and closing $\{ \} \langle \rangle$ ($\langle \rangle$ would later be replaced with $\{ \}$ so both are counted together). For example:

$(\text{some}\{te\})(t) \rightarrow \mathrm{\text{some}\{te\}(t)}.$

List of available styles:

- $\{\text{rtext}\} / \{\wedge\{r\}\text{text}\} \rightarrow \mathrm{\text{text}}$ (**math regular**),
- $\{\text{i}x\} / \{\wedge\{i\}x\} \rightarrow \mathrm{\textit{x}}$ (**math italic**),
- $\{\text{b}x\} / \{\wedge\{b\}x\} \rightarrow \mathrm{\textbf{x}}$ (**math bold**),
- $\{\text{\beta}x\} / \{\wedge\{\beta\}x\} \rightarrow \mathrm{\textbf{\textit{x}}}$ (**math bold italic**),
- $\{\text{mtext}\} / \{\wedge\{m\}\text{text}\} \rightarrow \mathrm{\texttt{text}}$ (**math monospace**),
- $\{\text{c}A\} / \{\wedge\{c\}A\} \rightarrow \mathrm{\textcal{A}}$ (**math calligraphic**,
no cyrillic support, see Monotype Corsiva),
- $\{\text{ttext}\} / \{\wedge\{t\}\text{text}\} \rightarrow \text{text}$ (**text**),
- $\{\text{ti}text\} / \{\wedge\{ti\}\text{text}\} \rightarrow \textit{text}$ (**text italic**),
- $\{\text{tb}text\} / \{\wedge\{tb\}\text{text}\} \rightarrow \textbf{text}$ (**text bold**),
- $\{\text{t\beta}text\} / \{\wedge\{t\beta\}\text{text}\} \rightarrow \textit{\textbf{text}}$ (**text bold italic**),
- $\{\vec{x}\} / \{\text{\r{x}}\} \rightarrow \mathrm{\textbf{x}}$ (**vector bold notation**,
combining right arrow above U+20D7, first one is ‘space’ + $\vec{}$),
- $\{\text{\:}x\} / \{\text{\:}x\} \rightarrow \mathrm{\textbf{x}}$ (**vector bold notation**,
braille pattern dots-45/dots-12 U+2818/U+2803 [right upper 2/left upper

$2]),$

- $\{\cdot A\} / \{\cdot A\} \rightarrow \mathbf{\{A\}}$ (matrix bold notation, braille pattern dots-124/dots-1245 U+280B/U+281B).

SugarTeX Completions for Atom:

- \rightarrow $\leftarrow \backslash^{\wedge} \rightarrow,$
- $:$ $\leftarrow \backslash^{\wedge} :,$
- $::$ $\leftarrow \backslash^{\wedge} ::,$
- $\ddot{}$ $\leftarrow \backslash^{\wedge} :.\text{rot.}$

Styles with special brackets

- `<βtext> / <^{\beta}>text> → \textit{\textbf{text}}` (**text bold italic**),
- `<^i>text> / <^{\i}>text> → \textit{text}` (**text italic**),
- `<^b>text> / <^{\b}>text> → \textbf{text}` (**text bold**),
- `<text> → \text{text}` (**text regular**,
single left/right-pointing angle quotation mark U+2039/U+203A),
- `<'text'> → \mathrm{text}` (**math regular**,
modifier letter begin/end high tone U+02F9/U+02FA).

SugarTeX Completions for Atom:

- `<` \leftarrow `\<`,
- `>` \leftarrow `\>`,
- `< >` \leftarrow `\<>`,
- `r r` \leftarrow `\^r\small.`

Greedy prefix unary operators

- $\{\in \text{ smth}\} / _ \in \text{ smth}__ \rightarrow \begin{cases} \text{ smth} \end{cases}$ (**piecewise**, element of with long horizontal stroke U+22F2).

```

. |x|. = {€ x. <if> x≥0 |
          -x. <if> x<0 }
..

```

SugarTeX finds non-escaped {€ or {<€ first then searches for non-escaped } or } that is not inside {} or {<} – SugarTeX counts opening and closing {}<> ({<> would later be replaced with {} so both are counted together).

SugarTeX Completions for Atom:

- {€ ← \-e,
- {€ ← \-E.

Standard prefix unary operators

- <matrix a → \begin{matrix} a
(left-pointing curved angle bracket U+29FC),
- ☹ A² a → \vphantom{A^2} a
(**invisible characters that adjust height**, ghost U+1F47B),
- →[⌈] text a → \xrightarrow{text} a
(**arrow with text above that adjusts to the text length**, rightwards arrow U+2192, top square bracket U+23B4),
- ←[⌈] long text, a → \xleftarrow{{long text}} a
(leftwards arrow U+2190).

SugarTeX finds non-escaped < * first (for example) then searches for a place before non-escaped }, , space, newline or end of the string that is not inside {} or {<} – SugarTeX counts opening and closing {}<> ({<> would later be replaced with {} so both are counted together).

SugarTeX Completions for Atom:

- < ← \<\big2,
- > ← \>\big2,
- <> ← \<>\big2,
- ☹ ← \ghost,

- $\hat{\hat{}} \leftarrow \backslash^^,$
- $\hat{\cdot} \leftarrow \backslash^]\rot,$
- $\rightarrow \leftarrow \backslash->,$
- $\leftarrow \leftarrow \backslash<-.$

Postfix unary operators

- $a \, x^{\rightarrow} \rightarrow a \, \backslash\vec{x}$ (**vector**, combining right arrow above U+20D7),
- $a \, x^{\overrightarrow{}} \rightarrow a \, \backslash\overrightarrow{}$ (**arrow above**, combining right harpoon above U+20D1),
- $a \, x^{\widehat{}} \rightarrow a \, \backslash\widehat{}$ **warning:** works only if the next character after $\widehat{}$ is $\}$, $\, ,$ newline or end of the string,
- $a \, x^{\hat{}} \rightarrow a \, \backslash\hat{}$ (modifier letter circumflex accent U+02C6),
- $a \, x^{\bar{}} \rightarrow a \, \backslash\bar{}$ (macron U+00AF),
- $a \, x^{\overline{}} \rightarrow a \, \backslash\overline{}$ (overline U+203E),
- $a \, x^{\dot{}} \rightarrow a \, \backslash\dot{}$ (dot above U+02D9),
- $a \, x^{\ddot{}} \rightarrow a \, \backslash\ddot{}$ (diaeresis U+00A8),
- $x + y + z^{\overbrace{}} \rightarrow x + \backslash\overbrace{}$ (top curly bracket U+23DE),
- $x + \{y + z\}^{\underbrace{}} \rightarrow x + \backslash\underbrace{}$ (bottom curly bracket U+23DF),
- $a \, x_{} \rightarrow a \, \backslash\underline{}$ **warning:** works only if the next character after $\underline{}$ is $\}$, $\, ,$ newline or end of the string (modifier letter low macron U+02CD),
- $a \, \text{matrix}\rangle \rightarrow a \, \backslash\end{matrix}$ (right-pointing curved angle bracket U+29FD),

SugarTeX finds non-escaped \rangle first (for example) then before it searches for a place after non-escaped $\{$, $\, ,$ space, newline or start of the string that is not inside $\{\}$ or $\langle \rangle$ – SugarTeX counts opening and closing $\{\}$, $\langle \rangle$ ($\langle \rangle$ would later be replaced with $\{\}$ so both are counted together).

In combination with styles:

When combining **one-character** postfix unary operators with styles the order in which operators are applied changes:

`[bx→] → \vec{\mathbf{x}}`

SugarTeX Completions for Atom:

- `→` ← `\^->`,
- `↗` ← `\^->\har`,
- `^` ← `\^ \small`,
- `˘` ← `\^_ \small` (macron),
- `˘` ← `\^ - \small` (macron),
- `¯` ← `\^_` (overline),
- `˙` ← `\^.`,
- `¨` ← `\^..`,
- `⌢` ← `\^}\rot`,
- `⌣` ← `_}\rot`,
- `_` ← `_`,
- `⟨` ← `\<\big2`,
- `⟩` ← `\>\big2`,
- `⟨⟩` ← `\<>\big2`.

Center binary operators

Matrices

Family of `*matrix` amsmath macros is given by `|` operator (broken bar U+00A6, braille pattern dots-124 U+280B):

`[a . b | c . d]` →

`\begin{bmatrix}a . b|c . d\end{bmatrix}` →

`\begin{bmatrix}a &b\\c &d\end{bmatrix}`

All brackets:

- $\langle a \cdot b \mid c \cdot d \rangle \rightarrow \dots\text{matrix}\dots$ (**no brackets**,
modifier letter low left/right arrowhead U+02F1/U+02F2),
- $\{a \cdot b \mid c \cdot d\} \rightarrow \dots\text{Bmatrix}\dots$ (**curly brackets**),
- $\langle (a \cdot b \mid c \cdot d) \rangle / \{(a \cdot b \mid c \cdot d)\} \rightarrow \dots\text{pmatrix}\dots$,
- $\langle [a \cdot b \mid c \cdot d] \rangle / \{[a \cdot b \mid c \cdot d]\} \rightarrow \dots\text{bmatrix}\dots$,
- $\langle |a \cdot b \mid c \cdot d| \rangle / \{|a \cdot b \mid c \cdot d|\} /$
 $\langle |a \cdot b \mid c \cdot d| \rangle / \{|a \cdot b \mid c \cdot d|\} \rightarrow \dots\text{vmatrix}\dots$
(box drawings light vertical U+2502, for math in markdown tables),
- $\langle ||a \cdot b \mid c \cdot d|| \rangle / \{||a \cdot b \mid c \cdot d||\} \rightarrow \dots\text{Vmatrix}\dots$
(double vertical line U+2016).

SugarTeX finds non-escaped binary operator separator \mid first then:

- searches for a place after non-escaped $\{$ or \langle that is not inside $\{\}$ or $\langle \rangle$,
- searches for a place before non-escaped $\}$ or \rangle that is not inside $\{\}$ or $\langle \rangle$,
- it also figures out bracket type properly,
- this way it finds two arguments (SugarTeX counts opening and closing $\{\}$, $\langle \rangle$ would later be replaced with $\{\}$ so both are counted together).

SugarTeX Completions for Atom:

- $\& \leftarrow \backslash\&$,
- $\small \leftarrow \backslash_o\small$,
- $| \leftarrow \backslash|$,
- $|| \leftarrow \backslash||$,
- $\langle \leftarrow \backslash_<$,
- $\rangle \leftarrow \backslash_>$,
- $\langle \rangle \leftarrow \backslash_<>$,
- $\| \leftarrow \backslash\|$,
- $|/2 \leftarrow \backslash|/2$,
- $\cdot \leftarrow \backslash^{\cdot}\cdot\backslash\text{rot}.$

General fractions without bars

Fractions works almost the same as Matrices - they add brackets and stack arguments: first arg is atop of the second arg. But with some differences:

- they use $\frac{ }{ }$ or $\frac{ }{ }$ as a separator (broken bar U+00A6, braille pattern dots-45 U+2818 / dots-12 U+2803),
- cannot handle more than one line break (so two args only),
- they use `\genfrac` amsmath macro,
- they can have size modifiers after $\frac{ }{ }$:
 - $\frac{ }{ }^d$ - display mode,
 - $\frac{ }{ }^t$ - text mode,
 - $\frac{ }{ }^s$ - smaller,
 - $\frac{ }{ }^{xs}$ - extra small,
- left and right brackets can be different.

Examples:

- $\frac{(x}{y)}$,
- $\frac{[x}{y]}$,
- $\{x}{y}$ (**curly brackets**),
- $\frac{x}{y}$ (**no brackets**, modifier letter low left/right arrowhead U+02F1/U+02F2),
- $\boxed{\frac{x}{y}}$, $\boxed{\frac{x}{y}}$ (box drawings light vertical U+2502, for math in markdown tables),
- $\frac{x}{y}$ (double vertical line U+2016).

Arguments search algorithm is the same as for matrices.

SugarTeX Completions for Atom:

- $\frac{ }{ } \leftarrow \frac{ }{ }$,
- $\frac{ }{ } \leftarrow \frac{ }{ }$,
- $\frac{ }{ } \leftarrow \frac{ }{ }^d$,
- $\frac{ }{ } \leftarrow \frac{ }{ }^t$,
- $\frac{ }{ } \leftarrow \frac{ }{ }^s$,
- $\frac{ }{ } \leftarrow \frac{ }{ }^{xs}$,
- $\frac{ }{ } \leftarrow \frac{ }{ }$,

- $\lvert \leftarrow \backslash \lvert / 2,$
- $\dot{} \leftarrow \backslash ^\cdot :$

Greedy center binary operators

Arguments search algorithm is the same as for matrices (except it now does not have brackets).

1. $\langle \text{smth1} \mid \dot{}^t \text{smth2} \rangle \rightarrow$
 $\backslash \text{begin}\{\text{smallmatrix}\}\text{smth1}\mid \text{smth2}\backslash \text{end}\{\text{smallmatrix}\},$
 (Braille Pattern Dots-1245 U+281B).

```
...(\langle a \rangle .b \mid \dot{\phantom{x}}^t c \rangle .d)...
```

2. $\langle \text{smth1} \mid \dot{} \text{smth2} \rangle \rightarrow$
 $\backslash \text{begin}\{\text{array}\}\text{smth1}\mid \text{smth2}\backslash \text{end}\{\text{array}\},$
 (Braille Pattern Dots-1245 U+281B).

```
..
.[\langle                                     \langle cccc \mid c \rangle
  X_{11} \ .X_{12} \ .X_{13} \ .\cdots \ .X_{1n} \ \mid \dot{\phantom{x}}
  X_{21} \ .X_{22} \ .X_{23} \ .\cdots \ .X_{2n} \ \mid
  \vdots \ .\vdots \ .\vdots \ .\ddots \ .\vdots \ \mid
  X_{p1} \ .X_{p2} \ .X_{p3} \ .\cdots \ .X_{pn} \ \rangle ].
..
```

3. $\langle \text{smth1} \mid \# \text{smth2} \rangle \rightarrow$
 $\backslash \text{begin}\{\text{aligned}\}\text{smth1}\mid \text{smth2}\backslash \text{end}\{\text{aligned}\},$

```
..
.|x|. = .{\langle x. \langle if \rangle x \ge 0 \ \mid \#
          -x. \langle if \rangle x < 0 \ \rangle \rangle .
..
```


4. `\smth1 _ smth2` / `\smth1 _ smth2` →

`\substack{smth1|smth2}`,

(modifier letter shelf U+02FD / bottom square bracket U+23B5)

`\sum_{0\leq i\leq N _ 0\leq j\leq M} (ij)^3`

5. `\smth1 _{} smth2` / `\smth1 _{} smth2` →

`\begin{subarray}{l}smth1|smth2\end{subarray}`,

(modifier letter shelf U+02FD / bottom square bracket U+23B5)

`\sum_{0\leq i\leq N _{} 0\leq j\leq M} (ij)^3`

Instead of `_` (left) it can also be `_c` (center) or `_r` (right).

SugarTeX Completions for Atom:

- `\^` ← `\^::`,
- `_` ← `_`,
- `_` ← `_ \rot`,
- `_` ← `_ \rot2`,
- `\|` ← `\|`,
- `\|` ← `\|/2`.

Standard center binary operators

Fractions

- `x/y` → `\frac{x}{y}` (division slash U+2215),
- `1+x/y` → `\frac{1+x}{y}`,
- `1 + {x + z}/y` → `1 + \frac{{x + z}}{y}`,
- `x/{}^dy` → `\dfrac{x}{y}`,
- `x/{}^ty` → `\tfrac{x}{y}`,
- `x/{}_cy` → `\cfrac{x}{y}`,

- x/sy and $x/^{sy}$ are the same as $x/^ty$ but smaller and use `\genfrac` macros. Bar thickness can be set this way: `{0.5pt}x/sy`.

Roots, overset, underset

- $\sqrt{64} \rightarrow \sqrt{64}$ (square root U+221A),
- $\sqrt[6]{64} \rightarrow \sqrt[6]{64}$,
- $1 + \sqrt[6]{64} \rightarrow 1 + \sqrt[6]{64}$,
- $\lim_{x \rightarrow 0} / \lim_{x \rightarrow 0} \rightarrow \underset{x \rightarrow 0}{\lim}$ (modifier letter shelf U+02FD / bottom square bracket U+23B5),
- $\{x + \dots + x\}^{k \text{ times}} \rightarrow \overset{k \text{ times}}{\{x + \dots + x\}}$ (top square bracket U+23B4).

Binomial coefficients

- $(i|c_n) \rightarrow \binom{i}{n}$,
- $(i|c^d_n) \rightarrow \dbinom{i}{n}$ (display),
- $(i|c^t_n) \rightarrow \tbinom{i}{n}$ (text).

In this case SugarTeX finds non-escaped binary operator separator `|c` first then searches for `(` and `)`. Other stop symbols do not work.

SugarTeX finds non-escaped binary operator separator (like `/`) first then:

- searches for a place after non-escaped `{`, `,`, space, newline or start of the string that is not inside `{}` or `<>`,
- searches for a place before non-escaped `}`, `,`, space, newline or end of the string that is not inside `{}` or `<>`,
- this way it finds two arguments (SugarTeX counts opening and closing `{}`, `<>` would later be replaced with `{}` so both are counted together).

SugarTeX Completions for Atom:

- `_` \leftarrow `_`,
- `_` \leftarrow `_ \backslash rot`,
- `_` \leftarrow `_ \backslash rot2`,

- $\hat{}$ \leftarrow `\^`,
- $\hat{}^{\circ}$ \leftarrow `\^]\rot`,
- $\frac{}{}$ \leftarrow `\/`,
- $\sqrt{}$ \leftarrow `\^1/2`,
- $\|$ \leftarrow `\|`,
- $\|/2$ \leftarrow `\|/2`.

Regular expressions loop replacements

Nothing. But can be tweaked.

Regular expressions post-replacements

Nothing. But can be tweaked.

Simple post-replacements

- $\bar{}$ \rightarrow `\|` (broken bar U+00A6, this should be after other $\bar{}$ replacements),
- $\text{\textcircled{\scriptsize x}}$ \rightarrow `&` (modifier letter low ring U+02F3, this should be after brackets and other $\text{\textcircled{\scriptsize x}}$ replacements),
- \leftarrow \rightarrow `{` and \rightarrow \leftarrow `}` (modifier letter low left/right arrowhead U+02F1/U+02F2),
- $\text{\textcircled{\scriptsize x}}$ \rightarrow `_` (modifier letter low macron U+02CD),
- \updownarrow \rightarrow `\displaystyle` (up down arrow U+2195),
- $\text{\textcircled{\scriptsize x}}$ \rightarrow `\textstyle`,
- $\text{\textcircled{\scriptsize x}}$ \rightarrow `\scriptstyle`,
- $\text{\textcircled{\scriptsize x}}$ \rightarrow `\scriptscriptstyle`,

- Superscripts and Subscripts replacements give:
- $\updownarrow^d \rightarrow \backslash displaystyle,$
- $\updownarrow^t \rightarrow \backslash textstyle,$
- $\updownarrow^s \rightarrow \backslash scriptstyle,$
- $\updownarrow^{xs} \rightarrow \backslash scriptscriptstyle.$

SugarTeX Completions for Atom:

- $\mid \leftarrow \backslash,$
- $\mid \leftarrow \backslash /2,$
- $\cdot \leftarrow \backslash \&,$
- $\cdot \leftarrow \backslash _o \backslash small,$
- $\prec \leftarrow \backslash _< ,$
- $\succ \leftarrow \backslash _> ,$
- $\prec \succ \leftarrow \backslash _<> ,$
- $_ \leftarrow \backslash _ ,$
- $\updownarrow \leftarrow \backslash <-> \backslash rot.$

Escapable characters

All one-character replacements from:

- Prefix unary operators,
- Postfix unary operators,
- Center binary operators,
- Nullary operators,
- Simple pre-replacements,
- Simple post-replacements,

and $\in, \succ, \text{'}^{\circ}, \updownarrow, _$

(element of with long horizontal stroke U+22F2, single right-pointing angle quotation mark U+203A, modifier letter end high tone U+02FA, up down arrow U+2195, modifier letter low vertical line U+02CC)

are escapable with `\`.

Examples

$$\begin{aligned}\nabla \times [\vec{B}] - 1/c \partial[\vec{E}]/\partial t &= 4\pi/c [\vec{j}] \quad | \# \\ \nabla \cdot [\vec{E}] &= 4\pi\rho \quad | \\ \nabla \times [\vec{E}] + 1/c \partial[\vec{B}]/\partial t &= [\vec{0}] \quad | \\ \nabla \cdot [\vec{B}] &= 0 \quad >\end{aligned}$$

where $[\vec{B}], [\vec{E}], [\vec{j}]: \mathbb{R}^4 \rightarrow \mathbb{R}^3$ – vector functions of the form $(t, x, y, z) \mapsto [\vec{f}](t, x, y, z)$, $[\vec{f}] = (f_x, f_y, f_z)$.

renders to:

$$\begin{aligned} \nabla \times \mathbf{B} - \frac{1}{c} \frac{\partial \mathbf{E}}{\partial t} &= \frac{4\pi}{c} \mathbf{j} \\ \nabla \cdot \mathbf{E} &= 4\pi \rho \\ \nabla \times \mathbf{E} + \frac{1}{c} \frac{\partial \mathbf{B}}{\partial t} &= 0 \\ \nabla \cdot \mathbf{B} &= 0 \end{aligned} \quad , \quad (1)$$

where $\mathbf{B}, \mathbf{E}, \mathbf{j} : \mathbb{R}^4 \rightarrow \mathbb{R}^3$ – vector functions of the form $(t, x, y, z) \mapsto \mathbf{f}(t, x, y, z)$, $\mathbf{f} = (f_x, f_y, f_z)$

(you can see it in the [PDF version of this documentation](#)).

TODO

- Add examples to every section,
- Add more examples here at the end.

