

Program Analysis

Lecture 13: *Current Research Topics*
Winter term 2011/2012

Prof. Thorsten Holz

Anouncements

- Today's lecture ends at ~10am
 - Last exercise afterwards
- Exams on February 22
 - Prepare the exercises you had to solve during the semester and you should pass the exam
 - Bonus points will be announced via Moodle

Static vs. Dynamic Analysis I

- Static analysis
 - Code is not executed
 - All possible branches can be examined (in theory)
 - Requires lots of expert knowledge
- Problems of static analysis
 - Undecidable in general, approximations necessary
 - Disassembly difficult: obfuscated code + packers

Static vs. Dynamic Analysis II

- Dynamic analysis (*Anubis, CWSandbox, BitBlaze*)
 - Code is executed
 - Observe instructions that are actually executed
- Problems of dynamic analysis
 - Only a single path is examined (*multi-path execution*)
 - Analysis environment possibly not *invisible* (NDSS'10)
 - Analysis environment possibly not *comprehensive*

Motivation

- It might be useful to have full control over the analysis environment
- Virtualization is an interesting technique that might be helpful
- Program to be analyzed is executed in guest system
- Our instrumentation is performed in host system
- We have full control, we can even stop guest and perform arbitrary analysis



Anubis Overview

Systems Security
Ruhr-University Bochum



Anubis Overview

Systems Security
Ruhr-University Bochum

- We execute binary sample
 ➔ dynamic analysis



Anubis Overview

Systems Security
Ruhr-University Bochum

- We execute binary sample
 - ➔ dynamic analysis
- ... within an emulated environment ...
 - ➔ Emulation of a complete PC (CPU + hardware)
 - ➔ Qemu as emulator, uses Windows XP SP2



Anubis Overview

Systems Security
Ruhr-University Bochum


- We execute binary sample
 - ➔ dynamic analysis
- ... within an emulated environment ...
 - ➔ Emulation of a complete PC (CPU + hardware)
 - ➔ Qemu as emulator, uses Windows XP SP2
- ... and observe all activity
 - ➔ *System calls and Windows API calls*

Web Interface

- <http://anubis.iseclab.org>
- Enables **analysis** of **unknown binaries**
- Results via web browser or e-mail
- Analyzed several million binary samples
- Used by people around the world
- Exchange of information with AV vendors and security companies

Web Interface


Systems Security
Ruhr-University Bochum



Web Interface

- <http://anubis.iseclab.org>
- Enables **analysis** of **unknown binaries**
- Results via web browser or e-mail
- Analyzed several million binary samples
- Used by people around the world
- Exchange of information with AV vendors and security companies

Intuition



- *Virtual Machine Introspection*
- Programm analysis techniques
 - Taint analysis
 - Symbolic execution
 - *Program Slicing*
 - *Analysis of information flow*


Multi-Path Execution

```
0: int x;  
1: x = read_input();  
2: if (x > 0)  
3:     if (x < 2)  
4:         printf("ok");  
5: exit(0);
```

- We want to traverse all paths, find all conditions
- Iteratively explore the different paths
- Store execution state and reset state if necessary

Multi-Path Execution

```
0: int x;  
1: x = read_input();  
2: if (x > 0)  
3:   if (x < 2)  
4:     printf("ok");  
5: exit(0);
```




- We want to traverse all paths, find all conditions
- Iteratively explore the different paths
- Store execution state and reset state if necessary

Multi-Path Execution

Relative increase	Number of samples
0 % - 10 %	21
10 % - 50 %	71
50 % - 200 %	37
> 200 %	43

- Works with real-world malware samples
- Limitations
 - State explosion, especially for memory
 - Network state is lost on restore

Inspector Gadget



Inspector Gadget


- Malware analyst is typically interested in specific *algorithm* implemented by malware sample
- Domain generation algorithm of Conficker
- Binary update for bots
- Template download of spambots
- Can we automatically extract the algorithm?

Conficker

- *Conficker* algorithm to compute domains
 - *Which C&C domains will be used?*
 - Depends on current date, retrieved by issuing an HTTP request to external webserver

Conficker

- *Conficker* algorithm to compute domains
- Which C&C domains will be used?
- Depends on current date, retrieved by issuing an HTTP request to external webserver



Source: "KYE: Containing Conficker"
F. Leder, T. Werner

Motivation



Systems Security
Ruhr-University Bochum

Question:

Can we extract from a given binary sample a certain behavior in an automated and efficient way?




Input: binary executable




Output: extracted algorithm that can be executed in an autonomous way

Kolbitsch et al., IEEE S&P 2010

Overview



Overview




Evaluation

Sample	Gadget	# Instructions extracted ¹	# Functions extracted	# API function references	Contains dynamically unpacked code
Conficker	Domain Flux	385 (511)	8	23	<i>yes</i>
Pushdo	Binary Update	926 (1410)	15	19	<i>no</i>
Cutwail	Spam Template	2091 (3575)	51	19	<i>yes</i>
URLZone	Configuration	1036 (1430)	27	17	<i>yes</i>

- Works on real-world malware
- Automated extraction of specific algorithm
 - Analyst needs to specify what she is interested in
 - But we might not include all relevant code

Conficker



Source: Porras et al.: "A Foray into Conficker's Logic and Rendezvous Points", LEET'09

Conficker

Systems Security

Ruhr-University Bochum

ysodtmnq.org
ylkwa.org
fvgwbijrih.com
byhmvpzynvn.biz
lxggsrccct.info
igvnycyx.info
kdathezjp.com
rqeubkg.net
fcmremoo.org
ilcsea.com
eydxnhtqpoj.net
pocomecwapn.biz
aoxcuetqqm.com
jgxlrqkc.biz
yswtxkeo.biz
hcmem.biz
dcinu.net


fxgoswinvuc.com
mnxtest.info
gwfvi.org
btrgonoq.org
emohwqe.org
sppmfy.org
zhwpjb.org
iqgvjuaz.com
bnhvv.com
dicntiqhv.info
cnbdwljc.info
xqyeoncaooq.info
pplkxgcv.biz
yjjry.info
vejfoshm.net
uvnff.info
origmhqf.net

vealjox.com
hsxwcogs.biz
fjvddjusifj.org
lgpdk.net
tuqueszsnx.org
sflxwx.com
yqecdzyf.net
jyoacdcj.biz
cttqmf.com
iysfbrspiam.com
pscrdwugwa.com
yxvtwzw.com
bujykwamdgf.info
tddhmrbtno.net
jqwjdig.biz
...




Challenges

Original code

```
if (X == c) {  
      
}
```

Obfuscated code

```
if (Hash(X) == Hc) {  
    Decr(BE, X)  
      
}
```

Where, $H_c = \text{Hash}(c)$, $B_E = \text{Encr}(B, c)$

- Conditional code-obfuscation (Sharif et al., NDSS'08)
- Only observe behavior seen during execution
- Attacks against MPE, symbolic execution, and forced conditional execution

Challenges

- Virtual machine based packers
 - “virtual CPU” executes packed code
 - Impedes static and also dynamic analysis
 - Automatically cross-compile to x86?
- Analysis of kernel-based malware
 - Context not always clear
 - Tricky use of OS specific techniques

Summary

- Different approaches for automated analysis
 - Dynamic approaches help a lot
 - *Inspector Gadget* to automatically extract algorithms
 - Works with real-world malware, but still prototype
- Many open problems remain
 - Especially related to packers, kernel-level malware, ...

Questions?

Systems Security
Ruhr-University Bochum

Contact:

Prof. Thorsten Holz

thorsten.holz@rub.de

@thorstenholz on Twitter

More information:

<http://syssec.rub.de>

<http://moodle.rub.de>

