

1. Code in Mosaic

This example collects the supported ways to put code-like text in a Mosaic document. Inline code uses backticks, as in `cargo mos check` or `#set text(font: "Noto Sans")`.

Inline code can also span a soft source line break when a short phrase needs to stay visually code-shaped in the editor and output: `a sad student wrote this`.

1.1. Preformatted command transcripts

Use `#pre[[...]]` for terminal output, command transcripts, or other raw text where the content is not tied to a programming language.

```
$ cargo mos check examples/code/main.mos
$ cargo mos build examples/code/main.mos
Finished `dev` profile
```

1.2. Code blocks

Use `#code[[...]]` for code examples. Mosaic preserves the raw block text and renders it with the monospace face.

```
fn main() {
    println!("hello, mosaic");
}
```

Code blocks are raw long-bracket bodies. A plain `[[...]]` body can contain single closing brackets and backslash-bracket text literally. When the body needs `]]`, add matching equals signs to the delimiter.

```
let brackets = "open [ and escaped close \]";
let literal = "single ] and pair ]] are both fine";
let slash_close = "\\]";
println!("{brackets} {literal} {slash_close}");
```

1.3. Choosing a form

Use inline code for identifiers and small fragments such as `NodeKind::Raw`. Use `#pre[[...]]` for pasted terminal sessions. Use `#code[[...]]` for source snippets that should stand on their own.