

Sampling and anti-aliasing exercise

Kjartan Halvorsen


September 26, 2019

The Bessel filter

A second order Bessel filter

$$H(s) = \frac{3}{(s/\omega_0)^2 + 3(s/\omega_0) + 3},$$

has been designed to give attenuation of 0.1 at a desired Nyquist frequency, i.e. $|H(i\omega_N)| = 0.1$.



1. What is the bandwidth of the filter?
2. Determine the filter parameter ω_0 in terms of ω_N .
3. What is the phase shift at the Nyquist frequency?
4. Assume that the cross-over frequency of the loop gain is $\omega_c = 0.1\omega_N$. What is the phase shift at this frequency?
5. What delay T does this correspond to if the filter is approximated as a pure delay $H(i\omega) \approx e^{-i\omega T}$?
6. How large is the delay in terms of the sampling period $h = \frac{\pi}{\omega_N}$?

Choice of bandwidth of antialiasing filter

Table 7.3 The time delay T_d as a function of the desired attenuation at the Nyquist frequency for fourth- and sixth-order Bessel filters. The sampling period is denoted h .

β	Fourth Order		Sixth Order	
	ω_B/ω_N	T_d/h	ω_B/ω_N	T_d/h
0.001	0.1	5.6	0.2	4.8
0.01	0.2	3.2	0.3	3.1
0.05	0.3	2.1	0.4	2.3
0.1	0.4	1.7	0.4	2.0
0.2	0.5	1.4	0.5	1.7
0.5	0.7	0.9	0.7	1.2
0.7	1.0	0.7	1.0	0.9

The table can be used to find the delay in the feedback path caused by an antialiasing filter. For instance, if we want to have an attenuation at the Nyquist frequency equal to $\beta = 0.01$, then a fourth-order Bessel low-pass filter will give a delay of about $T_d = 3.2h$, that is a delay of more than 3 sampling periods.

1. What is the advantage of using an antialiasing filter of higher order than 2?
2. If we can only accept a time delay of maximum two sampling periods, what is the attenuation we can obtain at the Nyquist frequency?
3. If the bandwidth frequency of the antialiasing filter is chosen equal to the Nyquist frequency, $\omega_B = \omega_N$, then by definition of the bandwidth of a filter we have that the attenuation at ω_N is 0.7=-3dB. If the sampling period is 0.4 seconds. What is the time delay due to a sixth-order antialiasing filter?
4. What is the attenuation of a forth-order filter at $5\omega_B$

Discuss choice of sampling frequency and antialiasing filter

A continuous-time signal $f(t)$ with the Fourier transform $F(\omega)$ given below is to be sampled for the purpose of feedback control. It is known that the signal is corrupted by noise in the form of a sinusoid of frequency $5\omega_0$.

Discuss the choice of sampling frequency and antialiasing filter

Hints:

- There are two alternatives: With antialiasing filter, with no antialiasing filter, but digital low-pass filtering.
- When sampling, the frequencies are "folded" at the Nyquist frequency.

