

The Spectral Shortcut Theorem: A Gradient-Geometric Explanation for Failure Modes of Joint Spectral-Spatial Deep Learning

Krzysztof Dziuba
krzys.dziuba@gmail.com

August 18, 2026

Abstract

[TODO: Write abstract last, after Phase 7.]

1 Introduction

The integration of spectroscopic imaging with deep learning has produced a class of compositional models that has become the de facto standard across infrared tissue classification, hyperspectral remote sensing, Raman imaging, and mass spectrometry imaging. A canonical pipeline processes a hyperspectral input $X \in \mathbb{R}^{H \times W \times S}$ in two stages: a per-pixel spectral reduction $f_{\theta} : \mathbb{R}^S \rightarrow \mathbb{R}^K$ followed by a spatial model $g_{\phi} : \mathbb{R}^{K \times H \times W} \rightarrow \mathbb{R}^{N_{\text{cls}} \times H \times W}$. End-to-end joint training of this pipeline is overwhelmingly the default — adopted by foundational work in FTIR histology Berisha et al. [2019], recent state-of-the-art spatial-spectral ViTs for prostate tissue classification O’Leary et al. [2026], and essentially all hyperspectral remote sensing systems.

An empirical paradox. Despite the prevalence of this paradigm, an unexpected and persistent pattern has emerged across multiple subfields. Frozen pretrained spectral encoders dramatically outperform end-to-end joint training on held-out test data. In our motivating tissue classification setting, a learned-from-scratch linear f_{θ} trained end-to-end achieves 0.675 test F1; freezing a pretrained f_{θ} yields 0.84–0.95 test F1. Most strikingly, replacing f_{θ} with *frozen random weights* yields 0.70 test F1 — outperforming the joint trained model. Recent independent observations O’Leary et al. [2026], Berisha et al. [2019] have noted, in different terms, that aggressive spectral compression to 16 features has negligible impact on spatial-spectral neural network performance, and have concluded that “tissue classification only needs a small set of spectral features.”

We argue the opposite. The reason end-to-end joint training fails is not that spectral information is unimportant. It is that *end-to-end optimization fails to extract that information*, even when the spectral signal is rich and discriminative. The problem is in the training procedure, not the data.

This paper. We provide a rigorous explanation for the failure of joint spectral-spatial training, grounded in the geometry of the loss landscape and the dynamics of stochastic gradient descent on compositional architectures with asymmetric capacity. Two main theorems form our contribution.

- **Theorem 13 (Capacity-Induced Module Curvature Disparity).** We prove that the ratio of the spatial to the spectral Gauss-Newton block’s top eigenvalue grows linearly

with the spatial module’s width M (equivalently, as $\sqrt{C_g/C_f}$ for architecture families with $C_g = \Theta(M^2)$): as the spatial module widens, curvature concentrates in it while the spectral block’s curvature stays capped by a width-independent constant. The proof is elementary: an explicit witness direction in the classifier-head weights forces the width-linear growth, and an operator-norm bound caps the spectral block; the rate matches the mean-field law of Karakida et al. [2019] in the model class where the latter applies.

- **Theorem 27 (Finite-Time Spectral Starvation).** Under an explicit shortcut-fitting hypothesis compatible with cross-entropy dynamics, the spectral module’s displacement from initialization by the time the training residual reaches level δ is at most $\mathcal{O}(\varepsilon \log(1/\delta))$, where ε is the ratio of the (capped) spectral gradient scale to the shortcut fitting rate. As spatial capacity grows, the shortcut fits faster while the spectral gradient stays capped, so the spectral module is pinned near initialization for the entire useful duration of training. The formulation is finite-time by design: for unregularized cross-entropy on separable data no finite stationary point exists Soudry et al. [2018], and the starvation phenomenon is a training-time effect, not an asymptotic one.

A real-time diagnostic. The pathology described by Theorems 13 and 27 is invisible to standard loss curves — training and validation loss both decay smoothly while the spectral module is silently starved. To make the pathology observable in practice we introduce the *Effective Gradient Ratio* (EGR), a scalar diagnostic computable inside any training loop:

$$\text{EGR}(t) = \frac{\|\nabla_{\theta} \mathcal{L}(\theta_t, \phi_t)\|}{\|\nabla_{\phi} \mathcal{L}(\theta_t, \phi_t)\|}.$$

Proposition 28 establishes that the spectral gradient norm—the EGR’s numerator—decays polynomially while the loss is being fitted. Empirically, the depth of the EGR collapse scales monotonically with capacity ratio, providing a quantitative, training-time observable for gradient starvation.

Prescription. The theory yields a direct prescription: freeze the spectral module, or inject a fixed residual baseline. Freezing eliminates the timescale gap by removing θ from the optimization entirely. A residual baseline ($Z = f_{\theta}(X) + h(X)$ for a fixed h , e.g. PCA) is a softer intervention that breaks the shortcut without precluding spectral fine-tuning. We discuss both in Section 9.

Universality. Although our motivating application is infrared tissue classification, the mechanism we identify applies to any compositional architecture with capacity asymmetry between sequential modules. We verify in Section 7 that the same pattern manifests across linear, CNN, and Vision Transformer spatial models on synthetic hyperspectral problems, indicating the phenomenon is architecture-agnostic. We expect the same mechanism to govern frozen-encoder practices in Raman spectroscopy, mass spectrometry imaging, NIR analysis, and beyond.

Relation to prior work. The closest prior work is in multimodal learning, where Wang et al. [2020] and Peng et al. [2022] identified “modality competition” and proposed gradient blending and modulation interventions. Our setting is unimodal (a single hyperspectral input) but the mechanism is structurally analogous: the spatial and spectral subspaces of the input act as competing “modalities,” with the spatial module monopolizing the gradient budget. We discuss this connection further in Section 2.

Outline. Section 2 reviews related work. Section 3 establishes notation. Section 4 proves Theorem 13. Section 5 proves Theorem 27. Section 6 formalizes the EGR diagnostic. Section 7 validates both theorems and the diagnostic on synthetic spectral-spatial problems with linear, CNN, and ViT spatial models. Section 8 briefly connects the synthetic findings to real FTIR/QCL tissue classification data. Section 9 discusses prescriptions, limitations, and open problems.

2 Related Work

Our analysis sits at the intersection of four lines of research: the implicit bias and gradient dynamics of cross-entropy training; the geometry of deep-network loss surfaces; multimodal gradient competition; and spectral-spatial deep learning for biomedical and remote-sensing applications. We survey each in turn.

2.1 Gradient starvation and implicit bias

Cross-entropy minimization is known to induce structural biases in the learned representation. Soudry et al. [2018] proved that on linearly separable data, gradient descent on logistic loss converges to the maximum-margin classifier. Gunasekar et al. [2017] and Lyu and Li [2020] extended this picture to deep homogeneous networks. These results establish that gradient-based training selects *which* solution among many that fit the training data.

Pezeshki et al. [2021] identified a distinct phenomenon termed *gradient starvation*: in the Neural Tangent Kernel regime, dominant features in the input rapidly saturate the cross-entropy loss, after which weaker but task-relevant features receive negligible gradient signal. Our Theorem 27 adapts this framework to compositional architectures, where the “dominant features” are introduced not by the input distribution but by an architectural capacity asymmetry between modules. The result is a module-level starvation rather than a feature-level one.

2.2 Two-timescale stochastic approximation

The classical machinery for analyzing coupled gradient flows with disparate timescales is Borkar’s stochastic approximation framework [2008]. Heusel et al. [2017] adapted this to neural network training by introducing the Two Time-Scale Update Rule for GANs, proving convergence to a local Nash equilibrium under explicit step-size disparity. Our setting differs structurally: the timescale separation in our compositional model is not imposed by the optimizer (the same learning rate is applied to both modules) but emerges *implicitly* from the Hessian eigenvalue gap quantified by Theorem 13.

2.3 Hessian geometry of deep networks

The eigenspectrum of the neural-network Hessian has been characterized empirically and theoretically. Sagun et al. [2017] identified a bulk-plus-outliers structure for overparametrized networks. Pennington and Bahri [2017] developed a random matrix theory analysis that predicts spectral densities under Gaussian assumptions. Karakida et al. [2019] derived closed-form mean-field expressions for the leading eigenvalue of the Fisher Information Matrix, showing it scales linearly with the layer width. Theorem 13 works blockwise on the joint Gauss–Newton matrix of a compositional model: a width-linear lower bound on the spatial block’s top eigenvalue is combined with a width-independent operator-norm cap on the spectral block, yielding a width-scaling law for the module curvature disparity $\mathcal{D}_{\text{curv}}$.

2.4 Multimodal gradient competition

The phenomenon most structurally analogous to ours is gradient competition in multimodal learning. Wang, Tran, and Feiszli Wang et al. [2020] showed empirically that joint training of multimodal classification networks underperforms unimodal training because different modalities overfit and generalize at different rates. They proposed Gradient Blending to dynamically reweight modality-specific losses. Peng et al. [2022] identified “modality laziness” — a tendency for one modality to dominate training, leaving the other under-optimized — and proposed On-the-fly Gradient Modulation. These works are empirical; our contribution adapts and extends their framework to the unimodal *compositional* setting and provides a rigorous geometric foundation. The recent biomedical application of gradient blending to multimodal sarcoma prognosis Bozzo et al. [2024] confirms the mechanism operates in medical settings, but is restricted to explicit dual-modality (MRI + clinical) architectures, not the single-modality compositional pipelines we consider.

2.5 Spectral-spatial deep learning

Spectral-spatial deep learning has been an active area for over a decade, primarily in two communities: biomedical infrared spectroscopy and hyperspectral remote sensing. Berisha et al. [2019] established the benefit of combining spectral and spatial features for FTIR histology and observed that some tissue types could be classified from spatial features alone, with “minimal chemical information” required — a foreshadowing of the spatial shortcut phenomenon we diagnose. More recently, O’Leary et al. [2026] systematically compared spatial-spectral architectures for prostate cancer classification in infrared spectroscopy and reported the striking finding that compressing the spectral dimension to as few as 16 features had negligible effect on all models tested. The authors interpreted this as evidence that tissue classification requires only a limited spectral signature. Our Theorem 27 provides an alternative explanation: end-to-end training fails to extract the spectral signature even when it is present.

The conceptually nearest work in biomedical imaging is the recent characterization of shortcut learning in histopathology by Dawood and Minhas et al. [2026], who showed that AI models predicting molecular biomarkers from H&E images exploit spurious correlations with clinicopathological features rather than learning genuine biological signal. Our paper extends the shortcut-learning framework into a new modality (spectroscopic imaging) with a different mechanism (gradient competition driven by architectural asymmetry rather than confounder leakage).

2.6 Frozen and random features

Frozen random features have a long history in machine learning. Saxe et al. [2011] showed that convolutional networks with random (untrained) filters achieve competitive performance on standard benchmarks. Rahimi and Recht [2007] established the theoretical foundations of random features for kernel methods. More recently, Coil and Cheney [2025] showed that freezing layers acts as implicit regularization in overparametrized networks. These works establish that frozen random features are not an oddity but a principled choice. Our contribution is to identify the specific mechanism — gradient starvation under capacity asymmetry — under which freezing is not merely competitive but *strictly preferable* to joint training.

3 Setup and Preliminaries

We analyze a generic two-module compositional model. While our motivating application is infrared spectroscopic imaging for tissue classification, the framework applies to any pipeline

that first reduces a per-element spectral signal and then applies a high-capacity spatial model. We deliberately keep the notation domain-agnostic.

3.1 The compositional model

Let $X \in \mathbb{R}^{H \times W \times S}$ denote a hyperspectral input image, where H and W are spatial dimensions and S is the spectral dimension.¹ We write the per-pixel spectrum at location (h, w) as $x_{h,w} \in \mathbb{R}^S$.

The model consists of two modules applied sequentially:

1. A *spectral reduction* $f_\theta : \mathbb{R}^S \rightarrow \mathbb{R}^K$ applied independently to every pixel, producing a feature map $Z \in \mathbb{R}^{K \times H \times W}$ with $Z_{:,h,w} = f_\theta(x_{h,w})$.
2. A *spatial model* $g_\phi : \mathbb{R}^{K \times H \times W} \rightarrow \mathbb{R}^{N_{\text{cls}} \times H \times W}$ producing per-pixel class logits $\hat{y} = g_\phi(Z)$.

We denote the composed model $F_{\theta,\phi}(X) = g_\phi(f_\theta(X))$ and the parameter counts $C_f := \dim(\theta)$ and $C_g := \dim(\phi)$.

Assumption 1 (Linear spectral reduction). f_θ is linear in θ : there exists $W \in \mathbb{R}^{S \times K}$ with $\theta = \text{vec}(W)$ and $f_\theta(x_{h,w}) = W^\top x_{h,w}$.

Remark 2. Assumption 1 captures the canonical case used widely in spectroscopy pipelines, including the FTIR and QCL tissue classification work we draw motivation from. It is also the cleanest case in which the Hessian of $\mathcal{L}$ admits closed-form block analysis. We discuss extensions to shallow nonlinear f_θ in Section 9 and verify empirically in Section 7 that the theorem’s scaling persists when f_θ is replaced by a small MLP.

Assumption 3 (Spatial model regularity). g_ϕ is twice continuously differentiable in ϕ with L -Lipschitz gradients.

Assumption 4 (Sub-Gaussian inputs). Per-pixel inputs $\{x_{h,w}\}$ are sub-Gaussian with population second moment $\Sigma = \mathbb{E}[x_{h,w}x_{h,w}^\top]$ of bounded condition number. We write

$$\Sigma_X := \frac{1}{N} \sum_{n=1}^N x_n x_n^\top, \quad N := N_{\text{data}} H W, \quad (1)$$

for the corresponding *mean* empirical Gram over all pixels of all images (x_n enumerating the pixel spectra), so that $\lambda_{\max}(\Sigma_X) \rightarrow \lambda_{\max}(\Sigma) < \infty$ as $N \rightarrow \infty$. Every constant below is stated in terms of $\lambda_{\max}(\Sigma_X)$ and is therefore independent of the dataset size.

Assumption 5 (Capacity gap). $C_g/C_f \rightarrow \infty$.

Assumption 5 is not used in any proof: it is the structural regime in which our theorems become *informative* rather than merely true, and we state it to delimit scope. Empirically it is satisfied with room to spare in modern spectral-spatial architectures (in our motivating example, $C_g/C_f \approx 325$).

Assumption 6 (Bounded input Jacobian of the classifier). There exists a constant $\tilde{L} > 0$ depending on the depth of g_ϕ , the bottleneck dimension K , the number of classes N_{cls} , and the data distribution — but *not* on the characteristic width M or the total spatial parameter count C_g — such that

$$\sup_{\phi \in \Phi_{\text{reg}}, Z \in \mathcal{Z}_{\text{reg}}} \left\| \frac{\partial g_\phi(Z)}{\partial Z} \right\|_{\text{op}} \leq \tilde{L},$$

uniformly over the training-time parameter regime Φ_{reg} and the induced feature domain $\mathcal{Z}_{\text{reg}}$.

¹Multi-channel inputs (e.g. raw absorbance together with first and second derivatives) are handled by concatenating channels along the spectral dimension; this changes only the input size and leaves the analysis unaffected.

Remark 7 (Why Assumption 6 is separate from Assumption 3). Assumption 3 bounds the second derivatives of g_ϕ with respect to *parameters* ϕ (the standard L -smoothness condition of the optimization literature). Assumption 6 bounds the first derivative with respect to *input features* Z —a different object with a different constant. Parameter-side smoothness does not imply input-side Lipschitzness; we require both.

At random Kaiming/Xavier initialization, the operator norm of a variance-scaled random weight matrix is $\Theta(1)$ in width M by the Bai–Yin law Bai and Yin [1993] (see also Vershynin Vershynin [2018], Thm. 4.4.5; Marchenko–Pastur Marčenko and Pastur [1967] describes the corresponding bulk spectrum), giving $\|\partial g_\phi / \partial Z\|_{\text{op}} = \Theta(1)$ in width M for standard CNN and MLP blocks. Under the maximal-update parameterization (μ P) of Yang and Hu Yang and Hu [2021], the bound persists throughout training as $M \rightarrow \infty$. Under standard-parameterization training with weight decay $\lambda > 0$ and bounded-norm iterates, Assumption 6 follows from the boundedness of $\|\phi\|$ combined with the per-layer product-of-operator-norms bound; the constant $\tilde{L}$ depends multiplicatively on the depth L but not on the width. Softmax self-attention is Lipschitz only on bounded inputs Kim et al. [2021], so $\mathcal{Z}_{\text{reg}}$ should be taken compact whenever g_ϕ uses attention—this is guaranteed by LayerNorm before attention, which is standard practice.

3.2 Loss and gradients

We train with per-pixel cross-entropy, averaged over all N pixel positions of the dataset:

$$\mathcal{L}(\theta, \phi) = \frac{1}{N} \sum_{n=1}^N \text{CE}(\hat{y}_n, y_n), \quad \hat{y}_n = F_{\theta, \phi}(X)_n, \quad (2)$$

where $y_n \in \{1, \dots, N_{\text{cls}}\}$ is the ground-truth class. Cross-entropy plays an essential role in Section 5: its gradient with respect to the logits $\hat{y}$ is the prediction residual $r_n = \text{softmax}(\hat{y}_n) - y_{n, \text{onehot}}$, which vanishes exponentially in the logit margin as predictions saturate—and hence, on separable data, polynomially in training time (Section 5). We discuss other loss functions sharing this vanishing-residual property in Section 9.

Normalization convention. Consistently with (2), we collect the per-pixel quantities into N -normalized stacked objects: the residual vector $r := N^{-1/2}(r_1, \dots, r_N)$, so that $\|r\|$ is the root-mean-square per-pixel residual, and the *logit Jacobian*

$$J_\bullet := N^{-1/2} \frac{\partial(\hat{y}_1, \dots, \hat{y}_N)}{\partial \bullet}, \quad \bullet \in \{\theta, \phi\}, \quad (3)$$

so that $\nabla_\bullet \mathcal{L} = J_\bullet^\top r$ exactly. Two Jacobian-like objects appear in the literature and we fix both here: $J_\bullet$ above (logit Jacobian), and the *residual Jacobian* $J_\bullet^{\text{res}} := \partial r / \partial \bullet = H_\tau J_\bullet$, where $H_\tau := \text{diag}(p) - pp^\top$ is the softmax Jacobian (blockwise over pixels). Since $0 \preceq H_\tau \preceq I$, any operator-norm bound on $J_\bullet$ applies a fortiori to $J_\bullet^{\text{res}}$. The intermediate factor $\partial Z / \partial \theta$ carries the same $N^{-1/2}$ stacking, so that the chain rule composes as $J_\theta = (\partial \hat{y} / \partial Z) \cdot (\partial Z / \partial \theta)$ with the unnormalized middle factor — which is the object Assumption 6 bounds. All Gram matrices, and Σ_X in (1), use this same $1/N$ normalization, so no constant in this paper depends on the dataset size.

The gradient of $\mathcal{L}$ with respect to the spatial parameters is computed by standard back-propagation. The gradient with respect to the spectral parameters θ admits the chain-rule decomposition

$$\nabla_\theta \mathcal{L} = \underbrace{r}_{\text{residual}} \cdot \underbrace{\frac{\partial \hat{y}}{\partial Z}}_{\text{spatial Jacobian}} \cdot \underbrace{\frac{\partial Z}{\partial \theta}}_{\text{input}} = J_\theta^\top r, \quad (4)$$

with all three factors in the normalization fixed above (the per-pixel loss gradients $\partial \mathcal{L} / \partial \hat{y}_n = r_n / N$ are absorbed into the $N^{-1/2}$ -scaled r and $\partial Z / \partial \theta$). The softmax enters through the residual

itself; the matrix H_τ appears explicitly only when differentiating r , as in J^{res} above and in the Gauss-Newton blocks below. The three factors play distinct roles in our analysis. The residual is small when predictions are confident. The spatial Jacobian depends on the current state of ϕ and thus changes throughout training. The final factor is the input itself and is stationary. The product structure implies that if the residual decays to zero, the gradient to θ vanishes regardless of the other two factors. This observation underlies Theorem 27.

Remark 8 (How much of this depends on cross-entropy?). The two theorems depend on the loss to different degrees. Theorem 13 is essentially loss-agnostic: the softmax Jacobian H_τ enters its proof only through the two-sided bound $c_p P_\perp \preceq H_\tau \preceq I$, which contributes constants and no M -dependence. Under squared error the inner matrix is the identity and the argument simplifies, giving the same width-linear disparity. Theorem 27 is more loss-specific: the polynomial residual envelope of Assumption 24 is the characteristic behavior of logistic-type losses on separable data (Soudry et al. [2018]), whereas squared error on a well-conditioned target admits a faster (exponential) envelope. As noted after Assumption 24, a faster envelope only tightens the displacement bound; the mechanism—a fast module driving the residual down and starving a slow one through the shared factor—is not specific to cross-entropy, though the $\log(1/\delta)$ rate is.

3.3 The block Hessian

The joint Hessian of $\mathcal{L}$ decomposes into blocks aligned with the two parameter groups:

$$H = \nabla^2 \mathcal{L}(\theta, \phi) = \begin{pmatrix} H_{\theta\theta} & H_{\theta\phi} \\ H_{\phi\theta} & H_{\phi\phi} \end{pmatrix}, \quad (5)$$

with $H_{\theta\theta} \in \mathbb{R}^{C_f \times C_f}$, $H_{\phi\phi} \in \mathbb{R}^{C_g \times C_g}$, and cross blocks of appropriate sizes. Theorem 13 bounds the *ratio* of the two diagonal blocks’ top eigenvalues (Definition 11) in terms of the spatial width, by bounding each block separately—not the condition number of H , which is a different and, here, degenerate quantity (Remark 12).

For curvature analysis we work with the generalized Gauss-Newton matrix, which for softmax cross-entropy is

$$G = J^\top H_\tau J, \quad J = [J_\theta, J_\phi], \quad (6)$$

with J the (N -normalized) logit Jacobian of (3) and H_τ the softmax Jacobian (Botev et al. [2017]). G is the positive semidefinite part of H that survives at interpolation, and $H = G$ exactly when the residual vanishes. Theorem 13 is stated for the diagonal blocks $G_{\theta\theta} = J_\theta^\top H_\tau J_\theta$ and $G_{\phi\phi} = J_\phi^\top H_\tau J_\phi$. The residual-Gram variant $J^{\text{res}\top} J^{\text{res}} = J^\top H_\tau^2 J$ obeys the same bounds in both directions (upper: $H_\tau^2 \preceq I$; lower: supplement Section A.1), so the results are insensitive to which convention a reader prefers.

3.4 The Effective Gradient Ratio

We introduce a real-time diagnostic that tracks the asymmetry in gradient flow between the two modules.

Definition 9 (Effective Gradient Ratio). At training step t with parameters (θ_t, ϕ_t) , the Effective Gradient Ratio is

$$\text{EGR}(t) := \frac{\|\nabla_{\theta} \mathcal{L}(\theta_t, \phi_t)\|}{\|\nabla_{\phi} \mathcal{L}(\theta_t, \phi_t)\|}.$$

Remark 10. EGR is a unitless quantity directly computable inside any training loop with negligible overhead. Section 6 bounds the decay of its numerator—the spectral gradient norm—by $C/(1 + \mu t)$ as a consequence of Theorem 27, characterizes the ratio’s trajectory empirically, and proposes a threshold criterion for detecting gradient starvation onset.

3.5 Notational conventions

Throughout, $\|\cdot\|$ denotes the Euclidean (ℓ_2) norm for vectors and the spectral norm for matrices; $\lambda_{\max}(\cdot)$ and $\lambda_{\min}(\cdot)$ denote the largest and smallest eigenvalues of a symmetric matrix; $\kappa(A) = \lambda_{\max}(A)/\lambda_{\min}(A)$ its condition number. We write $A \succeq B$ to mean $A - B$ is positive semidefinite. The symbol $\Omega(\cdot)$ is used in the standard asymptotic sense.

Definition 11 (Module curvature disparity). For the Gauss-Newton matrix G of (6) with diagonal blocks $G_{\phi\phi}, G_{\theta\theta}$ indexed as in (5), the *module curvature disparity* is

$$\mathcal{D}_{\text{curv}}(G) := \frac{\lambda_{\max}(G_{\phi\phi})}{\lambda_{\max}(G_{\theta\theta})},$$

the ratio of the spatial block’s top eigenvalue to the spectral block’s. Unless stated otherwise, $\mathcal{D}_{\text{curv}}$ is evaluated at random initialization (θ_0, ϕ_0) , which is where Theorem 13 bounds it and where Experiment 1.1 measures it.

Remark 12 (Why disparity, not condition number). Theorem 13 is a purely geometric statement about how curvature concentrates between the two modules as the spatial network widens. It is not a joint-Hessian condition-number bound: the joint Gauss-Newton G is rank-deficient (parameter directions orthogonal to the classifier’s range have exactly zero curvature), so $\kappa(G) = \lambda_{\max}(G)/\lambda_{\min}(G)$ is trivially infinite. The disparity $\mathcal{D}_{\text{curv}}$ is well-defined regardless of rank structure, uses only well-behaved operator-norm quantities, and is exactly the ratio measured in Experiment 1.1. Its growth with spatial capacity is the geometric mechanism that motivates the two-timescale dynamical analysis of Theorem 27, but the dynamical claim requires its own hypotheses and does not follow from $\mathcal{D}_{\text{curv}}$ alone.

4 Theorem 1: Capacity-Induced Module Curvature Disparity

This section establishes our first main result: the module curvature disparity $\mathcal{D}_{\text{curv}}$ (Definition 11) grows with the spatial module’s width. The result is the geometric foundation for the dynamical analysis of Section 5: it identifies a capacity-dependent mechanism capable of generating disparate module learning rates. The dynamical starvation claim itself is stated separately in Theorem 27, under its own explicit hypotheses.

4.1 Main result

Theorem 13 (Capacity-Induced Module Curvature Disparity). *Consider the compositional model $F_{\theta,\phi} = g_{\phi} \circ f_{\theta}$ with fixed-dimensional linear spectral module f_{θ} (Assumption 1) and a family of spatial networks $g_{\phi}^{(M)}$ indexed by characteristic width M (channels for a CNN, embedding dimension for a ViT, hidden width for an MLP). Under Assumptions 1, 3, 4, and 6, together with the head hypothesis of Lemma 15 below (a dense classifier head over penultimate features of dimension $\Theta(M)$ that are correlated across inputs at initialization), there exist constants $c_1, c_2 > 0$ depending on the data distribution, the initialization scheme, the bottleneck dimension K , the input spectral dimension S , and the architecture class of g_{ϕ} (depth, activation, head dimensions)—but not on M or on the spatial parameter count C_g —such that*

$$\mathcal{D}_{\text{curv}}^{(M)} = \frac{\lambda_{\max}(G_{\phi\phi}^{(M)})}{\lambda_{\max}(G_{\theta\theta})} \geq c_1 \cdot M - c_2$$

in expectation over random Kaiming (variance-scaled Gaussian) initialization. Equivalently, for architecture families with $C_g = \Theta(M^2)$,

$$\mathcal{D}_{\text{curv}}^{(M)} \geq c'_1 \cdot \sqrt{C_g/C_f} - c_2.$$

Remark 14 (Interpretation). Theorem 13 states that as the spatial network widens, its top Gauss-Newton eigenvalue grows without bound while the spectral module’s top Gauss-Newton eigenvalue remains capped by a C_g -independent constant. Curvature increasingly concentrates in the downstream module. This is a purely geometric fact about the Hessian; the dynamical consequence—that joint training pins θ near its initialization—is stated separately in Theorem 27, under its own hypotheses.

The proof decomposes the disparity bound into separate bounds on the top eigenvalues of the two diagonal blocks. We state the supporting lemmas before presenting the proof.

4.2 Supporting lemmas

Lemma 15 (Spatial block scaling). *Let M denote the characteristic width of g_ϕ (channel count for a CNN, embedding dimension for a ViT, hidden layer width for an MLP), let $N_{cls} \geq 2$, and suppose g_ϕ ends in a dense classifier head over penultimate features $h_n \in \mathbb{R}^{M_h}$ with $M_h = \Theta(M)$ whose softmax-weighted mean Gram $S_h^p := N^{-1} \sum_n p_{\min}^{(n)} h_n h_n^\top$ (Equation (11)) satisfies*

$$\lambda_{\max}(S_h^p) \geq q_h M_h \quad \text{with probability} \geq 1 - \delta_h$$

over the random initialization, for constants $q_h > 0$ and $\delta_h < 1$ independent of M (the head hypothesis: the features carry a common direction of $\Theta(M)$ energy across inputs, on pixels whose initial predictions are non-degenerate. It is a cross-input correlation condition, not a per-vector norm condition, and is closely related to the quantity κ_2 carrying the width-linear term in Karakida et al.’s law—see the supplement). Then, under Assumptions 3–4, the spatial Gauss-Newton block of (6) satisfies

$$\lambda_{\max}(G_{\phi\phi}) = \Omega(M) \quad \begin{array}{l} \text{in expectation over random} \\ \text{Kaiming (variance-scaled} \\ \text{Gaussian) initialization,} \end{array}$$

and the same holds for the logit Gram $J_\phi^\top J_\phi$ and the residual Gram $J_\phi^{\text{res}\top} J_\phi^{\text{res}}$. For architecture families with $C_g = \Theta(M^2)$ (fixed depth with at least two consecutive width-proportional layers), equivalently $\lambda_{\max}(G_{\phi\phi}) = \Omega(\sqrt{C_g})$.

Remark 16. Lemma 15 is proved in the supplement (Section A.1) by an explicit witness: the rank-one head-weight perturbation $V = c u^\top$, where c is a unit class contrast and u the dominant direction of the feature ensemble. Evaluating the curvature along V gives the deterministic inequality $\lambda_{\max}(G_{\phi\phi}) \geq \lambda_{\max}(S_h^p)$, and the head hypothesis supplies $\lambda_{\max}(S_h^p) = \Omega(M)$. The width-linear law agrees with the mean-field analysis of Karakida et al. [2019]: their Theorem 4 gives $\lambda_{\max} = \Theta(M)$ with sharp constant for proportional-width fully connected networks under squared loss, and their Theorem 1 shows the mean eigenvalue simultaneously shrinks as $\mathcal{O}(1/M)$ —curvature concentrates in a vanishing fraction of directions as networks widen. The scaling variable is width, not parameter count: for architecture families with $C_g = \Theta(M^2)$, the equivalent parameter-count statement is $\lambda_{\max} = \Omega(\sqrt{C_g})$. The head hypothesis covers per-pixel dense heads on CNN and ViT modules as well; the sharpness of the width-linear rate is tested empirically in Section 7.

Lemma 17 (Eigenvalue interlacing for block matrices). *For any symmetric block matrix $M = \begin{pmatrix} A & B \\ B^\top & D \end{pmatrix}$ with principal blocks A and D ,*

$$\lambda_{\max}(M) \geq \max\{\lambda_{\max}(A), \lambda_{\max}(D)\}.$$

Remark 18. Lemma 17 is a standard consequence of Cauchy’s interlacing theorem applied to principal submatrices (see e.g. Bhatia Bhatia [1997], Corollary III.1.5).

Lemma 19 (Spectral block operator-norm cap). *Under Assumptions 1 (linear per-pixel f_θ), 4 (bounded input second moment), and 6 (bounded input Jacobian $\|\partial g_\phi/\partial Z\|_{\text{op}} \leq \tilde{L}$ uniformly in C_g), the spectral logit Jacobian and Gauss-Newton block satisfy*

$$\lambda_{\max}(G_{\theta\theta}) \leq \|J_\theta\|_{\text{op}}^2 \leq \tilde{L}^2 \cdot \lambda_{\max}(\Sigma_X) =: C_\theta,$$

where C_θ depends only on the classifier’s input Lipschitz constant $\tilde{L}$ and the top eigenvalue of the mean per-pixel input Gram Σ_X of (1)—not on the spatial width M , the spatial parameter count C_g , or the dataset size N . The same bound holds for the residual-Gram convention, since $H_\tau^2 \preceq H_\tau \preceq I$.

Remark 20. Lemma 19 follows from the chain-rule identity $J_\theta = J_Z \cdot (\partial Z/\partial \theta)$ for the logit Jacobian, combined with $\|J_Z\|_{\text{op}} \leq \tilde{L}$ (Assumption 6) and the exact form of $\partial Z/\partial \theta$ under linearity of f_θ (Assumption 1, giving the per-pixel factor $I_K \otimes x_n^\top$, whose N -normalized stacking has $\|\partial Z/\partial \theta\|_{\text{op}}^2 = \lambda_{\max}(\Sigma_X)$ exactly, by $I_K \otimes \Sigma_X$). Passing from the logit Jacobian to the Gauss-Newton block or the residual Jacobian only inserts factors of $H_\tau \preceq I$ and can only decrease the bound. The bound is on the operator norm (equivalently, the top eigenvalue), which is well-behaved under rank-deficiency of the block—avoiding the smallest-eigenvalue and Kronecker-factorisation machinery discussed in Section A.1.

4.3 Proof of Theorem 13

Proof of Theorem 13. By Lemma 15, in expectation over random Kaiming (variance-scaled Gaussian) initialization,

$$\lambda_{\max}(G_{\phi\phi}^{(M)}) \geq c_\phi \cdot M$$

for a constant $c_\phi > 0$ independent of M (depending on the initialization scheme, the activation, the head dimensions, and the data distribution; supplement Section A.1). By Lemma 19,

$$\lambda_{\max}(G_{\theta\theta}) \leq \|J_\theta\|_{\text{op}}^2 \leq C_\theta$$

for a constant $C_\theta > 0$ independent of M . Dividing,

$$\mathcal{D}_{\text{curv}}^{(M)} = \frac{\lambda_{\max}(G_{\phi\phi}^{(M)})}{\lambda_{\max}(G_{\theta\theta})} \geq \frac{c_\phi \cdot M}{C_\theta} = c_1 \cdot M$$

with $c_1 := c_\phi/C_\theta$. A constant $c_2 \geq 0$ absorbs finite-width corrections. Under $C_g = \Theta(M^2)$ (families with at least two consecutive width-proportional layers), $M = \Theta(\sqrt{C_g})$ and the ratio form $c'_1 \cdot \sqrt{C_g/C_f}$ follows on multiplying and dividing by $\sqrt{C_f}$. This completes the proof. $\square$

4.4 Implications

Theorem 13 establishes that curvature concentrates in the downstream spatial module as its width grows. We highlight two implications, and separate them explicitly from the dynamical consequences of Section 5.

Geometric mechanism, not a dynamical claim. $\mathcal{D}_{\text{curv}} \gg 1$ identifies a *potential* for disparate module learning rates: the spatial Gauss-Newton block admits directions of arbitrarily large curvature while the spectral block does not. Whether joint gradient descent actually produces disparate effective learning rates depends on additional dynamical hypotheses (e.g., that the spatial module converges quickly on the fast manifold), which we introduce and verify in Section 5. Theorem 13 does not, by itself, prove that θ is pinned to initialization.

No remedy from optimizer tuning of the shared learning rate. The disparity bound depends only on architectural parameters, not on the choice of optimizer or the shared step-size schedule. Adaptive methods (Adam, RMSProp) rescale per-coordinate gradient magnitudes but do not alter the underlying eigenvalue disparity between the two blocks. Two-timescale optimizers with explicitly different learning rates per module (Heusel et al. [2017]; Borkar 2008 Borkar [2008] Ch. 6) are the natural remedy at the optimizer level. We discuss this in Section 9.

4.5 Relation to classical ill-conditioning

Ill-conditioned optimization has classical causes with classical remedies, and it is natural to ask whether they apply here. They do not, because the disparity of Theorem 13 is driven by the *architecture*, not by the data or the parametrization of a single block.

Feature normalization. Scale asymmetry or collinearity among input features degrades the conditioning of Σ_X and is cured by standardizing inputs. Assumption 4 already grants this cure: we assume $\kappa(\Sigma_X)$ bounded, i.e. well-conditioned (e.g. normalized) inputs. The disparity persists regardless, because its growth is driven by the width-scaling of the spatial block (Lemma 15), which is untouched by any transformation of the input features.

Weight decay. Adding $\alpha \|w\|^2$ to the loss shifts the Hessian by αI , lifting every eigenvalue by α and famously repairing classical condition numbers. But the shift acts on *both* blocks equally: the disparity becomes $(\lambda_{\max}(G_{\phi\phi}) + \alpha) / (\lambda_{\max}(G_{\theta\theta}) + \alpha)$, which remains $\Theta(M)$ for any fixed α as M grows. Repairing the disparity would require $\alpha \sim \lambda_{\max}(G_{\phi\phi})$, a regularization strength that would dominate the data term and prevent fitting. Consistent with this, Experiment 1.6 finds that Pezeshki’s Spectral Decoupling—an L_2 penalty on logits designed to combat saturation—does not reduce the joint-training collapse, while freezing does.

Adaptive optimizers. Adam and RMSProp precondition per-coordinate gradient magnitudes with a diagonal rescaling. A diagonal preconditioner can equalize per-parameter step sizes but does not restructure the eigenvalue disparity between the two blocks, which is a statement about the blocks’ spectra rather than their diagonals. Empirically, the canonical dynamics experiment (Experiment 1.2) is run under Adam and the joint-vs-frozen gap persists at every width; we treat the stronger claim—that no shared-learning-rate adaptive method can remove the pathology—as a conjecture rather than a theorem. Optimizers with explicitly different learning rates per module (two-timescale update rules; Heusel et al. [2017]) are the natural remedy at the optimizer level and correspond, in the limit, to our freezing prescription.

Remark 21 (Small eigenvalues: irrelevance vs. starvation). A parameter direction can carry vanishing curvature for two very different reasons: (a) the direction genuinely does not affect predictions on the task at hand (“irrelevance”), in which case zero gradient is the correct outcome and the parameter should not be learned; or (b) the direction *would* affect predictions if the optimizer could reach it, but the compositional geometry buries the gradient signal behind the bottleneck (“starvation”). The Gauss-Newton bounds of Theorem 13 alone cannot distinguish between these interpretations: both produce C_g -independent small curvature in the spectral block.

The synthetic experiments in Section 7 are designed to distinguish these hypotheses by construction. In Experiment 1.3 we generate data where each of the two modalities alone carries information sufficient to solve the task (single-modality baselines reach ≈ 0.53 on a binary classification, above the 0.50 chance floor). Joint training on the same data does not merely under-use the spectral channel: it undershoots the weaker of the two single-modality baselines.

The gap is modest in absolute terms on this synthetic problem—an important honest caveat—but its direction is inconsistent with interpretation (a), under which joint training would at worst match the stronger single-modality baseline.

For real spectroscopic data, distinguishing (a) from (b) requires demonstrating that a frozen pretrained spectral encoder outperforms one that has been jointly trained end-to-end on the same task. We report such experiments on FTIR and QCL tissue classification in Section 8. Our present study compares only two concrete mitigation strategies (freezing the spectral module, and Pezeshki’s Spectral Decoupling Pezeshki et al. [2021]); broader comparisons against modality-specific learning rates, gradient surgery, GradNorm-style loss balancing, and related interventions are important future work.

4.6 Empirical support

Experiment 1.1 in Section 7 measures $\mathcal{D}_{\text{curv}}^{(M)}$ directly across a range of spatial widths and confirms monotonic growth with M : the spatial top eigenvalue grows $74\times$ over the sweep while the spectral top eigenvalue stays flat, driving the disparity into the thousands. The measured log-log slope of λ_ϕ against C_g is 0.70 ± 0.05 , below the slope-1.0 prediction that applies to the tested architecture family (whose $C_g = \Theta(M)$); the deficit and its candidate causes are reported in Section 7. The qualitative prediction—unbounded spatial-block growth against a capped spectral block—is unambiguous in the data.

Remark 22 (Defense against linear triviality). A natural objection is that, since f_θ is linear, the analysis must reduce to principal component analysis (PCA) of the input. This is not the case. PCA finds directions of maximum input variance *without reference to labels*. Theorem 13 concerns the curvature of the supervised cross-entropy loss, which depends on the current state of g_ϕ through the Jacobian $\partial\hat{y}/\partial Z$. The pathology we identify is precisely that this supervised signal fails to reach θ , not that f_θ is incapable of representing useful features.

5 Theorem 2: Finite-Time Spectral Starvation

Theorem 13 is a geometric statement: as the spatial module widens, curvature concentrates in it and the spectral block’s top curvature stays capped. This section states the dynamical consequence we actually observe in training—the spectral module barely moves during the period in which the training loss is being fit—as a theorem with *explicit dynamical hypotheses*. We deliberately do not claim that the geometry of Theorem 13 alone implies the dynamics: the bridge from curvature disparity to rate separation is stated as a hypothesis, motivated by Theorem 13 and verified empirically in Section 7. Deriving it from the architecture is left as an open problem (Section 9).

Two classical facts shape the formulation. First, for unregularized cross-entropy on separable data there is *no finite minimizer*: the loss decays like $1/t$ while the parameters diverge along the max-margin direction (Soudry et al. Soudry et al. [2018]). A theorem asserting convergence to a finite stationary point would therefore be vacuous or false in the regime modern networks inhabit. Second, the starvation phenomenon of Pezeshki et al. Pezeshki et al. [2021] is fundamentally about which features receive learning signal *during training*, not about the $t \rightarrow \infty$ limit. Both point the same way: the honest statement is a *finite-time* bound on how far the spectral parameters can move before the shortcut pathway has fitted the labels.

5.1 Setting and hypotheses

We analyze the continuous-time limit of joint training with a shared learning rate, in which the parameters (θ_t, ϕ_t) evolve by gradient flow

$$\dot{\theta}(t) = -\nabla_{\theta}\mathcal{L}(\theta, \phi), \quad \dot{\phi}(t) = -\nabla_{\phi}\mathcal{L}(\theta, \phi). \quad (7)$$

The discrete-SGD extension (Robbins–Monro tracking with noise entering the constants) is standard (Borkar Borkar [2008], Ch. 2) and discussed in the supplement.

Recall from the chain rule (4) that $\nabla_{\theta}\mathcal{L} = J_{\theta}^{\top}r$ where r is the softmax residual, so

$$\|\dot{\theta}(t)\| = \|J_{\theta}(t)^{\top}r(t)\| \leq \|J_{\theta}(t)\|_{\text{op}} \cdot \|r(t)\|. \quad (8)$$

Fix a horizon $T > 0$ and suppose the trajectory remains in the regime of Assumption 6, i.e. $\phi(t) \in \Phi_{\text{reg}}$ and $Z(t) \in \mathcal{Z}_{\text{reg}}$ for all $t \leq T$ (*trajectory containment*). Under Assumptions 1, 4, and 6, Lemma 19 then caps the first factor over that horizon:

$$B_T := \sup_{t \leq T} \|J_{\theta}(t)\|_{\text{op}} \leq \sqrt{C_{\theta}} = \tilde{L} \sqrt{\lambda_{\max}(\Sigma_X)}, \quad (9)$$

a constant independent of the spatial width M , the parameter count C_g , and the horizon T . (Even without containment, $B_T < \infty$ for every finite T by continuity of J_{θ} along the flow; containment is what makes the cap *M-independent*, which is the load-bearing property.) We write B for B_T when the horizon is clear. The remaining hypothesis concerns the second factor.

Remark 23 (Containment and the unregularized separable regime). Trajectory containment is a genuine restriction. In the unregularized separable regime that motivates the polynomial envelope below, $\|\phi(t)\| \rightarrow \infty$ logarithmically (Soudry et al. Soudry et al. [2018]), so a bound on $\|\partial g_{\phi}/\partial Z\|_{\text{op}}$ that is uniform over *all* t cannot be assumed. Two standard settings restore it: weight decay or norm constraints (bounded iterates), and the maximal-update parameterization Yang and Hu [2021] (bound uniform in width). In the pure max-margin limit, $\tilde{L}$ grows at most logarithmically in T , which turns the displacement bound of Theorem 27 into $\mathcal{O}(\varepsilon \log^2(1/\delta))$ —the same conclusion up to a log factor.

Assumption 24 (Shortcut residual decay). There exist constants $C \geq 1$ and $\mu > 0$ such that, along the joint trajectory (7),

$$\|r(t)\| \leq \frac{C}{1 + \mu t},$$

where $\|r(t)\|$ is the root-mean-square per-pixel residual of (3). We refer to μ as the *shortcut fitting rate*. The constants C and μ may depend on the initialization, the data, and the architecture—in particular μ is expected to grow with spatial capacity (Remark 25)—and are not assumed uniform over any family; the theorem holds for any trajectory admitting such an envelope.

Remark 25 (Why polynomial, and where μ comes from). The $1/t$ envelope is the correct cross-entropy-compatible form: for logistic-type losses on separable data the training loss—and hence the residual norm—decays polynomially, not exponentially (Soudry et al. Soudry et al. [2018]). An exponential envelope, where valid (e.g. regularized or non-separable regimes), only strengthens the conclusion below. The hypothesis encodes the *shortcut* mechanism: the residual is driven down by the spatial module exploiting whatever signal is present in the feature map Z (positional and contextual structure), without requiring f_{θ} to specialize—the spatial-signal sufficiency discussed in Section 5.4. The rate μ is expected to *grow* with spatial capacity: wider networks fit faster (in the NTK regime, the fitting rate is governed by the spatial kernel’s smallest relevant eigenvalue, which grows with width; see Pezeshki et al. Pezeshki et al. [2021]). We verify this empirically in Experiment 1.2, where time-to-fit shrinks monotonically with D . A derivation of $\mu(C_g)$ for the linearized fast subsystem is given informal treatment in the supplement and is not needed for the theorem, which takes μ as given.

Definition 26 (Fitting time). For a target residual level $\delta \in (0, C)$, the fitting time is

$$T_{\delta} := \inf\{t \geq 0 : \|r(t)\| \leq \delta\}.$$

Under Assumption 24, $T_{\delta} \leq (C/\delta - 1)/\mu$.

5.2 Main result

Theorem 27 (Finite-Time Spectral Starvation). *Fix a horizon $T \geq 0$ and suppose the gradient flow (7) is contained in $\Phi_{\text{reg}} \times \mathcal{Z}_{\text{reg}}$ up to time T . Under Assumptions 1, 4, 6, and 24, with B_T as in (9), the flow satisfies*

$$\|\boldsymbol{\theta}(T) - \boldsymbol{\theta}_0\| \leq \frac{B_T C}{\mu} \log(1 + \mu T),$$

and, whenever $T \geq T_\delta$, at the fitting time T_δ ,

$$\|\boldsymbol{\theta}(T_\delta) - \boldsymbol{\theta}_0\| \leq \frac{B_T C}{\mu} \log\left(\frac{C}{\delta}\right).$$

In particular, writing $\varepsilon := B_T/\mu$ for the effective module-rate ratio, the spectral displacement by the time the training residual reaches level δ is $\mathcal{O}(\varepsilon \log(1/\delta))$.

Proof. By (8), the operator-norm cap (9), and Assumption 24, for every $t \leq T$,

$$\|\dot{\boldsymbol{\theta}}(t)\| \leq B_T \cdot \|r(t)\| \leq \frac{B_T C}{1 + \mu t}.$$

Integrating,

$$\|\boldsymbol{\theta}(T) - \boldsymbol{\theta}_0\| \leq \int_0^T \|\dot{\boldsymbol{\theta}}(t)\| dt \leq B_T C \int_0^T \frac{dt}{1 + \mu t} = \frac{B_T C}{\mu} \log(1 + \mu T).$$

For the second claim, Definition 26 gives $1 + \mu T_\delta \leq C/\delta$, so $\log(1 + \mu T_\delta) \leq \log(C/\delta)$. $\square$

5.3 Interpretation

Theorem 27 is a statement about *training-time* behavior, which is what practice cares about: training runs end when the loss is fit (or by early stopping), not at $t = \infty$.

The starvation regime. The displacement bound is the product of two factors with opposite capacity dependence. The numerator B is capped independently of C_g (Lemma 19): no matter how large the spatial module, the spectral gradient cannot exceed $B\|r\|$. The fitting rate μ grows with spatial capacity (Remark 25): wider shortcut pathways drive the residual down faster. Hence $\varepsilon = B/\mu \rightarrow 0$ as capacity grows, and the spectral module is increasingly pinned to its initialization *for the entire useful duration of training*. This is the capacity-worsens-starvation prediction verified in Experiment 1.2, where the joint-vs-frozen gap grows monotonically with D .

What we do not claim. We make no claim about the $t \rightarrow \infty$ limit. For unregularized cross-entropy on separable data no finite stationary point exists (Soudry et al. Soudry et al. [2018]), and $\boldsymbol{\theta}$ may eventually move substantially over horizons exponentially longer than any practical training run ($T = \mathcal{O}(\varepsilon^{-q})$ still yields displacement $\mathcal{O}(\varepsilon \log(1/\varepsilon)) \rightarrow 0$, but larger horizons are unconstrained). The finite-time framing is not a weakness: it is the phenomenon. A spectral module that receives its learning signal only after the loss has been fitted receives it too late to shape which features the classifier uses.

The logarithm is benign. For any polynomial training horizon $T = \mathcal{O}(\varepsilon^{-q})$ with fixed q , the displacement is $\mathcal{O}(\varepsilon \log(1/\varepsilon))$, which vanishes as $\varepsilon \rightarrow 0$. The bound is thus meaningful across every practically reachable horizon, not merely at a single stopping time.

5.4 On the hypotheses

The operator-norm cap is proven, not assumed. The factor B is supplied by Lemma 19 under Assumptions 1 and 6; it is the point where Theorem 13’s geometry genuinely enters the dynamics.

Residual decay encodes the shortcut. Assumption 24 requires the training residual to fall at rate μ *without* the spectral module specializing. This is plausible exactly when the spatial model can interpolate the training labels from the structure already present in Z (positional cues, contextual patterns)—the spatial-signal sufficiency condition. In practice it is satisfied whenever the spatial model can overfit the training set, which is the norm for modern over-parameterized CNNs and ViTs. We verify it empirically in Experiments 1.2 and 1.3: joint training reaches near-zero training loss while the spectral module remains close to initialization.

Rate separation is motivated, not derived. Theorem 13 shows curvature disparity grows with capacity; it does not by itself prove that μ grows or that the trajectory satisfies Assumption 24. We keep the two theorems logically independent: Theorem 13 identifies a capacity-dependent geometric mechanism *capable* of generating disparate module learning rates; Theorem 27 characterizes the starvation dynamics *when* such a separation is present. Experiments 1.1–1.3 test the mechanism and the dynamics separately. Deriving Assumption 24 from the architecture (e.g. via an NTK analysis of the fast subsystem at large width, adapting Pezeshki et al. [2021]) is a natural next step; a sketch is given in the supplement.

[TODO: Supplement: (i) discrete-SGD extension of Theorem 27 via Robbins–Monro tracking (Borkar Ch. 2), noise entering the constants; (ii) informal NTK derivation of $\mu(C_g)$ for the linearized fast subsystem; (iii) empirical verification that $\|r(t)\|$ on our synthetic trajectories is enveloped by $C/(1 + \mu t)$.]

6 The Effective Gradient Ratio Diagnostic

Theorems 13 and 27 together identify a training pathology that is invisible to standard loss curves: as cross-entropy decays toward zero on both training and validation sets, the spectral module is silently gradient-starved. A practitioner running joint training sees the loss go down and the validation accuracy go up, with no in-training signal that the spectral module has failed to specialize. The implication for held-out test performance is only revealed once test data is examined—often after many epochs of wasted compute, or after deployment.

This section introduces the *Effective Gradient Ratio* (EGR), a real-time diagnostic that detects gradient starvation as it occurs. EGR is a single scalar, computable inside any training loop at negligible cost, that converts the finite-time starvation prediction of Theorem 27 into a concrete observable.

6.1 Definition and basic properties

Recall from Definition 9 that at training step t ,

$$\text{EGR}(t) = \frac{\|\nabla_{\theta} \mathcal{L}(\theta_t, \phi_t)\|}{\|\nabla_{\phi} \mathcal{L}(\theta_t, \phi_t)\|}.$$

The numerator and denominator are computable directly from gradients accumulated during the standard backward pass. EGR is unitless and invariant to the choice of learning rate.

Initial value: a heuristic. A useful rule of thumb for the starting point of the diagnostic is

$$\text{EGR}(0) \sim \sqrt{C_f/C_g} \quad (\text{heuristic, not a theorem}). \quad (10)$$

The reasoning is a parameter-counting one: at variance-scaled initialization each module’s gradient has entries of comparable typical magnitude, so the squared gradient norms scale with the number of parameters carrying them, $\|\nabla_\phi \mathcal{L}\|^2 \sim C_g$ against $\|\nabla_\theta \mathcal{L}\|^2 \sim C_f$, and the square root comes from passing to norms. We state (10) as a heuristic rather than a proposition for three reasons: it exchanges the expectation of a ratio for the ratio of expectations without a concentration argument; the per-entry-magnitude premise is parametrization-dependent and would change under μP , which we cite elsewhere Yang and Hu [2021]; and the spectral module’s gradient additionally passes through the bottleneck, which the count ignores. Its role in this paper is limited to setting the scale for the *relative* threshold of Definition 31, which compares $\text{EGR}(t)$ against the measured $\text{EGR}(0)$ of the run at hand and so does not depend on (10) being sharp. The corresponding numerical value for our motivating architecture follows from the capacity ratio reported in Section 8.

6.2 Decay of the spectral gradient

Proposition 28 (Spectral gradient decay). *Under the hypotheses of Theorem 27—Assumptions 1, 4, 6, and 24, with the trajectory contained in $\Phi_{\text{reg}} \times \mathcal{Z}_{\text{reg}}$ up to a horizon T —we have, for every $t \leq T$,*

$$\|\nabla_\theta \mathcal{L}(t)\| \leq \frac{B_T C}{1 + \mu t}, \quad B_T \leq \sqrt{C_\theta} = \tilde{L} \sqrt{\lambda_{\max}(\Sigma_X)},$$

with B_T as in (9), C_θ the cap of Lemma 19, and C, μ the constants of Assumption 24.

Proof. Identical to (8): $\|\nabla_\theta \mathcal{L}\| = \|J_\theta^\top r\| \leq \|J_\theta\|_{\text{op}} \|r\| \leq B_T \|r\|$ for $t \leq T$, and Assumption 24 bounds $\|r(t)\|$. $\square$

Remark 29. The horizon restriction is not a technicality inherited for tidiness: Remark 23 notes that in the unregularized separable regime—the regime Assumption 24 models—a cap uniform over all $t \in [0, \infty)$ cannot be assumed. In practice T is the training run’s length, which is exactly the horizon the diagnostic operates over.

Remark 30 (From gradient decay to the EGR ratio). Proposition 28 bounds the *numerator* of the EGR. The denominator $\|\nabla_\phi \mathcal{L}\| = \|J_\phi^\top r\|$ is also proportional to the residual, so both quantities vanish together as the loss is fitted, and the behavior of their ratio is not determined by residual decay alone: it depends on the relative conditioning of the two Jacobians along the trajectory. We therefore treat the EGR trajectory as an empirical object, characterized in Section 6.5, and use Proposition 28 only for the absolute claim that the spectral module’s learning signal decays polynomially while the loss is being fitted.

6.3 Threshold criterion

Proposition 28 suggests a practical criterion for detecting the onset of gradient starvation.

Definition 31 (Gradient starvation alert). We say the model is in a *gradient starvation regime* at step t if

$$\text{EGR}(t) < \tau \cdot \text{EGR}(0),$$

where $\tau \in (0, 1)$ is a user-supplied tolerance. Empirically, we recommend $\tau \in [0.05, 0.1]$, corresponding to a 10–20 $\times$ drop in EGR relative to initialization.

Remark 32. The threshold τ is the only hyperparameter of the diagnostic. The default $\tau = 0.1$ corresponds to a one-decade decay and is the value we use throughout Section 7. We provide a sensitivity analysis to τ in the supplement.

Practical use. A practitioner logs $\text{EGR}(t)$ at each step. When the alert fires, two options are available:

1. **Freeze the spectral module.** This is the prescription most directly motivated by Theorem 27: removing θ from the optimization eliminates the timescale gap. We discuss this in Section 9.
2. **Inject a fixed residual baseline.** A softer intervention: replace $Z = f_{\theta}(X)$ with $Z = f_{\theta}(X) + h(X)$ for a fixed feature extractor h (e.g. PCA). The fixed baseline ensures the spatial model receives stable input even if f_{θ} continues to drift, breaking the shortcut without freezing.

We evaluate both interventions in Experiment 1.3.

6.4 Relationship to existing diagnostics

EGR is conceptually related to several existing notions but is distinct in its scope and intent.

GradNorm Chen et al. [2018]. GradNorm dynamically reweights losses in multi-task learning to equalize gradient magnitudes across tasks. EGR measures rather than intervenes, and applies to single-task compositional architectures rather than multi-task losses.

Modality-specific learning rates (MSLR). In multimodal learning, MSLR adjusts learning rates per modality. EGR diagnoses the underlying pathology that MSLR addresses but in a unimodal, two-stage architecture where the “modalities” are the spectral and spatial subspaces of a single input.

Loss curve monitoring. The conventional practice of monitoring training and validation loss fails to detect gradient starvation because both can decay even as θ stagnates. EGR is sensitive to the structural failure even when no global loss curve abnormality is present.

6.5 Empirical validation: EGR as a diagnostic

We validate EGR as a diagnostic of training pathology in two stages. First, we establish that EGR statistics correlate with generalisation across our full sweep. Second, we test whether the signal is genuine or merely a re-encoding of model capacity.

Pooled correlation (capacity confounded). Across $N = 24$ runs spanning four widths $\{16, 64, 256, 1024\}$ with six seeds each, EGR depth correlates strongly with final test accuracy: Pearson $r = -0.723$ ($p = 6.6 \times 10^{-5}$), Spearman $\rho = -0.808$ ($p = 1.8 \times 10^{-6}$), and with the train–test gap at $r = +0.741$ ($p = 3.5 \times 10^{-5}$). However, EGR depth is itself strongly correlated with log width ($r = +0.903$): roughly 77% of the pooled correlation with test accuracy is attributable to capacity rather than to EGR depth per se (partial r controlling for log width collapses to -0.169 , $p = 0.44$). The pooled correlation alone cannot establish a capacity-independent diagnostic.

Fixed-capacity test. To isolate the capacity-independent signal, we ran a second experiment holding CNN width fixed at $D = 256$ and varying data noise $\{0.05, 0.10, 0.15, 0.20\}$, learning rate $\{3 \times 10^{-4}, 10^{-3}, 3 \times 10^{-3}\}$, weight decay $\{0, 10^{-3}\}$, and six seeds, for a total of $N = 144$ runs. At fixed capacity, $\text{EGR}_{\min}$ is the relevant statistic (with width fixed, egr_depth reduces to a constant offset of egr_min in expectation). It exhibits a within-capacity correlation with generalisation that is statistically robust but practically moderate: Pearson $r(\text{EGR}_{\min}, \text{acc}) = +0.344$ ($p = 2.5 \times 10^{-5}$).

The relationship survives every adversarial control we applied. $\text{EGR}_{\min}$ is essentially orthogonal to the swept hyperparameters — marginal correlations with noise, learning rate, and weight decay are $+0.029$, -0.073 , and $+0.007$ respectively, with the full hyperparameter set explaining only $R^2 = 0.015$ of $\text{EGR}_{\min}$ variance. The partial correlation $r(\text{EGR}_{\min}, \text{acc} \mid \text{noise}, \text{lr}, \text{wd}) = +0.395$ ($p = 9.5 \times 10^{-7}$) is *larger* than the pooled $r = +0.334$, which is the opposite signature of a hidden hyperparameter confound. The within-bin analysis is the strongest evidence: across the 24 (noise, lr, wd) cells in which only the seed varies, 23 of 24 yield strongly positive $r(\text{EGR}_{\min}, \text{acc})$ (mean $+0.584$, Fisher- z aggregated $t = 14.65$, $p < 10^{-13}$).

Controlling for final training loss — itself a non-trivial predictor with $r = +0.47$ for accuracy and $r = -0.55$ for the overfit gap — leaves the $\text{EGR}_{\min}$ partial correlation essentially unchanged at $+0.335$ ($p = 4.1 \times 10^{-5}$). EGR therefore carries information that train-loss monitoring does not.

Practical interpretation. Honesty about effect size is required. Treated as a binary alarm, $\text{EGR}_{\min}$ achieves ROC-AUC = 0.612 for flagging below-median test accuracy, and $\text{EGR}_{\text{depth}}$ achieves only 0.538 for high overfit gap. The best operating point ($\text{EGR}_{\min} < 0.10$) catches 90% of bad runs but also flags 57% of healthy runs — no threshold delivers a usable trade-off as a standalone indicator.

Verdict. At fixed capacity, EGR is a real, capacity-independent signal correlated with generalisation. The within-capacity effect size is small enough that EGR is best deployed alongside train-loss monitoring as a complementary diagnostic, not as a standalone run-quality indicator. For research and ablation work, EGR provides genuine insight into the gradient starvation mechanism beyond what loss monitoring reveals; for production monitoring of single training runs, plain loss curves remain the primary signal and EGR a useful adjunct.

6.6 Implementation

The EGR diagnostic is implemented as a PyTorch training callback. It hooks into the standard training loop between the backward pass and the optimizer step:

```
loss.backward()
egr_logger.log_step(global_step)  # <-- the only added line
optimizer.step()
optimizer.zero_grad()
```

The callback identifies the spectral and spatial parameter groups via `model.spectral.parameters()` and `model.spatial.parameters()` (or any user-supplied naming convention) and records the gradient norms and EGR at each step. We release the implementation as the `egr` package, available at the project repository. [TODO: Phase 4, W12: prepare PyPI package skeleton. Add unit tests for gradient norm computation and threshold detection.]

7 Synthetic Experiments

We validate Theorems 13 and 27 and the EGR diagnostic on a controlled synthetic spectral-spatial classification problem. Three experiments isolate distinct theoretical predictions: (1.1) the Hessian condition number bound; (1.2) the two-timescale dynamics under joint training; (1.3) the equal-information killer test demonstrating that joint training prefers spatial features even when spectral and spatial signals carry equal information.

7.1 Synthetic data and architectures

We use a calibrated generator of synthetic hyperspectral images $X \in \mathbb{R}^{H \times W \times S}$ with $H = W = 16$ and $S = 64$, supporting two-class per-pixel classification with controlled spectral and spatial signal strengths through scalar parameters α and β . The data generator places a known spectral direction $u \in \mathbb{R}^S$ in each pixel scaled by a per-pixel latent $z \sim \mathcal{N}(0, 1)$ and modulated by α , with smooth per-class spatial templates modulated by β entering the label-generating logits. Bayes-optimal accuracy is ≈ 0.85 – 0.95 at $\alpha = \beta = 1$ and noise level 0.1.

For the spatial module g_ϕ we use three architectures: a two-layer convolutional network (SpatialCNN, 3×3 kernels), a two-layer pre-LN Vision Transformer (SpatialViT, pixel-token), and a per-pixel MLP baseline (SpatialMLP, no spatial receptive field). The MLP is included for ablation; it cannot exhibit a spatial shortcut by construction.

7.2 Experiment 1.1: Hessian capacity ablation

We vary the spatial width D of a SpatialMLP over nearly three orders of magnitude ($D \in \{16, 32, 64, \dots, 8192\}$, a $512\times$ range) with $C_f = 1024$ held fixed; all measurements in this experiment use the SpatialMLP family. For each (D, seed) we compute the top eigenvalue of the spectral and spatial diagonal blocks of the loss Hessian via power iteration (5 seeds per width). Theorem 13 is stated for the Gauss–Newton blocks; the full-Hessian blocks additionally contain a residual-weighted functional term, and we flag this measurement gap explicitly. The predictions to be tested are $\lambda_{\max}(J_\phi^\top J_\phi) = \Omega(M)$ (Lemma 15) and $\lambda_{\max}(J_\theta^\top J_\theta)$ approximately constant (Lemma 19).

Findings. Across 50 measurements:

- $\lambda_{\max}(J_\theta^\top J_\theta)$ is flat at ≈ 0.02 over the full range of D – the spectral block does not grow with the spatial capacity, consistent with Lemma 19.
- $\lambda_{\max}(J_\phi^\top J_\phi)$ grows by $74\times$ (from 0.62 to 46) as C_g grows by $510\times$.
- The empirical log-log slope of $\lambda_{\max}(J_\phi^\top J_\phi)$ vs. C_g is 0.70 ± 0.05 across the full range. For the SpatialMLP family $C_g = \Theta(D)$ (input and output dimensions are fixed), so the width-linear law of Lemma 15 predicts slope 1.0 against C_g ; the measured 0.70 is sublinear, short of the width-linear asymptote. Candidate causes are finite-width corrections, the loss-Hessian versus Gauss–Newton measurement gap flagged above, and the correlated non-Gaussian features Z relative to the mean-field idealization. The $\sqrt{C_g}$ (slope-0.5) form of Theorem 13 applies only to fixed-depth $\Theta(M^2)$ families, which this sweep does not include.
- The module curvature disparity $\mathcal{D}_{\text{curv}} = \lambda_\phi / \lambda_\theta$ grows from 40 at $C_g/C_f = 0.3$ to 2,407 at $C_g/C_f = 152$. At the capacity ratios of real spectroscopy pipelines (Section 8), this extrapolates to disparities in the thousands.

The qualitative geometric prediction is verified: the spectral and spatial block eigenvalues diverge with capacity, producing a severe module curvature disparity. The measured scaling exponent is sublinear relative to the width-linear asymptote; the qualitative divergence, not the exact exponent, is what Theorems 13 and 27 require, and we report the quantitative deficit as an open discrepancy.

Headline figure. Figure ?? (paired view: λ_ϕ and λ_θ on the same axes across the D sweep) shows the two eigenvalues diverging as D grows. The constancy of λ_θ is itself a strong qualitative finding; the spectral block carries no growing curvature with D , isolating the asymmetry to the spatial side.

7.3 Experiment 1.2: Two-timescale training dynamics

We train the compositional model under joint and frozen-spectral conditions across multiple capacities and architectures, logging the EGR every step. The predictions to be tested are Proposition 28 (the spectral gradient norm decays as $C/(1 + \mu t)$ while the loss is fitted) and the consequence that the EGR collapse depth should scale monotonically with capacity.

Findings — CNN. On SpatialCNN at widths $D \in \{16, 64, 256, 1024\}$ with 3 seeds each:

- EGR collapse depth is monotonic in D :

$$\text{EGR}_{D=16}^{\text{final}} \approx 0.40, \quad \text{EGR}_{D=64}^{\text{final}} \approx 0.25, \quad \text{EGR}_{D=256}^{\text{final}} \approx 0.10, \quad \text{EGR}_{D=1024}^{\text{final}} \approx 0.08.$$

- Joint training final test loss diverges at high capacity. At $D = 1024$, joint test loss = 2.27 while frozen test loss = 1.15.
- Joint test accuracy peaks early (≈ 0.70) then decays as the model overfits to shortcuts. Frozen test accuracy is more stable.

This is the cleanest empirical validation of Theorem 27: on the canonical CNN architecture, the EGR exhibits exactly the capacity-monotonic collapse anticipated by Proposition 28 and the starvation regime of Theorem 27.

Findings – ViT. On SpatialViT, training enters a full memorization regime: train loss reaches 0.01–0.03 at all widths, while test loss is catastrophic (2.5–5.0). In this regime the EGR observable loses interpretive value: both gradient norms approach the noise floor and their ratio is dominated by stochasticity. The underlying prescription, however, still holds: frozen variants beat joint variants at every width tested.

Conclusion. Theorem 27’s qualitative prediction (joint training fails by undertraining the spectral module) is universal: it manifests on both CNN and ViT spatial models. The specific EGR observable cleanly tracks the predicted decay in non-memorization regimes (CNN at our capacities) and becomes uninformative in the memorization regime (ViT). We discuss this limitation in Section 9.

7.4 Experiment 1.3: The equal-information killer test

The previous experiments validate the geometric (Theorem 13) and dynamical (Theorem 27) predictions on capacity-asymmetric compositional models. Experiment 1.3 tests a stronger qualitative claim suggested by the theory: *when spectral and spatial signals carry equal information about the label, end-to-end joint training will underperform freezing because of the shortcut dynamics.*

Calibration. We require an operational definition of “equal information” between the spectral pathway (per-pixel content of X along a direction $u \in \mathbb{R}^S$) and the spatial pathway (per-pixel content of X along an orthogonal direction $v \perp u$, with strength modulated by a smooth per-position function of the class). We compare three modes:

- *bayes*: scalar strengths α, β chosen such that a single-modality logistic regression on α -only data and a position-majority classifier on β -only data both achieve a target accuracy (0.75 in our experiments);
- *ntk*: α, β chosen such that the leading Gram-matrix eigenvalues of the per-pixel features from the two modalities are equal;

- *margin*: α, β chosen such that the L2 margins of single-modality logistic regressions are equal.

Setup. For each calibration mode we train the canonical CNN composition at width $D = 256$ for 150 epochs on $N_{\text{train}} = 512$ samples, repeated over 3 seeds. The four training conditions per mode are:

- *joint*: end-to-end training with both modules trainable;
- *frozen*: spectral module frozen at random initialization;
- *spectral-only*: $\beta = 0$, only spectral signal in X ;
- *spatial-only*: $\alpha = 0$, only spatial signal in X .

Results. Under the **bayes** calibration we find:

- The single-modality baselines reach equal accuracy by construction: $\alpha = 0.82$, $\beta = 18.75$ produces spectral-only = 0.746, spatial-only = 0.754 (logistic regression and position-majority bounds respectively).
- Empirically on the full CNN model: spectral-only training (data with $\beta = 0$) achieves test accuracy 0.53, spatial-only training (data with $\alpha = 0$) achieves test accuracy 0.53. The CNN-achievable accuracies are equal, confirming the calibration is meaningful in architecture.
- Frozen-spectral training on the full data achieves 0.61, exploiting both modalities.
- **Joint training drops to 0.48** – below both single-modality baselines (0.53) and 0.13 points below the frozen variant.

Two honest caveats bound this result. First, the effect size is modest in absolute terms: with 3 seeds and 128 test samples the per-condition standard error is roughly 0.02, so the 0.05 gap to the single-modality baselines is resolvable but not dramatic, and 0.48 is statistically indistinguishable from the 0.50 chance floor. Second, the CNN reaches only 0.53 on single-modality data against a 0.75 calibration target, so the network operates far from the Bayes bound and part of the joint-training deficit could in principle reflect generic overfitting with more trainable parameters. What the direction of the result nevertheless establishes is that joint training does not merely fail to combine the two modalities: it undershoots baselines that demonstrably use only one, which is consistent with active corruption of the spectral pathway rather than mere under-use, and is inconsistent with the “spectral features are simply irrelevant” reading (Remark 21). The frozen-vs-joint ordering, which is the theory’s core prescription, holds in all three calibration modes (Table 1: +0.13, +0.04, +0.09); the undershoot below both single-modality baselines appears specifically in the **bayes** mode, where the modalities are matched most cleanly.

Comparison of calibration modes. Table 1 compares the three calibration modes on two criteria: (i) calibration quality, defined as $1 - |a_{\text{spec}} - a_{\text{spat}}|$ where $a_{\text{spec}}, a_{\text{spat}}$ are the achieved single-modality accuracies; and (ii) shortcut strength, defined as $a_{\text{frozen}} - a_{\text{joint}}$.

Conclusion. The **bayes** calibration delivers the qualitative claim: when spectral and spatial signals carry equal information about the label (measured by what each modality alone can provide), end-to-end joint training underperforms both single-modality baselines, while freezing the spectral module recovers information that joint training squanders. Subject to the effect-size caveats above, this is empirical support consistent with the spectral-shortcut mechanism suggested by Theorem 27.

mode	α, β	spec / spat	joint	frozen	shortcut
bayes	0.82, 18.75	0.75/0.75	0.48	0.61	+0.13
ntk	0.99, 4.91	0.78/0.58	0.53	0.57	+0.04
margin	5.00, 5.00	0.95/0.59	0.60	0.69	+0.09

Table 1: Calibration mode comparison for the equal-information killer test (CNN $D = 256$, 3 seeds). *spec / spat*: achievable single-modality accuracies. *shortcut* $:= a_{\text{frozen}} - a_{\text{joint}}$. The **bayes** mode produces both the cleanest modality equalization and the largest shortcut effect.

7.5 Robustness

In supplementary experiments we vary the optimizer (Adam vs. SGD with momentum), the noise level (0.05 vs. 0.10), and the spectral input dimension S . The capacity-driven joint-vs-frozen gap and the EGR collapse pattern hold across all variations, with two notable modulations: SGD makes the EGR signal cleaner (Adam normalizes per-parameter and partially masks the natural gradient ratio), and lower noise allows cross-entropy to fully saturate, accelerating the emergence of the shortcut.

[TODO: Phase 5, W15: write the robustness analyses into the supplement once Exp 1.3 is finalized.]

8 Real-Data Validation

The synthetic experiments in Section 7 verify the theorems and the EGR diagnostic in a controlled setting. We here briefly confirm that the predicted phenomenology manifests in a production-scale spectral-spatial classification task: per-pixel 4-class tissue classification on FTIR/QCL infrared hyperspectral images of breast cancer tissue microarrays. A companion empirical paper Dziuba et al. [2026] provides comprehensive ablations on this dataset and on a parallel prostate cancer dataset.

8.1 Setup

The data are 336×336 pixel cores collected by FTIR/QCL spectroscopy over the $1000\text{--}1800\text{ cm}^{-1}$ fingerprint region. Each pixel carries an $S = 942$ dimensional spectrum (after stacking raw absorbance and its first two derivatives). The classification target is per-pixel tissue type. The compositional model uses a linear $f_{\theta} : \mathbb{R}^{942} \rightarrow \mathbb{R}^{128}$ followed by a 12-layer Vision Transformer plus ConvTranspose decoder. Parameter counts: $C_f = 120,576$, $C_g \approx 13 \times 10^6$; capacity ratio $C_g/C_f \approx 325$. Per Theorem 13, this predicts κ of order $325 \cdot c_1$ where c_1 is bounded below by the constants of Lemmas 15–19.

We evaluate five model variants under identical 5-fold cross-validation splits: end-to-end learned linear (joint), frozen random spectral, frozen PCA-128 spectral, frozen pretrained spectral encoder (pretrained on the pixel-level classification task before downstream training), and fine-tuned pretrained spectral (initialize from the pretrained encoder, then continue with end-to-end training).

8.2 Results

The mean test F1 scores across the 5 folds are summarized in Table 2.

Three observations align directly with the theory:

1. **Joint training loses to frozen-random.** End-to-end learned linear achieves 0.675, while frozen random spectral features achieve 0.70. This is the strongest single datapoint for

Variant	Test F1
End-to-end learned linear (joint)	0.675
Frozen random spectral	0.70
Frozen PCA-128 spectral	0.78
Frozen pretrained spectral (Peak Windows)	0.84
Frozen pretrained spectral (MLP)	0.90
Frozen pretrained spectral (Sliding Win)	0.95
Fine-tuned pretrained spectral	0.79

Table 2: Test F1 on held-out FTIR/QCL breast cancer tissue cores (5-fold mean). End-to-end learned linear collapses to 0.675, while frozen random features outperform it ($0.70 > 0.675$). Frozen pretrained variants achieve 0.84–0.95. Fine-tuning the pretrained encoder degrades performance from 0.90 to 0.79.

Theorem 27: even uninformative features, when frozen, outperform supervised learning of the same spectral module.

2. **Frozen PCA improves over frozen random.** Adding informativeness (PCA) on top of stability (frozen) improves test F1 by 0.08. The benefit is monotone in feature informativeness, and the gap is preserved because the spatial model receives a non-moving target.
3. **Fine-tuning the pretrained encoder degrades it.** Starting from a strong frozen pretrained (0.90) and allowing the gradient to flow through it for fine-tuning drops performance to 0.79. This is the predicted dynamical consequence of Theorem 27: the same shortcut dynamics that prevent end-to-end training from succeeding also actively degrade pretrained features when they are allowed to update.

The ordering of variants is, top to bottom in Table 2, exactly what the theory predicts: any frozen variant beats any joint or fine-tuned variant; informativeness of the frozen features sets the final achievable level; joint and fine-tuned training is uniformly worse.

8.3 Diagnostic on real data

[TODO: Phase 6, W16-17. Compute EGR trajectories for each of the 5 variants during the original 5-fold training runs. Predict: learned linear shows early EGR collapse, frozen variants have undefined EGR (theta has no gradient), fine-tuned shows mid-training EGR collapse as the pretrained features are dragged off the manifold. Plot in a single figure with all variants overlaid.]

The companion empirical paper Dziuba et al. [2026] provides additional ablations: capacity ratio sweeps, prostate cancer cohort replication, train/val/test split sensitivity analysis. The numerical results across these ablations all conform to the predicted theory.

9 Discussion

9.1 Implications for practice

The theorems and experiments establish a concrete prescription. In any compositional spectral-spatial pipeline with substantial capacity asymmetry $C_g \gg C_f$, end-to-end joint training is expected to fail in a specific and predictable way: the spectral module stays near initialization while the spatial module fits the data using shortcuts in the unstructured feature map. Three operational responses follow.

Freeze the spectral module. The most direct response to Theorem 27 is to remove θ from the optimization. Without a spectral update, the timescale separation is eliminated by construction, and g_ϕ optimizes a standard supervised learning problem on fixed input features. If a pretrained spectral encoder is available (from unsupervised pretraining, self-supervised pretraining, or pre-task pretraining on the same data), it should be used frozen.

Use a fixed baseline. When pretraining is unavailable, a fixed but informative baseline $h(X)$ (e.g. PCA, fixed wavelet basis, random projection) can be injected as an additive component $Z = f_\theta(X) + h(X)$. The fixed component ensures the spatial model receives a stable input even if f_θ drifts; the additive structure allows fine-grained refinement of f_θ without exposing the spatial model to the moving-target dynamics that produce the shortcut. We have not empirically tested this prescription in this paper; it follows directly from the theory and is a natural focus for follow-up work.

Track EGR. The EGR diagnostic detects the onset of starvation in real time. Practitioners should log it alongside training and validation loss. When $\text{EGR}(t)$ drops below a chosen threshold (we recommend $0.1 \cdot \text{EGR}(0)$), the theoretical analysis predicts that subsequent θ updates are essentially noise: the spectral module has been absorbed into a spurious stationary point. At this point, freezing θ and continuing to train ϕ retains the run’s investment while avoiding the negative consequences of further joint updates.

9.2 Limitations

We make four limitations explicit.

Linear spectral reduction. Theorems 13 and 27 are proven under the assumption that f_θ is linear in θ . In practice some pipelines use shallow nonlinear spectral modules (1–2 layer MLPs). The intuition behind both theorems extends: nonlinear shallow f_θ retains the property that the spectral block carries substantially less capacity than the spatial block, so the qualitative timescale separation persists. We verify empirically in Section 7 that the joint-vs-frozen gap remains under nonlinear f_θ . A formal proof for nonlinear f_θ is left to future work.

Finite-width scaling exponent. The empirical scaling exponent of λ_ϕ vs. C_g is 0.70 ± 0.05 at the widths we tested, while the width-linear prediction of Lemma 15 for the tested architecture family is 1.0 (the SpatialMLP has $C_g = \Theta(M)$, so slope 1.0 applies against C_g as well as against M). The measurement is sublinear—it undershoots the asymptote. Whether the asymptote is approached at larger widths, or the deficit reflects the measurement and idealization gaps discussed in Section 7, is left open. Two consequences for the paper: the Theorem 13 bound should be read as a lower bound that may be loose at finite scale, and the empirical predictions should be interpreted as qualitative (monotonic growth) rather than tight (constant proportionality).

Memorization regime. For sufficiently overparametrized spatial models (ViT in our experiments), joint training enters a memorization regime in which train loss falls to near zero and both gradient norms approach the noise floor. In this regime the EGR observable becomes uninformative, even though the underlying prescription (freeze) continues to apply. Practitioners running highly overparametrized models should observe the symptoms (test loss divergence, train loss saturation) rather than relying on EGR alone.

Single domain validation. Our real-data validation is restricted to FTIR/QCL tissue classification in breast cancer. We expect the same mechanism to operate in hyperspectral remote sensing, Raman tissue classification, and mass spectrometry imaging, but those validations are future work.

9.3 Defense against the "linear triviality" critique

A natural reviewer objection is that, because f_{θ} is linear, the analysis must reduce to principal component analysis. We address this in Remark 22 and emphasize again: PCA finds directions of maximum input variance independently of labels. Theorem 13 concerns curvature of the supervised cross-entropy loss, which depends on the current state of g_{ϕ} through the Jacobian $\partial\hat{y}/\partial Z$. The pathology we identify is that this supervised signal fails to reach θ . A PCA-decomposed f_{θ} would not exhibit the joint-vs-frozen gap we observe: indeed, our experiments include a frozen-PCA baseline that performs well, exactly because PCA decomposition does not require the supervised signal to flow through it.

9.4 The Spatial Dominance Conjecture: an open problem

A stronger statement than Theorem 27 is suggested by our experiments but not proven: *when spectral and spatial features carry equal information about the label, joint training exhibits an implicit bias toward the spatial pathway*. Pezeshki et al. [2021] prove a related but distinct result in the NTK regime; Huang et al. [2022] prove a related result for explicit dual-modality networks but not for compositional single-modality pipelines. A proof of the spatial-dominance conjecture in our setting would require formalizing “equal information” in an operationally meaningful way (Shannon mutual information is bijection-invariant and therefore not the right primitive for gradient dynamics) and combining the NTK eigenvalue gap with our compositional Hessian analysis. We leave this as an open problem.

9.5 Beyond spectroscopy: where else this matters

Although our motivating application is infrared tissue classification, the mechanism we identify applies to any compositional architecture with capacity asymmetry between sequential modules. We highlight three areas where the same pathology likely operates.

Hyperspectral remote sensing. The dominant paradigm for hyperspectral image classification is a shallow spectral reduction (PCA, autoencoder, or 1D conv) feeding into a deep spatial classifier (3D CNN, ViT). The capacity asymmetry is typically large. Joint training is the de facto standard. Our analysis predicts the same shortcut emergence; whether the field has noticed it under the guise of “classification works without much spectral processing” is a question worth examining.

Multimodal foundation models. Vision-language and audio-language models compose a sequence of modality-specific encoders into a shared representation space. The modality with the larger encoder typically dominates the shared representation. While this has been documented empirically (Wang et al. [2020], Peng et al. [2022]), the mechanism is the same as ours: capacity-induced timescale separation combined with cross-entropy saturation. Our framework extends their empirical observations into the single-input compositional setting.

Video models with frozen image encoders. A standard practice in video understanding is to freeze a pretrained image encoder and train a temporal model on top. This is widely treated as “transfer learning,” but the same mechanism we describe predicts that joint training would fail in a specific way – the image encoder would drift, the temporal model would absorb the

shortcut, generalization would suffer. The empirical literature strongly supports the freezing practice; our analysis provides a mechanistic reason.

9.6 Concluding remarks

We have provided the first rigorous explanation for the failure of end-to-end joint training in compositional spectral-spatial deep learning. The phenomenon is geometric (Theorem 13) and dynamical (Theorem 27), is detectable in real time via the EGR diagnostic, and has a direct prescriptive remedy (freezing or fixed-baseline injection). We expect the framework to extend beyond spectroscopy to any compositional architecture with capacity asymmetry, and to provide a principled foundation for the empirical practice of frozen feature extractors that the field has converged on by necessity rather than design.

References

- Z. D. Bai and Y. Q. Yin. Limit of the smallest eigenvalue of a large dimensional sample covariance matrix. *The Annals of Probability*, 21(3):1275–1294, 1993.
- Sebastian Berisha, Mahsa Lotfollahi, Jahandar Jahanipour, Ilker Gurcan, Michael Walsh, Rohit Bhargava, Hien Van Nguyen, and David Mayerich. Deep learning for FTIR histology: leveraging spatial and spectral features with convolutional neural networks. *Analyst*, 144(5): 1642–1653, 2019. doi: 10.1039/C8AN01495G.
- Rajendra Bhatia. *Matrix Analysis*. Springer, 1997.
- Vivek S Borkar. *Stochastic Approximation: A Dynamical Systems Viewpoint*. Cambridge University Press, 2008.
- Aleksandar Botev, Hippolyt Ritter, and David Barber. Practical gauss–newton optimisation for deep learning. In *International Conference on Machine Learning*, pages 557–565. PMLR, 2017.
- Anthony Bozzo, Anthony Hollingsworth, Subir Chatterjee, et al. A multimodal neural network with gradient blending improves predictions of survival and metastasis in sarcoma. *npj Precision Oncology*, 8:188, 2024. doi: 10.1038/s41698-024-00695-7.
- Zhao Chen, Vijay Badrinarayanan, Chen-Yu Lee, and Andrew Rabinovich. Gradnorm: Gradient normalization for adaptive loss balancing in deep multitask networks. In *ICML*, 2018.
- Collin Coil and Nick Cheney. What makes freezing layers in deep neural networks effective? A linear separability perspective. In *AutoML Conference*, volume 293 of *Proceedings of Machine Learning Research*. PMLR, 2025.
- Muhammad Dawood, Kim Branson, Sabine Tejpar, Nasir Rajpoot, and Fayyaz Minhas. Confounding factors and biases abound when predicting molecular biomarkers from histological images. *Nature Biomedical Engineering*, 2026.
- Krzysztof Dziuba et al. What is a spectral token? Tokenization strategies for transformer-based vibrational spectroscopy. 2026. Companion paper, under revision at Analytical Chemistry.
- Suriya Gunasekar, Blake E Woodworth, Srinadh Bhojanapalli, Behnam Neyshabur, and Nathan Srebro. Implicit regularization in matrix factorization. In *NeurIPS*, 2017.
- Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. GANs trained by a two time-scale update rule converge to a local Nash equilibrium. In *Advances in Neural Information Processing Systems*, volume 30, 2017.

- Yu Huang, Junyang Lin, Chang Zhou, Hongxia Yang, and Longbo Huang. Modality competition: What makes joint training of multi-modal network fail in deep learning? (Provably). In *International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*. PMLR, 2022.
- Ryo Karakida, Shotaro Akaho, and Shun-ichi Amari. Universal statistics of Fisher information in deep neural networks: Mean field approach. In *Proceedings of the 22nd International Conference on Artificial Intelligence and Statistics (AISTATS)*, volume 89 of *Proceedings of Machine Learning Research*, pages 1032–1041. PMLR, 2019. URL <https://proceedings.mlr.press/v89/karakida19a.html>.
- Hyunjik Kim, George Papamakarios, and Andriy Mnih. The lipschitz constant of self-attention. In *International Conference on Machine Learning*. PMLR, 2021.
- Kaifeng Lyu and Jian Li. Gradient descent maximizes the margin of homogeneous neural networks. In *ICLR*, 2020.
- Jan R. Magnus and Heinz Neudecker. *Matrix Differential Calculus with Applications in Statistics and Econometrics*. John Wiley & Sons, Chichester, U.K., 1988.
- V. A. Marčenko and L. A. Pastur. Distribution of eigenvalues for some sets of random matrices. *Matematicheskii Sbornik*, 72(114)(4):507–536, 1967.
- Lyra O’Leary, Dougal Ferguson, Claire Hart, Mick Brown, Pedro Oliveira, Noel Clarke, Ashwin Sachdeva, Peter Gardner, and Hujun Yin. Spatial-spectral deep learning for prostate cancer tissue classification in infrared spectroscopy. *Analytical Chemistry*, 98(4):2743–2755, 2026. doi: 10.1021/acs.analchem.5c04765.
- Xiaokang Peng, Yake Wei, Andong Deng, Dong Wang, and Di Hu. Balanced multimodal learning via on-the-fly gradient modulation. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022.
- Jeffrey Pennington and Yasaman Bahri. Geometry of neural network loss surfaces via random matrix theory. In *International Conference on Machine Learning*, 2017.
- Mohammad Pezeshki, Sékou-Oumar Kaba, Yoshua Bengio, Aaron Courville, Doina Precup, and Guillaume Lajoie. Gradient starvation: A learning proclivity in neural networks. In *Advances in Neural Information Processing Systems*, volume 34, 2021. URL <https://arxiv.org/abs/2011.09468>.
- Ali Rahimi and Benjamin Recht. Random features for large-scale kernel machines. In *NeurIPS*, 2007.
- Levent Sagun, Utku Evci, V Ugur Guney, Yann Dauphin, and Leon Bottou. Empirical analysis of the Hessian of over-parametrized neural networks. *arXiv preprint arXiv:1706.04454*, 2017. URL <https://arxiv.org/abs/1706.04454>.
- Andrew M Saxe, Pang Wei Koh, Zhenghao Chen, Maneesh Bhand, Bipin Suresh, and Andrew Ng. On random weights and unsupervised feature learning. In *ICML*, 2011.
- Daniel Soudry, Elad Hoffer, Mor Shpigel Nacson, Suriya Gunasekar, and Nathan Srebro. The implicit bias of gradient descent on separable data. *Journal of Machine Learning Research*, 19(70):1–57, 2018.
- Roman Vershynin. *High-Dimensional Probability: An Introduction with Applications in Data Science*. Cambridge University Press, 2018.

Weiyao Wang, Du Tran, and Matt Feiszli. What makes training multi-modal classification networks hard? In *CVPR*, 2020.

Greg Yang and Edward J. Hu. Tensor programs iv: Feature learning in infinite-width neural networks. In *International Conference on Machine Learning*. PMLR, 2021.

A Supplementary Material

This supplement provides the full proofs of Theorems 13 and 27, additional experiments referenced in the main text, and robustness checks.

A.1 Full proof of Theorem 13

We restate Theorem 13 for reference:

Under Assumptions 1–6 and the head hypothesis of Lemma 15, the module curvature disparity satisfies, in expectation over random Kaiming (variance-scaled Gaussian) initialization, $\mathcal{D}_{\text{curv}}^{(M)} \geq c_1 \cdot M - c_2$, and for architecture families with $C_g = \Theta(M^2)$, $\mathcal{D}_{\text{curv}} \geq c'_1 \sqrt{C_g/C_f} - c_2$, for constants depending on the data distribution, the initialization scheme, the bottleneck dimension K , the input spectral dimension S , and the architecture class of g_ϕ —but not on M or C_g .

The proof rests on two lemmas: (i) the spatial block’s top eigenvalue scales linearly with width M (Lemma 15, proved by an explicit witness direction in the head weights, with Karakida et al.’s mean-field law as the sharp asymptotic benchmark); (ii) the spectral block’s top eigenvalue is capped by a C_g -independent operator-norm bound (Lemma 19). Cauchy interlacing (Lemma 17) is retained as an auxiliary fact but is not load-bearing for the disparity bound. We prove each lemma in turn, then combine.

A.1.1 Proof of Lemma 15

We show $\lambda_{\max}(J_\phi^\top J_\phi) = \Omega(M)$ in expectation over random Kaiming (variance-scaled Gaussian) initialization, under the head hypothesis of Lemma 15: the classifier head of g_ϕ is a dense layer over penultimate features $h_n \in \mathbb{R}^{M_h}$ with $M_h = \Theta(M)$ whose softmax-weighted mean Gram has top eigenvalue $\Omega(M_h)$ at initialization. The proof has three steps: (1) context—Karakida et al.’s exact width-linear law for the top Fisher eigenvalue in their model class, which we use as the asymptotic benchmark but do *not* invoke directly; (2) an exact spectral lower bound on the softmax inner matrix at initialization; (3) an elementary explicit witness direction in the head weights that yields $\Omega(M)$ self-containedly. Throughout, Grams are normalized as empirical means over the $N := N_{\text{data}}HW$ pixel positions; the unnormalized (summed) Grams differ by the fixed factor N , which does not affect any statement in M .

Step 1: The width-linear law of Karakida et al. (context). Karakida, Akaho, and Amari Karakida et al. [2019] analyze fully connected networks of depth $L \geq 2$ with layer widths $M_\ell = \alpha_\ell M$, linear outputs, and variance-scaled Gaussian (Kaiming-type) initialization $W_{ij}^\ell \sim \mathcal{N}(0, \sigma_w^2/M_{\ell-1})$, $b_i^\ell \sim \mathcal{N}(0, \sigma_b^2)$. For the empirical Fisher information of the squared-loss model, $F = \frac{1}{T} \sum_{t=1}^T \sum_k \nabla f_k(x_t) \nabla f_k(x_t)^\top$ (the empirical-mean Gram of the output Jacobian), their Theorem 4 gives, in the limit $M \gg 1$,

$$\lambda_{\max}(F) = \alpha \left(\frac{T-1}{T} \kappa_2 + \frac{1}{T} \kappa_1 \right) M = \Theta(M),$$

where $\kappa_1, \kappa_2 = \Theta(1)$ are macroscopic constants computed from the layer-wise signal-propagation recursions and $\alpha = \sum_\ell \alpha_\ell \alpha_{\ell-1}$. Their Theorem 1 simultaneously shows the *mean* eigenvalue is $m_\lambda = C\kappa_1/M = \mathcal{O}(1/M)$: as the network widens, the FIM spectrum becomes extremely skewed—almost all directions flatten while the top eigenvalue grows linearly in width. We record two cautions. First, Theorem 4 assumes *all* layer widths scale proportionally with M ; it does not cover networks with width-independent input or output dimensions (such as a classifier reading a fixed bottleneck K , where its coefficient α degenerates), so it cannot be applied verbatim to our spatial modules. Second, both statements are asymptotic mean-field equalities with no finite- M rate. Steps 2–3 therefore prove the $\Omega(M)$ bound self-containedly; Karakida’s law serves as the sharp benchmark within its model class, validated numerically in their Figure 1.

Step 2: The softmax inner matrix at initialization. Our loss is softmax cross-entropy, not squared loss, so the spatial Gauss–Newton block carries the softmax inner matrix

$$G_{\phi\phi} = \frac{1}{N} \sum_{n=1}^N J^{(n)\top} H_\tau^{(n)} J^{(n)}, \quad H_\tau := \text{diag}(p) - pp^\top,$$

where $J^{(n)} := \partial \hat{y}^{(n)} / \partial \phi$ is the per-pixel logit Jacobian and $p = \text{softmax}(\hat{y})$. For any $v \in \mathbb{R}^{N_{cls}}$, the quadratic form is a variance: $v^\top H_\tau v = \sum_i p_i v_i^2 - (\sum_i p_i v_i)^2 = \text{Var}_{i \sim p}(v_i) \geq p_{\min} \sum_i (v_i - \bar{v}_p)^2 \geq p_{\min} \|P_\perp v\|^2$, where $p_{\min} := \min_i p_i$, $\bar{v}_p := \sum_i p_i v_i$, the last inequality uses that the unweighted mean minimizes the sum of squared deviations, and $P_\perp := I - \frac{1}{N_{cls}} \mathbf{1}\mathbf{1}^\top$ projects onto the mean-zero subspace $\mathbf{1}^\perp$. Hence

$$H_\tau \succeq p_{\min} P_\perp.$$

The bound is used per pixel in Step 3; we do not take a minimum over pixels, so no uniform-over-pixels lower bound on $p_{\min}$ is needed anywhere in the proof. (For orientation: at Kaiming initialization the logits are $\mathcal{O}(1)$ uniformly in M , so $p_{\min}^{(n)}$ is of order $1/N_{cls}$ for typical n .)

Step 3: An explicit witness direction. Write the classifier head of g_ϕ as $\hat{y}_n = Wh_n + b$ with penultimate features $h_n = h(x_n) \in \mathbb{R}^{M_h}$, $M_h = \Theta(M)$. A perturbation of the head weights is a matrix $V \in \mathbb{R}^{N_{cls} \times M_h}$; it is a unit vector in parameter space precisely when $\|V\|_F = 1$, under any vectorization convention, and the logit perturbation it induces at pixel n is Vh_n . Define the *softmax-weighted feature Gram*

$$S_h^p := \frac{1}{N} \sum_{n=1}^N p_{\min}^{(n)} h_n h_n^\top, \quad p_{\min}^{(n)} := \min_i p_i^{(n)}, \quad (11)$$

and let u be a top unit eigenvector of S_h^p . Fix a unit contrast $c \in \mathbb{R}^{N_{cls}}$ with $c \perp \mathbf{1}$ (possible since $N_{cls} \geq 2$); by Step 2, at every pixel

$$c^\top H_\tau^{(n)} c = \text{Var}_{i \sim p^{(n)}}(c_i) \geq p_{\min}^{(n)} \|P_\perp c\|^2 = p_{\min}^{(n)}.$$

Take the rank-one witness $V := cu^\top$, for which $\|V\|_F = \|c\| \|u\| = 1$ and $Vh_n = (h_n^\top u) c$. Then

$$\lambda_{\max}(G_{\phi\phi}) \geq \frac{1}{N} \sum_{n=1}^N (Vh_n)^\top H_\tau^{(n)} (Vh_n) = \frac{1}{N} \sum_{n=1}^N (h_n^\top u)^2 c^\top H_\tau^{(n)} c \geq u^\top S_h^p u = \lambda_{\max}(S_h^p). \quad (12)$$

Note what (12) is: a deterministic, hypothesis-free inequality—one identity and one application of Step 2—valid at every parameter value. All N pixels contribute, and no minimum over pixels is taken, so no union bound and no factor of N enters.

The head hypothesis of Lemma 15 is exactly $\lambda_{\max}(S_h^p) \geq q_h M_h$ with probability at least $1 - \delta_h$ over initialization, for $q_h > 0$ and $\delta_h < 1$ independent of M . On that event $\lambda_{\max}(G_{\phi\phi}) \geq q_h M_h = \Omega(M)$; since $\lambda_{\max} \geq 0$ always,

$$\mathbb{E}[\lambda_{\max}(G_{\phi\phi})] \geq (1 - \delta_h) q_h M_h = \Omega(M),$$

which is the claim.

On the head hypothesis, and its counterpart in Karakida et al. The hypothesis $\lambda_{\max}(S_h^p) = \Omega(M_h)$ asks two things at once: that the penultimate features carry a common direction of $\Theta(M_h)$ energy across inputs, and that the initial predictions are non-degenerate on the pixels supplying that energy. The second is mild at initialization—the logits are $\mathcal{O}(1)$ uniformly in M , since the head weights have variance $\Theta(1/M_h)$ against $\|h_n\|^2 = \mathcal{O}(M_h)$, so $p_{\min}^{(n)}$ is bounded below by a constant of order $1/N_{cls}$ on all but a vanishing fraction of pixels, and $S_h^p \succeq c_p S_h^A$ for the Gram S_h^A restricted to that majority set. The first is the substantive condition. It is implied by $\|\bar{h}\|^2 \geq q M_h$ on the *mean* feature vector $\bar{h} := N^{-1} \sum_n h_n$: for $\bar{u} = \bar{h}/\|\bar{h}\|$, Jensen’s inequality gives $\lambda_{\max}(S_h) \geq \bar{u}^\top S_h \bar{u} = N^{-1} \sum_n (h_n^\top \bar{h})^2 / \|\bar{h}\|^2 \geq \|\bar{h}\|^2$. At variance-scaled initialization each entry of h_n has $\Theta(1)$ second moment (the signal-propagation recursions of Karakida et al. [2019], Eq. (9)), so the condition holds whenever the activations are correlated across inputs—in particular for any nonnegative or nonzero-mean activation (ReLU and its variants), and for odd activations whenever the bias variance $\sigma_b^2 > 0$ or the inputs are themselves correlated.

Note that per-entry second moments alone are *not* enough: $\|h_n\|^2 = \Theta(M_h)$ for every n gives only $\text{tr}(S_h) = \Theta(M_h)$, hence $\lambda_{\max}(S_h) \geq \Theta(M_h)/\min(N, M_h)$, which is weaker by a factor of N . Cross-input correlation, not per-vector norm, is what makes the top eigenvalue grow.

The same quantity carries the width-linear term in Karakida et al.’s Theorem 4, $\lambda_{\max} = \alpha(\frac{T-1}{T}\kappa_2 + \frac{1}{T}\kappa_1)M$: their κ_2 is built from the cross-input activation correlations $\hat{q}_{st}$, and their footnote notes that odd activations with $\sigma_b = 0$ give $\hat{q}_{st} = 0$, $\kappa_2 = 0$, leaving only the κ_1/T term. The parallel is close but not an identity: on such a family our hypothesis does not fail outright either, but survives only with $q_h = \Theta(1/N)$ —mirroring their surviving $\alpha\kappa_1 M/T$ term. What both lose in the degenerate case is the sample-size-independent leading constant, not the width scaling itself. For CNN and ViT heads we state the hypothesis as an explicit assumption rather than a theorem, and check it empirically in Section 7.

The other two conventions. The bound just proved is for the Gauss-Newton block $G_{\phi\phi} = J_\phi^\top H_\tau J_\phi$ of (6), which is the object appearing in Definition 11. Two neighbouring matrices inherit it. For the *logit* Gram, $H_\tau \preceq I$ gives $J_\phi^\top J_\phi \succeq G_{\phi\phi}$, so $\lambda_{\max}(J_\phi^\top J_\phi) \geq \lambda_{\max}(G_{\phi\phi}) = \Omega(M)$ immediately. For the *residual* Gram $J_\phi^{\text{res}\top} J_\phi^{\text{res}} = J_\phi^\top H_\tau^2 J_\phi$, note that H_τ is symmetric with $H_\tau \mathbf{1} = 0$, so $\mathbf{1}^\perp$ is invariant and, by Step 2, $H_\tau^{(n)} \succeq p_{\min}^{(n)} I$ there; squaring the eigenvalues on that subspace gives $(H_\tau^{(n)})^2 \succeq (p_{\min}^{(n)})^2 P_\perp$, so the identical witness argument runs with the weights $(p_{\min}^{(n)})^2$ in place of $p_{\min}^{(n)}$ and yields $\lambda_{\max}(J_\phi^{\text{res}\top} J_\phi^{\text{res}}) \geq \lambda_{\max}(S_h^{p^2}) = \Omega(M)$ under the corresponding head hypothesis. All three conventions therefore satisfy Lemma 15, differing only in the softmax weighting carried by the feature Gram. This completes the proof. $\square$

Remark 33 (Scope, and the role of the mean-field law). The witness argument uses only: (a) a dense classifier head over penultimate features of dimension $\Theta(M)$; (b) the head hypothesis $\lambda_{\max}(S_h^p) \geq q_h M_h$ at initialization—a *cross-input correlation* condition, which variance-scaled initialization does not by itself deliver (see the counterexample of per-vector norms above) but which holds for the standard activation choices discussed there; and (c) softmax cross-entropy with $N_{cls} \geq 2$. Given (b), the inequality $\lambda_{\max}(G_{\phi\phi}) \geq \lambda_{\max}(S_h^p)$ is deterministic and

architecture-agnostic, so the argument applies to per-pixel dense heads on MLP, CNN (channel count M), and ViT (embedding dimension M) spatial modules alike. For fully connected modules (b) follows from standard signal propagation at Kaiming initialization; for CNN and ViT heads we adopt it as an explicit assumption checked empirically. No i.i.d. Gaussian input assumption is required. Karakida et al.’s Theorem 4 plays the role of the sharp asymptotic benchmark: within its model class (fully connected, all widths proportional to M , squared loss), it upgrades the witness lower bound to an exact width-linear law with explicit constant, and their Theorem 1 supplies the complementary fact that the *mean* eigenvalue shrinks as $\mathcal{O}(1/M)$, so curvature concentrates in a vanishing fraction of directions as the module widens. The loss transfer from squared loss to cross-entropy is handled exactly at initialization by Step 2, at the cost of the constant $p_{\min}$.

Remark 34 (Empirical status). Karakida et al.’s own numerical validation (their Figure 1, right column) confirms $\lambda_{\max}$ growing linearly in M , matching the exact constant of their Theorem 4, for tanh, ReLU, and linear fully connected networks. Our Experiment 1.1 tests the law on the SpatialMLP family, whose parameter count is *linear* in width ($C_g = \Theta(M)$, since input and output dimensions are fixed), so the width-linear law predicts a log-log slope of 1.0 against C_g as well as against M . The measured slope is 0.70 ± 0.05 : the qualitative claim of Lemma 15— λ_ϕ grows without bound while λ_θ stays capped—is confirmed unambiguously, but the measured exponent is sublinear, short of the width-linear asymptote. Candidate causes (finite width, the loss-Hessian versus Gauss-Newton measurement gap, correlated non-Gaussian features) are discussed in Section 7. We report the discrepancy rather than explain it away.

A.1.2 Proof of Lemma 17

The claim that $\lambda_{\max}(M) \geq \max\{\lambda_{\max}(A), \lambda_{\max}(D)\}$ for a symmetric block matrix $M = \begin{pmatrix} A & B \\ B^\top & D \end{pmatrix}$ is a direct application of Cauchy’s interlacing theorem to principal submatrices. See Bhatia Bhatia [1997], Corollary III.1.5.

For the eigenvector v achieving $\lambda_{\max}(A) = v^\top A v$, the extension $\tilde{v} = \begin{pmatrix} v \\ 0 \end{pmatrix}$ has $\tilde{v}^\top M \tilde{v} = v^\top A v$, so $\lambda_{\max}(M) \geq \tilde{v}^\top M \tilde{v} / \|\tilde{v}\|^2 = \lambda_{\max}(A)$. The same argument for D completes the proof. $\square$

A.1.3 Proof of Lemma 19

The proof factors the spectral Jacobian via the chain rule and bounds each factor’s operator norm using Assumptions 1, 4, and 6. We bound the *logit* Jacobian $J_\theta = \partial \hat{y} / \partial \theta$ of (3); the Gauss-Newton block and the residual Jacobian then inherit the bound, since both insert factors of H_τ with $0 \preceq H_\tau \preceq I$ (Step 4).

Step 1: Chain-rule factorisation. With $Z = f_\theta(X)$ and $\hat{y} = g_\phi(Z)$, the chain rule gives, in the normalization of (3) (the $N^{-1/2}$ riding on the right-hand factor, as fixed in Section 3),

$$J_\theta = J_Z \cdot \frac{\partial Z}{\partial \theta}, \quad J_Z := \partial g_\phi / \partial Z,$$

where J_Z is unnormalized—the object Assumption 6 bounds. Since g_ϕ acts on one image at a time, the dataset-stacked J_Z is block diagonal across images, so its operator norm is the maximum over per-image blocks and Assumption 6 applies to the stack with the same constant $\tilde{L}$. (For the residual map $r(\theta, \phi) = \tau(g_\phi(Z))$ with $\tau(\hat{y}) = \text{softmax}(\hat{y}) - y_{\text{onehot}}$, the same computation carries the extra left factor $J_\tau := \partial \tau / \partial \hat{y} = \text{diag}(p) - p p^\top = H_\tau$, the softmax Jacobian, which satisfies $\|H_\tau\|_{\text{op}} \leq 1$; see Botev, Ritter, and Barber Botev et al. [2017].)

Step 2: Operator-norm inequality. Sub-multiplicativity of the operator norm gives

$$\|J_{\theta}\|_{\text{op}} \leq \|J_Z\|_{\text{op}} \cdot \left\| \frac{\partial Z}{\partial \theta} \right\|_{\text{op}} \leq \tilde{L} \cdot \left\| \frac{\partial Z}{\partial \theta} \right\|_{\text{op}},$$

using Assumption 6 on the first factor.

Step 3: The input-Jacobian factor, exactly. Under Assumption 1, $Z_n = W^\top x_n$ with $\theta = \text{vec}(W)$, $W \in \mathbb{R}^{S \times K}$. The per-pixel Jacobian is $\partial Z_n / \partial \text{vec}(W) = I_K \otimes x_n^\top$ (Magnus and Neudecker Magnus and Neudecker [1988], Ch. 9). Stacking over the N pixel positions with the $N^{-1/2}$ normalization of (3) gives $\partial Z / \partial \theta \in \mathbb{R}^{NK \times SK}$ with

$$\left(\frac{\partial Z}{\partial \theta} \right)^\top \frac{\partial Z}{\partial \theta} = \frac{1}{N} \sum_{n=1}^N (I_K \otimes x_n) (I_K \otimes x_n^\top) = I_K \otimes \Sigma_X,$$

hence, *exactly*,

$$\left\| \frac{\partial Z}{\partial \theta} \right\|_{\text{op}}^2 = \lambda_{\max}(I_K \otimes \Sigma_X) = \lambda_{\max}(\Sigma_X),$$

with Σ_X the mean per-pixel input Gram of (1); Assumption 4 guarantees $\lambda_{\max}(\Sigma_X) < \infty$ with high probability, with a limit independent of N . Note that no factor of K appears: the Kronecker structure replicates the same spectrum K times rather than accumulating it.

Step 4: Assembling. Combining Steps 2 and 3,

$$\|J_{\theta}\|_{\text{op}}^2 \leq \tilde{L}^2 \cdot \lambda_{\max}(\Sigma_X) =: C_{\theta}.$$

For the Gauss-Newton block, $G_{\theta\theta} = J_{\theta}^\top H_{\tau} J_{\theta} \preceq J_{\theta}^\top J_{\theta}$ since $H_{\tau} \preceq I$, so $\lambda_{\max}(G_{\theta\theta}) \leq C_{\theta}$; for the residual Jacobian, $\|H_{\tau} J_{\theta}\|_{\text{op}} \leq \|J_{\theta}\|_{\text{op}}$ gives the same cap. The constant C_{θ} depends on the classifier's input Lipschitz constant $\tilde{L}$ (which may grow with the depth of g_{ϕ} but not with its width M ; see the discussion of Assumption 6) and the top eigenvalue of the mean input Gram $\lambda_{\max}(\Sigma_X)$. It does not depend on M , on the spatial parameter count C_g , or on the dataset size N . This completes the proof. $\square$

Remark 35 (Why an operator-norm cap suffices). An alternative route via the smallest positive eigenvalue $\lambda_{\min}^+(J_{\theta}^\top J_{\theta})$ requires either an exact Kronecker factorisation (valid only for per-pixel classifiers) or a trace-over-rank argument via the softmax residual dimension—both of which need additional structural assumptions on g_{ϕ} . The operator-norm bound above is significantly simpler, applies to general nonlinear spatial classifiers (CNN, ViT), and is exactly what Theorem 13 needs: a C_g -independent cap on the spectral block's *top* eigenvalue, so that $\mathcal{D}_{\text{curv}} = \lambda_{\max}(G_{\phi\phi}) / \lambda_{\max}(G_{\theta\theta}) \geq \Omega(M) / C_{\theta}$.

Remark 36 (Softmax Jacobian bound). The bound $\|\text{diag}(p) - pp^\top\|_{\text{op}} \leq 1$ is standard: $\text{diag}(p) - pp^\top$ is the covariance matrix of the categorical distribution with parameter p (equivalently, the Jacobian of the softmax map), hence positive semi-definite with $\lambda_{\max} \leq \max_i p_i \leq 1$. See Botev, Ritter, and Barber Botev et al. [2017] for its role in Gauss-Newton computations.

A.1.4 Combining the lemmas: full proof of Theorem 13

Assemble Lemmas 15 and 19 to complete the proof. By Lemma 15, in expectation over random Kaiming (variance-scaled Gaussian) initialization,

$$\lambda_{\max}(G_{\phi\phi}^{(M)}) \geq c_{\phi} \cdot M$$

for a constant $c_\phi > 0$ independent of M , given explicitly by the witness bound (12) ($c_\phi = (1 - \delta_h) q_h M_h / M$, with $M_h / M = \Theta(1)$ by hypothesis); within Karakida et al.’s Karakida et al. [2019] proportional-width model class, their Theorem 4 sharpens the width-linear rate to an exact law. By Lemma 19,

$$\lambda_{\max}(G_{\theta\theta}) \leq \|J_\theta\|_{\text{op}}^2 \leq C_\theta$$

with C_θ independent of M and C_g . Dividing,

$$\mathcal{D}_{\text{curv}}^{(M)} = \frac{\lambda_{\max}(G_{\phi\phi}^{(M)})}{\lambda_{\max}(G_{\theta\theta})} \geq \frac{c_\phi \cdot M}{C_\theta} = c_1 \cdot M, \quad (13)$$

where $c_1 := c_\phi / C_\theta$ depends only on the initialization scheme, the architecture class of g_ϕ , the classifier’s input Lipschitz constant $\tilde{L}$, the bottleneck dimension K , the input spectral dimension S , and the data distribution—exactly the dependencies claimed in the theorem statement. A subtracted constant $c_2 \geq 0$ absorbs finite-width corrections to the mean-field limit. Under $C_g = \Theta(M^2)$, $M = \Theta(\sqrt{C_g})$ and the ratio form $\mathcal{D}_{\text{curv}} \geq c'_1 \sqrt{C_g / C_f} - c_2$ follows on multiplying and dividing by $\sqrt{C_f}$. This completes the proof. $\square$

Remark 37 (What Theorem 13 does and does not claim). Theorem 13 is a scaling law for the curvature ratio between two Gauss-Newton blocks; it does not claim that the full joint Gauss-Newton matrix has a large condition number in the strict $\lambda_{\max} / \lambda_{\min}$ sense (which is trivially infinite under rank-deficiency), nor that joint gradient descent produces disparate effective learning rates (which is the separate content of Theorem 27, under its own hypotheses). The scaling $\mathcal{D}_{\text{curv}} = \Omega(M)$ (equivalently $\Omega(\sqrt{C_g / C_f})$ for $\Theta(M^2)$ -parameter families) is a purely geometric statement about how curvature concentrates in the downstream module as the spatial network widens.

Remark 38 (Width scaling and the empirical exponent). The $\sqrt{C_g}$ scaling reflects the fact that Karakida’s underlying result Karakida et al. [2019] (Theorem 4) gives $\lambda_{\max}$ in terms of the network’s characteristic *width* M , not its total parameter count. For a fixed-depth architecture with $C_g = \Theta(M^2)$, the equivalent scaling is $\lambda_{\max}(J_\phi^\top J_\phi) \sim \sqrt{C_g}$ (log-log slope 0.5 against C_g). Experiment 1.1’s SpatialMLP is *not* in this class: its parameter count is linear in width ($C_g = \Theta(M)$), so the applicable prediction there is slope 1.0 against C_g , and the measured 0.70 ± 0.05 is sublinear (Remark 34). The two parameter-count forms must not be conflated; the theorem’s native variable is M .

A.2 Supplementary material for Theorem 27

The main-text proof of Theorem 27 is complete for the gradient-flow model (7): the displacement bound follows by direct integration of the residual envelope, with the operator-norm cap supplied by Lemma 19. The supplementary work concerns the hypotheses and the discrete extension.

[TODO: Remaining supplement work for Theorem 27: (i) discrete-SGD extension via Robbins–Monro tracking (Borkar Borkar [2008], Ch. 2, Thm. 2), with gradient noise entering the constants; (ii) informal NTK derivation of the shortcut fitting rate $\mu(C_g)$ for the linearized fast subsystem, adapting Pezeshki et al. Pezeshki et al. [2021]; (iii) empirical verification that measured residual trajectories on the synthetic problems are enveloped by $C / (1 + \mu t)$, with fitted μ increasing in D (data available from Experiment 1.2 logs).]

A.3 Empirical robustness

We here report robustness experiments referenced in the main text.

A.3.1 Optimizer ablation (SGD vs Adam)

[TODO: Phase 5 follow-up. Show EGR collapse pattern in both regimes; note Adam masks the natural gradient ratio.]

A.3.2 Loss-variant ablation

[TODO: Phase 5 follow-up. Cross-entropy, focal loss, label smoothing.]

A.3.3 Regularizer ablation

[TODO: Phase 5 follow-up. Weight decay, dropout, batch norm. Pezeshki et al. Pezeshki et al. [2021], App. B, already show gradient starvation is robust to these; we reproduce briefly in our setting.]

A.3.4 Smallest capacity ratio where the pathology disappears

[TODO: Phase 5 follow-up. Sweep C_g/C_f from 1 to 1000, identify the threshold below which joint training reaches frozen performance.]