

Mac Pro (Late 2013) 12 core - 2xAMD FirePro D700 6144 MB - 16 GB 1866 MHz DDR3

Condition: **Used**
"*AS NEW*"

Time left: 6h 15m 1s Today 6:50PM

Current bid: **EUR 2,220.00** [43 bids]
Approximately
23,229.54 SEK

Place bid

Enter EUR 2,230.00 or more

Add to watch list

Zero
Customs charges

Longtime
Member

Shipping: **EUR 30.00 (approx. 313.91 SEK)** Pacco Ordinario Internazionale | See details
Item location: Venezia, Italy
Ships to: Europe

Delivery: Varies for items shipped from an international location

Payments:

Returns: Seller does not accept returns | See details

Shop with confidence

eBay Money Back Guarante
Get the item you ordered or money back. Learn more

Seller information

kbalda (99)

Save this Seller
Contact seller
See other items

People who viewed this item also viewed

Feedback or



Hynix 64GB 4X16GB 2RX4 PC3-14900R DDR3-

1,702.85 SEK
Free shipping



SGI Origin 2100 Server 4x 350MHz CPU's 2GB

52,023.82 SEK
+ 20,383.03 SEK

Description | Shipping and payments

eBay item number: 273

Seller assumes all responsibility for this listing.

Last updated on Feb 16, 2019 09:51:22 PST View all revisions

Item specifics

Condition: **Used :**
Seller Notes: "AS NEW"

Marca:	Apple

Mac Pro Top Equipped.
Absolutely perfect, No scratches, No noises, Fast and Reliable.
Sorry, I lost original carry package.

Il 16-feb-19 alle 18:51:22 CET, il venditore ha aggiunto le seguenti informazioni sull'oggetto:

Added ssd infos.

Tina:~ cattura$ /usr/local/sbin/smartctl -a disk1s1

```
smartctl 7.0 2018-12-30 r4883 [Darwin 18.2.0 x86_64] (sf-7.0-1)
Copyright (C) 2002-18, Bruce Allen, Christian Franke, www.smartmontools.org

=== START OF INFORMATION SECTION ===
Model Family:     Apple SD/SM/TS...E/F/G SSDs
Device Model:     APPLE SSD SM0512F
Serial Number:    S1FWNYADA14761
LU WWN Device Id: 5 002538 655584d30
Firmware Version: UXM8JA1Q
User Capacity:    500. 277. 790. 720 bytes [500 GB]
Sector Sizes:     512 bytes logical, 4096 bytes physical
Rotation Rate:    Solid State Device
Device is:        In smartctl database [for details use: -P show]
ATA Version is:   ATA8-ACS T13/1699-D revision 4c
SATA Version is:  SATA 3.0, 6.0 Gb/s (current: 6.0 Gb/s)
Local Time is:    Sat Feb 16 18:44:29 2019 CET
SMART support is: Available - device has SMART capability.
SMART support is: Enabled

=== START OF READ SMART DATA SECTION ===
SMART overall-health self-assessment test result: PASSED

General SMART Values:
Offline data collection status:  (0x00) Offline data collection activity
                                        was never started.
                                        Auto Offline Data Collection: Disabled.
Self-test execution status:      (   0) The previous self-test routine completed
                                        without error or no self-test has ever
                                        been run.
Total time to complete Offline
data collection:                (    0) seconds.
Offline data collection
capabilities:                    (0x5f) SMART execute Offline immediate.
                                        Auto Offline data collection on/off support.
                                        Abort Offline collection upon new
                                        command.
                                        Offline surface scan supported.
                                        Self-test supported.
                                        No Conveyance Self-test supported.
                                        Selective Self-test supported.
SMART capabilities:            (0x0003) Saves SMART data before entering
                                        power-saving mode.
                                        Supports SMART auto save timer.
Error logging capability:        (0x01) Error logging supported.
                                        General Purpose Logging supported.
Short self-test routine
recommended polling time:        (   2) minutes.
Extended self-test routine
recommended polling time:        (  10) minutes.


SMART Attributes Data Structure revision number: 40
Vendor Specific SMART Attributes with Thresholds:
ID# ATTRIBUTE_NAME          FLAG     VALUE WORST THRESH TYPE      UPDATED  WHEN_FAILED RAW_VALUE
  1 Raw_Read_Error_Rate     0x001a   200   200   000    Old_age   Always       -       0
  5 Reallocated_Sector_Ct   0x0033   100   100   000    Pre-fail  Always       -       0
  9 Power_On_Hours          0x0032   099   099   000    Old_age   Always       -       1594
 12 Power_Cycle_Count       0x0032   098   098   000    Old_age   Always       -       1524
169 Unknown_Apple_Attrib    0x0013   253   253   010    Pre-fail  Always       -       4153921248768
173 Wear_Leveling_Count     0x0032   194   194   100    Old_age   Always       -       68731535392
174 Host_Reads_MiB          0x0022   099   099   000    Old_age   Always       -       7952353
175 Host_Writes_MiB         0x0022   099   099   000    Old_age   Always       -       8771961
192 Power-Off_Retract_Count 0x0012   099   099   000    Old_age   Always       -       91
194 Temperature_Celsius     0x0022   067   067   000    Old_age   Always       -       33 (Min/Max 15/75)
197 Current_Pending_Sector  0x0022   100   100   000    Old_age   Always       -       0
199 UDMA_CRC_Error_Count    0x001a   200   200   000    Old_age   Always       -       0
240 Unknown_SSD_Attribute   0x0022   100   100   000    Old_age   Always       -       0

SMART Error Log Version: 1
No Errors Logged

SMART Self-test log structure revision number 1
No self-tests have been logged.  [To run self-tests, use: smartctl -t]

SMART Selective self-test log data structure revision number 1
 SPAN  MIN_LBA  MAX_LBA  CURRENT_TEST_STATUS
    1        0        0  Not_testing
    2        0        0  Not_testing
    3        0        0  Not_testing
    4        0        0  Not_testing
    5        0        0  Not_testing
Selective self-test flags (0x0):
  After scanning selected spans, do NOT read-scan remainder of disk.
If Selective self-test is pending on power-up, resume after 0 minute delay.
```

People were also interested in



Hynix 64GB 4x16GB 2Rx4 PC3-14900R DDR3-1866

1,727.75 SEK

Free



Hynix 64GB 4X16GB 2RX4 PC3-14900R DDR3-

1,702.85 SEK

Free



SGI Origin 2100 Server 4x 350MHz CPU's 2GB

52,023.82 SEK

+ 20,383.03 SEK



Micron 128GB 8x16GB 2Rx4 PC3-14900R DDR3-

3,405.70 SEK

Free



Hynix 16Gb PC3-14900 1866MHz DIMM HMT42-

371.51 SEK

+ 150.59 SEK



SK HYNIX 16GB DDR3-1866 PC3

1,256.59 SEK

+ Shipping

People who viewed this item also viewed

Feedback or



Hynix 64GB 4X16GB 2RX4 PC3-14900R DDR3-

1,702.85 SEK

Free shipping



SGI Origin 2100 Server 4x 350MHz CPU's 2GB

52,023.82 SEK

+ 20,383.03 SEK

Back to home page

Copyright © 1995-2019 eBay Inc. All Rights Reserved. Accessibility, User Agreement, Privacy, Cookies and AdChoice